

e. Detention/Water Quality Criteria

Detention and Water Quality criteria for Pond analysis are obtained from EPCDCM V1 Chapter 11 – Detention Storage, from EPCDCM V2 Chapter 2 – Stormwater Quality Management & Chapter 4 – New Development Stormwater Management

THE DEVELOPER PREFERS A VEGITATED TRICKLE CHANNEL. THE DFEVLEOPER AND HIS MAINTENANCE ENTITY ARE AWARE OF THE MAINTENANCVE REQUIREMENTS, INCLUDING POTENTIAL FOR ADDITIONAL MAITENANCE DUE TO THE TYPE OF TRICKLE CHANNEL AND ACCEPTS THE RESPONSIBILITY.

Plans show soil riprap

IV. Drainage Facility

a. General Concept

In the proposed condition, lots with public, rural local roadways. Lots will not be developed. Some building, proposed lot areas are analyzed for the proposed lot area are captured in roadside swales and conveyed to private full spectrum water quality and detention pond Pond A. Where grade allows, roadside ditches discharge directly into FSD ponds down grouted riprap rundowns and into a concrete bottom forebay. Pond A provides water quality treatment and detention for the applicable portions of the site and will be maintained by the entity assigned with a detention maintenance agreement. Portions of lots that do not drain towards proposed roadways will follow historic drainage patterns to the drainageway tributaries and are excluded from water quality treatment per EPC DCM Appendix I.7.1.B – Large Lot Single Family Sites. Existing natural drainage tributaries on site will be analyzed for stability and capacity, and where deficient, improved to accommodate the 100-yr flows. See ‘Water Quality & Detention’ section below for additional information.

b. Water Quality & Detention

Historically, undeveloped site area drains directly to the onsite drainageways and Black Squirrel Creek. In the proposed condition, road profiles are designed to direct developed lot area towards roadside ditches. Due to the size and variability of existing grade on the proposed lots, not all lot area drains towards the proposed roadways. In this scenario, those lot areas will utilize the EPC DCM Appendix I.7.1.B – Large Lot Single Family Sites water quality exclusion. However, the exclusion does not relinquish detention requirements for developed area. Based upon proposed condition Rational Method calculations, the development of the site has a marginal increase on peak flows in the 100-year scenario. The table below compares the flows leaving the site at each design point between the existing condition and the proposed fully developed condition.

The marginal increase in flows will not adversely affect downstream drainageways and associated facilities. For specific design point comparisons, please see the drainage maps and included summary tables in Appendix F. All outfall points will be designed to be stable up to and including the 100-yr event. Detailed and final design will be included with the FDR and Final Plat/CD’s.

EXISTING V. PROPOSED FLOW (INDIVIDUAL DESIGN POINTS)							
DP#		Q _{5-yr}			Q _{100-yr}		
EX	PROP	EX	PROP	Δ	EX	PROP	Δ
1	3	12.9	11.7	-9%	34.3	33.9	-1%
2	5	34.3	34.3	0%	77.4	81.0	5%

All flows leaving the site have remained consistent with the historic/existing conditions, with the exception of a small increase in flow. The increase is considered negligible, however, please see the Existing Conditions Report for more information. When designing the drainageway downstream of this design pond, please consider the proposed flow.

THE DEVELOPER PREFERS A VEGITATED TRICKLE CHANNEL. THE DEVELOPER AND HIS MAINTENANCE ENTITY ARE AWARE OF THE MAINTENANCE REQUIREMENTS, INCLUDING POTENTIAL FOR ADDITIONAL MAINTENANCE DUE TO THE TYPE OF TRICKLE CHANNEL AND ACCEPTS THE RESPONSIBILITY.

See comments in GEC plan

Pond A: Pond A consists of Basin A1 and Basin A2. Basin A1 has a storage volume of 0.053 ac-ft, the EURV is 0.051 ac-ft, and the 100-year design flow is 1.4 cfs. Basin A2 has a storage volume of 0.053 ac-ft, the EURV is 0.051 ac-ft, and the 100-year design flow is 1.4 cfs. Storms are released in 40, 66 and 68 hours, respectively. The outlet structure is a 18" RCP pipe with restrictor plate. A concrete channel conveys flow towards the outlet structure and is 9" deep and has greater than twice the capacity of the forebay release rate. A 10' maintenance road is provided to the bottom of the pond to facilitate future maintenance of the pond facilities. A 10' wide maintenance road is provided to the bottom of the pond to facilitate future maintenance of the pond facilities. A 10' wide maintenance road is provided to the bottom of the pond to facilitate future maintenance of the pond facilities.

A riprap trickle channel conveys flow towards the outlet structure and is 9" deep and has greater than twice the capacity of the forebay release rate. A 10' maintenance road is provided to the bottom of the pond to facilitate future maintenance of the pond facilities. A 10' wide maintenance road is provided to the bottom of the pond to facilitate future maintenance of the pond facilities. A 10' wide maintenance road is provided to the bottom of the pond to facilitate future maintenance of the pond facilities. A 10' wide maintenance road is provided to the bottom of the pond to facilitate future maintenance of the pond facilities.

Turf Reinforcement Mat has been added in two location along Swale A1. See GEC plans and Drainage Map for specifics. Please note, the swale is expected to remain stable while passing the 100-yr design flows, but the TRM was added to ensure stability in these areas as a precaution to reduce erosion potential and help to establish vegetation.

c. Major Drainageways

There are not major drainage ways located north of the site. Full channel analysis was completed. Preliminary analysis was included in the PDR, under EDARP files no. SP251.

Please include velocities in the swale and discuss the 90 degree bend at the north end of the property and if this area requires any armoring.

Existing Tributary A: In the existing condition, Existing Tributary A conveys offsite and on-site flow through the site and to Black Squirrel Creek. At the upstream limit Camelot Subdivision DP-6 Pond discharges into the tributary. To accommodate the proposed subdivision lot boundaries, the tributary is routed around the western and northern limits of Basin A3 as Proposed Swale A. Proposed Swale A will continue to bypass the existing discharge from the Camelot Subdivision DP-6 Pond, in addition to the discharge from on-site Pond A. Proposed swale A is a V swale, with grass lining, 6:1 side slopes, a 2.33' total depth, and is located per the Rural Major Arterial County Cross section. Where the tributary crosses offsite along the northern boundary of Basin A3, the proposed swale will tie into the existing tributary for the offsite portion. Portions of the existing Tributary are proposed to be filled in. Cross sectional output tables and hydraulic calcs for Proposed Swale A are presented in Appendix C.

please include grass type as max velocity is dependent on type.

Existing Tributary A2: In the existing condition, Existing Tributary A2 conveys offsite and on-site flow through the site and to Black Squirrel Creek. At the upstream limit, Antler Ridge Estates DP UBS-2 Pond discharges into the tributary under Ayer Road via an existing 42" RCP culvert. To accommodate the proposed subdivision lot boundaries, the tributary is routed around the western limits of the Filing No. 1 site in proposed Swale A2. Swale A2 will continue to bypass the existing discharge from the Antler Ridge Estates DP UBS-2 Pond, in addition to the discharge from on-site area. Swale A2 will be grass lined. Cross sectional output tables and hydraulic calcs for Proposed Swale A2 and Existing Tributary A2 are presented in Appendix C.


please include velocities of the swale

d. Operations & Maintenance

Include a cost estimate for each PCM with line items for all components (ex: riprap, road base, forebay, trickle channel, outlet structure, outlet pipe, spillway, etc). Input the total value into the FAE form under "Permanent Pond/BMP (provide engineer's estimate)" in Section 1. The total should not include grading, which is a separate line item in Section 1: "Earthwork." The cost estimate should include labor costs (as a separate line item or added into the cost of each component).


V2 - Drainage Report Review 1 Comments.pdf Markup Summary

Bret Dilts - DPW Engineering (3)




Subject: Engineer
Page Label: 2
Author: Bret Dilts - DPW Engineering
Date: 3/20/2026 10:42:54 AM
Status:
Color: ■
Layer:
Space:

Please include velocities in the swale and discuss the 90 degree bend at the north end of the property and if this area requires any armoring.



Subject: Engineer
Page Label: 2
Author: Bret Dilts - DPW Engineering
Date: 3/20/2026 10:43:40 AM
Status:
Color: ■
Layer:
Space:


please include velocities of the swale



Subject: Engineer
Page Label: 2
Author: Bret Dilts - DPW Engineering
Date: 3/20/2026 11:00:43 AM
Status:
Color: ■
Layer:
Space:


please include grass type as max velocity is dependent on type.

EPC Stormwater- Zachary (5)



Subject: SW - Highlight
Page Label: 1
Author: EPC Stormwater- Zachary
Date: 3/17/2026 1:31:24 PM
Status:
Color: ■
Layer:
Space:

grouted riprap rundowns



Subject: SW - Textbox with Arrow
Page Label: 1
Author: EPC Stormwater- Zachary
Date: 3/17/2026 1:32:12 PM
Status:
Color: ■
Layer:
Space:

Plans show soil riprap



Subject: SW - Highlight
Page Label: 2
Author: EPC Stormwater- Zachary
Date: 3/18/2026 8:15:45 AM
Status:
Color: ■
Layer:
Space:

A riprap trickle channel

downstream of
See comments in GEC
plan
detention for
RV is 0.051 ac-ft
in 40, 66 and 68
with restrictor
riprap trickle

Subject: SW - Textbox with Arrow
Page Label: 2
Author: EPC Stormwater- Zachary
Date: 3/18/2026 8:16:06 AM
Status:
Color: ■
Layer:
Space:

See comments in GEC plan

Copyright 2025 by EPC Stormwater, Inc. All rights reserved. This document is the property of EPC Stormwater, Inc. and is intended for the use of the client only. It is not to be distributed, copied, or reproduced in any form without the written permission of EPC Stormwater, Inc. The information contained herein is confidential and may be subject to change without notice. EPC Stormwater, Inc. is not responsible for any errors or omissions in this document. The user assumes all liability for any use of this document. EPC Stormwater, Inc. is not a contractor and does not provide any services. EPC Stormwater, Inc. is a consulting firm and provides consulting services only. EPC Stormwater, Inc. is not a design firm and does not provide any design services. EPC Stormwater, Inc. is not a construction firm and does not provide any construction services. EPC Stormwater, Inc. is not a real estate firm and does not provide any real estate services. EPC Stormwater, Inc. is not a financial institution and does not provide any financial services. EPC Stormwater, Inc. is not a government agency and does not provide any government services. EPC Stormwater, Inc. is not a public utility and does not provide any public utility services. EPC Stormwater, Inc. is not a professional corporation and does not provide any professional services. EPC Stormwater, Inc. is not a partnership and does not provide any partnership services. EPC Stormwater, Inc. is not a sole proprietorship and does not provide any sole proprietorship services. EPC Stormwater, Inc. is not a trust and does not provide any trust services. EPC Stormwater, Inc. is not a limited liability company and does not provide any limited liability company services. EPC Stormwater, Inc. is not a corporation and does not provide any corporation services. EPC Stormwater, Inc. is not a partnership and does not provide any partnership services. EPC Stormwater, Inc. is not a sole proprietorship and does not provide any sole proprietorship services. EPC Stormwater, Inc. is not a trust and does not provide any trust services. EPC Stormwater, Inc. is not a limited liability company and does not provide any limited liability company services. EPC Stormwater, Inc. is not a corporation and does not provide any corporation services.

Subject: SW - Textbox
Page Label: 2
Author: EPC Stormwater- Zachary
Date: 3/18/2026 8:23:37 AM
Status:
Color: ■
Layer:
Space:

Include a cost estimate for each PCM with line items for all components (ex: riprap, road base, forebay, trickle channel, outlet structure, outlet pipe, spillway, etc). Input the total value into the FAE form under "Permanent Pond/BMP (provide engineer's estimate)" in Section 1. The total should not include grading, which is a separate line item in Section 1: "Earthwork." The cost estimate should include labor costs (as a separate line item or added into the cost of each component).