



**ENTECH**  
ENGINEERING, INC.

505 ELKTON DRIVE  
COLORADO SPRINGS, CO 80907  
PHONE (719) 531-5599

**PAVEMENT DESIGN REPORT  
LATIGO TRAILS FILING NO. 9  
EL PASO COUNTY, COLORADO**

Prepared for:  
**RDMA, LLC**  
**2130 Academy Circle, Suite F**  
**El Paso County, CO**

Attn: Akeem Seriki/Glenn Kunkel

June 13, 2024

Respectfully Submitted,

ENTECH ENGINEERING, INC.

Stuart Wood  
Staff Geologist

Reviewed by:



Digitally signed by Joseph C Goode III  
Date: 06/13/24

Joseph C. Goode III, P.E.  
Sr. Engineer

SW:JCG/ed

Entech Job No. 231802

**Table of Contents**

**1 Introduction ..... 1**

**2 Project Description ..... 1**

**3 Subsurface Explorations and Laboratory Testing ..... 1**

    3.1 Subsurface Exploration Program ..... 1

    3.2 Geotechnical Index and Engineering Property Testing ..... 2

**4 Subgrade Conditions ..... 2**

    4.1 Subsurface Conditions ..... 2

    4.2 Groundwater ..... 3

**5 Pavement Design Recommendations ..... 3**

    5.1 Subgrade Conditions ..... 3

    5.2 Swell Mitigation ..... 4

    5.3 Traffic Loading ..... 4

    5.4 Pavement Design ..... 4

**6 Construction Recommendations ..... 5**

    6.1 Earthwork Recommendations for Pavement Subgrade ..... 5

        6.1.1 Subgrade Preparation ..... 5

        6.1.2 Fill Placement and Compaction ..... 6

    6.2 Aggregate Base Course ..... 6

    6.3 Concrete Degradation Due to Sulfate Attack ..... 6

    6.4 Construction Observation ..... 6

**7 Closure ..... 6**

**Figures**

Figure 1: Vicinity Map

Figure 2: Site and Exploration Plan

**List of Appendices**

Appendix A: Test Boring Logs

Appendix B: Laboratory Test Results

Appendix C: Pavement Design Calculations

## **1 Introduction**

Entech Engineering, Inc. (Entech) completed a subsurface exploration program and a pavement design for roadways within the Latigo Trails Filing No. 9. This report describes the subsurface exploration program conducted for the proposed roadway improvements and provides a pavement section alternative and construction recommendations. Entech participated in this project as a subconsultant to RDMA, LLC. The contents of this report, including the pavement design recommendations, are subject to the limitations and assumptions presented in Section 7.

## **2 Project Description**

Latigo Trails Filing No. 9 is located east of Curtis Road and south of Judge Orr Road in eastern El Paso County, Colorado (Figure 1). The proposed roadway construction includes portions of Conestoga Trail South, Buffalo River Trail, and the Horse Canyon Trail cul-de-sac. The extent of our investigation is shown in Figure 2. The topography of the site consists of gently rolling hills and valleys with rough-graded roads and utilities installed. Surrounding properties include vacant land or land being developed for residential lots. Vegetation was absent along the roadways due to recent site grading.

## **3 Subsurface Explorations and Laboratory Testing**

### **3.1 Subsurface Exploration Program**

Subsurface conditions at the project site were explored by ten test borings, designated TB-1 through TB-10, drilled on April 23, 2024. The locations of the test borings are shown on the Site and Exploration Plan (Figure 2). The borings were drilled to depths of 5 to 10 feet below the existing ground surface (bgs). The drilling was performed using a truck-mounted, continuous flight auger drill rig supplied and operated by Entech. Descriptive boring logs providing the lithologies of the subsurface conditions encountered during drilling are presented in Appendix A. Groundwater levels were measured in each of the open boreholes at the conclusion of drilling.

Soil and bedrock samples were obtained from the borings utilizing the Standard Penetration Test (ASTM D1586) using a split-barrel California sampler. Results of the Standard Penetration Test (SPT) are included on the boring logs in terms of N-values expressed in blows per foot (bpf). Soil and bedrock samples recovered from the borings were visually classified and recorded on the boring logs. The soil classifications were later verified utilizing laboratory testing and grouped by

soil type. The soil type numbers are included on the boring logs. It should be understood that the soil descriptions shown on the boring logs may vary between boring location and sample depths. It should also be noted that the lines of stratigraphic separation shown on the boring logs represent approximate boundaries between soil types and the actual stratigraphic transitions may be more gradual or variable with location.

### **3.2 Geotechnical Index and Engineering Property Testing**

Water content testing (ASTM D2216) was performed on the samples recovered from the borings and the results are shown on the boring logs. Grain-Size Analysis (ASTM D422) and Atterberg Limits testing (ASTM D4318) were performed on selected samples to assist in classifying the materials encountered in the borings.

One-dimensional swell/collapse testing (ASTM D4546) was performed on a select sample to determine the expansive or compressive characteristics of the soil. For pavement design, a modified proctor (ASTM D1557) and California Bearing Ratio (CBR) test (ASTM D1883) were completed. Soluble sulfate testing was performed on select soil samples to evaluate the potential for below-grade degradation of concrete due to sulfate attack. The laboratory testing results are presented in Appendix B and summarized in Table B-1.

## **4 Subgrade Conditions**

Four primary soil types and two bedrock types were encountered in the test borings drilled for the subsurface investigation. Each soil type was classified in accordance with the Unified Soil Classification System (USCS) and the American Association of State Highway and Transportation Officials (AASHTO) soil classification system using the laboratory testing results and the observations made during drilling.

### **4.1 Subsurface Conditions**

Subsurface conditions along the proposed roadway generally consisted of medium dense to dense silty to clayey sand fill (Soil Type 1), medium dense clayey sand fill (Soil Type 2), native dense silty sand to sand with silt (Soil Type 3), and native dense clayey sand (Soil Type 4). Sandstone bedrock, which classified as very dense silty sand to sand with silt (Soil Type 5) and (Soil Type 6), was also encountered. Water soluble sulfate tests indicated that the soils exhibit a negligible potential for sulfate attack. Laboratory test results are presented in Appendix B and are

summarized in Table B-1. Soil Types and corresponding AASHTO soil classifications are listed as follows:

- Soil Type 1: A-2-4 and A-1-b
- Soil Type 2: A-6
- Soil Type 3: A-1-b
- Soil Type 4: A-2-6
- Soil Type 5: A-1-b

Please identify the test sample from this group of soil types

#### 4.2 Groundwater

Groundwater was not encountered in the test borings. Groundwater fluctuations are possible and will depend on seasonal variations, local precipitation, runoff, and other factors; however, we do not anticipate groundwater to affect the proposed construction.

### 5 Pavement Design Recommendations

Pavement design recommendations were made in accordance with the *El Paso County Engineering Criteria Manual (ECM)*.

#### 5.1 Subgrade Conditions

Please add an explanation for why this was the sample chosen for the pavement design.

California Bearing Ratio (CBR) testing was performed on a representative sample of the Type 1 silty sand fill subgrade from TB-1 to determine the support characteristic of the subgrade soils for the roadway section. The results of the CBR testing are presented in Appendix B and summarized in Exhibit 1.

**Exhibit 1: Subsurface Laboratory Testing Summary**

Design Parameter	Value
Soil Type	1 – Silty Sand Fill
CBR at 95%	56.53
Design CBR	10
Liquid Limit	NV
Plasticity Index	NP
Percent Passing 200	31.9
AASHTO Classification	A-2-4
Unified Soils Classification	SM

## 5.2 Swell Mitigation

El Paso County requires swell mitigation for soils with swell testing results greater than 2% under a 150 pounds per square foot (psf) surcharge. Based on the classifications, mitigation for expansive soils will not be required on this site.

Please include a reference to the TIS included with Latigo Preserve Fil No. 9, PCD file number SF2136

## 5.3 Traffic Loading

Traffic data is not available for Latigo Trails, Filing No. 9; however, the roadways classify as local low-volume residential based on the current development plans. The *El Paso County Engineering Criteria Manual* provides default 18-kip equivalent single axle loadings (ESAL) based on the street classifications (ECM Section D.3.3, Table D-2). For design, a default ESAL value of 36,500 was used for the local low-volume residential designations.

Please double check the classification listed. These roads are rural local per the TIS and the low volume classification is only used for urban classifications

## 5.4 Pavement Design

The pavement section was determined utilizing the *El Paso County Engineering Criteria Manual*, the CBR testing, and the default ESAL value. Design parameters used in the pavement analysis are presented in Exhibit 2.

**Exhibit 2: Pavement Design Parameters**

Design Parameter	Value
Reliability	80%
Standard Deviation	0.45
Serviceability Loss ( $\Delta$ psi)	2.5
Design CBR	10
Resilient Modulus	15,000 psi
Structural Coefficients	
Hot Bituminous Pavement	0.44
Aggregate Base Course	0.11

The recommended hot mix asphalt (HMA) over aggregate base course (ABC) composite pavement section for the roadways at Latigo Trails Filing No. 9 is provided in Exhibit 3. The pavement design calculations are presented in Appendix C.

**Exhibit 3: Recommended Pavement Section**

Pavement Area	Design ESAL	Alternative <sup>1</sup>
Conestoga Trail South, Buffalo River Trail, and Horse Canyon Trail	36,500	1. 4.0 inches HMA over 4.0 inches ABC

*ABC = Aggregate Base Course; ESAL = equivalent single axle loads; HMA = Hot Mix Asphalt*

**Notes:**

1. Pavement alternative meets the minimum HMA and ABC thickness required per *El Paso County Pavement Design Manual*.

**6 Construction Recommendations**

Pavement design recommendations provided herein are contingent on good construction practices and poor construction techniques may result in poor performance. Our analyses assumed that this project will be constructed according to the *El Paso County Engineering Criteria Manual* and the *Pikes Peak Region Asphalt Paving Specifications*.

**6.1 Earthwork Recommendations for Pavement Subgrade**

Proper subgrade preparation is required for adequate pavement performance. Paving areas should be cleared of all deleterious materials including but not limited to: existing pavements, utility poles, and fence poles. Surface vegetation, if any, should be removed by stripping, with the depth to be field determined.

**6.1.1 Subgrade Preparation**

To provide uniform subgrade support and mitigate any potentially expansive soils, we recommend overexcavating 12 inches of the roadway subgrade, scarifying an additional 6 inches, moisture conditioning the scarified subgrade to within +/-2% of its optimum moisture content, and compacting it to 95% of the Modified Proctor Maximum Dry Density (ASTM D1557). The overexcavated subgrade soils can then be replaced in 6-inch compacted lifts to the same specifications as described above.

The final moisture-treated subgrade surface should be proof-rolled with a fully loaded, tandem-axle, 10-yard dump truck or equivalent. Any areas that are delineated to be soft, loose, or yielding during proof-rolling should be removed and reconditioned or replaced.

### 6.1.2 Fill Placement and Compaction

Granular fill placed as part of the pavement subgrade shall consist of non-expansive, granular soil, free of organic matter, unsuitable materials, debris, and cobbles greater than 3 inches in diameter. Additionally, any granular fill placed as part of the roadway subgrade should have a minimum CBR of 10. All granular fill placed within the pavement subgrade should be compacted to a minimum of 95% of its maximum Modified Proctor Dry Density (ASTM D1557) at +/-2% of optimum moisture content. Fill material should be placed in horizontal lifts such that each finished lift has a compacted thickness of 6 inches or less. Entech should approve any imported fill to be used within the pavement subgrade area prior to delivery to the site.

### 6.2 Aggregate Base Course

Reference ECM section D.5.5.1  
and table D-6

ABC materials shall conform to the *El Paso County Standard Specifications Manual*, Section 300 Aggregate Base Course. ABC materials should be compacted to a minimum of 95% of their maximum Modified Proctor Dry Density (ASTM D1557) at +/-2% of optimum moisture content.

### 6.3 Concrete Degradation Due to Sulfate Attack

Sulfate solubility testing was conducted on several samples recovered from the test borings to evaluate the potential for sulfate attack on concrete. The test results indicated less than 0.01% soluble sulfate (by weight). The test results indicate the sulfate component of the in-place soils presents a negligible exposure threat to concrete placed below the site grade.

Type 1L or Type II cement is recommended for all concrete on this site. To further avoid concrete degradation during construction, it is recommended that concrete not be placed on frozen or wet ground.

### 6.4 Construction Observation

Subgrade preparation for pavement structures should be observed by Entech in order to verify that (1) no anomalies are present, (2) materials similar to those described in this report have been encountered or placed, and (3) no soft spots, expansive or organic soil, or debris are present in the pavement subgrade prior to paving.



## 7 Closure

The subsurface investigation, geotechnical evaluation, and recommendations presented in this report are intended for use by RDMA with application to the paving of the Latigo Trails Filing No.



9 project in east El Paso County, Colorado. In conducting the subsurface investigation, laboratory testing, engineering evaluation, and reporting, Entech Engineering, Inc. endeavored to work in accordance with generally accepted professional geotechnical and geologic practices and principles consistent with the level of care and skill ordinarily exercised by members of the geotechnical profession currently practicing in the same locality and under similar conditions. No other warranty, expressed or implied, is made. During final design and/or construction, if conditions are encountered that appear different from those described in this report, Entech Engineering, Inc. requests to be notified so that the evaluation and recommendations presented herein can be reviewed and modified as appropriate.

If there are any questions regarding the information provided herein, or if Entech Engineering, Inc. can be of further assistance, please do not hesitate to contact us.




**ENTECH**  
ENGINEERING, INC.

**VICINITY MAP**  
LATIGO TRAILS FILING No. 9  
RDMA

JOB NO.  
231802

**FIG. 1**



CONESTOGA TRAIL SOUTH, BUFFALO RIVER TRAIL, HORSE CANYON TRAIL

Roadway Classification: Local **low-volume** Residential

Design 18-kip ESAL = 36,500

Soil Type 1 (AASHTO A-2-4)

Pavement Section: 4" HMA over 4" ABC

Please add a hatching or color indicating the areas to receive the proposed pavement section



**TB- APPROXIMATE TEST BORING LOCATION AND NUMBER**




**SITE AND EXPLORATION PLAN**

LATIGO TRAILS FILING No. 9  
RDMA

JOB NO.  
231802

**FIG. 2**



## **APPENDIX A: Test Boring Logs**

**TABLE A-1**  
**DEPTH TO BEDROCK**

TEST BORING	DEPTH TO BEDROCK (ft.)
1	4
2	>5
3	3
4	SURFACE
5	SURFACE
6	SURFACE
7	SURFACE
8	SURFACE
9	4
10	4

TEST BORING 1  
DATE DRILLED 4/23/2024

TEST BORING 2  
DATE DRILLED 4/23/2024

REMARKS

REMARKS

DRY TO 10', 4/23/24

DRY TO 5', 4/23/24

FILL 0-4', SAND, SILTY, BROWN,  
MEDIUM DENSE, MOIST

FILL 0-5', SAND, CLAYEY, BROWN,  
MEDIUM DENSE, MOIST

SANDSTONE, VERY WEAK,  
BROWN, MODERATELY  
WEATHERED (SAND, SILTY, VERY  
DENSE, MOIST)

Depth (ft)	Symbol	Samples	Blows per foot	Watercontent %	Soil Type	Depth (ft)	Symbol	Samples	Blows per foot	Watercontent %	Soil Type
0-4	(Symbol)		17	9.4	1	0-5	(Symbol)		16	8.4	1
5	(Symbol)	50 10"	50 10"	6.4	5	5	(Symbol)		17	7.2	1
10	(Symbol)	50 8"	50 8"	7.8	5	10	(Symbol)				
15	(Symbol)					15	(Symbol)				
20	(Symbol)					20	(Symbol)				



**TEST BORING LOGS**  
LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802

**FIG. A-1**

TEST BORING 3  
 DATE DRILLED 4/23/2024

TEST BORING 4  
 DATE DRILLED 4/23/2024

REMARKS

REMARKS

DRY TO 5', 4/23/24

FILL 0-2', SAND, CLAYEY, BROWN, DENSE, MOIST  
 SAND, SILTY, BROWN  
 SANDSTONE, EXTREMELY WEAK, LIGHT BROWN, HIGHLY WEATHERED (SAND, CLAYEY, VERY DENSE, MOIST)

Depth (ft)	Symbol	Samples	Blows per foot	Watercontent %	Soil Type
0-2	[Symbol]		31	3.9	1
2-3	[Symbol]				3
3-5	[Symbol]		50	9.3	6
5-10	[Symbol]		10"		
10-15	[Symbol]				
15-20	[Symbol]				
20	[Symbol]				

DRY TO 10', 4/23/24

SANDSTONE, EXTREMELY WEAK, TAN, HIGHLY WEATHERED (SAND, WITH SILT, VERY DENSE, MOIST)

Depth (ft)	Symbol	Samples	Blows per foot	Watercontent %	Soil Type
0-5	[Symbol]		50	5.6	5
5-11"	[Symbol]		11"		
11-9"	[Symbol]		9"	8.4	5
9-10"	[Symbol]		10"	8.5	5
10-15	[Symbol]		4"		
15-20	[Symbol]				
20	[Symbol]				



**TEST BORING LOGS**  
 LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. A-2**

TEST BORING 5  
DATE DRILLED 4/23/2024

TEST BORING 6  
DATE DRILLED 4/23/2024

REMARKS

REMARKS

DRY TO 5', 4/23/24

SANDSTONE, EXTREMELY WEAK,  
TAN, HIGHLY WEATHERED (SAND,  
WITH SILT to SAND, CLAYEY, VERY  
DENSE, MOIST)

Depth (ft)	Symbol	Samples	Blows per foot	Watercontent %	Soil Type
5	[Symbol]	[Sample]	50 11"	7.2	5
5	[Symbol]	[Sample]	50 9"	7.2	5
10	[Symbol]	[Sample]			
15	[Symbol]	[Sample]			
20	[Symbol]	[Sample]			

DRY TO 5', 4/23/24

SANDSTONE, EXTREMELY WEAK,  
TAN, HIGHLY WEATHERED (SAND,  
WITH SILT, VERY DENSE, MOIST)

Depth (ft)	Symbol	Samples	Blows per foot	Watercontent %	Soil Type
5	[Symbol]	[Sample]	50 11"	6.5	5
5	[Symbol]	[Sample]	50 9"	12.8	5
10	[Symbol]	[Sample]			
15	[Symbol]	[Sample]			
20	[Symbol]	[Sample]			



**TEST BORING LOGS**  
LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802

**FIG. A-3**



TEST BORING 7  
 DATE DRILLED 4/23/2024

TEST BORING 8  
 DATE DRILLED 4/23/2024

REMARKS

REMARKS

DRY TO 10', 4/23/24

SANDSTONE, EXTREMELY WEAK,  
 TAN, HIGHLY WEATHERED (SAND,  
 WITH SILT, VERY DENSE, MOIST)

SANDSTONE, VERY WEAK, TAN,  
 MODERATELY WEATHERED  
 (SAND, CLAYEY, VERY DENSE,  
 MOIST)

Depth (ft)	Symbol	Samples	Blows per foot	Watercontent %	Soil Type
5	[Symbol]	[Sample]	50 6"	4.1	5
5	[Symbol]	[Sample]	50 6"	5.5	5
10	[Symbol]	[Sample]	50 6"	9.8	6

DRY TO 5', 4/23/24

SANDSTONE, EXTREMELY WEAK,  
 OLIVE, HIGHLY WEATHERED  
 (SAND, CLAYEY, DENSE to VERY  
 DENSE, MOIST)

Depth (ft)	Symbol	Samples	Blows per foot	Watercontent %	Soil Type
5	[Symbol]	[Sample]	41	8.9	6
5	[Symbol]	[Sample]	50 11"	8.2	6



**TEST BORING LOGS**  
 LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. A-4**

TEST BORING 9  
DATE DRILLED 4/23/2024

TEST BORING 10  
DATE DRILLED 4/23/2024

REMARKS

REMARKS

DRY TO 5', 4/23/24

SAND, WITH SILT, BROWN, MEDIUM DENSE, MOIST

SANDSTONE, VERY WEAK, LIGHT BROWN, MODERATELY WEATHERED (SAND, SILTY, VERY DENSE, MOIST)


Depth (ft)	Symbol	Samples	Blows per foot	Watercontent %	Soil Type
0-5	(Symbol: dots and dashes)		24	3.6	3
5	(Symbol: dots)	50 9"		9.8	5
10					
15					
20					

DRY TO 5', 4/23/24

FILL 0-4', SAND, CLAYEY, BROWN, MEDIUM DENSE, MOIST

SANDSTONE, EXTREMELY WEAK, LIGHT BROWN, MODERATELY WEATHERED (SAND, CLAYEY, DENSE, MOIST)

Depth (ft)	Symbol	Samples	Blows per foot	Watercontent %	Soil Type
0-4	(Symbol: dots and dashes)		10	9.9	2
5	(Symbol: dots)	37	7.7		6
10					
15					
20					



**TEST BORING LOGS**  
LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802  
**FIG. A-5**



## **APPENDIX B: Laboratory Test Results**

**TABLE B-1  
SUMMARY OF LABORATORY TEST RESULTS**


SOIL TYPE	TEST BORING NO.	DEPTH (FT)	WATER (%)	DRY DENSITY (PCF)	PASSING NO. 200 SIEVE (%)	LIQUID LIMIT	PLASTIC LIMIT	PLASTIC INDEX	SULFATE (WT %)	SWELL/ COLLAPSE (%)	AASHTO CLASS.	USCS	SOIL DESCRIPTION
1, CBR	1	0-3			31.9	NV	NP	NP			A-2-4	SM	FILL, SAND, SILTY
1	1	1-2			23.1	28	22	6			A-1-b	SM	FILL, SAND, SILTY
1	2	1-2			20.6	30	20	10	<0.01		A-2-4	SC	FILL, SAND, CLAYEY
1	3	1-2			19.3	28	24	4			A-1-b	SM	FILL, SAND, CLAYEY
2	10	1-2			40.0	37	23	14	<0.01		A-6	SC	FILL, SAND, CLAYEY
3	9	1-2			8.4	NV	NP	NP			A-1-b	SW-SM	SAND, WITH SILT
3	8	1-2			8.8	NV	NP	NP	<0.01		A-1-b	SW-SM	SAND, WITH SILT
4	10	5			37.4	24	15	9			A-2-6	SC	SAND, CLAYEY
5	4	1-2			7.6	NV	NP	NP			A-1-b	SW-SM	SANDSTONE (SAND, WITH SILT)
5	5	1-2			11.6	NV	NP	NP			A-1-b	SW-SM	SANDSTONE (SAND, WITH SILT)
5	6	1-2			7.6	NV	NP	NP			A-1-b	SW-SM	SANDSTONE (SAND, WITH SILT)
5	7	1-2			8.2	NV	NP	NP			A-1-b	SW-SM	SANDSTONE (SAND, WITH SILT)
5	1	10			15.0	31	23	8			A-1-b	SM	SANDSTONE (SAND, SILTY)
5	9	5			15.7	NV	NP	NP			A-1-b	SM	SANDSTONE (SAND, SILTY)
6	3	5			31.1	28	19	9	<0.01		A-2-4	SC	SANDSTONE (SAND, CLAYEY)
6	8	5			13.1	41	21	20			A-2-6	SC	SANDSTONE (SAND, CLAYEY)
6	7	10	14.8	85.6	35.2				<0.01	-2.8		SC	SANDSTONE (SAND, CLAYEY)

Please include moisture content for samples

TEST BORING 1  
DEPTH (FT) 0-3

SOIL DESCRIPTION FILL, SAND, SILTY  
SOIL TYPE 1, CBR

**Sieve Analysis  
Grain Size Distribution**



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3\"	
1 1/2\"	
3/4\"	
1/2\"	
3/8\"	100.0%
4	99.1%
10	88.7%
20	71.6%
40	58.9%
100	41.3%
200	31.9%

**ATTERBERG LIMITS**

Plastic Limit	NP
Liquid Limit	NV
Plastic Index	NP

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SM  
AASHTO CLASSIFICATION: A-2-4  
AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802

**FIG. B-1**

TEST BORING 1  
 DEPTH (FT) 1-2

SOIL DESCRIPTION FILL, SAND, SILTY  
 SOIL TYPE 1



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	97.9%
10	76.7%
20	60.2%
40	48.7%
100	30.7%
200	23.1%

**ATTERBERG LIMITS**

Plastic Limit	22
Liquid Limit	28
Plastic Index	6

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SM  
 AASHTO CLASSIFICATION: A-1-b  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. B-2**

TEST BORING 2  
 DEPTH (FT) 1-2

SOIL DESCRIPTION FILL, SAND, CLAYEY  
 SOIL TYPE 1



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	98.0%
10	77.7%
20	58.5%
40	46.0%
100	27.2%
200	20.6%

**ATTERBERG LIMITS**

Plastic Limit	20
Liquid Limit	30
Plastic Index	10

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SC  
 AASHTO CLASSIFICATION: A-2-4  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. B-3**

TEST BORING 3  
 DEPTH (FT) 1-2

SOIL DESCRIPTION FILL, SAND, CLAYEY  
 SOIL TYPE 1



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	95.4%
10	70.4%
20	43.3%
40	30.9%
100	22.2%
200	19.3%

**ATTERBERG LIMITS**

Plastic Limit	24
Liquid Limit	28
Plastic Index	4

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SM  
 AASHTO CLASSIFICATION: A-1-b  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**

LATIGO TRAILS, FILING NO. 9  
 RDMA


JOB NO.  
 231802

**FIG. B-4**



TEST BORING 4  
 DEPTH (FT) 1-2

SOIL DESCRIPTION SANDSTONE (SAND, WITH SILT)  
 SOIL TYPE 5



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	94.0%
10	65.4%
20	44.1%
40	29.9%
100	10.8%
200	7.6%

**ATTERBERG LIMITS**

Plastic Limit	NP
Liquid Limit	NV
Plastic Index	NP

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SW-SM  
 AASHTO CLASSIFICATION: A-1-b  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. B-5**

TEST BORING 5  
 DEPTH (FT) 1-2

SOIL DESCRIPTION SANDSTONE (SAND, WITH SILT)  
 SOIL TYPE 5



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	100.0%
3/8"	98.2%
4	85.8%
10	60.2%
20	46.9%
40	35.9%
100	17.4%
200	11.6%

**ATTERBERG LIMITS**

Plastic Limit	NP
Liquid Limit	NV
Plastic Index	NP

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SW-SM  
 AASHTO CLASSIFICATION: A-1-b  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. B-6**

TEST BORING 6  
 DEPTH (FT) 1-2

SOIL DESCRIPTION SANDSTONE (SAND, WITH SILT)  
 SOIL TYPE 5



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	88.4%
10	73.7%
20	55.7%
40	28.3%
100	10.3%
200	7.6%

**ATTERBERG LIMITS**

Plastic Limit	NP
Liquid Limit	NV
Plastic Index	NP

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SW-SM  
 AASHTO CLASSIFICATION: A-1-b  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. B-7**

TEST BORING 7  
 DEPTH (FT) 1-2

SOIL DESCRIPTION SANDSTONE (SAND, WITH SILT)  
 SOIL TYPE 5



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	100.0%
3/8"	89.2%
4	75.1%
10	51.0%
20	33.9%
40	19.6%
100	10.3%
200	8.2%

**ATTERBERG LIMITS**

Plastic Limit	NP
Liquid Limit	NV
Plastic Index	NP

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SW-SM  
 AASHTO CLASSIFICATION: A-1-b  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**

LATIGO TRAILS, FILING NO. 9  
 RDMA


JOB NO.  
 231802

**FIG. B-8**

TEST BORING 8  
 DEPTH (FT) 1-2

SOIL DESCRIPTION SAND, WITH SILT  
 SOIL TYPE 3

**Sieve Analysis  
 Grain Size Distribution**



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	100.0%
3/8"	95.5%
4	84.2%
10	57.7%
20	32.0%
40	20.1%
100	11.5%
200	8.8%

**ATTERBERG LIMITS**

Plastic Limit	NP
Liquid Limit	NV
Plastic Index	NP

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SW-SM  
 AASHTO CLASSIFICATION: A-1-b  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**

LATIGO TRAILS, FILING NO. 9  
 RDMA


JOB NO.  
 231802

**FIG. B-9**

TEST BORING 10  
DEPTH (FT) 1-2

SOIL DESCRIPTION FILL, SAND, CLAYEY  
SOIL TYPE 2

**Sieve Analysis  
Grain Size Distribution**



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	98.5%
10	85.0%
20	71.0%
40	59.6%
100	47.4%
200	40.0%

**ATTERBERG LIMITS**

Plastic Limit	23
Liquid Limit	37
Plastic Index	14

**SOIL CLASSIFICATION**

USCS CLASSIFICATION:	SC
AASHTO CLASSIFICATION:	A-6
AASHTO GROUP INDEX:	2



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802

**FIG. B-11**

TEST BORING 9  
 DEPTH (FT) 1-2

SOIL DESCRIPTION SAND, WITH SILT  
 SOIL TYPE 3



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	95.8%
10	71.8%
20	45.7%
40	26.4%
100	12.7%
200	8.4%

**ATTERBERG LIMITS**

Plastic Limit	NP
Liquid Limit	NV
Plastic Index	NP

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SW-SM  
 AASHTO CLASSIFICATION: A-1-b  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. B-10**

TEST BORING 1  
 DEPTH (FT) 10

SOIL DESCRIPTION SANDSTONE (SAND, SILTY)  
 SOIL TYPE 5



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	93.9%
10	60.9%
20	39.4%
40	26.5%
100	17.2%
200	15.0%

**ATTERBERG LIMITS**

Plastic Limit	23
Liquid Limit	31
Plastic Index	8

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SM  
 AASHTO CLASSIFICATION: A-1-b  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**

LATIGO TRAILS, FILING NO. 9  
 RDMA


JOB NO.  
 231802

**FIG. B-12**



TEST BORING 9  
 DEPTH (FT) 5

SOIL DESCRIPTION SANDSTONE (SAND, SILTY)  
 SOIL TYPE 5



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	90.8%
10	55.2%
20	37.6%
40	29.2%
100	19.6%
200	15.7%

**ATTERBERG LIMITS**

Plastic Limit	NP
Liquid Limit	NV
Plastic Index	NP

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SM  
 AASHTO CLASSIFICATION: A-1-b  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. B-13**

TEST BORING 3  
 DEPTH (FT) 5

SOIL DESCRIPTION SANDSTONE (SAND, CLAYEY)  
 SOIL TYPE 6



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	
4	100.0%
10	96.8%
20	87.6%
40	68.7%
100	39.7%
200	31.1%

**ATTERBERG LIMITS**

Plastic Limit	19
Liquid Limit	28
Plastic Index	9

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SC  
 AASHTO CLASSIFICATION: A-2-4  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802

**FIG. B-14**

TEST BORING 8  
 DEPTH (FT) 5

SOIL DESCRIPTION SANDSTONE (SAND, CLAYEY)  
 SOIL TYPE 6



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	100.0%
3/8"	96.4%
4	86.6%
10	63.3%
20	40.4%
40	24.5%
100	15.8%
200	13.1%

**ATTERBERG LIMITS**

Plastic Limit	21
Liquid Limit	41
Plastic Index	20

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SC  
 AASHTO CLASSIFICATION: A-2-6  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. B-15**

TEST BORING 10  
 DEPTH (FT) 5

SOIL DESCRIPTION SAND, CLAYEY  
 SOIL TYPE 4



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	96.9%
10	86.1%
20	71.0%
40	61.2%
100	48.2%
200	37.4%

**ATTERBERG LIMITS**

Plastic Limit	15
Liquid Limit	24
Plastic Index	9

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SC  
 AASHTO CLASSIFICATION: A-2-6  
 AASHTO GROUP INDEX: 0



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
 RDMA

JOB NO.  
 231802

**FIG. B-16**

TEST BORING 7  
DEPTH (FT) 10

SOIL DESCRIPTION SANDSTONE (SAND, CLAYEY)  
SOIL TYPE 6



**GRAIN SIZE ANALYSIS**

U.S. Sieve #	Percent Finer
3"	
1 1/2"	
3/4"	
1/2"	
3/8"	100.0%
4	97.5%
10	87.6%
20	73.3%
40	63.9%
100	47.8%
200	35.2%

**SOIL CLASSIFICATION**

USCS CLASSIFICATION: SC  
AASHTO CLASSIFICATION:  
AASHTO GROUP INDEX:



**LABORATORY TEST RESULTS**


LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802

**FIG. B-17**

TEST BORING 7  
DEPTH (FT) 10

SOIL DESCRIPTION SANDSTONE (SAND, CLAYEY)  
SOIL TYPE 6



**SWELL/COLLAPSE TEST RESULTS**

NATURAL UNIT DRY WEIGHT (PCF): 86  
NATURAL MOISTURE CONTENT: 14.8%  
SWELL/COLLAPSE (%): -2.8%



**SWELL TEST RESULTS**

LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802

**FIG. B-18**


SAMPLE LOCATION TB-1 @ 0-3'

SOIL DESCRIPTION FILL, SAND, SILTY, BROWN  
SOIL TYPE 1

**PROCTOR DATA**

IDENTIFICATION: SM  
PROCTOR TEST #: 1  
TEST BY: DK  
TEST DESIGNATION: ASTM-1557-A  
MAXIMUM DRY DENSITY (PCF): 127.6  
OPTIMUM MOISTURE: 7.1

**Compaction Curve**



**LABORATORY TEST RESULTS**

LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802

**FIG. B-19**

SAMPLE LOCATION TB-1 @ 0-3'

SOIL DESCRIPTION FILL, SAND, SILTY, BROWN  
SOIL TYPE 1

**CBR TEST LOAD DATA**

Piston Diameter (cm): 4.958

Piston Area (in<sup>2</sup>): 2.993

Penetration Depth (inches)	10 BLOWS Mold # 1		25 BLOWS Mold # 2		56 BLOWS Mold # 3	
	Load (lbs)	Stress (psi)	Load (lbs)	Stress (psi)	Load (lbs)	Stress (psi)
0.000	0	0.00	0	0.00	0	0.00
0.025	437	146.03	746	249.29	1095	365.91
0.050	723	241.60	1440	481.20	2020	675.02
0.075	881	294.40	1855	619.88	2826	944.36
0.100	992	331.49	2166	723.81	3588	1198.99
0.125	1062	354.89	2410	805.34	4150	1386.80
0.150	1125	375.94	2600	868.84	4653	1554.88
0.175	1186	396.32	2768	924.98	5195	1736.00
0.200	1239	414.03	2916	974.43	5740	1918.12
0.300	1427	476.86	3482	1163.57	6000	2005.01
0.400	1565	522.97	3813	1274.18		
0.500	1713	572.43	4182	1397.49		

**MOISTURE AND DENSITY DATA**

	Mold # 1	Mold # 2	Mold # 3
Can #	350	351	352
Wt. Can	7.99	7.97	8.12
Wt. Can+Wet	239.14	232.82	196.74
Wt. Can+Dry	210.97	209.51	179.94
Wt. H2O	28.17	23.31	16.8
Wt. Dry Soil	202.98	201.54	171.82
Moisture Content	13.88%	11.57%	9.78%
Wet Density (PCF)	126.0	132.5	138.6
Dry Density (PCF)	117.6	123.7	129.4
% Compaction	92%	97%	101%
CBR	33.15	72.38	119.90

**PROCTOR DATA**

Maximum Dry Density (pcf)	127.6
Optimum Moisture	7.1
90% of Max. Dry Density (pcf)	114.8
95% of Max. Dry Density (pcf)	121.2

CBR at 90% of Max. Density = 15.26 ~ R VALUE 50

CBR at 95% of Max. Density = 56.53 ~ R VALUE 76



**LABORATORY TEST RESULTS**

LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802


**FIG. B-20**




SAMPLE LOCATION TB-1 @ 0-3'

SOIL DESCRIPTION FILL, SAND, SILTY, BROWN  
SOIL TYPE 1

Stress VS Penetration



Bearing Ratio VS Dry Density




LABORATORY TEST RESULTS

LATIGO TRAILS, FILING NO. 9  
RDMA

JOB NO.  
231802

FIG. B-21



## **APPENDIX C: Pavement Design Calculations**

## FLEXIBLE PAVEMENT DESIGN

### PROJECT DATA

Project Location: Latigo Trails Filing No. 9 Local (low volume) Roadways

Job Number: 231802

### DESIGN DATA

Equivalent (18-kip) Single Axle Load Applications (ESAL):	ESAL ( $W_{18}$ ) =	36,500
Design CBR	CBR =	10
Standard Deviation	$S_o$ =	0.44
Loss in Serviceability	$\Delta psi$ =	2.5
Reliability	Reliability =	80
Reliability (z-statistic)	$Z_R$ =	-0.84
Soil Resilient Modulus	$M_R$ =	15,000 psi

Required Structural Number (SN): ➔ SN = 1.38

### DESIGN EQUATIONS

#### Resilient Modulus

If using CBR:

$$M_R = (CBR) \times 1,500$$

If using R-Value:

$$M_R = 10^{[(S_1 + 18.72) / 6.24]} \text{ where } S_1 = [(R\text{-value} - 5) / 11.29] + 3$$

#### Required Structural Number

$$\log_{10} W_{18} = Z_R \cdot S_o + 9.36 \cdot \log_{10} (SN+1) - 0.20 + \frac{\log_{10} \left[ \frac{\Delta PSI}{4.2 - 1.5} \right]}{0.40 + \frac{1094}{(SN+1)^{5.19}}} + 2.32 \cdot \log_{10} M_R - 8.07$$

#### Pavement Section Thickness

$SN^* = C_1 D_1 + C_2 D_2$       where:

- $C_1$  = Strength Coefficient - HMA
- $C_2$  = Strength Coefficient - ABC
- $D_1$  = Depth of HMA (inches)
- $D_2$  = Depth of ABC (inches)

### RECOMMENDED THICKNESSES

Layer	Material	Coefficient	Thickness ( $D^*_i$ )	$SN^*_i$	SN
1	HMA	$C_1 = 0.44$	4.0 inches	1.760	-
2	ABC	$C_2 = 0.12$	4.0 inches	0.480	
				$SN^* = 2.240$	1.38

Pavement SN > Required SN, Design is Acceptable

Please revise this value per ECM table D-3

# Pavement Design Report\_.pdf Markup Summary

## Engineer (13)

s and corresponding AASHTO soil classification:

-b [Please identify the test sample from this group of soil types](#)

**Subject:** Engineer  
**Page Label:** 5  
**Author:** dotdilts  
**Date:** 9/12/2024 10:27:18 AM  
**Status:**  
**Color:** ■  
**Layer:**  
**Space:**

Please identify the test sample from this group of soil types

  
INTRECH  
INTRECH is a leading provider of software solutions for the construction industry. Our software solutions help construction professionals manage their business more effectively and efficiently. We offer a wide range of software solutions for construction professionals, including project management, financial management, and human resources management. Our software solutions are designed to be easy to use and integrate with existing systems. We are committed to providing excellent customer service and support. For more information, please contact us at [info@intrech.com](mailto:info@intrech.com).


**Subject:** Engineer  
**Page Label:** 6  
**Author:** dotdilts  
**Date:** 9/12/2024 10:40:24 AM  
**Status:**  
**Color:** ■  
**Layer:**  
**Space:**

Please include a reference to the TIS included with Latigo Preserve Fil No. 9, PCD file number SF2136

  
INTRECH  
INTRECH is a leading provider of software solutions for the construction industry. Our software solutions help construction professionals manage their business more effectively and efficiently. We offer a wide range of software solutions for construction professionals, including project management, financial management, and human resources management. Our software solutions are designed to be easy to use and integrate with existing systems. We are committed to providing excellent customer service and support. For more information, please contact us at [info@intrech.com](mailto:info@intrech.com).

**Subject:** Engineer  
**Page Label:** 6  
**Author:** dotdilts  
**Date:** 9/12/2024 10:56:41 AM  
**Status:**  
**Color:** ■  
**Layer:**  
**Space:**

# #  
# 7 6 #0+

  
INTRECH  
INTRECH is a leading provider of software solutions for the construction industry. Our software solutions help construction professionals manage their business more effectively and efficiently. We offer a wide range of software solutions for construction professionals, including project management, financial management, and human resources management. Our software solutions are designed to be easy to use and integrate with existing systems. We are committed to providing excellent customer service and support. For more information, please contact us at [info@intrech.com](mailto:info@intrech.com).

**Subject:** Engineer  
**Page Label:** 6  
**Author:** dotdilts  
**Date:** 9/12/2024 10:58:43 AM  
**Status:**  
**Color:** ■  
**Layer:**  
**Space:**

Please double check the classification listed. These roads are rural local per the TIS and the low volume classification is only used for urban classifications

  
INTRECH  
INTRECH is a leading provider of software solutions for the construction industry. Our software solutions help construction professionals manage their business more effectively and efficiently. We offer a wide range of software solutions for construction professionals, including project management, financial management, and human resources management. Our software solutions are designed to be easy to use and integrate with existing systems. We are committed to providing excellent customer service and support. For more information, please contact us at [info@intrech.com](mailto:info@intrech.com).

**Subject:** Engineer  
**Page Label:** 8  
**Author:** dotdilts  
**Date:** 9/12/2024 11:02:57 AM  
**Status:**  
**Color:** ■  
**Layer:**  
**Space:**

, !! ! ; % 0

Modified Proctor Dry Density (ASTM D1557) at +1-2% of should be placed in horizontal lifts such that each finished lift is less than 100mm. Intretech should approve any imported fill to be used prior to delivery to the site.  
[Reference ECM section D.5.5.1 and table D-6](#)  
\*See County Standard Specifications Manual, Section 200.00. Imported fill should be compacted to a minimum of 95% of that of (ASTM D1557) at +1-2% of optimum moisture content.  
Sulfate Attack

**Subject:** Engineer  
**Page Label:** 8  
**Author:** dotdilts  
**Date:** 9/12/2024 11:05:48 AM  
**Status:**  
**Color:** ■  
**Layer:**  
**Space:**

Reference ECM section D.5.5.1 and table D-6

H, BUFFALO RIVER  
ocal low-volume Resi  
500  
4)

**Subject:** Engineer  
**Page Label:** 11  
**Author:** dotdilts  
**Date:** 9/12/2024 11:06:59 AM  
**Status:**  
**Color:**   
**Layer:**  
**Space:**

ow volume

TRAIL HORSE CANYON TRAIL  
Please add a hatching or color indicating the areas to receive the proposed pavement section

**Subject:** Engineer  
**Page Label:** 11  
**Author:** dotdilts  
**Date:** 9/12/2024 11:08:16 AM  
**Status:**  
**Color:**   
**Layer:**  
**Space:**

Please add a hatching or color indicating the areas to receive the proposed pavement section

Station	Moisture	Temp	Sample
1+00	11.5	20	100
1+05	11.5	20	100
1+10	11.5	20	100
1+15	11.5	20	100
1+20	11.5	20	100
1+25	11.5	20	100
1+30	11.5	20	100
1+35	11.5	20	100
1+40	11.5	20	100
1+45	11.5	20	100
1+50	11.5	20	100

Please include moisture content for samples

**Subject:** Engineer  
**Page Label:** 20  
**Author:** dotdilts  
**Date:** 9/12/2024 11:11:54 AM  
**Status:**  
**Color:**   
**Layer:**  
**Space:**

Please include moisture content for samples

Design Recommendations  
Please add an explanation for why this was the sample chosen for the pavement design.

**Subject:** Engineer  
**Page Label:** 5  
**Author:** dotdilts  
**Date:** 9/12/2024 11:37:29 AM  
**Status:**  
**Color:**   
**Layer:**  
**Space:**

Please add an explanation for why this was the sample chosen for the pavement design.

U.T.T  
0.12

**Subject:** Engineer  
**Page Label:** 43  
**Author:** dotdilts  
**Date:** 9/12/2024 11:40:13 AM  
**Status:**  
**Color:**   
**Layer:**  
**Space:**

\* (&

Layer	Material	Coefficient	TS
1	HMA	C <sub>1</sub> = 0.44	4
2	ABC	C <sub>2</sub> = 0.12	4

Please revise this value per ECM table D-3


**Subject:** Engineer  
**Page Label:** 43  
**Author:** dotdilts  
**Date:** 9/12/2024 11:41:16 AM  
**Status:**  
**Color:**   
**Layer:**  
**Space:**

Please revise this value per ECM table D-3

the maximum Modified Proctor Dry Density (ASTM D1557) at  $\pm 2\%$  of the maximum dry density. The material should be placed in horizontal lifts such that each lift is 4 to 6 inches or less. Each lift should represent any required lift or subgrade area prior to delivery to the site.

conform to the [411000 County Standard Specifications Manual](#), Section 2.02.01. All materials should be compacted to a minimum of 95% of the maximum dry density (ASTM D1557) at  $\pm 2\%$  of optimum moisture content.

Test Due to Sulfate Attack  
was conducted on several samples recovered from the best barge sulfate attack on concrete. The best results indicated less than 0.5

-----  
**Subject:** Engineer  
**Page Label:** 8  
**Author:** dotdilts  
**Date:** 9/12/2024 2:56:53 PM  
**Status:**  
**Color:**   
**Layer:**  
**Space:**

!

\*