

Planning and Community Development Department 2880 International Circle Colorado Springs, Colorado 80910

DEVIATION REQUEST AND DECISION FORM

Updated: 6/26/2019

Phone: 719.520.6300 Fax: 719.520.6695

Website www.elpasoco.com

PROJECT INFORMATION

Project Name: Sterling Ranch - CDR 20-005 Vollmer, Marksheffel and Sterling Ranch Rd. Construction Drawing Review

Schedule No.(s): 5200000364

Legal Description: PT SE4SE4 LY S of Vollmer Rd ex RD w/ MR Sect 32-12-65 Ex Tr 2 Conv by Rec #210065613

APPLICANT INFORMATION

Company: SR Land, LLC.
Name: Jim Morley

Mailing Address: 20 Boulder Crescent, Suite 102, COLORADO SPRINGS, COLORADO, 80903

Phone Number: (719) 491-3024

FAX Number: N/A

Email Address: Jmorley3870@aol.com

ENGINEER INFORMATION

Company: JR ENGINEERING

Name: MIKE BRAMLETT Colorado P.E. Number: 32314

Mailing Address: 5475 TECH CENTER DRIVE, SUITE 235, COLORADO SPRINGS, COLORADO 80919

Phone Number: 719-593-2593

FAX Number: N/A

Email Address: MBRAMLETT@JRENGINEERING.COM

L

OWNER, APPLICANT, AND ENGINEER DECLARATION

To the best of my knowledge, the information on this application and all additional or supplemental documentation is true, factual and complete. I am fully aware that any misrepresentation of any information on this application may be grounds for denial. I have familiarized myself with the rules, regulations and procedures with respect to preparing and filing this application. I also understand that an incorrect submittal will be cause to have the project removed from the agenda of the Planning Commission, Board of County Commissioners and/or Board of Adjustment or delay review until corrections are made, and that any approval of this application is based on the representations made in the application and may be revoked on any breach of representation or condition(s) of approval.

Signature of owner (or author	ized representative)	•	•	•	Da
Engineer's Seal, Signature And Date of Signature	Г		7		

L

DEVIATION REQUEST (Attach diagrams, figures, and other documentation to clarify request)

A deviation from the standards of or in Section ECM section 2.2.4 Roadway Functional Classifications of the	Engineering Cri	teria
Manual (ECM) is requested for the Marksheffel Road Right of Way and cross section.		

Identify the specific ECM standard which a deviation is requested:				
Identify the specific ECM standard which a deviation is requested: Marksheffel Road will be owned and maintained by the City of Colorado Springs as a 4 lane urban principal arterial cross section.				
The ECM does not currently have a cross section that is consistent with the city standard for this type of roadway.				
The Edwidoes not currently have a cross section that is consistent with the city standard for this type of foadway.				
State the reason for the requested deviation:				
The purpose of this deviation is to document the cross-section and ROW dedication necessary to be build Marksheffel Rd to the				
city standard from Vollmer Road to just south of the intersection of Sterling Ranch road.				
In the future(Sterling Ranch Phase 2) Marksheffel will be constructed using the city cross section south to the Sterling Ranch				
boundary.				
For lain the ground allowed the and according to the FOM standards (Managerial and Sable and Sab				
Explain the proposed alternative and compare to the ECM standards (May provide applicable regional or national standards used				
as basis):				
See Exhibit A for a cross section and right of way width that is proposed for Marksheffel Road.				
The applicant will provide:				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides.				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side.				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				
From station 43+43.86 to station 45+93.94: A 119 foot wide right of way to allow for turning movements at .Vollmer Road. The pavement mat will be 80 ft wide with 30" wide curb and gutter both sides. From station 45+94 to station 47+74: A transitional taper to the "typical cross section From station 47+74 to the end of the proposed roadway within Filing 2 at station 57+65: The typical cross section of a107 foot wide right of way. The pavement mat will be 68 ft wide providing 4 through lanes with a six foot asphalt should on each side. There will be a 12 ft. wide striped median to provide for turning movements See Exhibit B for a history of earlier discussions on the roadway requirements and eventual Memo of Understanding between El				

TS OF CONSIDERATION east one of the conditions listed below must be met for this deviation request to be considered.)	
The ECM standard is inapplicable to the particular situation. Topography, right-of-way, or other geographical conditions or impediments impose an undue hardship and an equivaler rnative that can accomplish the same design objective is available and does not compromise public safety or accessib. A change to a standard is required to address a specific design or construction problem, and if not modified, the standard one an undue hardship on the applicant with little or no material benefit to the public.	ility.
vide justification: Engineering Criteria Manual does not contemplate roadways that will be owned and maintained by the City of Coloracings.	ob
ERIA FOR APPROVAL	
ECM section 5.8.7 the request for a deviation may be considered if the request is not based exclusively on financial iderations . The deviation must not be detrimental to public safety or surrounding property. The applicant must include orting information demonstrating compliance with all of the following criteria :	
deviation will achieve the intended result with a comparable or superior design and quality of improvement.	
s request is not based on financial considerations. The roadway will be owned and maintained by the City of Colorado	Springs.
e deviation will not adversely affect safety or operations.	
deviation will not adversely affect safety or operations. deviation will not adversely affect safety or operations as it is part of the City roadway system.	

The deviation will not adversely affect maintenance and its associated cost.				
Maintenance of the El Paso County roadways will not be impacted as it is part of the City roadway system.				
The deviation will not adversely affect aesthetic appearance.				
The deviation has no bearing on the aesthetic appearance.				
The deviation has no bearing on the destricted appearance.				
The deviation meets the design intent and nurnose of the FCM standards				
The deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
The deviation meets the design intent and purpose of the ECM standards. Yes, the deviation meets the design intent and purpose of the ECM standards.				
Yes, the deviation meets the design intent and purpose of the ECM standards.				
Yes, the deviation meets the design intent and purpose of the ECM standards. The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable.				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				
Yes, the deviation meets the design intent and purpose of the ECM standards. The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable.				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				
The deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, as applicable. Yes, the deviation meets the control measure requirements of Part I.E.3 and Part I.E.4 of the County's MS4 permit, this project is				


REVIEW AND RECOMMENDATION:

Approved by the ECM Administrator		
This request has been determined to have met the criteria for approval. hereby granted based on the justification provided.	A deviation from Section	_ of the ECM is
Γ	٦	
1	I	
	-	
Denied by the ECM Administrator		
This request has been determined not to have met criteria for approval. hereby denied.	A deviation from Section	_ of the ECM is
Γ	٦	
L	J	

ECM ADMINISTRATOR COMMENTS/CONDITIONS:

Conditions of deviation approval:

- 1. El Paso County will not maintain Marksheffel Road with the proposed design, and will only facilitate approvals and coordinate transfer of the road, upon completion of construction, to the City of Colorado Springs. Ultimate plan approval, notice to proceed, and MS4/stormwater enforcement remains under the County's jurisdiction until such time that the road is actually annexed into the City.
- 2. Construction of the approved cross-section (above) is at the developer's risk as the County cannot guarantee City acceptance of the road and associated deeds. Any revisions necessary to meet County requirements due to a change in City commitments will be the developer's responsibility.
- 3. The City may require construction of the full four-lane cross-section from Vollmer Road southeast along platted areas (Sterling Ranch Filing No. 2).
- 4. The City may require a 25% escrow contribution to the traffic signal at Vollmer Road.
- 5. The intersection at Vollmer Road shall be designed and constructed to allow for realignment of Tahiti Drive from the northwest at an appropriate location entering the new intersection.
- 6. Any additional easements necessary for drainage, slope easements and other public improvements shall be shown on plans as "public improvements easements." If these easements are required, they shall be provided by separate recorded document (non-exclusive public easements) approved by El Paso County and referenced on the plans prior to plan approval.
- 7. A 25-foot non-exclusive County trail corridor easement is required along the northeast side of Marksheffel Road and shall be shown on all plans. It is assumed that this corridor will remain under County Jurisdiction.



TYPICAL SECTION
MARKSHEFFEL ROAD
STERLING RANCH FIL 2
JOB NO. 2518801
JAN, 26, 2021
SHEET 1 OF 1



Centennial 303-740-9393 • Colorado Springs 719-593-2593 Fort Collins 970-491-9888 • www.jrengineering.com