Stormwater Detention and Infiltration Design Data Sheet

Workbook Protectes

Worksheet Protects

Stormwater Facility Name: Sievers Business Center Extended Detention Basin

Facility Location & Jurisdiction: 1945 Deer Creek Road, El Paso County

User Input: Watershed Characteristics

ft/ft	0.028	Watershed Slope =
ft	530	Watershed Length =
acres	2.77	Watershed Area =
percent	82.9%	Watershed Imperviousness =
percent		Percentage Hydrologic Soil Group A =
percent	100.0%	Percentage Hydrologic Soil Group B =
percent		Percentage Hydrologic Soil Groups C/D =

Location for 1-hr Rainfall Depths (use dropdown):

User Input

WQCV Treatment Method = Extended Detention

User Defined	User Defined	User Defined User Defin	
Stage [ft]	Area [ft^2]	Stage [ft]	Discharge [cfs]
0.00	0	0.00	0.00
0.20	123	0.20	0.01
1.20	448	1.20	0.01
2.20	1,252	2.20	0.03
3.20	2,497	3.20	0.04
4.20	3,863	4.20	0.07
5.20	5,157	5.20	0.09
6.20	6,602	6.20	3.12
7.20	7,949	7.20	4.28
			-
-			
-	-		
 			-
			-

After completing and printing this worksheet to a pdf, go to: https://maperture.digitaldataservices.com/gvh/?viewer=cswdif create a new stormwater facility, and attach the pdf of this worksheet to that record.

Routed Hydrograph Results

	Routed Hyurd	graph Results					200
Design Storm Return Period =	WQCV	2 Year	5 Year	10 Year	50 Year	100 Year	
One-Hour Rainfall Depth =	0.53	1.19	1.50	1.75	2.25	2.52	in
Calculated Runoff Volume =	0.080	0.217	0.284	0.350	0.478	0.552	acre-ft
OPTIONAL Override Runoff Volume =							acre-ft
Inflow Hydrograph Volume =	0.080	0.216	0.283	0.349	0.478	0.552	acre-ft
Time to Drain 97% of Inflow Volume =	35.5	55.3	59.5	58.1	55.8	54.5	hours
Time to Drain 99% of Inflow Volume =	37.5	60.6	66.1	65,5	64.3	63.5	hours
Maximum Ponding Depth =	3.27	4.83	5.29	5.54	5.96	6.17	ft
Maximum Ponded Area =	0.06	0.11	0.12	0.13	0.14	0.15	acres
Maximum Volume Stored =	0.073	0.204	0.256	0.287	0.344	0.376	acre-ft

Stormwater Detention and Infiltration Design Data Sheet

