



COLUMN PLAN

SCALE: 1" = 4'

N



COLUMN PLAN LEGEND

- - 3-2x6 LAMINATED COLUMN LOCATION
- - 3-2x8 LAMINATED COLUMN LOCATION
- - 4-2x10 LAMINATED COLUMN LOCATION
- - HEADERED TRUSS LOCATION
- ⊙ - (12) 12'-2" x 14'-1" OVERHEAD DOORS
- ⊙ - DOUBLE 3/4" OSB SHEARWALL LOCATION (SEE DETAILS ON SHEET S5)
- ⊙ - CONTINUE OVERHEAD DOOR HEADER THROUGH THESE BAYS
- 18" - 18" DIAMETER FOOTING WITH 4" TO BOTTOM OF 21" THICK CONCRETE PAD (2500 PSI MINIMUM), 20" BELOW BOTTOM OF PRECAST CONCRETE COLUMN AROUND EXPOSED REBAR CAGE AND 3/4"x1/4" THREADED ROD WITH AN ADDITIONAL MINIMUM 1" ABOVE BOTTOM OF PRECAST CONCRETE COLUMN. PLACE CONCRETE BELOW AND ABOVE BOTTOM OF LOWER COLUMN IN ONE OPERATION.
- 30" - 30" DIAMETER FOOTING WITH 4" TO BOTTOM OF 21" THICK CONCRETE PAD (2500 PSI MINIMUM), 20" BELOW BOTTOM OF PRECAST CONCRETE COLUMN AROUND EXPOSED REBAR CAGE AND 3/4"x1/4" THREADED ROD WITH AN ADDITIONAL MINIMUM 1" ABOVE BOTTOM OF PRECAST CONCRETE COLUMN. PLACE CONCRETE BELOW AND ABOVE BOTTOM OF LOWER COLUMN IN ONE OPERATION.

T-GAP STORAGE
 COLORADO SPRINGS, CO

CO ALLIED DESIGN ARCHITECTURAL & ENGINEERING GROUP, P.C.
 100 S. PRESHING P.O. BOX 110 MORTON, IL 61550
 PHONE NUMBER: 309-268-4105

DRAWN BY:	MILICH
DATE:	1/26/2017
CHECKED BY:	B. HUGHEY
DATE:	2/16/2017
REVISED DATE:	---
REVISED DATE:	---
REVISED DATE:	---

