

# Construction Drawings\_V2.pdf Markup Summary 12-7-2021

## EPC Stormwater - Glenn Reese (4)

Label TSB B on the plan (assuming it corresponds to EDB B. And what about the other two TSB's onsite? Add a row to this table for each of them.



**Author:** EPC Stormwater - Glenn Reese  
**Subject:** Contractor  
**Page Label:** 5  
**Date:** 12/2/2021 11:44:13 AM  
**Status:**  
**Color:** ■  
**Layer:**  
**Space:**

Label TSB B on the plan (assuming it corresponds to EDB B. And what about the other two TSB's onsite? Add a row to this table for each of them.



**Author:** EPC Stormwater - Glenn Reese  
**Subject:** Contractor  
**Page Label:** 6  
**Date:** 12/2/2021 11:56:13 AM  
**Status:**  
**Color:** ■  
**Layer:**  
**Space:**

Note on page 96 of the FDR, a well screen is recommended for the orifice diameters specified. This bar-type of trash rack will allow large debris (>1.5") between trash rack and orifice place causing orifice to clog more frequently than a well screen.



**Author:** EPC Stormwater - Glenn Reese  
**Subject:** Contractor  
**Page Label:** 6  
**Date:** 12/2/2021 11:58:29 AM  
**Status:**  
**Color:** ■  
**Layer:**  
**Space:**

Specify installation instructions and mix ratio for soil riprap. As an example, note: "Per MHFD Spec Section 31-37-00, the soil material shall be native or topsoil and mixed with 65% riprap and 35% soil by volume. And soil riprap shall consist of uniform mixture of soil and riprap without voids." And specify the riprap designation per Table 1 of the same spec.



**Author:** EPC Stormwater - Glenn Reese  
**Subject:** Contractor  
**Page Label:** 6  
**Date:** 12/2/2021 12:00:31 PM  
**Status:**  
**Color:** ■  
**Layer:**  
**Space:**

clarify that this ramp is to be gravel.