



LSC TRANSPORTATION CONSULTANTS, INC.
2504 East Pikes Peak Avenue, Suite 304
Colorado Springs, CO 80909
(719) 633-2868
FAX (719) 633-5430
E-mail: lsc@lsctrans.com
Website: <http://www.lsctrans.com>

Rhetoric Subdivision
Traffic Impact Analysis
PCD File No.: PPR2341 & SF2325
(LSC #S224330)
March 20, 2024


Traffic Engineer's Statement

This traffic report and supporting information were prepared under my responsible charge and they comport with the standard of care. So far as is consistent with the standard of care, said report was prepared in general conformance with the criteria established by the County for traffic reports.



Developer's Statement

I, the Developer, have read and will comply with all commitments made on my behalf within this report.



MARCH 20, 2024
Date

Rhetoric Subdivision

Traffic Impact Analysis

Prepared for:

Colorado Concrete Crushing, LLC
20 Boulder Crescent, Suite 100
Colorado Springs, CO 80903

Contact: Mr. Eric S. Howard, Manager

MARCH 20, 2024

LSC Transportation Consultants

Prepared by: Kirstin D. Ferrin, P.E.

Reviewed by: Jeffrey C. Hodsdon, P.E.

PCD FILE NO.: PPR2341 & SF2325

LSC #S224330



CONTENTS

| | |
|---|----|
| REPORT CONTENTS..... | 1 |
| RECENT TRAFFIC REPORTS..... | 2 |
| LAND USE AND ACCESS..... | 2 |
| Land Use..... | 2 |
| Access..... | 2 |
| Existing Asphalt and Concrete Recycling Operations | 3 |
| EXISTING ROAD AND TRAFFIC CONDITIONS..... | 3 |
| TRIP GENERATION..... | 4 |
| Initial Phase and Operations..... | 4 |
| Future Trip Generation Estimate | 5 |
| TRIP DISTRIBUTION AND ASSIGNMENT | 5 |
| BACKGROUND TRAFFIC..... | 6 |
| TOTAL TRAFFIC..... | 6 |
| LEVEL OF SERVICE ANALYSIS..... | 6 |
| SIGNAL WARRANT THRESHOLD ANALYSIS – AM AND PM PEAK HOURS | 7 |
| DEVIATION REQUESTS | 8 |
| MARKSHEFFEL/STERLING RANCH ROAD INTERSECTION RECOMMENDATIONS..... | 8 |
| EL PASO COUNTY ROADWAY IMPROVEMENT FEE PROGRAM..... | 8 |
| FINDINGS & RECOMMENDATIONS..... | 9 |
| Enclosures: | 10 |
| Tables 1, 2, and 4 | |
| Figures 1-9 | |
| Traffic Count Reports | |
| MTCP Maps | |
| Level of Service Reports | |
| Appendix Tables 1-2 | |
| Vollmer Road Approved CD | |



LSC TRANSPORTATION CONSULTANTS, INC.
2504 East Pikes Peak Avenue, Suite 304
Colorado Springs, CO 80909
(719) 633-2868
FAX (719) 633-5430
E-mail: lsc@lsctrans.com
Website: <http://www.lsctrans.com>

March 20, 2024

Mr. Eric S. Howard, Manager
Colorado Concrete Crushing, LLC
20 Boulder Crescent, Suite 100
Colorado Springs, CO 80903

RE: Rhetoric Subdivision
Traffic Impact Analysis
El Paso County, Colorado
PCD FILE NO.: PPR2341 & SF23252241
LSC #S224330

Dear Mr. Howard:

LSC Transportation Consultants, Inc. has prepared this traffic impact analysis for the proposed Rhetoric Subdivision located east of Vollmer Road and south of Marksheffel Road in El Paso County, Colorado. The site location is shown in Figure 1.

REPORT CONTENTS

The preparation of this report included the following:

- A summary of the existing and proposed land uses and access;
- The existing roadway and traffic conditions in the site's vicinity, including the roadway widths, surface conditions, lane geometries, traffic controls, and posted speed limits; and in-progress changes to the existing conditions, based on the design plans and construction of Vollmer Road improvements, Marksheffel Road and Sterling Ranch Road, as shown on the construction plans by Sterling Ranch;
- Estimates of projected short-term background traffic volumes;
- The projected average weekday and peak-hour vehicle trips to be generated by the concrete recycling operation during the design hour; projections of potential future development trip generation on Lot No. 1 and the remaining portion of Lot No. 2.
- The assignment of the estimated design-hour site-generated traffic volumes at the intersection of Marksheffel Road/Sterling Ranch Road;
- The projected short-term total design-hour traffic volumes;

- The projected levels of service at the intersection of Marksheffel Road/Sterling Ranch Road intersection; a preliminary traffic signal warrant analysis;
- Recommendations for auxiliary turn lanes at the intersection of Marksheffel Road/Sterling Ranch Road;
- Other recommendations; and
- County Road Improvement Fee Program information and an estimate of the fee amount.

RECENT TRAFFIC REPORTS

Appendix Table 1, which includes a list of other traffic studies within Sterling Ranch and in the vicinity of area of study completed within the past five years (that LSC is aware of), is attached for reference.

LAND USE AND ACCESS

Land Use

The 32.4263-acre parcel (EPC Parcel No. 5300000743) is located south of the Sterling Ranch master planned community and north of the Pioneer Landscape Centers. The site is currently zoned for industrial uses. It is planned to be subdivided into two lots and for right-of-way (ROW) dedication for an extension of Sterling Ranch Road, as shown in Figure 2.

An asphalt and concrete recycling facility is currently operating on the south 7.7 acres of Lot 2. There are currently no plans for the remaining 16.36 acres. However, based on the current zoning, this area could potentially be developed for industrial uses in the future.

The 4.74-acre Lot 1 is intended for mini-warehouse uses **in the future** and will be developed under a separate site development plan application.

Access

Access for the Rhetoric Subdivision is planned via an extension of Sterling Ranch Road southwest of Marksheffel Road. The extension of Sterling Ranch Road into the site is proposed to be a public street and would be classified as a Non-Residential Collector with 80feet of right-of-way. The recycling operation currently shares the existing Pioneer access to Vollmer Road, located about 905 feet southwest of the future Marksheffel alignment in the jurisdiction of the City of Colorado Springs. As part of this development, the recycling operation would no longer utilize the existing access but would instead have a full-movement access to the new section of Sterling Ranch Road about 585 feet southwest of Marksheffel Road.

Existing Asphalt and Concrete Recycling Operations

The operating hours for the existing asphalt and concrete recycling facility are Monday through Friday from 7:00 a.m. to 5:30 p.m. and one Saturday per month from 7:00 a.m. to noon. The operation currently has four employees but that may increase to up to six in the future.

Tandem trucks and semi-trucks that are owned by third parties transport materials on and off the site throughout the operating hours. No trucks are stored on-site overnight, so each truck load results in one entering truck trip and one exiting truck trip.

LSC was provided with information on the truck operations at the current facility from March 1, 2022, to December 31, 2022. The number of truck loads per day varies throughout the year based on construction activity in the Colorado Springs metropolitan area with the heaviest activity occurring from June to September. The applicant has noted a recent slowdown in demand for recycled materials product due to rising interest rates and reduced housing starts. The applicant anticipates that the summer 2022 traffic likely represents peak demand and resulting production with low probability/potential for future increases in production and associated truck traffic in the foreseeable future.

The maximum number of truck loads on a single day during that time period was 135 (127 tandem trucks and seven semi-trucks). The 85th-percentile weekday (Monday through Friday) number of truck loads was 61 loads per day (47 tandem trucks and 15 semi-trucks).

EXISTING ROAD AND TRAFFIC CONDITIONS

The adjacent streets are shown in Figure 1 and are described below. Copies of the *2016 El Paso County Major Transportation Corridors Plan (MTCP)*, *2040 Roadway Plan*, and *2016 MTCP 2060 Corridor Preservation Plan* with the site location identified on them have been attached to this report.

Marksheffel Road is a Principal Arterial extending north from the City of Fountain to about three quarters of a mile north of Woodmen Road. Marksheffel Road is planned ultimately to be widened to six lanes and extended north and west from Woodmen Road to connect to Research Parkway at Black Forest Road. Marksheffel Road is shown as a four-lane Principal Arterial adjacent to the site on the El Paso County *MTCP*. The City of Colorado Springs intends to take ownership and maintenance of Marksheffel Road when it is constructed from Vollmer to the east and south to where it will connect to the segment constructed north of Woodmen Road in the City.

The section of Marksheffel Road adjacent to Sterling Ranch (and this site) is planned to be constructed on 107 feet of right-of-way to the City's required cross section(s) and criteria. The section of Marksheffel Road between Sterling Ranch Road and Vollmer Road was recently

finished and the section of Marksheffel Road southeast of Sterling Ranch Road (to connect to the segment recently constructed) will be completed in 2024 and will open the connection to Woodmen Road. Marksheffel will be constructed as a four-lane roadway to the previously-agreed-upon cross section.

Vollmer Road is currently a five-lane urban street within the City of Colorado Springs limits between Black Forest Road and Cowpoke Road; and a two-lane, rural, paved roadway north of Cowpoke Road extending to north of Hodgen Road. In the southbound direction, Vollmer Road has a posted speed limit of 45 mph. South of the existing site access, Vollmer Road is within the City limits and has a 40-mph posted speed limit. The *2040 El Paso County Major Transportation Corridors Plan (MTCP)* and the Sterling Ranch master traffic study show Vollmer Road as a four-lane Urban Minor Arterial just north of the existing site access. South of the existing site access, Vollmer is classified as a Minor Arterial (including four through lanes, a center turn lane, bicycle lanes in each direction, and a detached sidewalk). The Sterling Ranch development is currently working on improvements to Vollmer Road north of the existing site access. The section south of the existing site access to Dry Needle Place is a three-lane cross section (two southbound travel lanes and one northbound travel lane) with a striped bicycle lane in the southbound direction. South of Dry Needle Place, the cross section has been completed to the full City cross section.

Sterling Ranch Road is a planned Urban Non-Residential Collector shown extending through the Sterling Ranch development between Marksheffel Road and the north end of the Sketch Plan area (near Arroya Road). Sterling Ranch Road has been constructed between Marksheffel Road and Dines Boulevard and will be constructed north to Briargate Parkway in the short term with the Sterling Ranch East Phase 1 Preliminary Plan. A short segment of Sterling Ranch Road is planned to be constructed **south** of Marksheffel Road as part of the currently-proposed development.

TRIP GENERATION

Initial Phase and Operations

Initially, no new development is proposed for the site, other than the changes to the access for the existing asphalt and concrete recycling operation (operating on the southern eight-acres of Lot 2) as proposed. LSC conducted the traffic counts at the existing access to Vollmer Road that Colorado Concrete Crushing shares with Pioneer Sand on May 25, 2022. As the count data did not identify the portion related to the site operations, LSC has estimated the number of trips based on the number of employees and operation data provided by Colorado Concrete Crushing. Table 1 shows the trip-generation estimates. The estimated trips on May 24, 2022 due to the employees was based on the number of existing employees and the nationally published trip-generation rates for ITE Land Use 110 – Light Industrial from *Trip Generation, 11th Edition, 2021* by the Institute of Transportation Engineers (ITE). The number of truck trips

during the peak hours was estimated by LSC by assuming that trucks arrive and depart from the site evenly throughout the operating hours.

As shown in Appendix Table 2, the truck activity on the site varies throughout the year with peak activity occurring from July to September. As traffic counts were conducted in May, LSC has selected a “design” day to use for this analysis. The “design” day selected was the 85th percentile from the weekday truck-load data for 2022 provided by Colorado Concrete Crushing. The “design” day also assumes two additional employees in the future. Based on the existing economic conditions, no increases in truck traffic from what was recorded in 2022 are anticipated in the short-term/intermediate-term future. Table 1 shows the projected short-term “design day” traffic volumes and the difference between the May 24, 2022 traffic volumes and the “design day” volumes.

Future Trip Generation Estimate

Table 2 shows the potential future trip-generation estimate for the entire Rhetoric Subdivision. Vehicle trips due to development of Lot 1 have been estimated using the nationally published trip-generation rates for Land Use 151: Mini-Warehouse from *Trip Generation, 11th Edition, 2021* by the Institute of Transportation Engineers (ITE). Vehicle trips due to potential future development of the remaining portion of Lot 2 have been estimated using the nationally published trip-generation rates for Land Use 130: Industrial Park.

At buildout, the Rhetoric Subdivision could potentially be expected to generate 954 vehicle trips on the average weekday, with about half entering and half exiting the site during a 24-hour period. During the morning peak hour, which generally occurs for one hour between 6:30 and 8:30 a.m., about 72 vehicles would enter and 24 vehicles would exit the site. During the afternoon peak hour, which generally occurs for one hour between 4:15 and 6:15 p.m., about 28 vehicles would enter and 71 vehicles would exit the site.

TRIP DISTRIBUTION AND ASSIGNMENT

The directional distribution of the site-generated traffic volumes on the street and roadway system serving the site is one of the most important factors in determining the site’s traffic impacts. Figure 3 shows the estimated directional distribution of the traffic related to the existing asphalt and concrete operation and for the potential future land uses.

When the distribution percentages from Figure 3 are applied to the new, external trip-generation estimates (from Table 2), the resulting site-generated traffic volumes can be determined. Figure 4 shows the “design day” site-generated traffic volumes due to the existing asphalt and concrete recycling facility following the change to the access from Vollmer Road to a new extension of Sterling Ranch Road. Figure 5 shows the potential future additional site-generated traffic volumes, should Lot 1 be developed for mini warehouse uses as intended

and the remaining portion of Lot 2 is developed for industrial uses consistent with the existing zoning.

BACKGROUND TRAFFIC

Background traffic is the traffic estimated to be on the adjacent roadways and at adjacent intersections without the proposed development's trip generation of site-generated traffic volumes. Background traffic includes the through traffic and the traffic generated by nearby developments but assumes zero traffic generated by the site.

Figures 6 and 7 show the projected short-term and 2044 background traffic volumes. The background traffic volumes are estimates by LSC, based on work completed by LSC in the area including Sterling Ranch East Filings 1 and 2, FourSquare at Sterling Ranch, Sterling Ranch Filing 5, and Sterling Ranch East Filing 5. The short-term background traffic volumes assume the section of Marksheffel Road between Sterling Ranch Road and the existing terminus north of Woodmen Road has been constructed.

TOTAL TRAFFIC

Figure 8 shows the sum of the short-term background traffic volumes from Figure 6 plus the "design day" asphalt and concrete facility-generated traffic volumes from Figure 4. These volumes represent the projected short-term total traffic assuming only the existing asphalt and concrete recycling on the south portion of Lot 2. This scenario assumes no development on Lot 1 or the remaining portion of Lot 2 in the short-term.

Figure 9 shows the 2044 total traffic volumes. These volumes are the sum of the 2044 background traffic volumes from Figure 7 plus the "design day" asphalt and concrete facility-generated traffic volumes from Figure 4 plus the potential future additional site-generated traffic volumes from Figure 5. This scenario assumes Lot 1 has been developed for mini warehouse uses as intended and the remaining portion of Lot 2 is developed for industrial uses consistent with the existing zoning.

LEVEL OF SERVICE ANALYSIS

Level of service (LOS) is a quantitative measure of the level of congestion or delay at an intersection. Level of service is indicated on a scale from "A" to "F." LOS A represents control delay of less than 10 seconds for unsignalized intersections. LOS F represents control delay of more than 50 seconds for unsignalized intersections. Table 3 shows the level of service delay ranges.

Table 3: Intersection Levels of Service Delay Ranges

| Level of Service | Signalized Intersections | Unsignalized Intersections |
|------------------|---|--|
| | Average Control Delay (seconds per vehicle) | Average Control Delay (seconds per vehicle) ⁽¹⁾ |
| A | 10.0 sec or less | 10.0 sec or less |
| B | 10.1-20.0 sec | 10.1-15.0 sec |
| C | 20.1-35.0 sec | 15.1-25.0 sec |
| D | 35.1-55.0 sec | 25.1-35.0 sec |
| E | 55.1-80.0 sec | 35.1-50.0 sec |
| F | 80.1 sec or more | 50.1 sec or more |

(1) For unsignalized intersections, if V/C ratio is greater than 1.0 the level of service is LOS F, regardless of the projected average control delay per vehicle.

The intersection of Marksheffel/Sterling Ranch Road has been analyzed to determine the projected short-term and 2044 total intersection levels of service based on the unsignalized intersection analysis procedures from the *Highway Capacity Manual 6th Edition*. The intersection was also analyzed assuming signal control using Synchro. Figures 8 and 9 show the level of service analysis results. The level of service reports are attached.

The southbound left-turn movement at this intersection is projected to operate at LOS F during the afternoon peak hour, based on projected short-term **background** traffic volumes. This intersection is planned as a future signalized intersection. However, traffic-signal warrant(s) may not be met in the short-term. It is not uncommon for the minor street approach/movements at a stop-sign-controlled intersection to operate at LOS E or F as the traffic volumes approach the levels needed to meet vehicular-volume traffic-signal warrants. The addition of the site-generated traffic is projected to increase the delay for the southbound left-turn movement from 62.3 seconds per vehicle to 89.3 seconds per vehicle. If this intersection is converted to traffic-signal control all movements are projected to operate at LOS D or better, based on both the short-term and 2044 total traffic volumes.

SIGNAL WARRANT THRESHOLD ANALYSIS – AM AND PM PEAK HOURS

The intersection of Marksheffel/Sterling Ranch was analyzed to determine if the thresholds for Four-Hour and/or Eight-Hour Vehicular-Volume Traffic-Signal Warrant thresholds would be reached or exceeded, based on the projected short-term traffic volumes.

The off-peak-hour volumes are estimates by LSC, based on the peak-hour traffic volumes, 72-hour machine counts conducted by LSC on Vollmer Road in November 2020, and vehicle time-of-day distribution data for single-family homes published by the Institute of Transportation Engineers.

Table 4 shows the results of the analysis for the intersection of Marksheffel/Sterling Ranch. As shown in Table 4, in the short-term, only five of the hours analyzed are projected to meet the thresholds for an Eight-Hour Vehicular-Volume Traffic-Signal and only three of the hours analyzed are projected to meet the thresholds for a Four-Hour Vehicular-Volume Traffic-Signal Warrant. This analysis indicates that traffic-signal warrant(s) will likely **not** be met at the intersection of Marksheffel/Sterling Ranch in the short-term. The minor-approach volume threshold for an Eight-Hour Vehicular-Volume Warrant is 75 vehicles per hour and the minor-approach volume threshold for a Four-Hour Vehicular-Volume Warrant is 80 vehicles per hour. As the projected northbound left-turn volume from the south leg is less than these thresholds, it is likely that a traffic signal will only be warranted at this intersection with future development within the Sterling Ranch Sketch Plan area north of Marksheffel Road.

DEVIATION REQUESTS

No requests for deviations to the criteria contained in the El Paso County *Engineering Criteria Manual* are planned to be submitted as part of this development.

MARKSHEFFEL/STERLING RANCH ROAD INTERSECTION RECOMMENDATIONS

- A northwest-bound left-turn lane on Marksheffel Road approaching Sterling Ranch Road should be included with the design plans for Marksheffel Road currently under review by the City of Colorado Springs. This lane should be 200 feet long plus a 180-foot taper.
- A southeast-bound right-turn lane should be constructed on Marksheffel Road approaching Sterling Ranch Road. This lane should be 200 feet long plus a 180-foot taper.
- The City of Colorado Springs will require the developer to remit \$150,000 for the future anticipated traffic signal at the intersection of Marksheffel/Sterling Ranch.

EL PASO COUNTY ROADWAY IMPROVEMENT FEE PROGRAM

This development is required to participate in the El Paso County Roadway Improvement Fee Program. The Road Impact Fee Schedule does not include a fee for the existing asphalt and concrete crushing use. Therefore, the County will require that the fee be calculated based on *ITE Trip Generation* rates. Since the land use is not directly in the ITE manual the County will require the fee be calculated based on ITE Land Use 140: Manufacturing — the units of measure being per acre.

The calculation is based on 3.6 acres as the predictor variable. The 3.6 acres represent the approximate “active work area” within the 7.7-acre portion of Lot 2 - the asphalt and concrete recycling facility.

3.6 acres x 39.53 trips/acre/day = 142 trips per day

The cost per trip is \$398.55, therefore the total fee obligation would be \$56,594

The PID option for any future development on Lots 1 or 2 will be identified with a future Preliminary Plan/Plat submittal. Note: only the 5 mil PID option is available for a mini-warehouse land use.

FINDINGS & RECOMMENDATIONS

- Please refer to the trip generation section of this report for details regarding the estimated trip-generation estimate for the asphalt and concrete recycling facility used in the access design volumes. The trip-generation estimate has been based on actual daily load data for the concrete recycling operation.
- Colorado Concrete Crushing is currently operating on the site (and currently using the Vollmer access). Truck activity on the site varies based on daily demand and overall construction activity in the Colorado Springs metropolitan area. Based on current economic conditions it is not anticipated that activity will increase significantly from the activity levels in 2022 in the foreseeable future.
- If in the future Lot 1 is developed for mini warehouse uses and the remaining portion of Lot 2 is developed with industrial uses consistent with the existing zoning, the Rhetoric Subdivision could potentially be expected to generate 954 vehicle trips on the average weekday, with about half entering and half exiting the site during a 24-hour period. During the morning peak hour, which generally occurs for one hour between 6:30 and 8:30 a.m., about 72 vehicles would enter and 24 vehicles would exit the site. During the afternoon peak hour, which generally occurs for one hour between 4:15 and 6:15 p.m., about 28 vehicles would enter and 71 vehicles would exit the site.
- The southbound left-turn movement at this intersection is projected to operate at LOS F during the afternoon peak hour, based on projected short-term **background** traffic volumes. This intersection is planned as a future signalized intersection. However, traffic-signal warrant(s) may not be met in the short term. It is not uncommon for the minor-street approach/movements at a stop-sign-controlled intersection to operate at LOS E or F as the traffic volumes approach the levels needed to meet vehicular-volume traffic-signal warrants. The addition of the site-generated traffic is projected to increase the delay for the southbound left-turn movement from 62.3 seconds per vehicle to 89.3 seconds per vehicle. If this intersection is converted to traffic-signal control, all movements are projected to operate at LOS D or better, based on both the short-term and 2044 total traffic volumes.
- The classification of the proposed extension of Sterling Ranch Road into the site as a public street and would Non-Residential Collector with 80feet of right-of-way.
- A northwest-bound left-turn lane on Marksheffel Road approaching Sterling Ranch Road should be included with the design plans for Marksheffel Road currently under review by the City of Colorado Springs. This lane should be 200 feet long plus a 180-foot taper.
- A southeast-bound right-turn lane should be constructed on Marksheffel Road approaching Sterling Ranch Road. This lane should be 200 feet long plus a 180-foot taper.
- The City of Colorado Springs will require the developer to remit \$150,000 for the future anticipated traffic signal at the intersection of Marksheffel/Sterling Ranch.

- The applicant will be required to participate in the El Paso County Road Improvement Fee Program. The Road Impact Fee Schedule does not include land use category and associated fee rate for the existing asphalt and concrete crushing use (given the unique nature of the land use). As discussed above, the “full fee” for this use would be \$56,594. The PID option for any future development on Lots 1 or 2 will be identified with a future Preliminary Plan/Plat submittal.

* * * * *

Please contact me if you have any questions regarding this report.

Respectfully submitted,

LSC TRANSPORTATION CONSULTANTS, INC.

By Jeffrey C. Hodsdon, P.E.
Principal

JCH/KDF:jas

Enclosures: Tables 1, 2, and 4
Figures 1-9
Traffic Count Reports
MTCP Maps
Level of Service Reports
Appendix Tables 1-2
Vollmer Road Approved CD

Tables 1, 2, and 4



**Table 1
Initial Phase Trip Generation Estimate
Rhetoric Subdivision**

| Vehicle Type | Number of Employees or Truck Loads | Trip Generation Rates ⁽¹⁾ | | | | | | | Total Trips Generated | | | | | | | | | | | | | |
|--|------------------------------------|--------------------------------------|------|-------|-------------------|------|---------------------|------|--|-----------|-----------|-------------------|-----------|---------------------|----------|-----------|-----------|-----------|----------|----------|----------|----------|
| | | Average Weekday Traffic | | | Morning Peak Hour | | Afternoon Peak Hour | | Average Weekday Traffic | | | Morning Peak Hour | | Afternoon Peak Hour | | | | | | | | |
| | | In | Out | Total | In | Out | In | Out | In | Out | Total | In | Out | In | Out | | | | | | | |
| Estimated site-generated trips on the day traffic counts were conducted at the existing site access (May 24, 2022) | | | | | | | | | | | | | | | | | | | | | | |
| Passenger Car (employee) | 4 | 1.55 | 1.55 | 3.10 | 0.44 | 0.09 | 0.11 | 0.38 | 6 | 6 | 12 | 2 | 0 | 0 | 2 | | | | | | | |
| Tandem Truck | 18 | 1 | 1 | 2 | 0.10 | 0.10 | 0.10 | 0.10 | 18 | 18 | 36 | 2 | 2 | 2 | 2 | | | | | | | |
| Semi-Truck | 6 | 1 | 1 | 2 | 0.10 | 0.10 | 0.10 | 0.10 | 6 | 6 | 12 | 1 | 1 | 1 | 1 | | | | | | | |
| | | | | | | | | | Total | 30 | 30 | 60 | 5 | 3 | 3 | 5 | | | | | | |
| Estimated site-generated trips on the "design" day (Weekday 85th Percentile) | | | | | | | | | | | | | | | | | | | | | | |
| Passenger Car (employee) | 6 | 1.55 | 1.55 | 3.10 | 0.44 | 0.09 | 0.11 | 0.38 | 9 | 9 | 18 | 3 | 1 | 1 | 2 | | | | | | | |
| Tandem Truck | 47 | 1 | 1 | 2 | 0.10 | 0.10 | 0.10 | 0.10 | 47 | 47 | 94 | 5 | 5 | 5 | 5 | | | | | | | |
| Semi-Truck | 15 | 1 | 1 | 2 | 0.10 | 0.10 | 0.10 | 0.10 | 15 | 15 | 30 | 2 | 2 | 2 | 2 | | | | | | | |
| | | | | | | | | | Total | 71 | 71 | 142 | 10 | 8 | 8 | 9 | | | | | | |
| | | | | | | | | | Difference between the "counted" day and the "design" day | | | | | | | 41 | 41 | 82 | 5 | 5 | 5 | 4 |
| Notes: | | | | | | | | | | | | | | | | | | | | | | |
| (1) Employee trip generation rates were based on the rates for ITE Land Use 110 - General Light Industrial from "Trip Generation, 11th Edition, 2021" by the Institute of Transportation Engineers (ITE) | | | | | | | | | | | | | | | | | | | | | | |
| Truck trip generation rates assume the trucks arrive and exit evenly throughout the operating hours (7:00 am to 5:30 pm) | | | | | | | | | | | | | | | | | | | | | | |
| Source: LSC Transportation Consultants, Inc. | | | | | | | | | | | | | | | Mar-24 | | | | | | | |

**Table 2
Potential Future Trip Generation Estimate
Rhetoric Subdivision**

| Lot | ITE Code | ITE Land Use | Area (Acres) | Floor Area Ratio | Trip Generation Unit | | Daily | Trip Generation Rates ⁽¹⁾ | | | | Total Trip Generated | | | | |
|--|----------|--------------------------------|--------------|------------------|-----------------------|------|-------|--------------------------------------|------|--------------|-----|----------------------|--------------|-----------|--------------|-----------|
| | | | | | Quantity | Unit | | AM Peak Hour | | PM Peak Hour | | Daily | AM Peak Hour | | PM Peak Hour | |
| | | | | | | | | In | Out | In | Out | | In | Out | In | Out |
| Initial Trip Generation Estimate⁽²⁾ | | | | | | | | | | | | | | | | |
| 2 | --- | Asphalt and Concrete Recycling | 7.70 | --- | --- | --- | --- | --- | --- | --- | --- | 142 | 10 | 8 | 8 | 9 |
| Additional Trip Generation Estimate Based on Potential Future Land Uses | | | | | | | | | | | | | | | | |
| 1 | 151 | Mini-Warehouse | 4.74 | 0.3 | 60 KSF ⁽³⁾ | 1.45 | 0.05 | 0.04 | 0.07 | 0.08 | 87 | 3 | 2 | 4 | 5 | |
| 2 | 130 | Industrial Park | 16.36 | 0.3 | 215 KSF | 3.37 | 0.28 | 0.06 | 0.07 | 0.27 | 725 | 59 | 14 | 16 | 57 | |
| | | | | | | | | | | | | 812 | 62 | 16 | 20 | 62 |
| Total | | | | | | | | | | | | 954 | 72 | 24 | 28 | 71 |

Notes:

(1) Source: "Trip Generation, 11th Edition, 2021" by the Institute of Transportation Engineers (ITE)

(2) See Table 1

(3) KSF = thousand square feet of floor area

Source: LSC Transportation Consultants, Inc.

Mar-24

Table 4
Traffic Signal Warrant Analysis
Marksheffel Road/Sterling Ranch Road

Warrant Analysis⁽¹⁾

| Hour | Traffic Volumes ⁽²⁾ | | Warrant Thresholds | | | | Warrant Threshold Met? | | | | Warrant 2: Four Hour Vehicular Volume Evaluation | | | |
|------|-------------------------------------|--|--|-------------|-------|-------------|------------------------|-------------|-----------|-------------|--|--|------------------------------------|------------------------------------|
| | Major Marksheffel ⁽³⁾ | Minor SB Sterling Ranch ⁽⁴⁾ | Minor SB Sterling Ranch ⁽⁴⁾ | Condition A | | Condition B | | SB Approach | | NB Approach | | Warrant Threshold Minor Minimum | Warrant Threshold Met? SB | Warrant Threshold Met? NB |
| | | | | Major | Minor | Major | Minor | Condition | Condition | Condition | Condition | | | |
| | | | | A | B | A | B | A | B | A | B | | | |

Short-Term Background Traffic

| | | | | | | | | | | | | | | |
|----------|-----|-----|---|-----|-----|-----|----|-----|----|----|----|------------|-----|----|
| 12-1 AM | 35 | 8 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 1-2 AM | 16 | 8 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 2-3 AM | 13 | 0 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 3-4 AM | 16 | 8 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 4-5 AM | 24 | 34 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 5-6 AM | 57 | 83 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 6-7 AM | 175 | 247 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 7-8 AM | 393 | 427 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 8-9 AM | 443 | 360 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | 369 | No | No |
| 9-10 AM | 384 | 226 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 10-11 AM | 463 | 226 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | 359 | No | No |
| 11-12 PM | 548 | 214 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | 316 | No | No |
| 12-1 PM | 567 | 212 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | 307 | No | No |
| 1-2 PM | 589 | 224 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | 296 | No | No |
| 2-3 PM | 683 | 235 | 0 | 600 | 150 | 900 | 75 | Yes | No | No | No | 257 | No | No |
| 3-4 PM | 781 | 227 | 0 | 600 | 150 | 900 | 75 | Yes | No | No | No | 210 | Yes | No |
| 4-5 PM | 897 | 284 | 0 | 600 | 150 | 900 | 75 | Yes | No | No | No | 176 | Yes | No |
| 5-6 PM | 827 | 280 | 0 | 600 | 150 | 900 | 75 | Yes | No | No | No | 193 | Yes | No |
| 6-7 PM | 644 | 224 | 0 | 600 | 150 | 900 | 75 | Yes | No | No | No | 272 | No | No |
| 7-8 PM | 446 | 163 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | 367 | No | No |
| 8-9 PM | 427 | 117 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | 377 | No | No |
| 9-10 PM | 298 | 91 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 10-11 PM | 149 | 41 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 11-12 AM | 86 | 27 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |

Numbers of Hours the Warrant Thresholds Are Met

| | | | | | | |
|---------------------|---|---|---|----|---|----|
| 5 | 0 | 0 | 0 | | 3 | 0 |
| Warrant Met? | | | | No | | No |

Short-Term Total Traffic

| | | | | | | | | | | | | | | |
|----------|-----|-----|---|-----|-----|-----|----|-----|-----|----|----|------------|-----|----|
| 12-1 AM | 35 | 8 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 1-2 AM | 16 | 8 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 2-3 AM | 13 | 0 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 3-4 AM | 16 | 8 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 4-5 AM | 25 | 34 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 5-6 AM | 59 | 83 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 6-7 AM | 180 | 247 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 7-8 AM | 403 | 427 | 2 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 8-9 AM | 450 | 360 | 1 | 600 | 150 | 900 | 75 | No | No | No | No | 365 | No | No |
| 9-10 AM | 391 | 226 | 1 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 10-11 AM | 470 | 226 | 1 | 600 | 150 | 900 | 75 | No | No | No | No | 355 | No | No |
| 11-12 PM | 555 | 214 | 1 | 600 | 150 | 900 | 75 | No | No | No | No | 313 | No | No |
| 12-1 PM | 574 | 212 | 1 | 600 | 150 | 900 | 75 | No | No | No | No | 303 | No | No |
| 1-2 PM | 596 | 224 | 1 | 600 | 150 | 900 | 75 | No | No | No | No | 292 | No | No |
| 2-3 PM | 690 | 235 | 1 | 600 | 150 | 900 | 75 | Yes | No | No | No | 254 | No | No |
| 3-4 PM | 788 | 227 | 1 | 600 | 150 | 900 | 75 | Yes | No | No | No | 206 | Yes | No |
| 4-5 PM | 904 | 284 | 1 | 600 | 150 | 900 | 75 | Yes | Yes | No | No | 174 | Yes | No |
| 5-6 PM | 835 | 280 | 2 | 600 | 150 | 900 | 75 | Yes | No | No | No | 191 | Yes | No |
| 6-7 PM | 649 | 224 | 0 | 600 | 150 | 900 | 75 | Yes | No | No | No | 270 | No | No |
| 7-8 PM | 449 | 163 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | 366 | No | No |
| 8-9 PM | 429 | 117 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | 376 | No | No |
| 9-10 PM | 300 | 91 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 10-11 PM | 150 | 41 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |
| 11-12 AM | 87 | 27 | 0 | 600 | 150 | 900 | 75 | No | No | No | No | Low Volume | No | No |

Numbers of Hours the Warrant Thresholds Are Met

| | | | | | | |
|---------------------|---|---|---|----|---|----|
| 5 | 1 | 0 | 0 | | 3 | 0 |
| Warrant Met? | | | | No | | No |

Notes:

- (1) Thresholds are based on 2 or more lanes on the major approach and 1 lane on the minor approach (Warrant evaluation assuming the southbound left turn only for the minor street)
- (2) Off peak hour traffic volumes are based on the projected peak hour traffic volumes, 72-hour machine counts conducted on Vollmer Road in November 2020 and vehicle time-of-day distribution data published by the Institute of Transportation Engineers
- (3) The major street traffic includes all movements (left, through, and right)
- (4) The minor street traffic includes only the left turns from the minor street

Source: LSC Transportation Consultants, Inc.

Figures 1-9








Figure 1

Vicinity Map

Rhetoric Subdivision (LSC# S224330)





LEGEND: $\frac{XX\%}{XX\%} = \frac{\text{Percent of asphalt and concrete recycling trips}}{\text{Percent of mini-warehouse \& industrial trips}}$

Figure 3
**Directional Distribution
of Site-Generated Traffic**
Rhetoric Subdivision (LSC# S224330)







Figure 4

"Design Day" Asphalt and Concrete Recycling-Generated Traffic

LEGEND:

$$\frac{XX}{XX} = \frac{\text{AM Peak-Hour Traffic (veh/hr)}}{\text{PM Peak-Hour Traffic (veh/hr)}}$$

XXX = Average Weekday Traffic (vehicles per day)

Rhetoric Subdivision (LSC# S224330)







Figure 5

Potential Additional Future Site-Generated Traffic





Rhetoric Subdivision (LSC# S224330)

LEGEND:

$$\frac{XX}{XX} = \frac{\text{AM Peak-Hour Traffic (veh/hr)}}{\text{PM Peak-Hour Traffic (veh/hr)}}$$

XXX = Average Weekday Traffic (vehicles per day)





LEGEND:

$$\frac{XX}{XX} = \frac{\text{AM Peak-Hour Traffic (veh/hr)}}{\text{PM Peak-Hour Traffic (veh/hr)}}$$

$$\frac{C}{D} = \frac{\text{AM Entire Intersection Peak-Hour Level of Service}}{\text{PM Entire Intersection Peak-Hour Level of Service}}$$




$$\frac{A}{B} = \frac{\text{AM Individual Movement Peak-Hour Level of Service}}{\text{PM Individual Movement Peak-Hour Level of Service}}$$

⊥ = Stop Sign ⊞ = Traffic Signal

Short-Term Background Traffic

Figure 6

Rhetoric Subdivision (LSC# S224330)



LEGEND:

$$\frac{XX}{XX} = \frac{\text{AM Peak-Hour Traffic (veh/hr)}}{\text{PM Peak-Hour Traffic (veh/hr)}} \quad \frac{C}{D} = \frac{\text{AM Entire Intersection Peak-Hour Level of Service}}{\text{PM Entire Intersection Peak-Hour Level of Service}}$$



$$\frac{A}{B} = \frac{\text{AM Individual Movement Peak-Hour Level of Service}}{\text{PM Individual Movement Peak-Hour Level of Service}}$$

XXX = Average Weekday Traffic (vehicles per day)


= Traffic Signal

Figure 7 2043 Background Traffic


Rhetoric Subdivision (LSC# S224330)



Stop-Sign Control



Signal Control



LEGEND:

$$\frac{XX}{XX} = \frac{\text{AM Peak-Hour Traffic (veh/hr)}}{\text{PM Peak-Hour Traffic (veh/hr)}}$$

$$\frac{C}{D} = \frac{\text{AM Entire Intersection Peak-Hour Level of Service}}{\text{PM Entire Intersection Peak-Hour Level of Service}}$$

$$\frac{A}{B} = \frac{\text{AM Individual Movement Peak-Hour Level of Service}}{\text{PM Individual Movement Peak-Hour Level of Service}}$$



┆ = Stop Sign

⬮ = Traffic Signal



Figure 8
Short-Term Total Traffic

Rhetoric Subdivision (LSC# S224330)



LEGEND:

$$\frac{XX}{XX} = \frac{\text{AM Peak-Hour Traffic (veh/hr)}}{\text{PM Peak-Hour Traffic (veh/hr)}}$$

$$\frac{C}{D} = \frac{\text{AM Entire Intersection Peak-Hour Level of Service}}{\text{PM Entire Intersection Peak-Hour Level of Service}}$$

$$\frac{A}{B} = \frac{\text{AM Individual Movement Peak-Hour Level of Service}}{\text{PM Individual Movement Peak-Hour Level of Service}}$$

XXX = Average Weekday Traffic (vehicles per day)



Figure 9 2043 Total Traffic

Rhetoric Subdivision (LSC# S224330)

Traffic Counts



LSC Transportation Consultants, Inc.

2504 E. Pikes Peak Ave, Suite 304
 Colorado Springs, CO 80909
 719-633-2868

File Name : Vollmer Rd - Pioneer Sand Trucks AM
 Site Code : S22433
 Start Date : 5/25/2022
 Page No : 1

**Passenger Cars/
 Pickup-Trucks**

Groups Printed- Unshifted

| Start Time | Vollmer Rd Southbound | | | | | Pioneer Sand Acces Westbound | | | | | Vollmer Rd Northbound | | | | | Eastbound | | | | | Int. Total |
|-------------|-----------------------|------|------|------|------------|------------------------------|------|------|------|------------|-----------------------|------|------|------|------------|-----------|------|------|------|------------|------------|
| | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | |
| 06:30 | 0 | 49 | 0 | 0 | 49 | 3 | 0 | 2 | 0 | 5 | 13 | 15 | 0 | 0 | 28 | 0 | 0 | 0 | 0 | 0 | 82 |
| 06:45 | 0 | 49 | 3 | 0 | 52 | 1 | 0 | 0 | 0 | 1 | 14 | 26 | 0 | 0 | 40 | 0 | 0 | 0 | 0 | 0 | 93 |
| Total | 0 | 98 | 3 | 0 | 101 | 4 | 0 | 2 | 0 | 6 | 27 | 41 | 0 | 0 | 68 | 0 | 0 | 0 | 0 | 0 | 175 |
| 07:00 | 0 | 63 | 1 | 0 | 64 | 2 | 0 | 6 | 0 | 8 | 5 | 38 | 0 | 0 | 43 | 0 | 0 | 0 | 0 | 0 | 115 |
| 07:15 | 0 | 68 | 1 | 0 | 69 | 8 | 0 | 8 | 0 | 16 | 7 | 44 | 0 | 0 | 51 | 0 | 0 | 0 | 0 | 0 | 136 |
| 07:30 | 0 | 82 | 2 | 0 | 84 | 3 | 0 | 8 | 0 | 11 | 9 | 57 | 0 | 0 | 66 | 0 | 0 | 0 | 0 | 0 | 161 |
| 07:45 | 0 | 79 | 1 | 0 | 80 | 2 | 0 | 2 | 0 | 4 | 5 | 68 | 0 | 0 | 73 | 0 | 0 | 0 | 0 | 0 | 157 |
| Total | 0 | 292 | 5 | 0 | 297 | 15 | 0 | 24 | 0 | 39 | 26 | 207 | 0 | 0 | 233 | 0 | 0 | 0 | 0 | 0 | 569 |
| 08:00 | 0 | 58 | 4 | 0 | 62 | 1 | 0 | 8 | 0 | 9 | 7 | 64 | 0 | 0 | 71 | 0 | 0 | 0 | 0 | 0 | 142 |
| 08:15 | 0 | 57 | 1 | 1 | 59 | 1 | 0 | 7 | 0 | 8 | 3 | 52 | 0 | 0 | 55 | 0 | 0 | 0 | 0 | 0 | 122 |
| Grand Total | 0 | 505 | 13 | 1 | 519 | 21 | 0 | 41 | 0 | 62 | 63 | 364 | 0 | 0 | 427 | 0 | 0 | 0 | 0 | 0 | 1008 |
| Apprch % | 0 | 97.3 | 2.5 | 0.2 | | 33.9 | 0 | 66.1 | 0 | | 14.8 | 85.2 | 0 | 0 | | 0 | 0 | 0 | 0 | | |
| Total % | 0 | 50.1 | 1.3 | 0.1 | 51.5 | 2.1 | 0 | 4.1 | 0 | 6.2 | 6.2 | 36.1 | 0 | 0 | 42.4 | 0 | 0 | 0 | 0 | 0 | |

LSC Transportation Consultants, Inc.

2504 E. Pikes Peak Ave, Suite 304
 Colorado Springs, CO 80909
 719-633-2868

File Name : Vollmer Rd - Pioneer Sand Trucks AM

Site Code : S224330

Start Date : 5/25/2022

Page No : 1

Trucks

Groups Printed- Bank 1

| Start Time | Vollmer Rd Southbound | | | | | Pioneer Sand Acces Westbound | | | | | Vollmer Rd Northbound | | | | | Eastbound | | | | | Int. Total | |
|-------------|-----------------------|------|------|------|------------|------------------------------|------|------|------|------------|-----------------------|------|------|------|------------|-----------|------|------|------|------------|------------|----|
| | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | | |
| 06:30 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 |
| 06:45 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| Total | 0 | 0 | 1 | 0 | 1 | 3 | 0 | 2 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 |
| 07:00 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 4 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 |
| 07:15 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 7 | 0 | 13 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 14 |
| 07:30 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 |
| 07:45 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 2 |
| Total | 0 | 0 | 0 | 0 | 0 | 9 | 0 | 12 | 0 | 21 | 3 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 24 |
| 08:00 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 3 |
| 08:15 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 |
| Grand Total | 0 | 0 | 3 | 0 | 3 | 12 | 0 | 16 | 0 | 28 | 5 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 36 |
| Apprch % | 0 | 0 | 100 | 0 | | 42.9 | 0 | 57.1 | 0 | | 100 | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 | |
| Total % | 0 | 0 | 8.3 | 0 | 8.3 | 33.3 | 0 | 44.4 | 0 | 77.8 | 13.9 | 0 | 0 | 0 | 13.9 | 0 | 0 | 0 | 0 | 0 | 0 | |

LSC Transportation Consultants, Inc.

2504 E. Pikes Peak Ave, Suite 304
 Colorado Springs, CO 80909
 719-633-2868

File Name : Vollmer Rd - Pioneer Sand Trucks PM

Site Code : S224330

Start Date : 5/24/2022

Page No : 1

**Passenger Cars/
 Pickup-Trucks**

Groups Printed- Unshifted

| Start Time | Vollmer Rd Southbound | | | | | Pioneer Sand Acces Westbound | | | | | Vollmer Rd Northbound | | | | | Eastbound | | | | | Int. Total |
|-------------|-----------------------|------|------|------|------------|------------------------------|------|------|------|------------|-----------------------|------|------|------|------------|-----------|------|------|------|------------|------------|
| | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | |
| 16:00 | 0 | 72 | 1 | 0 | 73 | 2 | 0 | 8 | 0 | 10 | 6 | 69 | 0 | 0 | 75 | 0 | 0 | 0 | 0 | 0 | 158 |
| 16:15 | 0 | 61 | 2 | 0 | 63 | 1 | 0 | 7 | 0 | 8 | 11 | 69 | 0 | 0 | 80 | 0 | 0 | 0 | 0 | 0 | 151 |
| 16:30 | 0 | 64 | 1 | 0 | 65 | 2 | 0 | 8 | 0 | 10 | 6 | 75 | 0 | 0 | 81 | 0 | 0 | 0 | 0 | 0 | 156 |
| 16:45 | 0 | 54 | 2 | 0 | 56 | 6 | 0 | 8 | 0 | 14 | 2 | 72 | 0 | 0 | 74 | 0 | 0 | 0 | 0 | 0 | 144 |
| Total | 0 | 251 | 6 | 0 | 257 | 11 | 0 | 31 | 0 | 42 | 25 | 285 | 0 | 0 | 310 | 0 | 0 | 0 | 0 | 0 | 609 |
| 17:00 | 0 | 60 | 1 | 0 | 61 | 1 | 0 | 9 | 0 | 10 | 3 | 58 | 0 | 0 | 61 | 0 | 0 | 0 | 0 | 0 | 132 |
| 17:15 | 0 | 65 | 2 | 0 | 67 | 0 | 0 | 5 | 0 | 5 | 1 | 58 | 0 | 0 | 59 | 0 | 0 | 0 | 0 | 0 | 131 |
| 17:30 | 0 | 50 | 0 | 0 | 50 | 2 | 0 | 21 | 0 | 23 | 2 | 68 | 0 | 0 | 70 | 0 | 0 | 0 | 0 | 0 | 143 |
| 17:45 | 0 | 48 | 1 | 0 | 49 | 0 | 0 | 2 | 0 | 2 | 0 | 77 | 0 | 0 | 77 | 0 | 0 | 0 | 0 | 0 | 128 |
| Total | 0 | 223 | 4 | 0 | 227 | 3 | 0 | 37 | 0 | 40 | 6 | 261 | 0 | 0 | 267 | 0 | 0 | 0 | 0 | 0 | 534 |
| Grand Total | 0 | 474 | 10 | 0 | 484 | 14 | 0 | 68 | 0 | 82 | 31 | 546 | 0 | 0 | 577 | 0 | 0 | 0 | 0 | 0 | 1143 |
| Apprch % | 0 | 97.9 | 2.1 | 0 | | 17.1 | 0 | 82.9 | 0 | | 5.4 | 94.6 | 0 | 0 | | 0 | 0 | 0 | 0 | | |
| Total % | 0 | 41.5 | 0.9 | 0 | 42.3 | 1.2 | 0 | 5.9 | 0 | 7.2 | 2.7 | 47.8 | 0 | 0 | 50.5 | 0 | 0 | 0 | 0 | 0 | |

LSC Transportation Consultants, Inc.

2504 E. Pikes Peak Ave, Suite 304
 Colorado Springs, CO 80909
 719-633-2868

File Name : Vollmer Rd - Pioneer Sand Trucks PM

Site Code : S224330

Start Date : 5/24/2022

Page No : 1

Trucks

Groups Printed- Bank 1

| Start Time | Vollmer Rd Southbound | | | | | Pioneer Sand Acces Westbound | | | | | Vollmer Rd Northbound | | | | | Eastbound | | | | | Int. Total |
|-------------|-----------------------|------|------|------|------------|------------------------------|------|------|------|------------|-----------------------|------|------|------|------------|-----------|------|------|------|------------|------------|
| | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | |
| 16:00 | 0 | 0 | 1 | 0 | 1 | 1 | 0 | 2 | 0 | 3 | 3 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 7 |
| 16:15 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 2 | 0 | 2 | 5 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 8 |
| 16:30 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 4 |
| 16:45 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 3 |
| Total | 0 | 0 | 4 | 0 | 4 | 1 | 0 | 4 | 0 | 5 | 13 | 0 | 0 | 0 | 13 | 0 | 0 | 0 | 0 | 0 | 22 |
| 17:00 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 3 |
| 17:15 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 2 | 0 | 2 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 5 |
| 17:30 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 |
| 17:45 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 |
| Total | 0 | 0 | 4 | 0 | 4 | 0 | 0 | 3 | 0 | 3 | 4 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 11 |
| Grand Total | 0 | 0 | 8 | 0 | 8 | 1 | 0 | 7 | 0 | 8 | 17 | 0 | 0 | 0 | 17 | 0 | 0 | 0 | 0 | 0 | 33 |
| Apprch % | 0 | 0 | 100 | 0 | | 12.5 | 0 | 87.5 | 0 | | 100 | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | | |
| Total % | 0 | 0 | 24.2 | 0 | 24.2 | 3 | 0 | 21.2 | 0 | 24.2 | 51.5 | 0 | 0 | 0 | 51.5 | 0 | 0 | 0 | 0 | 0 | |

LSC Transportation Consultants, Inc.

2504 E. Pikes Peak Ave, Suite 304
 Colorado Springs, CO 80909
 719-633-2868

File Name : Vollmer Rd - Pioneer Sand Trucks PM


Site Code : S224330

Start Date : 5/24/2022

Page No : 2


Trucks

| Start Time | Vollmer Rd Southbound | | | | | Pioneer Sand Access Westbound | | | | | Vollmer Rd Northbound | | | | | Eastbound | | | | | Int. Total | |
|--|-----------------------|------|------|------|------------|-------------------------------|------|------|------|------------|-----------------------|------|------|------|------------|-----------|------|------|------|------------|------------|------|
| | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | Right | Thru | Left | Peds | App. Total | | |
| Peak Hour Analysis From 4:00:00 PM to 5:45:00 PM - Peak 1 of 1 | | | | | | | | | | | | | | | | | | | | | | |
| Peak Hour for Entire Intersection Begins at 4:00:00 PM | | | | | | | | | | | | | | | | | | | | | | |
| 4:00:00 PM | 0 | 0 | 1 | 0 | 1 | 1 | 0 | 2 | 0 | 3 | 3 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 7 |
| 4:15:00 PM | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 2 | 0 | 2 | 5 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 8 |
| 4:30:00 PM | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 4 |
| 4:45:00 PM | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 3 |
| Total Volume | 0 | 0 | 4 | 0 | 4 | 1 | 0 | 4 | 0 | 5 | 13 | 0 | 0 | 0 | 13 | 0 | 0 | 0 | 0 | 0 | 0 | 22 |
| % App. Total | 0 | 0 | 100 | 0 | | 20 | 0 | 80 | 0 | | 100 | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | | |
| PHF | .000 | .000 | .500 | .000 | .500 | .250 | .000 | .500 | .000 | .417 | .650 | .000 | .000 | .000 | .650 | .000 | .000 | .000 | .000 | .000 | .000 | .688 |




MTCP Maps





Map 14: 2040 Roadway Plan (Classification and Lanes)

Map 17: 2060 Corridor Preservation



Legend

- Freeway
- Expressway
- Principal Arterial
- Minor Arterial
- Collector
- Local

Number Of Through Lanes

- 6 Through Lanes
- 4 Through Lanes
- 2 Through Lanes

- Paving Project
- Roadway Improvements (2040 - 2060)
- County Boundaries
- Incorporated Cities/Towns

0 **NORTH** 5
Miles

Date: 11/15/2016

Level of Service Reports



| Intersection | | | | | | |
|--------------------------|------|------|------|------|------|------|
| Int Delay, s/veh | 12.2 | | | | | |
| Movement | EBL | EBT | WBT | WBR | SBL | SBR |
| Lane Configurations | ↘ | ↑↑ | ↑↑ | ↗ | ↘ | ↗ |
| Traffic Vol, veh/h | 38 | 133 | 80 | 142 | 427 | 150 |
| Future Vol, veh/h | 38 | 133 | 80 | 142 | 427 | 150 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Free | Free | Free | Free | Stop | Stop |
| RT Channelized | - | None | - | None | - | None |
| Storage Length | 300 | - | - | 205 | 155 | 0 |
| Veh in Median Storage, # | - | 0 | 0 | - | 0 | - |
| Grade, % | - | 0 | 0 | - | 0 | - |
| Peak Hour Factor | 85 | 85 | 85 | 85 | 85 | 85 |
| Heavy Vehicles, % | 2 | 2 | 2 | 2 | 2 | 2 |
| Mvmt Flow | 45 | 156 | 94 | 167 | 502 | 176 |


| Major/Minor | Major1 | Major2 | Minor2 | | |
|----------------------|--------|--------|--------|---|-----------|
| Conflicting Flow All | 261 | 0 | - | 0 | 262 47 |
| Stage 1 | - | - | - | - | 94 - |
| Stage 2 | - | - | - | - | 168 - |
| Critical Hdwy | 4.14 | - | - | - | 6.84 6.94 |
| Critical Hdwy Stg 1 | - | - | - | - | 5.84 - |
| Critical Hdwy Stg 2 | - | - | - | - | 5.84 - |
| Follow-up Hdwy | 2.22 | - | - | - | 3.52 3.32 |
| Pot Cap-1 Maneuver | 1300 | - | - | - | 705 1012 |
| Stage 1 | - | - | - | - | 919 - |
| Stage 2 | - | - | - | - | 844 - |
| Platoon blocked, % | | - | - | - | |
| Mov Cap-1 Maneuver | 1300 | - | - | - | 680 1012 |
| Mov Cap-2 Maneuver | - | - | - | - | 680 - |
| Stage 1 | - | - | - | - | 887 - |
| Stage 2 | - | - | - | - | 844 - |

| Approach | EB | WB | SB |
|----------------------|-----|----|----|
| HCM Control Delay, s | 1.7 | 0 | 20 |
| HCM LOS | | | C |

| Minor Lane/Major Mvmt | EBL | EBT | WBT | WBR | SBLn1 | SBLn2 |
|-----------------------|-------|-----|-----|-----|-------|-------|
| Capacity (veh/h) | 1300 | - | - | - | 680 | 1012 |
| HCM Lane V/C Ratio | 0.034 | - | - | - | 0.739 | 0.174 |
| HCM Control Delay (s) | 7.9 | - | - | - | 23.7 | 9.3 |
| HCM Lane LOS | A | - | - | - | C | A |
| HCM 95th %tile Q(veh) | 0.1 | - | - | - | 6.6 | 0.6 |

Timings
13: Marksheffel Rd & Sterling Ranch Rd

Short-Term Background Traffic
AM Peak Hour



| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|----------------------|-------|-------|-------|-------|-------|-------|
| Lane Configurations | ↖ | ↗ | ↖ | ↖ | ↖ | ↖ |
| Traffic Volume (vph) | 38 | 133 | 80 | 142 | 427 | 150 |
| Future Volume (vph) | 38 | 133 | 80 | 142 | 427 | 150 |
| Turn Type | pm+pt | NA | NA | Perm | Prot | Perm |
| Protected Phases | 5 | 2 | 6 | | 7 | |
| Permitted Phases | 2 | | | 6 | | 4 |
| Detector Phase | 5 | 2 | 6 | 6 | 7 | 4 |
| Switch Phase | | | | | | |
| Minimum Initial (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| Minimum Split (s) | 10.0 | 23.0 | 23.0 | 23.0 | 10.0 | 23.0 |
| Total Split (s) | 12.0 | 60.0 | 48.0 | 48.0 | 30.0 | 30.0 |
| Total Split (%) | 13.3% | 66.7% | 53.3% | 53.3% | 33.3% | 33.3% |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| Lead/Lag | Lead | | Lag | Lag | | |
| Lead-Lag Optimize? | Yes | | Yes | Yes | | |
| Recall Mode | None | Max | Max | Max | None | None |
| Act Effct Green (s) | 55.1 | 55.1 | 48.3 | 48.3 | 17.1 | 17.1 |
| Actuated g/C Ratio | 0.67 | 0.67 | 0.59 | 0.59 | 0.21 | 0.21 |
| v/c Ratio | 0.05 | 0.07 | 0.05 | 0.17 | 0.71 | 0.38 |
| Control Delay | 5.6 | 5.3 | 9.7 | 2.5 | 35.9 | 7.0 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay | 5.6 | 5.3 | 9.7 | 2.5 | 35.9 | 7.0 |
| LOS | A | A | A | A | D | A |
| Approach Delay | | 5.4 | 5.1 | | 28.4 | |
| Approach LOS | | A | A | | C | |

Intersection Summary

Cycle Length: 90
 Actuated Cycle Length: 82.2
 Natural Cycle: 60
 Control Type: Semi Act-Uncoord
 Maximum v/c Ratio: 0.71
 Intersection Signal Delay: 19.0
 Intersection LOS: B
 Intersection Capacity Utilization 29.3%
 ICU Level of Service A
 Analysis Period (min) 15

Splits and Phases: 13: Marksheffel Rd & Sterling Ranch Rd



| Intersection | | | | | | |
|--------------------------|------|------|------|------|------|------|
| Int Delay, s/veh | 15.6 | | | | | |
| Movement | EBL | EBT | WBT | WBR | SBL | SBR |
| Lane Configurations | ↘ | ↑↑ | ↑↑ | ↗ | ↘ | ↗ |
| Traffic Vol, veh/h | 130 | 108 | 178 | 481 | 283 | 100 |
| Future Vol, veh/h | 130 | 108 | 178 | 481 | 283 | 100 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Free | Free | Free | Free | Stop | Stop |
| RT Channelized | - | None | - | None | - | None |
| Storage Length | 300 | - | - | 205 | 155 | 0 |
| Veh in Median Storage, # | - | 0 | 0 | - | 0 | - |
| Grade, % | - | 0 | 0 | - | 0 | - |
| Peak Hour Factor | 85 | 85 | 85 | 85 | 85 | 85 |
| Heavy Vehicles, % | 2 | 2 | 2 | 2 | 2 | 2 |
| Mvmt Flow | 153 | 127 | 209 | 566 | 333 | 118 |


| Major/Minor | Major1 | Major2 | Minor2 | | |
|----------------------|--------|--------|--------|---|-----------|
| Conflicting Flow All | 775 | 0 | - | 0 | 579 105 |
| Stage 1 | - | - | - | - | 209 - |
| Stage 2 | - | - | - | - | 370 - |
| Critical Hdwy | 4.14 | - | - | - | 6.84 6.94 |
| Critical Hdwy Stg 1 | - | - | - | - | 5.84 - |
| Critical Hdwy Stg 2 | - | - | - | - | 5.84 - |
| Follow-up Hdwy | 2.22 | - | - | - | 3.52 3.32 |
| Pot Cap-1 Maneuver | 837 | - | - | - | 446 929 |
| Stage 1 | - | - | - | - | 806 - |
| Stage 2 | - | - | - | - | 669 - |
| Platoon blocked, % | | - | - | - | |
| Mov Cap-1 Maneuver | 837 | - | - | - | 364 929 |
| Mov Cap-2 Maneuver | - | - | - | - | 364 - |
| Stage 1 | - | - | - | - | 659 - |
| Stage 2 | - | - | - | - | 669 - |

| Approach | EB | WB | SB |
|----------------------|-----|----|------|
| HCM Control Delay, s | 5.6 | 0 | 48.5 |
| HCM LOS | | | E |

| Minor Lane/Major Mvmt | EBL | EBT | WBT | WBR | SBLn1 | SBLn2 |
|-----------------------|-------|-----|-----|-----|-------|-------|
| Capacity (veh/h) | 837 | - | - | - | 364 | 929 |
| HCM Lane V/C Ratio | 0.183 | - | - | - | 0.915 | 0.127 |
| HCM Control Delay (s) | 10.3 | - | - | - | 62.3 | 9.4 |
| HCM Lane LOS | B | - | - | - | F | A |
| HCM 95th %tile Q(veh) | 0.7 | - | - | - | 9.4 | 0.4 |

Timings
13: Marksheffel Rd & Sterling Ranch Rd

Short-Term Background Traffic
PM Peak Hour



| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|----------------------|-------|-------|-------|-------|-------|-------|
| Lane Configurations | ↗ | ↑↑ | ↑↑ | ↖ | ↘↘ | ↘ |
| Traffic Volume (vph) | 130 | 108 | 178 | 481 | 283 | 100 |
| Future Volume (vph) | 130 | 108 | 178 | 481 | 283 | 100 |
| Turn Type | pm+pt | NA | NA | Perm | Prot | Perm |
| Protected Phases | 5 | 2 | 6 | | 7 | |
| Permitted Phases | 2 | | | 6 | | 4 |
| Detector Phase | 5 | 2 | 6 | 6 | 7 | 4 |
| Switch Phase | | | | | | |
| Minimum Initial (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| Minimum Split (s) | 10.0 | 23.0 | 23.0 | 23.0 | 10.0 | 23.0 |
| Total Split (s) | 12.0 | 60.0 | 48.0 | 48.0 | 30.0 | 30.0 |
| Total Split (%) | 13.3% | 66.7% | 53.3% | 53.3% | 33.3% | 33.3% |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| Lead/Lag | Lead | | Lag | Lag | | |
| Lead-Lag Optimize? | Yes | | Yes | Yes | | |
| Recall Mode | None | Max | Max | Max | None | None |
| Act Effct Green (s) | 55.1 | 55.1 | 43.3 | 43.3 | 12.7 | 12.7 |
| Actuated g/C Ratio | 0.71 | 0.71 | 0.56 | 0.56 | 0.16 | 0.16 |
| v/c Ratio | 0.19 | 0.05 | 0.11 | 0.50 | 0.59 | 0.33 |
| Control Delay | 4.6 | 3.9 | 8.8 | 2.7 | 34.7 | 8.7 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay | 4.6 | 3.9 | 8.8 | 2.7 | 34.7 | 8.7 |
| LOS | A | A | A | A | C | A |
| Approach Delay | | 4.3 | 4.3 | | 27.9 | |
| Approach LOS | | A | A | | C | |

Intersection Summary


Cycle Length: 90
 Actuated Cycle Length: 77.8
 Natural Cycle: 60
 Control Type: Semi Act-Uncoord
 Maximum v/c Ratio: 0.59
 Intersection Signal Delay: 11.4
 Intersection LOS: B
 Intersection Capacity Utilization 45.3%
 ICU Level of Service A
 Analysis Period (min) 15

Splits and Phases: 13: Marksheffel Rd & Sterling Ranch Rd



Timings
13: Marksheffel Rd & Sterling Ranch Rd

2043 Background Traffic
AM Peak Hour



| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|----------------------|-------|-------|-------|-------|-------|-------|
| Lane Configurations | ↶ | ↷ | ↷ | ↷ | ↷ | ↷ |
| Traffic Volume (vph) | 160 | 900 | 809 | 175 | 478 | 328 |
| Future Volume (vph) | 160 | 900 | 809 | 175 | 478 | 328 |
| Turn Type | pm+pt | NA | NA | Perm | Prot | Perm |
| Protected Phases | 5 | 2 | 6 | | 4 | |
| Permitted Phases | 2 | | | 6 | | 4 |
| Detector Phase | 5 | 2 | 6 | 6 | 4 | 4 |
| Switch Phase | | | | | | |
| Minimum Initial (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| Minimum Split (s) | 10.0 | 23.0 | 23.0 | 23.0 | 10.0 | 10.0 |
| Total Split (s) | 10.0 | 60.0 | 50.0 | 50.0 | 30.0 | 30.0 |
| Total Split (%) | 11.1% | 66.7% | 55.6% | 55.6% | 33.3% | 33.3% |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| Lead/Lag | Lead | | Lag | Lag | | |
| Lead-Lag Optimize? | Yes | | Yes | Yes | | |
| Recall Mode | None | Max | Max | Max | None | None |
| Act Effct Green (s) | 55.1 | 55.1 | 45.1 | 45.1 | 18.1 | 18.1 |
| Actuated g/C Ratio | 0.66 | 0.66 | 0.54 | 0.54 | 0.22 | 0.22 |
| v/c Ratio | 0.45 | 0.41 | 0.45 | 0.20 | 0.68 | 0.69 |
| Control Delay | 10.0 | 7.7 | 13.1 | 2.4 | 34.8 | 19.2 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay | 10.0 | 7.7 | 13.1 | 2.4 | 34.8 | 19.2 |
| LOS | B | A | B | A | C | B |
| Approach Delay | | 8.0 | 11.2 | | 28.5 | |
| Approach LOS | | A | B | | C | |

Intersection Summary


Cycle Length: 90
 Actuated Cycle Length: 83.2
 Natural Cycle: 50
 Control Type: Semi Act-Uncoord
 Maximum v/c Ratio: 0.69
 Intersection Signal Delay: 14.9
 Intersection LOS: B
 Intersection Capacity Utilization 57.4%
 ICU Level of Service B
 Analysis Period (min) 15

Splits and Phases: 13: Marksheffel Rd & Sterling Ranch Rd



Timings
13: Marksheffel Rd & Sterling Ranch Rd

2043 Background Traffic
PM Peak Hour



| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|----------------------|-------|-------|-------|-------|-------|-------|
| Lane Configurations | ↶ | ↷ | ↷ | ↷ | ↷ | ↷ |
| Traffic Volume (vph) | 305 | 946 | 841 | 570 | 342 | 191 |
| Future Volume (vph) | 305 | 946 | 841 | 570 | 342 | 191 |
| Turn Type | pm+pt | NA | NA | Perm | Prot | Perm |
| Protected Phases | 5 | 2 | 6 | | 4 | |
| Permitted Phases | 2 | | | 6 | | 4 |
| Detector Phase | 5 | 2 | 6 | 6 | 4 | 4 |
| Switch Phase | | | | | | |
| Minimum Initial (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| Minimum Split (s) | 10.0 | 23.0 | 23.0 | 23.0 | 10.0 | 10.0 |
| Total Split (s) | 10.0 | 60.0 | 50.0 | 50.0 | 30.0 | 30.0 |
| Total Split (%) | 11.1% | 66.7% | 55.6% | 55.6% | 33.3% | 33.3% |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| Lead/Lag | Lead | | Lag | Lag | | |
| Lead-Lag Optimize? | Yes | | Yes | Yes | | |
| Recall Mode | None | Max | Max | Max | None | None |
| Act Effct Green (s) | 55.0 | 55.0 | 45.0 | 45.0 | 13.6 | 13.6 |
| Actuated g/C Ratio | 0.70 | 0.70 | 0.57 | 0.57 | 0.17 | 0.17 |
| v/c Ratio | 0.81 | 0.41 | 0.44 | 0.52 | 0.61 | 0.46 |
| Control Delay | 25.6 | 5.9 | 10.9 | 2.7 | 34.7 | 8.3 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay | 25.6 | 5.9 | 10.9 | 2.7 | 34.7 | 8.3 |
| LOS | C | A | B | A | C | A |
| Approach Delay | | 10.7 | 7.6 | | 25.2 | |
| Approach LOS | | B | A | | C | |

Intersection Summary

Cycle Length: 90
 Actuated Cycle Length: 78.7
 Natural Cycle: 50
 Control Type: Semi Act-Uncoord
 Maximum v/c Ratio: 0.81
 Intersection Signal Delay: 11.7
 Intersection LOS: B
 Intersection Capacity Utilization 62.4%
 ICU Level of Service B
 Analysis Period (min) 15

Splits and Phases: 13: Marksheffel Rd & Sterling Ranch Rd



HCM 6th TWSC
 13: Sterling Ranch Rd & Marksheffel Rd

Short-Term Total Traffic
 AM Peak Hour

| Intersection | | | | | | | | | | | | |
|--------------------------|------|------|------|------|------|------|------|------|------|------|------|------|
| Int Delay, s/veh | 15 | | | | | | | | | | | |
| Movement | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
| Lane Configurations | ↘ | ↑↑ | ↗ | ↘ | ↑↑ | ↗ | ↘ | ↗ | ↘ | ↘ | ↑ | ↗ |
| Traffic Vol, veh/h | 38 | 133 | 2 | 8 | 80 | 142 | 2 | 0 | 6 | 427 | 1 | 150 |
| Future Vol, veh/h | 38 | 133 | 2 | 8 | 80 | 142 | 2 | 0 | 6 | 427 | 1 | 150 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Free | Free | Free | Free | Free | Free | Stop | Stop | Stop | Stop | Stop | Stop |
| RT Channelized | - | - | None | - | - | None | - | - | None | - | - | None |
| Storage Length | 300 | - | 200 | 250 | - | 205 | 0 | - | - | 155 | - | 0 |
| Veh in Median Storage, # | - | 0 | - | - | 0 | - | - | 0 | - | - | 0 | - |
| Grade, % | - | 0 | - | - | 0 | - | - | 0 | - | - | 0 | - |
| Peak Hour Factor | 85 | 85 | 85 | 85 | 85 | 85 | 85 | 85 | 85 | 85 | 85 | 85 |
| Heavy Vehicles, % | 2 | 2 | 70 | 70 | 2 | 2 | 88 | 2 | 88 | 2 | 2 | 2 |
| Mvmt Flow | 45 | 156 | 2 | 9 | 94 | 167 | 2 | 0 | 7 | 502 | 1 | 176 |

| Major/Minor | Major1 | | | Major2 | | | Minor1 | | | Minor2 | | |
|----------------------|--------|---|---|--------|---|---|--------|------|------|--------|------|------|
| Conflicting Flow All | 261 | 0 | 0 | 158 | 0 | 0 | 312 | 525 | 78 | 280 | 360 | 47 |
| Stage 1 | - | - | - | - | - | - | 246 | 246 | - | 112 | 112 | - |
| Stage 2 | - | - | - | - | - | - | 66 | 279 | - | 168 | 248 | - |
| Critical Hdwy | 4.14 | - | - | 5.5 | - | - | 9.26 | 6.54 | 8.66 | 7.54 | 6.54 | 6.94 |
| Critical Hdwy Stg 1 | - | - | - | - | - | - | 8.26 | 5.54 | - | 6.54 | 5.54 | - |
| Critical Hdwy Stg 2 | - | - | - | - | - | - | 8.26 | 5.54 | - | 6.54 | 5.54 | - |
| Follow-up Hdwy | 2.22 | - | - | 2.9 | - | - | 4.38 | 4.02 | 4.18 | 3.52 | 4.02 | 3.32 |
| Pot Cap-1 Maneuver | 1300 | - | - | 1039 | - | - | 443 | 456 | 747 | 650 | 565 | 1012 |
| Stage 1 | - | - | - | - | - | - | 541 | 701 | - | 881 | 802 | - |
| Stage 2 | - | - | - | - | - | - | 735 | 678 | - | 817 | 700 | - |
| Platoon blocked, % | - | - | - | - | - | - | - | - | - | - | - | - |
| Mov Cap-1 Maneuver | 1300 | - | - | 1039 | - | - | 353 | 436 | 747 | 623 | 540 | 1012 |
| Mov Cap-2 Maneuver | - | - | - | - | - | - | 353 | 436 | - | 623 | 540 | - |
| Stage 1 | - | - | - | - | - | - | 522 | 676 | - | 850 | 795 | - |
| Stage 2 | - | - | - | - | - | - | 601 | 672 | - | 781 | 676 | - |

| Approach | EB | | | WB | | | NB | | | SB | | |
|----------------------|-----|--|--|-----|--|--|------|--|--|------|--|--|
| HCM Control Delay, s | 1.7 | | | 0.3 | | | 11.3 | | | 24.9 | | |
| HCM LOS | | | | | | | B | | | C | | |

| Minor Lane/Major Mvmt | NBLn1 | NBLn2 | EBL | EBT | EBR | WBL | WBT | WBR | SBLn1 | SBLn2 | SBLn3 |
|-----------------------|-------|-------|-------|-----|-----|-------|-----|-----|-------|-------|-------|
| Capacity (veh/h) | 353 | 747 | 1300 | - | - | 1039 | - | - | 623 | 540 | 1012 |
| HCM Lane V/C Ratio | 0.007 | 0.009 | 0.034 | - | - | 0.009 | - | - | 0.806 | 0.002 | 0.174 |
| HCM Control Delay (s) | 15.3 | 9.9 | 7.9 | - | - | 8.5 | - | - | 30.4 | 11.7 | 9.3 |
| HCM Lane LOS | | C | A | A | - | A | - | - | D | B | A |
| HCM 95th %tile Q(veh) | 0 | 0 | 0.1 | - | - | 0 | - | - | 8.1 | 0 | 0.6 |

Timings
13: Sterling Ranch Rd & Marksheffel Rd

Short-Term Total Traffic
AM Peak Hour

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | SBL | SBT | SBR | |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 38 | 133 | 2 | 8 | 80 | 142 | 2 | 0 | 427 | 1 | 150 | |
| Future Volume (vph) | 38 | 133 | 2 | 8 | 80 | 142 | 2 | 0 | 427 | 1 | 150 | |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Prot | NA | Perm | |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | 7 | 4 | | |
| Permitted Phases | 2 | | 2 | 6 | | 6 | 8 | | | | 4 | |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | 6 | 3 | 8 | 7 | 4 | 4 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | |
| Minimum Split (s) | 10.0 | 23.0 | 23.0 | 10.0 | 23.0 | 23.0 | 10.0 | 10.0 | 9.5 | 10.0 | 10.0 | |
| Total Split (s) | 11.0 | 50.0 | 50.0 | 10.0 | 49.0 | 49.0 | 10.0 | 10.0 | 20.0 | 20.0 | 20.0 | |
| Total Split (%) | 12.2% | 55.6% | 55.6% | 11.1% | 54.4% | 54.4% | 11.1% | 11.1% | 22.2% | 22.2% | 22.2% | |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.5 | 3.0 | 3.0 | |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 1.0 | 2.0 | 2.0 | |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 4.5 | 5.0 | 5.0 | |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lead | Lag | Lag | |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | |
| Recall Mode | None | Max | Max | None | Max | Max | None | None | None | None | None | |
| Act Effct Green (s) | 50.4 | 49.4 | 49.4 | 47.8 | 45.0 | 45.0 | 5.9 | 5.1 | 14.6 | 14.1 | 14.1 | |
| Actuated g/C Ratio | 0.65 | 0.64 | 0.64 | 0.62 | 0.58 | 0.58 | 0.08 | 0.07 | 0.19 | 0.18 | 0.18 | |
| v/c Ratio | 0.05 | 0.07 | 0.00 | 0.02 | 0.05 | 0.17 | 0.03 | 0.01 | 0.77 | 0.00 | 0.41 | |
| Control Delay | 5.6 | 6.9 | 0.0 | 5.9 | 9.3 | 1.6 | 30.0 | 0.0 | 40.2 | 29.0 | 8.6 | |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | |
| Total Delay | 5.6 | 6.9 | 0.0 | 5.9 | 9.3 | 1.6 | 30.0 | 0.0 | 40.2 | 29.0 | 8.6 | |
| LOS | A | A | A | A | A | A | C | A | D | C | A | |
| Approach Delay | | 6.5 | | | 4.4 | | | 6.7 | | 32.0 | | |
| Approach LOS | | A | | | A | | | A | | C | | |

Intersection Summary

Cycle Length: 90
 Actuated Cycle Length: 77.1
 Natural Cycle: 60
 Control Type: Semi Act-Uncoord
 Maximum v/c Ratio: 0.77
 Intersection Signal Delay: 20.9
 Intersection LOS: C
 Intersection Capacity Utilization 36.0%
 ICU Level of Service A
 Analysis Period (min) 15

Splits and Phases: 13: Sterling Ranch Rd & Marksheffel Rd



HCM 6th TWSC
13: Sterling Ranch Rd & Marksheffel Rd

Short-Term Total Traffic
PM Peak Hour

| Intersection | | | | | | | | | | | | |
|--------------------------|------|------|------|------|------|------|------|------|------|------|------|------|
| Int Delay, s/veh | 21.4 | | | | | | | | | | | |
| Movement | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
| Lane Configurations | ↘ | ↑↑ | ↗ | ↘ | ↑↑ | ↗ | ↘ | ↗ | | ↘ | ↑ | ↗ |
| Traffic Vol, veh/h | 130 | 108 | 2 | 6 | 178 | 481 | 2 | 0 | 7 | 283 | 1 | 100 |
| Future Vol, veh/h | 130 | 108 | 2 | 6 | 178 | 481 | 2 | 0 | 7 | 283 | 1 | 100 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Free | Free | Free | Free | Free | Free | Stop | Stop | Stop | Stop | Stop | Stop |
| RT Channelized | - | - | None | - | - | None | - | - | None | - | - | None |
| Storage Length | 300 | - | 200 | 250 | - | 205 | 0 | - | - | 155 | - | 0 |
| Veh in Median Storage, # | - | 0 | - | - | 0 | - | - | 0 | - | - | 0 | - |
| Grade, % | - | 0 | - | - | 0 | - | - | 0 | - | - | 0 | - |
| Peak Hour Factor | 85 | 85 | 85 | 85 | 85 | 85 | 85 | 85 | 85 | 85 | 85 | 85 |
| Heavy Vehicles, % | 2 | 2 | 88 | 88 | 2 | 2 | 78 | 2 | 78 | 2 | 2 | 2 |
| Mvmt Flow | 153 | 127 | 2 | 7 | 209 | 566 | 2 | 0 | 8 | 333 | 1 | 118 |

| Major/Minor | Major1 | | | Major2 | | | Minor1 | | | Minor2 | | |
|----------------------|--------|---|---|--------|---|---|--------|------|------|--------|------|------|
| Conflicting Flow All | 775 | 0 | 0 | 129 | 0 | 0 | 552 | 1222 | 64 | 593 | 658 | 105 |
| Stage 1 | - | - | - | - | - | - | 433 | 433 | - | 223 | 223 | - |
| Stage 2 | - | - | - | - | - | - | 119 | 789 | - | 370 | 435 | - |
| Critical Hdwy | 4.14 | - | - | 5.86 | - | - | 9.06 | 6.54 | 8.46 | 7.54 | 6.54 | 6.94 |
| Critical Hdwy Stg 1 | - | - | - | - | - | - | 8.06 | 5.54 | - | 6.54 | 5.54 | - |
| Critical Hdwy Stg 2 | - | - | - | - | - | - | 8.06 | 5.54 | - | 6.54 | 5.54 | - |
| Follow-up Hdwy | 2.22 | - | - | 3.08 | - | - | 4.28 | 4.02 | 4.08 | 3.52 | 4.02 | 3.32 |
| Pot Cap-1 Maneuver | 837 | - | - | 1001 | - | - | 286 | 178 | 787 | 389 | 383 | 929 |
| Stage 1 | - | - | - | - | - | - | 408 | 580 | - | 759 | 718 | - |
| Stage 2 | - | - | - | - | - | - | 691 | 400 | - | 622 | 579 | - |
| Platoon blocked, % | | - | - | - | - | - | | | | | | |
| Mov Cap-1 Maneuver | 837 | - | - | 1001 | - | - | 213 | 144 | 787 | ~ 329 | 311 | 929 |
| Mov Cap-2 Maneuver | - | - | - | - | - | - | 213 | 144 | - | ~ 329 | 311 | - |
| Stage 1 | - | - | - | - | - | - | 333 | 474 | - | 620 | 713 | - |
| Stage 2 | - | - | - | - | - | - | 598 | 397 | - | 503 | 473 | - |

| Approach | EB | | | WB | | | NB | | | SB | | |
|----------------------|-----|--|--|-----|--|--|------|--|--|------|--|--|
| HCM Control Delay, s | 5.6 | | | 0.1 | | | 12.4 | | | 68.3 | | |
| HCM LOS | | | | | | | B | | | F | | |

| Minor Lane/Major Mvmt | NBLn1 | NBLn2 | EBL | EBT | EBR | WBL | WBT | WBR | SBLn1 | SBLn2 | SBLn3 |
|-----------------------|-------|-------|-------|-----|-----|-------|-----|-----|-------|-------|-------|
| Capacity (veh/h) | 213 | 787 | 837 | - | - | 1001 | - | - | 329 | 311 | 929 |
| HCM Lane V/C Ratio | 0.011 | 0.01 | 0.183 | - | - | 0.007 | - | - | 1.012 | 0.004 | 0.127 |
| HCM Control Delay (s) | 22.1 | 9.6 | 10.3 | - | - | 8.6 | - | - | 89.3 | 16.6 | 9.4 |
| HCM Lane LOS | | C | A | B | - | - | A | - | F | C | A |
| HCM 95th %tile Q(veh) | | 0 | 0 | 0.7 | - | - | 0 | - | 11.4 | 0 | 0.4 |

Notes
 ~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon

Timings
13: Sterling Ranch Rd & Marksheffel Rd

Short-Term Total Traffic
PM Peak Hour

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | SBL | SBT | SBR |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Lane Configurations | | | | | | | | | | | |
| Traffic Volume (vph) | 130 | 108 | 2 | 6 | 178 | 481 | 2 | 0 | 283 | 1 | 100 |
| Future Volume (vph) | 130 | 108 | 2 | 6 | 178 | 481 | 2 | 0 | 283 | 1 | 100 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Prot | NA | Perm |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | 7 | 4 | |
| Permitted Phases | 2 | | 2 | 6 | | 6 | 8 | | | | 4 |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | 6 | 3 | 8 | 7 | 4 | 4 |
| Switch Phase | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| Minimum Split (s) | 10.0 | 23.0 | 23.0 | 10.0 | 23.0 | 23.0 | 10.0 | 10.0 | 9.5 | 10.0 | 10.0 |
| Total Split (s) | 11.0 | 50.0 | 50.0 | 10.0 | 49.0 | 49.0 | 10.0 | 10.0 | 20.0 | 20.0 | 20.0 |
| Total Split (%) | 12.2% | 55.6% | 55.6% | 11.1% | 54.4% | 54.4% | 11.1% | 11.1% | 22.2% | 22.2% | 22.2% |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.5 | 3.0 | 3.0 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 1.0 | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 4.5 | 5.0 | 5.0 |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lead | Lag | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Recall Mode | None | Max | Max | None | Max | Max | None | None | None | None | None |
| Act Effct Green (s) | 54.5 | 53.5 | 53.5 | 49.2 | 44.2 | 44.2 | 5.9 | 5.0 | 12.5 | 11.3 | 11.3 |
| Actuated g/C Ratio | 0.69 | 0.68 | 0.68 | 0.62 | 0.56 | 0.56 | 0.07 | 0.06 | 0.16 | 0.14 | 0.14 |
| v/c Ratio | 0.20 | 0.05 | 0.00 | 0.02 | 0.11 | 0.50 | 0.03 | 0.01 | 0.62 | 0.00 | 0.34 |
| Control Delay | 5.6 | 6.4 | 0.0 | 5.7 | 9.3 | 2.8 | 29.5 | 0.0 | 36.7 | 30.0 | 6.6 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay | 5.6 | 6.4 | 0.0 | 5.7 | 9.3 | 2.8 | 29.5 | 0.0 | 36.7 | 30.0 | 6.6 |
| LOS | A | A | A | A | A | A | C | A | D | C | A |
| Approach Delay | | 5.9 | | | 4.6 | | | 5.9 | | 28.9 | |
| Approach LOS | | A | | | A | | | A | | C | |

Intersection Summary

Cycle Length: 90
 Actuated Cycle Length: 79
 Natural Cycle: 60
 Control Type: Semi Act-Uncoord
 Maximum v/c Ratio: 0.62
 Intersection Signal Delay: 12.0
 Intersection LOS: B
 Intersection Capacity Utilization 53.7%
 ICU Level of Service A
 Analysis Period (min) 15

Splits and Phases: 13: Sterling Ranch Rd & Marksheffel Rd



Timings
13: Sterling Ranch Rd & Marksheffel Rd


2043 Total Traffic
AM Peak Hour

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | SBL | SBT | SBR | |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 160 | 900 | 27 | 39 | 809 | 175 | 9 | 2 | 478 | 6 | 328 | |
| Future Volume (vph) | 160 | 900 | 27 | 39 | 809 | 175 | 9 | 2 | 478 | 6 | 328 | |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Prot | NA | Perm | |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | 7 | 4 | | |
| Permitted Phases | 2 | | 2 | 6 | | 6 | 8 | | | | 4 | |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | 6 | 3 | 8 | 7 | 4 | 4 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 15.0 | 15.0 | 5.0 | 15.0 | 15.0 | 5.0 | 10.0 | 20.0 | 10.0 | 10.0 | |
| Minimum Split (s) | 10.0 | 20.0 | 20.0 | 10.0 | 20.0 | 20.0 | 10.0 | 15.0 | 25.0 | 20.0 | 20.0 | |
| Total Split (s) | 12.0 | 51.0 | 51.0 | 12.0 | 51.0 | 51.0 | 12.0 | 25.0 | 32.0 | 45.0 | 45.0 | |
| Total Split (%) | 10.0% | 42.5% | 42.5% | 10.0% | 42.5% | 42.5% | 10.0% | 20.8% | 26.7% | 37.5% | 37.5% | |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lead | Lag | Lag | |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | |
| Recall Mode | None | C-Max | C-Max | None | C-Max | C-Max | None | None | None | None | None | |
| Act Effct Green (s) | 79.8 | 70.8 | 70.8 | 72.5 | 65.4 | 65.4 | 10.2 | 10.0 | 23.1 | 26.7 | 26.7 | |
| Actuated g/C Ratio | 0.66 | 0.59 | 0.59 | 0.60 | 0.54 | 0.54 | 0.08 | 0.08 | 0.19 | 0.22 | 0.22 | |
| v/c Ratio | 0.42 | 0.46 | 0.04 | 0.17 | 0.45 | 0.20 | 0.10 | 0.16 | 0.77 | 0.02 | 0.61 | |
| Control Delay | 17.7 | 13.4 | 0.1 | 11.5 | 19.7 | 3.8 | 35.7 | 28.2 | 54.1 | 32.8 | 12.6 | |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | |
| Total Delay | 17.7 | 13.4 | 0.1 | 11.5 | 19.7 | 3.8 | 35.7 | 28.2 | 54.1 | 32.8 | 12.6 | |
| LOS | B | B | A | B | B | A | D | C | D | C | B | |
| Approach Delay | | 13.7 | | | 16.7 | | | 31.0 | | 37.2 | | |
| Approach LOS | | B | | | B | | | C | | D | | |

Intersection Summary

Cycle Length: 120
 Actuated Cycle Length: 120
 Offset: 0 (0%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 75
 Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.77
 Intersection Signal Delay: 21.4
 Intersection LOS: C
 Intersection Capacity Utilization 64.0%
 ICU Level of Service C
 Analysis Period (min) 15

Splits and Phases: 13: Sterling Ranch Rd & Marksheffel Rd



Timings
13: Sterling Ranch Rd & Marksheffel Rd


2043 Total Traffic
PM Peak Hour

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | SBL | SBT | SBR |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Lane Configurations | | | | | | | | | | | |
| Traffic Volume (vph) | 305 | 946 | 11 | 17 | 841 | 570 | 27 | 6 | 342 | 2 | 191 |
| Future Volume (vph) | 305 | 946 | 11 | 17 | 841 | 570 | 27 | 6 | 342 | 2 | 191 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Prot | NA | Perm |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | 7 | 4 | |
| Permitted Phases | 2 | | 2 | 6 | | 6 | 8 | | | | 4 |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | 6 | 3 | 8 | 7 | 4 | 4 |
| Switch Phase | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 15.0 | 15.0 | 5.0 | 15.0 | 15.0 | 5.0 | 10.0 | 20.0 | 10.0 | 10.0 |
| Minimum Split (s) | 10.0 | 20.0 | 20.0 | 10.0 | 20.0 | 20.0 | 10.0 | 15.0 | 25.0 | 20.0 | 20.0 |
| Total Split (s) | 20.0 | 68.0 | 68.0 | 12.0 | 60.0 | 60.0 | 10.0 | 15.0 | 25.0 | 30.0 | 30.0 |
| Total Split (%) | 16.7% | 56.7% | 56.7% | 10.0% | 50.0% | 50.0% | 8.3% | 12.5% | 20.8% | 25.0% | 25.0% |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lead | Lag | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Recall Mode | None | C-Max | C-Max | None | C-Max | C-Max | None | None | None | None | None |
| Act Effct Green (s) | 78.0 | 73.3 | 73.3 | 65.2 | 59.1 | 59.1 | 13.0 | 10.0 | 20.0 | 26.0 | 26.0 |
| Actuated g/C Ratio | 0.65 | 0.61 | 0.61 | 0.54 | 0.49 | 0.49 | 0.11 | 0.08 | 0.17 | 0.22 | 0.22 |
| v/c Ratio | 0.79 | 0.47 | 0.02 | 0.08 | 0.51 | 0.56 | 0.25 | 0.36 | 0.64 | 0.01 | 0.40 |
| Control Delay | 45.3 | 9.5 | 0.0 | 10.2 | 23.1 | 3.7 | 38.4 | 27.1 | 52.3 | 38.0 | 8.0 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay | 45.3 | 9.5 | 0.0 | 10.2 | 23.1 | 3.7 | 38.4 | 27.1 | 52.3 | 38.0 | 8.0 |
| LOS | D | A | A | B | C | A | D | C | D | D | A |
| Approach Delay | | 18.1 | | | 15.2 | | | 31.5 | | 36.4 | |
| Approach LOS | | B | | | B | | | C | | D | |

Intersection Summary

Cycle Length: 120
 Actuated Cycle Length: 120
 Offset: 0 (0%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 90
 Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.79
 Intersection Signal Delay: 20.1
 Intersection LOS: C
 Intersection Capacity Utilization 73.0%
 ICU Level of Service D
 Analysis Period (min) 15

Splits and Phases: 13: Sterling Ranch Rd & Marksheffel Rd



Appendix Tables 1-2



**Appendix Table 1
Area Traffic Impact Studies
Rhetoric Subdivision**

| Study | PCD File No⁽¹⁾ | Consultant | Date |
|---|---|-------------------------------------|-------------------------------|
| Sterling Ranch Reports | | | |
| Sterling Ranch Updated Traffic Impact Analysis | SKP07007 | LSC Transportation Consultants, Inc | June 5, 2008 |
| Sterling Ranch Phase 1 Traffic Impact Study | P151 | LSC Transportation Consultants, Inc | March 16, 2015 |
| Sterling Ranch Phases 1-3 Transportation Memorandum | SP1415 | LSC Transportation Consultants, Inc | October 2, 2017 |
| Branding Iron at Sterling Ranch Filing No. 1 and Homestead at Sterling Ranch Filing No. 1 Transportation Memorandum | SF1724 SF1725 | LSC Transportation Consultants, Inc | December 19, 2017 |
| Sterling Ranch Filing No. 2 Transportation Memorandum | SF1820 | LSC Transportation Consultants, Inc | April 3, 2018 |
| Sterling Ranch Phase 2 Preliminary Plan Traffic Impact Study | SP203 | LSC Transportation Consultants, Inc | December 20, 2018 |
| Homestead at Sterling Ranch Filing No. 2 Transportation Memorandum | SF194 | LSC Transportation Consultants, Inc | March 3, 2020 |
| Branding Iron at Sterling Ranch Filing No. 2 Transportation Memorandum | SF1918 | LSC Transportation Consultants, Inc | May 6, 2020 |
| Sterling Ranch Filing No. 2 and Phase 2 Traffic Impact Study | SF2015 SP191 | LSC Transportation Consultants, Inc | June 23, 2021 |
| Sterling Ranch Filing No. 3 Transportation Memorandum | SF2132 | LSC Transportation Consultants, Inc | April 19, 2022 |
| Homestead North Phase 1 Updated Transportation Memorandum | SP208 | LSC Transportation Consultants, Inc | January 11, 2022 |
| Homestead North Filing No. 1 Traffic Technical Memorandum | SF2213 | LSC Transportation Consultants, Inc | February 2, 2022 |
| Homestead North Filing No. 2 Traffic Technical Memorandum | SF2218 | LSC Transportation Consultants, Inc | April 15, 2022 |
| Homestead North Filing 3 Traffic Impact Study | SF2229 | LSC Transportation Consultants, Inc | June 17, 2022 |
| The Villages at Sterling Ranch East Preliminary Plan/Traffic Generation Analysis | PUDSP226 | SM Rocha, LLC | July 1, 2022 |
| Sterling Ranch Sketch Plan Amendment Master Traffic Impact Study | SKP224 | LSC Transportation Consultants, Inc | March 17, 2023 |
| Sterling Ranch East - Rezoning & Preliminary Plan Traffic Impact Study | SP-22-004, P-22-012, P-22-013 | LSC Transportation Consultants, Inc | March 17, 2023 ⁽²⁾ |
| Sterling Ranch East Filing Nos 1 & 2 Traffic Technical Memorandum | SF2235 SF2237 | LSC Transportation Consultants, Inc | February 10, 2023 |
| Sterling Ranch Filing No. 4 Transportation Memorandum | SF2230 | LSC Transportation Consultants, Inc | February 21, 2023 |
| Foursquare at Sterling Ranch East Transportation Memorandum | SF2236 | LSC Transportation Consultants, Inc | April 20, 2023 |
| Copper Chase at Sterling Ranch Traffic Impact Study | PUDSP222 | LSC Transportation Consultants, Inc | April 28, 2023 |
| Sterling Ranch East Filing 5 Rezone and Preliminary Plan Traffic Impact Study | SP235 | LSC Transportation Consultants, Inc | January 15, 2024 |
| Retreat at TimberRidge Reports | | | |
| The Retreat at TimberRidge Traffic Impact Analysis | PUD173 | LSC Transportation Consultants, Inc | January 25, 2018 |
| The Retreat at TimberRidge Preliminary Plan Traffic Technical Memorandum | SP182 | LSC Transportation Consultants, Inc | June 29, 2018 |
| The Retreat at TimberRidge Filing No. 1 Traffic Technical Memorandum | SF199 | LSC Transportation Consultants, Inc | April 3, 2020 |
| The Retreat at TimberRidge Filing No. 2 Updated Traffic Technical Memorandum | SF2121 | LSC Transportation Consultants, Inc | October 4, 2021 |
| The Retreat at TimberRidge Filing No. 3 Traffic Technical Memorandum | SF2241 | LSC Transportation Consultants, Inc | July 1, 2022 |
| The Retreat at TimberRidge Filing No. 4 Traffic Technical Memorandum | SF1827 | LSC Transportation Consultants, Inc | February 21, 2024 |
| Other Area Reports | | | |
| Wolf Ranch School Site Traffic Impact Study | OAR1720 | Matrix Design Group, Inc. | 5-May-17 |
| The Ranch Sketch Plan Traffic Impact Analysis | SKP186 | LSC Transportation Consultants, Inc | July 9, 2019 |
| Lodge III Traffic Impact Study | OAR | LSC Transportation Consultants, Inc | December 13, 2019 |
| Continental 613 Traffic Impact Study | OAR2177 | LSC Transportation Consultants, Inc | July 16, 2021 |
| Solace at Black Forest Traffic Impact and Access Analysis | OAR2134 | LSC Transportation Consultants, Inc | August 13, 2021 |
| Traffic Impact Study Addendum for Percheron | OAR2173 | SM Rocha, LLC | October, 2021 |
| Woodmen East Commercial Center Traffic Impact Analysis | OAR2191 | LSC Transportation Consultants, Inc | December 8, 2021 |
| Traffic Impact Study for Jaynes Property | SKP225 | SM Rocha, LLC | May, 2022 |
| Traffic Impact Study for Rhetoric Site | P2216 | SM Rocha, LLC | June, 2022 |
| Briargate-Stapleton Corridor Study (DRAFT) | briargate-stapleton.com | Wilson & Company | December 9, 2021 |
| Notes: | | | |
| (1) Follow the links listed below to obtain the most recent version of each listed study. To obtain a copy of the version of each study used in preparing this report please contact LSC Transportation Consultants, Inc. | | | |
| (2) With minor revision 4/3/2023 | | | |
| Source: LSC Transportation Consultants, Inc. | | | |

Appendix Table 2
Existing Truck Operations
Rhetoric Subdivision

| DATE | Day of the Week | Tandem | Semi | TOTAL LOADS | DATE | Day of the Week | Tandem | Semi | TOTAL LOADS |
|------------|-----------------|--------|------|-------------|------------|-----------------|--------|------|-------------|
| 3/6/2022 | Sunday | 0 | 0 | 0 | 5/23/2022 | Monday | 19 | 4 | 23 |
| 3/13/2022 | Sunday | 0 | 0 | 0 | 10/17/2022 | Monday | 19 | 4 | 23 |
| 3/20/2022 | Sunday | 0 | 0 | 0 | 11/3/2022 | Thursday | 17 | 6 | 23 |
| 3/27/2022 | Sunday | 0 | 0 | 0 | 9/30/2022 | Friday | 17 | 6 | 23 |
| 4/3/2022 | Sunday | 0 | 0 | 0 | 5/24/2022 | Tuesday | 18 | 6 | 24 |
| 4/10/2022 | Sunday | 0 | 0 | 0 | 10/13/2022 | Thursday | 20 | 4 | 24 |
| 4/17/2022 | Sunday | 0 | 0 | 0 | 10/21/2022 | Friday | 18 | 6 | 24 |
| 4/24/2022 | Sunday | 0 | 0 | 0 | 9/17/2022 | Saturday | 23 | 1 | 24 |
| 5/1/2022 | Sunday | 0 | 0 | 0 | 5/2/2022 | Monday | 25 | 0 | 25 |
| 5/8/2022 | Sunday | 0 | 0 | 0 | 11/21/2022 | Monday | 17 | 8 | 25 |
| 5/15/2022 | Sunday | 0 | 0 | 0 | 12/6/2022 | Tuesday | 23 | 2 | 25 |
| 6/12/2022 | Sunday | 0 | 0 | 0 | 10/6/2022 | Thursday | 12 | 13 | 25 |
| 6/19/2022 | Sunday | 0 | 0 | 0 | 10/27/2022 | Thursday | 21 | 4 | 25 |
| 6/26/2022 | Sunday | 0 | 0 | 0 | 12/29/2022 | Thursday | 25 | 0 | 25 |
| 7/3/2022 | Sunday | 0 | 0 | 0 | 5/27/2022 | Friday | 17 | 8 | 25 |
| 7/10/2022 | Sunday | 0 | 0 | 0 | 12/2/2022 | Friday | 20 | 5 | 25 |
| 7/17/2022 | Sunday | 0 | 0 | 0 | 10/31/2022 | Monday | 18 | 8 | 26 |
| 7/24/2022 | Sunday | 0 | 0 | 0 | 8/16/2022 | Tuesday | 26 | 0 | 26 |
| 7/31/2022 | Sunday | 0 | 0 | 0 | 10/12/2022 | Wednesday | 20 | 6 | 26 |
| 8/7/2022 | Sunday | 0 | 0 | 0 | 3/3/2022 | Thursday | 21 | 5 | 26 |
| 8/14/2022 | Sunday | 0 | 0 | 0 | 6/30/2022 | Thursday | 17 | 9 | 26 |
| 8/21/2022 | Sunday | 0 | 0 | 0 | 9/1/2022 | Thursday | 18 | 8 | 26 |
| 9/4/2022 | Sunday | 0 | 0 | 0 | 10/18/2022 | Tuesday | 21 | 6 | 27 |
| 9/11/2022 | Sunday | 0 | 0 | 0 | 10/19/2022 | Wednesday | 21 | 6 | 27 |
| 9/18/2022 | Sunday | 0 | 0 | 0 | 6/16/2022 | Thursday | 26 | 1 | 27 |
| 9/25/2022 | Sunday | 0 | 0 | 0 | 11/9/2022 | Wednesday | 20 | 8 | 28 |
| 10/2/2022 | Sunday | 0 | 0 | 0 | 12/28/2022 | Wednesday | 24 | 4 | 28 |
| 10/9/2022 | Sunday | 0 | 0 | 0 | 11/17/2022 | Thursday | 13 | 15 | 28 |
| 10/16/2022 | Sunday | 0 | 0 | 0 | 12/1/2022 | Thursday | 18 | 11 | 29 |
| 10/23/2022 | Sunday | 0 | 0 | 0 | 6/3/2022 | Friday | 25 | 4 | 29 |
| 10/30/2022 | Sunday | 0 | 0 | 0 | 4/12/2022 | Tuesday | 15 | 15 | 30 |
| 11/6/2022 | Sunday | 0 | 0 | 0 | 5/31/2022 | Tuesday | 23 | 7 | 30 |
| 11/13/2022 | Sunday | 0 | 0 | 0 | 12/14/2022 | Wednesday | 30 | 0 | 30 |
| 11/20/2022 | Sunday | 0 | 0 | 0 | 8/4/2022 | Thursday | 8 | 22 | 30 |
| 11/27/2022 | Sunday | 0 | 0 | 0 | 7/1/2022 | Friday | 14 | 16 | 30 |
| 12/4/2022 | Sunday | 0 | 0 | 0 | 12/20/2022 | Tuesday | 28 | 3 | 31 |
| 12/11/2022 | Sunday | 0 | 0 | 0 | 5/6/2022 | Friday | 31 | 0 | 31 |
| 12/18/2022 | Sunday | 0 | 0 | 0 | 12/5/2022 | Monday | 28 | 4 | 32 |
| 12/25/2022 | Sunday | 0 | 0 | 0 | 12/19/2022 | Monday | 29 | 3 | 32 |
| 3/21/2022 | Monday | 0 | 0 | 0 | 12/7/2022 | Wednesday | 26 | 6 | 32 |
| 7/4/2022 | Monday | 0 | 0 | 0 | 8/25/2022 | Thursday | 17 | 15 | 32 |
| 7/11/2022 | Monday | 0 | 0 | 0 | 6/10/2022 | Friday | 29 | 3 | 32 |
| 9/5/2022 | Monday | 0 | 0 | 0 | 5/17/2022 | Tuesday | 32 | 1 | 33 |
| 10/3/2022 | Monday | 0 | 0 | 0 | 6/15/2022 | Wednesday | 27 | 6 | 33 |
| 11/28/2022 | Monday | 0 | 0 | 0 | 8/30/2022 | Tuesday | 10 | 24 | 34 |
| 12/26/2022 | Monday | 0 | 0 | 0 | 10/25/2022 | Tuesday | 26 | 8 | 34 |
| 4/26/2022 | Tuesday | 0 | 0 | 0 | 12/27/2022 | Tuesday | 19 | 15 | 34 |
| 11/29/2022 | Tuesday | 0 | 0 | 0 | 3/30/2022 | Wednesday | 20 | 14 | 34 |
| 8/31/2022 | Wednesday | 0 | 0 | 0 | 5/18/2022 | Wednesday | 26 | 8 | 34 |
| 3/10/2022 | Thursday | 0 | 0 | 0 | 4/28/2022 | Thursday | 34 | 0 | 34 |
| 3/17/2022 | Thursday | 0 | 0 | 0 | 11/24/2022 | Thursday | 25 | 9 | 34 |
| 4/14/2022 | Thursday | 0 | 0 | 0 | 7/15/2022 | Friday | 26 | 8 | 34 |
| 4/21/2022 | Thursday | 0 | 0 | 0 | 8/26/2022 | Friday | 18 | 16 | 34 |
| 12/22/2022 | Thursday | 0 | 0 | 0 | 5/16/2022 | Monday | 35 | 0 | 35 |
| 4/1/2022 | Friday | 0 | 0 | 0 | 3/15/2022 | Tuesday | 29 | 6 | 35 |
| 4/22/2022 | Friday | 0 | 0 | 0 | 10/4/2022 | Tuesday | 28 | 7 | 35 |
| 11/18/2022 | Friday | 0 | 0 | 0 | 5/20/2022 | Friday | 27 | 8 | 35 |
| 11/25/2022 | Friday | 0 | 0 | 0 | 6/24/2022 | Friday | 24 | 11 | 35 |
| 12/23/2022 | Friday | 0 | 0 | 0 | 5/11/2022 | Wednesday | 36 | 0 | 36 |
| 12/30/2022 | Friday | 0 | 0 | 0 | 6/9/2022 | Thursday | 34 | 2 | 36 |
| 3/5/2022 | Saturday | 0 | 0 | 0 | 3/4/2022 | Friday | 36 | 0 | 36 |
| 4/2/2022 | Saturday | 0 | 0 | 0 | 9/9/2022 | Friday | 26 | 10 | 36 |
| 4/9/2022 | Saturday | 0 | 0 | 0 | 6/6/2022 | Monday | 24 | 13 | 37 |
| 4/16/2022 | Saturday | 0 | 0 | 0 | 10/24/2022 | Monday | 28 | 11 | 39 |
| 4/23/2022 | Saturday | 0 | 0 | 0 | 10/11/2022 | Tuesday | 31 | 8 | 39 |
| 4/30/2022 | Saturday | 0 | 0 | 0 | 3/2/2022 | Wednesday | 29 | 10 | 39 |
| 5/7/2022 | Saturday | 0 | 0 | 0 | 5/25/2022 | Wednesday | 38 | 1 | 39 |
| 5/14/2022 | Saturday | 0 | 0 | 0 | 10/5/2022 | Wednesday | 35 | 4 | 39 |
| 6/11/2022 | Saturday | 0 | 0 | 0 | 7/14/2022 | Thursday | 30 | 9 | 39 |
| 6/18/2022 | Saturday | 0 | 0 | 0 | 9/6/2022 | Tuesday | 30 | 10 | 40 |
| 6/25/2022 | Saturday | 0 | 0 | 0 | 3/14/2022 | Monday | 36 | 5 | 41 |
| 7/2/2022 | Saturday | 0 | 0 | 0 | 6/1/2022 | Wednesday | 43 | 0 | 43 |
| 7/16/2022 | Saturday | 0 | 0 | 0 | 8/17/2022 | Wednesday | 41 | 2 | 43 |
| 7/23/2022 | Saturday | 0 | 0 | 0 | 9/22/2022 | Thursday | 37 | 6 | 43 |
| 7/30/2022 | Saturday | 0 | 0 | 0 | 6/27/2022 | Monday | 40 | 4 | 44 |
| 8/13/2022 | Saturday | 0 | 0 | 0 | 8/12/2022 | Friday | 30 | 14 | 44 |
| 9/10/2022 | Saturday | 0 | 0 | 0 | 7/25/2022 | Monday | 36 | 9 | 45 |
| 10/8/2022 | Saturday | 0 | 0 | 0 | 8/15/2022 | Monday | 22 | 23 | 45 |
| 10/15/2022 | Saturday | 0 | 0 | 0 | 8/2/2022 | Tuesday | 28 | 17 | 45 |
| 10/22/2022 | Saturday | 0 | 0 | 0 | 5/26/2022 | Thursday | 42 | 3 | 45 |
| 10/29/2022 | Saturday | 0 | 0 | 0 | 7/19/2022 | Tuesday | 34 | 12 | 46 |
| 11/12/2022 | Saturday | 0 | 0 | 0 | 7/13/2022 | Wednesday | 32 | 14 | 46 |
| 11/19/2022 | Saturday | 0 | 0 | 0 | 5/12/2022 | Thursday | 47 | 0 | 47 |
| 11/26/2022 | Saturday | 0 | 0 | 0 | 8/8/2022 | Monday | 28 | 20 | 48 |
| 12/3/2022 | Saturday | 0 | 0 | 0 | 10/10/2022 | Monday | 35 | 13 | 48 |
| 12/10/2022 | Saturday | 0 | 0 | 0 | 6/14/2022 | Tuesday | 39 | 9 | 48 |
| 12/17/2022 | Saturday | 0 | 0 | 0 | 7/20/2022 | Wednesday | 40 | 8 | 48 |
| 12/24/2022 | Saturday | 0 | 0 | 0 | 9/16/2022 | Friday | 40 | 8 | 48 |
| 12/31/2022 | Saturday | 0 | 0 | 0 | 9/7/2022 | Wednesday | 39 | 10 | 49 |
| 3/7/2022 | Monday | 1 | 0 | 1 | 9/2/2022 | Friday | 49 | 0 | 49 |
| 5/4/2022 | Wednesday | 3 | 0 | 3 | 8/28/2022 | Sunday | 43 | 7 | 50 |
| 11/30/2022 | Wednesday | 0 | 3 | 3 | 9/12/2022 | Monday | 50 | 0 | 50 |
| 10/28/2022 | Friday | 3 | 0 | 3 | 7/26/2022 | Tuesday | 25 | 25 | 50 |
| 5/5/2022 | Thursday | 4 | 0 | 4 | 6/8/2022 | Wednesday | 34 | 16 | 50 |
| 3/19/2022 | Saturday | 4 | 0 | 4 | 11/2/2022 | Wednesday | 44 | 6 | 50 |
| 3/12/2022 | Saturday | 5 | 0 | 5 | 12/8/2022 | Thursday | 34 | 16 | 50 |
| 4/6/2022 | Wednesday | 6 | 0 | 6 | 11/5/2022 | Saturday | 34 | 16 | 50 |
| 11/16/2022 | Wednesday | 4 | 3 | 7 | 6/29/2022 | Wednesday | 48 | 3 | 51 |
| 3/26/2022 | Saturday | 8 | 0 | 8 | 5/19/2022 | Thursday | 39 | 12 | 51 |
| 4/7/2022 | Thursday | 9 | 0 | 9 | 6/13/2022 | Monday | 45 | 7 | 52 |
| 12/9/2022 | Friday | 7 | 2 | 9 | 9/28/2022 | Wednesday | 35 | 17 | 52 |
| 9/3/2022 | Saturday | 9 | 0 | 9 | 7/21/2022 | Thursday | 50 | 2 | 52 |
| 5/30/2022 | Monday | 10 | 0 | 10 | 7/27/2022 | Wednesday | 45 | 8 | 53 |
| 4/19/2022 | Tuesday | 10 | 0 | 10 | 8/29/2022 | Monday | 32 | 22 | 54 |
| 11/22/2022 | Tuesday | 4 | 6 | 10 | 9/13/2022 | Tuesday | 46 | 9 | 55 |
| 12/13/2022 | Tuesday | 10 | 0 | 10 | 9/23/2022 | Friday | 47 | 8 | 55 |
| 3/9/2022 | Wednesday | 10 | 0 | 10 | 6/30/2022 | Monday | 56 | 0 | 56 |
| 11/23/2022 | Wednesday | 3 | 7 | 10 | 6/22/2022 | Wednesday | 48 | 8 | 56 |
| 4/4/2022 | Monday | 9 | 2 | 11 | 4/8/2022 | Friday | 11 | 45 | 56 |
| 3/22/2022 | Tuesday | 11 | 0 | 11 | 8/6/2022 | Saturday | 50 | 7 | 57 |
| 4/27/2022 | Wednesday | 11 | 0 | 11 | 8/22/2022 | Monday | 48 | 10 | 58 |
| 3/11/2022 | Friday | 11 | 0 | 11 | 9/19/2022 | Monday | 53 | 6 | 59 |
| 3/18/2022 | Friday | 11 | 0 | 11 | 6/23/2022 | Thursday | 45 | 14 | 59 |
| 11/11/2022 | Friday | 3 | 8 | 11 | 6/28/2022 | Tuesday | 53 | 7 | 60 |
| 4/18/2022 | Monday | 12 | 0 | 12 | 8/9/2022 | Tuesday | 48 | 12 | 60 |
| 5/3/2022 | Tuesday | 12 | 0 | 12 | 7/6/2022 | Wednesday | 38 | 23 | 61 |
| 10/1/2022 | Saturday | 3 | 9 | 12 | 8/5/2022 | Wednesday | 38 | 23 | 61 |
| 4/25/2022 | Monday | 13 | 0 | 13 | 9/15/2022 | Thursday | 54 | 8 | 62 |
| 6/21/2022 | Tuesday | 9 | 4 | 13 | 3/25/2022 | Friday | 4 | 58 | 62 |
| 4/13/2022 | Wednesday | 13 | 0 | 13 | 4/11/2022 | Monday | 17 | 46 | 63 |
| 12/15/2022 | Thursday | 13 | 0 | 13 | 8/24/2022 | Wednesday | 53 | 10 | 63 |
| 9/27/2022 | Tuesday | 12 | 2 | 14 | 9/14/2022 | Wednesday | 56 | 7 | 63 |
| 3/16/2022 | Wednesday | 8 | 6 | 14 | 7/22/2022 | Friday | 53 | 10 | 63 |
| 4/20/2022 | Wednesday | 14 | 0 | 14 | 11/8/2022 | Tuesday | 26 | 39 | 65 |
| 12/12/2022 | Monday | 11 | 4 | 15 | 5/10/2022 | Tuesday | 66 | 0 | 66 |
| 11/1/2022 | Tuesday | 15 | 0 | 15 | 7/28/2022 | Thursday | 51 | 15 | 66 |
| 3/24/2022 | Thursday | 15 | 0 | 15 | 8/23/2022 | Tuesday | 50 | 18 | 68 |
| 8/20/2022 | Saturday | 9 | 6 | 15 | 3/1/2022 | Tuesday | 64 | 6 | 70 |
| 11/7/2022 | Monday | 7 | 9 | 16 | 8/18/2022 | Thursday | 47 | 23 | 70 |
| 12/21/2022 | Wednesday | 12 | 4 | 16 | 7/29/2022 | Friday | 43 | 27 | 70 |
| 4/15/2022 | Friday | 16 | 0 | 16 | 11/4/2022 | Friday | 44 | 27 | 71 |
| 12/16/2022 | Friday | 16 | 0 | 16 | 9/26/2022 | Monday | 67 | 6 | 73 |
| 11/14/2022 | Monday | 9 | 8 | 17 | 6/7/2022 | Tuesday | 65 | 8 | 73 |
| 11/15/2022 | Tuesday | 11 | 6 | 17 | 3/28/2022 | Monday | 13 | 62 | 75 |
| 10/14/2022 | Friday | 13 | 4 | 17 | 7/5/2022 | Tuesday | 65 | 10 | 75 |
| 3/23/2022 | Wednesday | 12 | 6 | 18 | 8/10/2022 | Wednesday | 47 | 29 | 76 |
| 9/8/2022 | Thursday | 10 | 8 | 18 | 6/2/2022 | Thursday | 72 | 4 | 76 |
| 6/17/2022 | Friday | 18 | 0 | 18 | 8/19/2022 | Friday | 59 | 17 | 76 |
| 9/24/2022 | Saturday | 13 | 6 | 19 | 3/31/2022 | Thursday | 16 | 61 | 77 |
| 3/8/2022 | Tuesday | 20 | 0 | 20 | 5/9/2022 | Monday | 79 | 0 | 79 |
| 9/29/2022 | Thursday | 20 | 0 | 20 | 7/18/2022 | Monday | 66 | 13 | 79 |
| 10/20/2022 | Thursday | 12 | 8 | 20 | 3/29/2022 | Tuesday | 17 | 68 | 85 |
| 11/10/2022 | Thursday | 12 | 8 | 20 | 8/11/2022 | Thursday | 81 | 8 | 89 |
| 4/29/2022 | Friday | 20 | 0 | 20 | 8/1/2022 | Monday | 75 | 24 | 99 |
| 4/5/2022 | Tuesday | 13 | 8 | 21 | 7/9/2022 | Saturday | 91 | 12 | 103 |
| 10/26/2022 | Wednesday | | | | | | | | |

Vollmer Road Approved CD



STERLING RANCH - VOLLMER ROAD FILING 2


COUNTY OF EL PASO, STATE OF COLORADO

STREET IMPROVEMENT PLAN

MARCH 2022
CDR 20-005

AGENCIES


| | |
|----------------------|---|
| OWNER/DEVELOPER: | SR LAND, LLC 20 BOULDER CRESCENT, SUITE 201 COLORADO SPRINGS, CO 80903 JAMES F. MORLEY (719) 471-1742 |
| CIVIL ENGINEER: | JR ENGINEERING, LLC 5475 TECH CENTER DRIVE COLORADO SPRINGS, CO 80919 MIKE BRAMLETT P.E. (303) 267-6240 |
| COUNTY ENGINEERING: | EL PASO COUNTY PLANNING AND COMMUNITY DEVELOPMENT 2880 INTERNATIONAL CIRCLE, SUITE 110 COLORADO SPRINGS, CO 80910 JEFF RICE, P.E. (719) 520-6300 |
| TRAFFIC ENGINEERING: | EL PASO COUNTY DEPARTMENT OF PUBLIC WORKS 3275 AKERS DRIVE COLORADO SPRINGS, CO 80922 JENNIFER IRVINE, P.E. (719) 520-6460 |
| WATER RESOURCES: | STERLING RANCH METRO DISTRICT ENGINEERS JDS-HYDRO CONSULTANTS 545 E. PIKES PEAK AVE., SUITE 300 COLORADO SPRINGS, CO 80903 JOHN MCGINN (719) 668-8769 |
| FIRE DISTRICT: | BLACK FOREST FIRE PROTECTION DISTRICT 11445 TEACHOUT ROAD COLORADO SPRINGS, CO 80908 CHIEF BRYAN JACK (719) 495-4300 |
| GAS DEPARTMENT: | COLORADO SPRINGS UTILITIES 7710 DURANT DR. COLORADO SPRINGS, CO 80947 TIM WENDT (719) 668-3556 |
| ELECTRIC DEPARTMENT: | MOUNTAIN VIEW ELECTRIC 11140 E. WOODMEN ROAD FALCON, CO 80831 (719) 495-2283 |
| COMMUNICATIONS: | QWEST COMMUNICATIONS (U.N.C.C. LOCATORS) (800) 922-1987 AT&T (LOCATORS) (719) 635-3674 |
| CITY STORMWATER: | STORMWATER ENTERPRISE 30 S. NEVADA AVENUE, SUITE 401 COLORADO SPRINGS, CO 80903 (719)-385-5918 |




VICINITY MAP
SCALE: 1"=1,000'

SHEET INDEX


- 1 COVER SHEET
- 2 NOTES AND DETAILS
- 3 PLAN & PROFILE - VOLLMER ROAD (SOUTH) STA 10+00 TO 23+50
- 4 PLAN & PROFILE - VOLLMER ROAD (SOUTH) STA 23+50 TO 37+00
- 5 MEDIAN DETAILS
- 6-7 SIGNAGE & STRIPING
- 8-10 CROSS SECTIONS
- 11 INTERSECTION DETAIL



VOLLMER ROAD
(MODIFIED) URBAN MINOR ARTERIAL CROSS SECTION
SCALE: NTS
ULTIMATE STA: 14+00.00 - 34+00.00



VOLLMER ROAD
INTERIM CROSS SECTION
SCALE: NTS
INTERIM STA: 29+76.26 - 34+00.93



VOLLMER ROAD
INTERIM CROSS SECTION
SCALE: NTS
INTERIM STA: 34+00.93 - 35+76.70

BENCHMARKS

1. THE TOP OF AN ALUMINUM SURVEYORS CAP, STAMPED "9853", AT THE SOUTHEAST BOUNDARY CORNER OF BARBARICK SUBDIVISION
NORTHING = 411416.273
EASTING = 235167.071
ELEVATION = 7023.42
2. THE TOP OF A RED PLASTIC SURVEYORS CAP, ILLEGIBLE, AT THE NORTHWEST BOUNDARY CORNER OF PAWNEE RANCHEROS SUBDIVISION
NORTHING = 410095.404
EASTING = 235052.131
ELEVATION = 7000.40
3. THE TOP OF A RED PLASTIC SURVEYORS CAP, STAMPED "38141", AT THE SOUTHWEST BOUNDARY CORNER OF BARBARICK SUBDIVISION
NORTHING = 411399.962
EASTING = 233849.817
ELEVATION = 7030.82

OWNER/DEVELOPER STATEMENT

I, THE OWNER/DEVELOPER HAVE READ AND WILL COMPLY WITH ALL OF THE REQUIREMENTS SPECIFIED IN THESE DETAILED PLANS AND SPECIFICATIONS.

James F. Morley 3/3/22
JAMES F. MORLEY DATE

SR LAND, LLC
20 BOULDER CRESCENT, SUITE 201
COLORADO SPRINGS, CO 80903

EL PASO COUNTY STATEMENT

COUNTY PLAN REVIEW IS PROVIDED ONLY FOR GENERAL CONFORMANCE WITH COUNTY DESIGN CRITERIA. THE COUNTY IS NOT RESPONSIBLE FOR THE ACCURACY AND ADEQUACY OF THE DESIGN, DIMENSIONS, AND/OR ELEVATIONS WHICH SHALL BE CONFIRMED AT THE JOB SITE. THE COUNTY THROUGH THE APPROVAL OF THIS DOCUMENT ASSUMES NO RESPONSIBILITY FOR COMPLETENESS AND/OR ACCURACY OF THIS DOCUMENT.

FILED IN ACCORDANCE WITH THE REQUIREMENTS OF THE EL PASO COUNTY LAND DEVELOPMENT CODE, DRAINAGE CRITERIA MANUAL, VOLUMES 1 AND 2, AND ENGINEERING CRITERIA MANUAL AS AMENDED.

IN ACCORDANCE WITH ECM SECTION 1.12, THESE CONSTRUCTION DOCUMENTS WILL BE VALID FOR CONSTRUCTION FOR A PERIOD OF 2 YEARS FROM THE DATE SIGNED BY THE EL PASO COUNTY ENGINEER. IF CONSTRUCTION HAS NOT STARTED WITHIN THOSE 2 YEARS, THE PLANS WILL NEED TO BE RESUBMITTED FOR APPROVAL, INCLUDING PAYMENT OF REVIEW FEES AT THE PLANNING AND COMMUNITY DEVELOPMENT DIRECTORS DISCRETION.

APPROVED
Engineering Department

JENNIFER IRVINE, P.E.

COUNTY ENGINEER/ECM ADMINISTRATOR

ENGINEER'S STATEMENT

THESE DETAILED PLANS AND SPECIFICATIONS WERE PREPARED UNDER MY DIRECT SUPERVISION. SAID PLANS AND SPECIFICATIONS HAVE BEEN PREPARED ACCORDING TO THE CRITERIA ESTABLISHED BY THE COUNTY FOR DETAILED ROADWAY, DRAINAGE, GRADING AND EROSION CONTROL PLANS AND SPECIFICATIONS, AND SAID PLANS AND SPECIFICATIONS ARE IN CONFORMITY WITH APPLICABLE MASTER DRAINAGE PLANS AND MASTER TRANSPORTATION PLANS. SAID PLAN AND SPECIFICATIONS MEET THE PURPOSES FOR WHICH THE PARTICULAR ROADWAY AND DRAINAGE FACILITIES ARE DESIGNED AND ARE CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF. I ACCEPT RESPONSIBILITY FOR ANY LIABILITY CAUSED BY ANY NEGLIGENT ACTS, ERRORS OR OMISSIONS ON MY PART IN PREPARATION OF THESE DETAILED PLANS AND SPECIFICATIONS.

Mike A. Bramlett 3/2/22
MIKE A. BRAMLETT, P.E. DATE
COLORADO P.E. 32314
FOR AND ON BEHALF OF JR ENGINEERING, LLC A WESTERN COMPANY

DISTRICT APPROVALS

THESE DOCUMENTS HAVE BEEN REVIEWED AND APPROVED FOR STORM DRAIN AND ASSOCIATED UTILITY SERVICE CONSTRUCTION.

James F. Morley 3/3/22
FOR AND ON BEHALF OF THE STERLING RANCH METRO DISTRICT DATE

UNTIL SUCH TIME AS THESE DRAWINGS ARE APPROVED BY THE EL PASO COUNTY ENGINEER, THESE DRAWINGS ARE NOT TO BE USED FOR ANY PURPOSES OTHER THAN THE PURPOSES DESIGNATED BY WRITTEN AUTHORIZATION.

PREPARED FOR
SR LAND, LLC
20 BOULDER CRESCENT
SUITE 201
COLORADO SPRINGS, CO 80903
JAMES F. MORLEY
(719) 471-1742

JR ENGINEERING
A Western Company



Centennial 303-747-9888 • Colorado Springs 719-589-2883
Fort Collins 970-491-9888 • www.jrengineering.com

| BY | DATE | REVISION | NO. | DESIGNED BY | DRAWN BY | CHECKED BY |
|----|------|----------|-----|-------------|----------|------------|
| | | | | | | |

STERLING RANCH -
VOLLMER ROAD FILING 2
COVER SHEET





Know what's below.
Call before you dig.

| Vollmer South CL | | | | | | | | | | |
|------------------|------------|----------|----------|------------------|-------------|-------------|--------|----------|--------|---------|
| Point | Design Pt | Station | Distance | Bearing | Northing | Easting | Radius | Delta | Length | Tangent |
| C1 | PC | 10+00.00 | | | 410021.2566 | 232043.6991 | | | | |
| | PI | 11+22.75 | | | 410116.7139 | 232120.8669 | 10000 | 1'24'23" | 245.48 | 122.75 |
| | PT | 12+45.48 | | | 410210.2482 | 232200.3545 | | | | |
| L1 | Begin Line | 12+45.48 | 1304.444 | N40° 21' 27.79"E | 410210.2482 | 232200.3545 | | | | |
| | End Line | 25+49.93 | | | 411204.2559 | 233045.0573 | | | | |

ASPHALT TO BE REMOVED

HORIZONTAL ORIGINAL SCALE: 1" = 50'
VERTICAL ORIGINAL SCALE: 1" = 5'




NOTE
OVERHEAD ELECTRIC LINE TO BE PLACED UNDERGROUND AT POLE SOUTH OF PIONEER DRIVE. CONTRACTOR TO COORDINATE WITH MVEA FOR ROUTING.
CONTRACTOR TO COORDINATE WITH BLACK HILLS AND OTHER EXISTING UTILITIES WITHIN PROJECT LIMITS TO COORDINATE RELOCATION IF NECESSARY

**VOLLMER ROAD
STA 10+00.00 TO STA 24+00.00**

SEE STERLING RANCH-MARKSHEFFEL ROAD STREET IMPROVEMENT PLANS

**VOLLMER SOUTH CL PROFILE
STA 9+50.00 TO 24+00.00**



**VOLLMER ROAD
STA 10+00.00 TO STA 23+50.00**

ENGINEER'S STATEMENT
PREPARED UNDER MY DIRECT SUPERVISION AND ON BEHALF OF JR ENGINEERING
Mike A. Bramlett
MIKE A. BRAMLETT, P.E.
COLORADO P.E. 32314
FOR AND ON BEHALF OF JR ENGINEERING, LOCAL ENGINEER
DATE 3/7/22

EPC 4/5/2022

UNTIL SUCH TIME AS THESE DRAWINGS ARE APPROVED BY THE APPROPRIATE REVIEWING AGENCIES, JR ENGINEERING APPROVES THEIR USE FOR PURPOSES DESIGNATED BY WRITTEN AUTHORIZATION.

PREPARED FOR
SR LAND, LLC
20 BOULDER CRESCENT
SUITE 201
COLORADO SPRINGS, CO 80903
JAMES F. MORLEY
(719) 471-1742



J.R. ENGINEERING
A Westman Company
Central 303-740-9888 • Colorado Springs 719-583-2583
Fort Collins 970-491-9888 • www.jrengineering.com

| BY | DATE | No. | REVISION |
|----|------|-----|----------|
| | | | |
| | | | |
| | | | |
| | | | |

STERLING RANCH -
VOLLMER ROAD FILING 2
PLAN & PROFILE
DESIGNED BY RAB
DRAWN BY KRW
CHECKED BY
SHEET 3 OF 11
JOB NO. 25188.01

| Vollmer South CL | | | | | | | | | | |
|------------------|------------|----------|----------|------------------|-------------|-------------|--------|-------|--------|---------|
| Point | Design Pt | Station | Distance | Bearing | Northing | Easting | Radius | Delta | Length | Tangent |
| L2 | Begin Line | 25+49.93 | 1025.900 | N37° 33' 44.75"E | 411204.2559 | 233045.0573 | | | | |
| | End Line | 35+75.83 | | | 412017.4765 | 233670.4724 | | | | |
| L3 | Begin Line | 35+75.83 | 223.394 | N39° 52' 40.53"E | 412017.4765 | 233670.4724 | | | | |
| | End Line | 37+99.22 | | | 412188.9114 | 233813.7020 | | | | |


ASPHALT TO BE REMOVED



UNTIL SUCH TIME AS THESE DRAWINGS ARE APPROVED BY THE AGENCIES, JR ENGINEERING APPROVES THEIR USES DESIGNATED BY WRITTEN AUTHORIZATION.

PREPARED FOR
SR LAND, LLC
 20 BOULDER CRESCENT
 SUITE 201
 COLORADO SPRINGS, CO 80903
 JAMES F. MORLEY
 (719) 471-1742


J.R. ENGINEERING
 A Westman Company
 Centennial 300-740-9888 • Colorado Springs 719-588-2583
 Fort Collins 970-491-9888 • www.jrengineering.com



SEE STERLING RANCH-ALZADA DRIVE STREET IMPROVEMENT PLANS

VOLLMER ROAD
STA 24+00.00 TO STA 38+00.00

VOLLMER SOUTH CL PROFILE
STA 24+00.00 TO 37+84.39




ENGINEER'S STATEMENT
 PREPARED UNDER MY DIRECT SUPERVISION AND ON BEHALF OF JR ENGINEERING
Mike A. Bramlett
 MIKE A. BRAMLETT, P.E.
 COLORADO P.E. 32314
 FOR AND ON BEHALF OF JR ENGINEERING, LOCAL ENGINEER

| BY | DATE | No. | REVISION | H-SCALE | V-SCALE | DATE | DESIGNED BY | DRAWN BY | CHECKED BY |
|----|------|-----|----------|---------|---------|--------|-------------|----------|------------|
| | | | | 1"=50' | 1"=5' | 3/7/22 | RAB | KRW | |
| | | | | | | | | | |

STERLING RANCH -
 VOLLMER ROAD FILING 2
 PLAN & PROFILE


SHEET 4 OF 11
 JOB NO. 25188.01




20 10 0 20 40
ORIGINAL SCALE: 1" = 20'



Know what's below.
Call before you dig.



KEY MAP
N.T.S.



**VOLLMER ROAD INTERIM STRIPED MEDIAN
(AND FUTURE RAISED MEDIAN)
STA 22+98.00 TO STA 29+25.00**

UNTIL SUCH TIME AS THESE DRAWINGS ARE APPROVED BY THE APPROPRIATE REVIEWING AGENCIES, JR ENGINEERING APPROVES THEIR USE ONLY AS DESIGNATED BY WRITTEN AUTHORIZATION.

PREPARED FOR
SR LAND, LLC
20 BOULDER CRESCENT
SUITE 201
COLORADO SPRINGS, CO 80903
JAMES F. MORLEY
(719) 471-1742

J.R. ENGINEERING
A Westman Company

Central 303-740-9888 • Colorado Springs 719-588-2583
Fort Collins 970-491-9888 • www.jrengineering.com

| BY | DATE | No. | REVISION |
|----|------|-----|----------|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

STERLING RANCH -
VOLLMER ROAD FILING 2
MEDIAN DETAILS

SHEET 5 OF 11
JOB NO. 25188.01

EPC 4/5/2022


ENGINEER'S STATEMENT

PREPARED UNDER MY DIRECT SUPERVISION AND ON BEHALF OF JR ENGINEERING

Mike A. Bramlett

MIKE A. BRAMLETT, P.E.
COLORADO P.E. 32314

FOR AND ON BEHALF OF JR ENGINEERING, LLC




DATE 3/7/22

| STRIPING LEGEND | | |
|-----------------|---|---|
| STRIPE | PAVEMENT MARKINGS | MARKING DESCRIPTION |
| ② | DOUBLE CENTERLINE LANE MARKINGS (EPOXY) | PARALLEL SOLID YELLOW, 4" WIDE, 12" APART |
| ③ | LANE LANES (EPOXY) | BROKEN WHITE, 4" WIDE, 10' SEGMENTS WITH 30" GAPS |
| ④ | BROKEN EDGE/BIKE LANE LINES (EPOXY) | BROKEN WHITE, 4" WIDE, 5' SEGMENTS WITH 15" GAPS |
| ⑤ | EDGE/BIKE LANE LINES (EPOXY) | SOLID WHITE, 4" WIDE |
| ⑥ | CHANNELIZING LINES (EPOXY) | SOLID WHITE, 8" WIDE |
| ⑦ | STOP LINES (THERMO PLASTIC) | SOLID WHITE, 24" WIDE |

NOTE: ALL STRIPING INSTALLATION SHALL BE PER COLORADO DEPARTMENT OF TRANSPORTATION (CDOT) "M&S STANDARDS" STANDARD PLAN NO. S-627-1.

NOTE TO CONTRACTOR:

- ALL 4" AND 8" SOLID OR SKIP PAVEMENT MARKINGS ARE TO BE EPOXY.
- SIGNS AND POLES SHALL BE PER CDOT STANDARDS S-614-8, S-1614-2, AND S-614-3, LATEST REVISION.
- ALL SIGNAGE INSTALLATION IS TO BE IN COMPLIANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD).



VOLLMER ROAD INTERIM CONDITION

EPC 4/5/2022

ENGINEER'S STATEMENT
 PREPARED UNDER MY DIRECT SUPERVISION AND ON BEHALF OF JR ENGINEERING

 MIKE A. BRAMLETT, P.E.
 COLORADO P.E. 32314
 FOR AND ON BEHALF OF JR ENGINEERING, LOCAL ENGINEER
 DATE 3/7/22



| | | | |
|--|--|----------|----------|
| PREPARED FOR SR LAND, LLC 20 BOULDER CRESCENT SUITE 201 COLORADO SPRINGS, CO 80903 JAMES F. MORLEY (719) 471-1742 | J.R. ENGINEERING A Westman Company Centennial 303-740-9383 • Colorado Springs 719-583-2583 Fort Collins 970-491-9888 • www.jrengineering.com | BY | DATE |
| | | | |
| STERLING RANCH - VOLLMER ROAD FILING 2 SIGNAGE & STRIPING | SHEET 6 OF 11 JOB NO. 25188.01 | No. | REVISION |
| | | H-SCALE | 1"=50' |
| | | V-SCALE | N/A |
| | | DATE | 3/7/22 |
| DESIGNED BY | RAB | DRAWN BY | KRW |
| CHECKED BY | | | |

| STRIPING LEGEND | | |
|-----------------|---|---|
| STRIPE | PAVEMENT MARKINGS | MARKING DESCRIPTION |
| ② | DOUBLE CENTERLINE LANE MARKINGS (EPOXY) | PARALLEL SOLID YELLOW, 4" WIDE, 12" APART |
| ③ | LANE LANES (EPOXY) | BROKEN WHITE, 4" WIDE, 10' SEGMENTS WITH 30" GAPS |
| ④ | BROKEN EDGE/BIKE LANE LINES (EPOXY) | BROKEN WHITE, 4" WIDE, 5' SEGMENTS WITH 15" GAPS |
| ⑤ | EDGE/BIKE LANE LINES (EPOXY) | SOLID WHITE, 4" WIDE |
| ⑥ | CHANNELIZING LINES (EPOXY) | SOLID WHITE, 8" WIDE |
| ⑦ | STOP LINES (THERMO PLASTIC) | SOLID WHITE, 24" WIDE |

NOTE: ALL STRIPING INSTALLATION SHALL BE PER COLORADO DEPARTMENT OF TRANSPORTATION (CDOT) "M&S STANDARDS" STANDARD PLAN NO. S-627-1.

NOTE TO CONTRACTOR:


- ALL 4" AND 8" SOLID OR SKIP PAVEMENT MARKINGS ARE TO BE EPOXY.
- SIGNS AND POLES SHALL BE PER CDOT STANDARDS S-614-8, S-1614-2, AND S-614-3, LATEST REVISION.
- ALL SIGNAGE INSTALLATION IS TO BE IN COMPLIANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD).



KEY MAP
N.T.S.

PREPARED FOR
SR LAND, LLC
20 BOULDER CRESCENT
SUITE 201
COLORADO SPRINGS, CO 80903
JAMES F. MORLEY
(719) 471-1742

J.R. ENGINEERING
A Westman Company
Central 303-740-9888 • Colorado Springs 719-588-2583
Fort Collins 970-491-9888 • www.jrengineering.com



*TIE-IN LOCATIONS APPROXIMATE. CONTRACTOR TO CONFIRM IN FIELD

VOLLMER ROAD SOUTHERN TIE-IN TO EXISTING


EPC 4/5/2022

ENGINEER'S STATEMENT

PREPARED UNDER MY DIRECT SUPERVISION AND ON BEHALF OF JR ENGINEERING

Mike A. Bramlett

MIKE A. BRAMLETT, P.E.
COLORADO P.E. 32314



DATE 3/7/22

FOR AND ON BEHALF OF JR ENGINEERING, INC.

| H-SCALE | V-SCALE | DATE | DESIGNED BY | DRAWN BY | CHECKED BY | No. | REVISION | BY | DATE |
|---------|---------|------|-------------|----------|------------|-----|----------|----|------|
| | | | | | | | | | |
| | | | | | | | | | |


STERLING RANCH -
VOLLMER ROAD FILING 2
SIGNAGE & STRIPING

SHEET 7 OF 11

JOB NO. 25188.01

LEGEND

- PROPOSED SURFACE
- - - EXISTING SURFACE
- - - FILING NO. 2 SURFACE















UNTIL SUCH TIME AS THESE DRAWINGS ARE APPROVED BY THE APPROPRIATE REVIEWING AGENCIES, OR ENGINEERING APPROVES THEIR USE, THESE DRAWINGS ARE DESIGNATED BY WRITTEN AUTHORIZATION.

PREPARED FOR
SR LAND, LLC
 20 BOULDER CRESCENT
 SUITE 201
 COLORADO SPRINGS, CO 80903
 JAMES F. MORLEY
 (719) 471-1742

J.R. ENGINEERING
 A Westman Company
 Centennial 300-740-9888 • Colorado Springs 719-583-2593
 Fort Collins 970-491-9888 • www.jrengineering.com

| H-SCALE | V-SCALE | DATE | DESIGNED BY | DRAWN BY | CHECKED BY | REVISION | |
|---------|---------|--------|-------------|----------|------------|----------|------|
| | | | | | | No. | DATE |
| 1"=50' | 1"=10' | 3/7/22 | RAB | KRW | | | |

**STERLING RANCH -
 VOLLMER ROAD FILING 2
 CROSS SECTIONS**




EPC 4/5/2022

LEGEND

- PROPOSED SURFACE
- - - EXISTING SURFACE
- - - FILING NO. 2 SURFACE

UNTIL SUCH TIME AS THESE DRAWINGS ARE APPROVED BY THE APPROPRIATE REVIEWING AGENCIES, OR ENGINEERING APPROVES THEIR USE, THESE DRAWINGS ARE DESIGNATED BY WRITTEN AUTHORIZATION.

PREPARED FOR
SR LAND, LLC
20 BOULDER CRESCENT
SUITE 201
COLORADO SPRINGS, CO 80903
JAMES F. MORLEY
(719) 471-1742



J.R. ENGINEERING
A Westman Company
Central 303-740-9888 • Colorado Springs 719-588-2583
Fort Collins 970-491-9888 • www.jrengineering.com


| BY | DATE | No. | REVISION |
|----|------|-----|----------|
| | | | |
| | | | |
| | | | |

| H-SCALE | V-SCALE | DATE | DESIGNED BY | DRAWN BY | CHECKED BY |
|---------|---------|--------|-------------|----------|------------|
| 1"=50' | 1"=10' | 3/7/22 | RAB | KRW | |



STERLING RANCH -
VOLLMER ROAD FILING 2
CROSS SECTIONS

SHEET 10 OF 11

JOB NO. 25188.01



20 10 0 20 40
ORIGINAL SCALE: 1" = 20'



**VOLLMER ROAD
INTERSECTION AT MARKSHEFFEL ROAD DETAIL**

EPC 4/5/2022

ENGINEER'S STATEMENT

PREPARED UNDER MY DIRECT SUPERVISION AND ON BEHALF OF JR ENGINEERING
Mike A. Bramlett
MIKE A. BRAMLETT, P.E.
COLORADO P.E. 32314
DATE 3/7/22
FOR AND ON BEHALF OF JR ENGINEERING, LLC

| H-SCALE | V-SCALE | DATE | DESIGNED BY | DRAWN BY | CHECKED BY |
|---------|---------|--------|-------------|----------|------------|
| 1"=50' | 1"=5' | 3/7/22 | RAB | KRW | |

| No. | REVISION | BY | DATE |
|-----|----------|----|------|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

UNTIL SUCH TIME AS THESE DRAWINGS ARE APPROVED BY THE APPROPRIATE REVIEWING AGENCIES, JR ENGINEERING APPROVES THEIR USES DESIGNATED BY WRITTEN AUTHORIZATION.
PREPARED FOR
SR LAND, LLC
20 BOULDER CRESCENT
SUITE 201
COLORADO SPRINGS, CO 80903
JAMES F. MORLEY
(719) 471-1742

J.R. ENGINEERING
A Westman Company
Central 303-740-9888 • Colorado Springs 719-583-2583
Fort Collins 970-491-9888 • www.jrengineering.com

STERLING RANCH -
VOLLMER ROAD FILING 2
INTERSECTION DETAIL