

**EXHIBIT H – PROJECT DRAWINGS**

# PLANS FOR PERMITTING

## TOWN OF RAMAH

### WASTEWATER SYSTEM IMPROVEMENTS

#### 0.015 MGD WASTEWATER TREATMENT PLANT

SECTION 1, TOWNSHIP 11S, RANGE 61W, 6TH PRINCIPAL MERIDIAN AND SECTION 1, TOWNSHIP 11S, RANGE 61W, 6TH P.M.

WWTP SITE APPROVAL NO. 06505

LIFT STATION SITE APPROVAL NO. 06507

**PREPARED FOR**

TOWN OF RAMAH  
CINDY TOMPKINS, TOWN ADMINISTRATOR  
719.541.2163  
113 S. COMMERCIAL STREET  
RAMAH, CO 80832

**EMERGENCY CONTACT**

CINDY TOMPKINS, TOWN ADMINISTRATOR  
719.541.2163

**CIVIL ENGINEERING**

ALICE M. ARSENAULT, P.E.  
P.E. NO. 53350  
ELEMENT ENGINEERING, LLC  
12687 W. CEDAR DR., SUITE 300  
LAKEWOOD, CO 80228  
303.981.0453

**ELECTRICAL ENGINEERING**


CRAIG TURNER, P.E.  
P.E. NO. 45462  
EV STUDIO  
5335 W 48TH AVE, STE 300  
DENVER, CO 80212  
303.670.7242

**STRUCTURAL ENGINEERING**


KATELYN WAGER, P.E.  
P.E. NO. 54327  
EV STUDIO  
5335 W 48TH AVE, STE 300  
DENVER, CO 80212  
303.670.7242

**UTILITIES**

MOUNTAIN VIEW ELECTRIC COMPANY – ELECTRIC  
1140 E. WOODMEN AVE.  
FALCON, CO 80831  
719-495-2283



**LOCATION MAP**  
NTS



**VICINITY MAP**  
NTS

**SHEET INDEX**

- CIVIL**
- C1 COVER
  - C2 GENERAL NOTES
  - C3 GENERAL NOTES
  - C4 PROCESS FLOW DIAGRAM & HYDRAULIC PROFILE
  - C5 TOPOGRAPHIC SURVEY
  - C6 TOPOGRAPHIC SURVEY
  - C7 PROPOSED IMPROVEMENTS, CONSTRUCTION PHASING, AND DECOMMISSIONING
  - C8 LIFT STATION YARD PIPING
  - C9 LIFT STATION SITE PLAN
  - C10 LIFT STATION DETAILS
  - C11 LIFT STATION NOTES & BALLASTING
  - C12 OVERFLOW DETAILS
  - C13 FORCE MAIN PLAN & PROFILE 0+00 – 6+00
  - C14 FORCE MAIN PLAN & PROFILE 6+00 – 16+00
  - C15 FORCE MAIN PLAN & PROFILE 16+00 – 27+00
  - C16 FORCE MAIN PLAN & PROFILE 27+00 – 38+00
  - C17 FORCE MAIN PLAN & PROFILE 38+00 – 46+75
  - C18 INFLUENT SCREEN DETAILS
  - C19 SPLITTER BOX & POND OVERFLOW PIPING
  - C20 HORIZONTAL CONTROL & GRADING
  - C21 POND GRADING PROFILES
  - C22 CUT & FILL PLAN
  - C23 POND DETAILS
  - C24 DRAINAGE SWALE PLAN & PROFILE
  - C25 GENERAL DETAILS
  - C26 GENERAL DETAILS
  - C27 GENERAL DETAILS
- ELECTRICAL**
- STRUCTURAL**

PUBLIC WORKS DIRECTOR \_\_\_\_\_ DATE \_\_\_\_\_

THESE PLANS HAVE BEEN APPROVED BY THE TOWN OF RAMAH. A TOWN REPRESENTATIVE WILL OBSERVE THE WORK FOR COMPLIANCE WITH THE APPROVED PLANS, BUT DOES NOT GUARANTEE THE CONTRACTOR'S PERFORMANCE. THE CONTRACTOR IS RESPONSIBLE FOR CONSTRUCTION OF THE FACILITIES IN ACCORDANCE WITH THE APPROVED PLANS AND WITH APPLICABLE RULES AND REGULATIONS. WORK NOT PERFORMED IN ACCORDANCE WITH THE APPROVED PLANS WILL NOT BE ACCEPTED. ACCEPTANCE OF THE WORK DOES NOT RELIEVE THE CONTRACTOR OF THEIR OBLIGATIONS UNDER APPLICABLE WARRANTIES.



NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT	COVER	TOWN OF RAMAH 113 S. COMMERCIAL STREET RAMAH, CO 80832
----------------------------	-------	--

PREPARED UNDER THE DIRECT SUPERVISION OF

FOR AND ON BEHALF OF  
ELEMENT ENGINEERING, LLC

DATE  
OCTOBER 2022

JOB NUMBER  
0043.0001

SCALE  
NTS

EDITION  
PERMITTING

SHEET  
C1 OF C27


**GENERAL NOTES**

- ALL WORK TO BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS.
- THE CONTRACTOR IS TO PROVIDE A DETAILED CONSTRUCTION SCHEDULE DELINEATING CONSTRUCTION MILESTONES AND THE NATURE OF WORK BEING PERFORMED. THE SCHEDULE SHALL DETAIL ACTIVITIES FROM THE START OF CONSTRUCTION THROUGH STARTUP. THIS SCHEDULE SHALL BE PROVIDED TO THE ENGINEER TWO (2) WEEKS PRIOR TO CONSTRUCTION AND UPDATED WEEKLY.
- THE CONTRACTOR SHALL PERFORM ALL WORK NECESSARY TO COMPLETE THE PROJECT IN ACCORDANCE WITH THE APPROVED CONSTRUCTION DRAWINGS INCLUDING SUCH INCIDENTALS AS MAY BE NECESSARY TO MEET APPLICABLE AGENCY REQUIREMENTS AND PROVIDE A COMPLETED PROJECT.
- THE CONTRACTOR SHALL FURNISH ALL MATERIALS, LABOR AND EQUIPMENT AND PERFORM WORK SHOWN OR IMPLIED AS NECESSARY FOR THE COMPLETED LIFT STATION, PIPING, AND EVAPORATION PONDS, READY FOR USE.
- THE ENGINEER HAS ATTEMPTED TO LOCATE EXISTING SUBSURFACE UTILITIES. HOWEVER, SOME MAY EXIST THAT ARE NOT SHOWN. THE CONTRACTOR SHALL POTHOLE AS NECESSARY AND EXERCISE CARE IN HIS WORK SO AS TO AVOID DAMAGE TO ANY UTILITIES. ANY DAMAGE TO EXISTING UTILITIES SHALL BE THE CONTRACTOR'S RESPONSIBILITY.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CONSTRUCTION STAKING. ALL DIMENSIONS, ELEVATIONS, AND LOCATIONS SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR PRIOR TO BEGINNING THE WORK.
- ANY SUBSURFACE CONDITIONS ENCOUNTERED THAT ARE UNUSUAL OR DIFFERENT THAN THOSE INDICATED BY THE ENGINEER SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE ENGINEER.
- CONTRACTOR SHALL OBTAIN, AT HIS OWN EXPENSE, ALL PERMITS REQUIRED OF THIS WORK AND SHALL FAITHFULLY ADHERE TO THE ALL PERMIT REQUIREMENTS.
- TEMPORARY AND PERMANENT EROSION CONTROL STRUCTURE METHODS SHALL BE IN ACCORDANCE WITH COUNTY REGULATIONS AND ARE TO BE UTILIZED DURING CONSTRUCTION.
- ALL EROSION CONTROL STRUCTURES SHOWN OR AS REQUIRED DURING CONSTRUCTION SHALL BE CONTINUOUSLY MAINTAINED THROUGH WARRANTY PERIOD AND UNTIL RE-VEGETATION TAKES HOLD.
- CONTRACTOR SHALL CLEAN UP, SEED, AND RESTORE DISTURBED AREAS IMMEDIATELY UPON COMPLETION OF THE WORK IN THE AFFECTED AREA.
- ALL EXISTING FACILITIES SHALL BE MAINTAINED IN-PLACE BY THE CONTRACTOR UNLESS OTHERWISE SHOWN OR DIRECTED. CONTRACTOR SHALL TAKE ALL PRECAUTIONS NECESSARY TO SUPPORT, MAINTAIN, OR OTHERWISE PROTECT EXISTING UTILITIES AND OTHER FACILITIES AT ALL TIMES DURING CONSTRUCTION. CONTRACTOR TO LEAVE EXISTING FACILITIES IN AN EQUAL OR BETTER-THAN-ORIGINAL CONDITION.
- THE CONTRACTOR SHALL ERECT AND MAINTAIN BARRICADES, WARNING SIGNS, CONES IN ACCORDANCE WITH STATE, LOCAL AND FEDERAL GUIDELINES TO ENSURE THE SAFETY OF WORKERS AND THE PUBLIC. ALL BARRICADES, SIGNS SHALL BE IN PLACE PRIOR TO THE BEGINNING OF ANY CONSTRUCTION ACTIVITY.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN APPROVAL FOR A TRAFFIC CONTROL PLAN. THE TRAFFIC CONTROL PLAN MUST BE SUBMITTED AND APPROVED BY COUNTY AND THE OWNER'S REPRESENTATIVE.
- UNLESS OTHERWISE GRANTED PERMISSION BY THE OWNER IN WRITING, THE CONTRACTOR MUST ALLOW ACCESS TO ALL PROPERTIES FOR BOTH RESIDENTS AND EMERGENCY VEHICLES.
- THE CONTRACTOR WILL BE HELD RESPONSIBLE FOR THE CLEANLINESS AND SAFETY OF ALL ROADWAYS ADJACENT TO THE PROJECT SITE. IF AT ANY TIME, THESE ROADWAYS ARE FOUND TO BE DANGEROUS OR NOT PASSABLE DUE TO DEBRIS OR MUD, THE COUNTY MAY SHUT THE PROJECT DOWN.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY THE ENGINEER OF ANY PROBLEM IN CONFORMING TO THE APPROVED PLANS FOR ANY ELEMENT OF THE PROPOSED IMPROVEMENTS PRIOR TO ITS CONSTRUCTION.
- BLUE STAKES - THE CONTRACTOR SHALL CONTACT THE UTILITY NOTIFICATION CENTER OF COLORADO AND THE FACILITY OPERATOR FOR LOCATION OF UNDERGROUND UTILITIES AT LEAST 48 HOURS PRIOR TO CONSTRUCTION, AS WELL AS ANY INDEPENDENT LOCATOR FOR PRIVATE LINES.
- THE CONTRACTOR SHALL NOTIFY THE INSPECTOR AT LEAST 48 HOURS PRIOR TO ANY DESIRED INSPECTION. THE CONTRACTOR SHALL NOTIFY THE ENGINEER 48 HOURS PRIOR TO THE START OF CONSTRUCTION.
- SURVEY MONUMENTS MUST BE SET WITHIN 60 DAYS OF COMPLETION OF THE PROJECT.
- SERVICE TRENCHES AND UTILITY MAIN TRENCHES SHALL BE COMPACTED THROUGHOUT THE DEPTH OF THE TRENCH PER THE SPECIFICATIONS.
- THE CONTRACTOR SHALL MAINTAIN ONE COMPLETE SET OF APPROVED DRAWINGS ON THE CONSTRUCTION SITE AT ALL TIMES WHEREON HE WILL RECORD ANY APPROVED DEVIATIONS IN THE CONSTRUCTION FROM THE APPROVED DRAWINGS AS WELL AS THE LOCATIONS AND DEPTHS OF ALL EXISTING UTILITIES. THESE FIELD RECORD DRAWINGS SHALL BE KEPT UP TO DATE AT ALL TIMES AND SHALL BE AVAILABLE FOR INSPECTION BY THE OWNER'S REPRESENTATIVE UPON REQUEST.
- UPON COMPLETION OF CONSTRUCTION AND PRIOR TO INITIAL ACCEPTANCE OF THE WORK, THE CONTRACTOR SHALL SUBMIT A CLEAN SET OF FIELD RECORD DRAWINGS CONTAINING ALL AS-BUILT INFORMATION TO THE ENGINEER. ALL INFORMATION SHOWN ON THE CONTRACTOR'S FIELD RECORD DRAWINGS SHALL BE SUBJECT TO VERIFICATION BY THE ENGINEER. IF SIGNIFICANT ERRORS OR DEVIATIONS ARE NOTED BY THE ENGINEER, AN AS-BUILT SURVEY PREPARED AND STAMPED BY A REGISTERED PROFESSIONAL LAND SURVEYOR SHALL BE COMPLETED AT THE CONTRACTOR'S EXPENSE.

- ALL SUBMITTAL RECORDS ARE TO BE KEPT ONSITE AS WELL AS ALL DAILY INSPECTION REPORTS, INCLUDING, BUT NOT LIMITED TO, COMPACTION TESTS, CONCRETE TESTS, ETC.
- MEGALUGS AND CONCRETE THRUST BLOCKS WILL BE REQUIRED FOR ALL MAIN LINES.
- TRACER WIRE IS REQUIRED ON ALL PIPES. TRACER WIRE SHALL BE 10 GAUGE DIRECT BURY SOLID SINGLE STRAND COPPER WIRE WITH TEST STATIONS AS SHOWN ON THE PLANS.
- ALL BOLTS FOR ABOVE GRADE FITTINGS SHALL BE ASTM 316 STAINLESS STEEL.
- CONTRACTOR SHALL HAUL OFF AND DISPOSE OF ANY EXCESS SPOIL MATERIAL, ANY MISCELLANEOUS DEBRIS, AND ANY STRUCTURES, PIPING OR OTHER DEBRIS CALLED OUT TO BE DEMOLISHED AT HIS OWN EXPENSE. ALL MATERIAL MUST BE DISPOSED OF IN AN APPROVED OFFSITE LOCATION.
- PIPE, FITTINGS, AND ACCESSORIES SHALL BE HANDLED IN SUCH A MANNER THAT WILL ENSURE INSTALLATION IN SOUND, UNDAMAGED CONDITION. EQUIPMENT, TOOLS, AND METHODS USED IN HANDLING AND INSTALLING PIPE AND FITTINGS SHALL NOT DAMAGE THE PIPE AND FITTINGS.
- PRECAUTIONS SHALL BE TAKEN TO PREVENT FOREIGN MATERIAL FROM ENTERING THE PIPE DURING INSTALLATION. DEBRIS, TOOLS, CLOTHING, OR OTHER OBJECTS SHALL NOT BE PLACED IN OR ALLOWED TO ENTER THE PIPE. END OF LINES TO BE PLUGGED TO PREVENT DEBRIS OR ANIMALS FROM ENTERING PIPE.
- CUTTING SHALL BE DONE IN A NEAT MANNER, WITHOUT DAMAGE TO THE PIPE OR THE LINING. CUTS SHALL BE SMOOTH, STRAIGHT, AND AT RIGHT ANGLES TO THE PIPE AXIS. AFTER CUTTING, THE ENDS OF THE PIPE SHALL BE DRESSED WITH A FILE OR POWER GRINDER TO REMOVE ALL ROUGHNESS AND SHARP EDGES. THE CUT ENDS OF PUSH-ON JOINT PIPE SHALL BE SUITABLY BEVELED.
- NO DEFLECTION SHALL BE PERMITTED ON INTERIOR PIPE AND FITTINGS.
- DIAMETRICALLY OPPOSITE NUTS SHALL BE TIGHTENED PROGRESSIVELY AND EVENLY. FINAL TIGHTENING SHALL BE DONE WITH A TORQUE LIMITING WRENCH SET FOR THE TORQUE RECOMMENDED BY THE MANUFACTURER FOR ALL FITTINGS AND SERVICE SADDLES.
- BEFORE THE JOINT IS ASSEMBLED, THE FLANGE FACES SHALL BE THOROUGHLY CLEANED OF ALL FOREIGN MATERIAL WITH A POWER WIRE BRUSH. THE GASKET SHALL BE CENTERED AND THE CONNECTING FLANGES DRAWN UP WATERTIGHT WITHOUT UNNECESSARY STRESSING OF THE FLANGES. ALL BOLTS SHALL BE TIGHTENED IN A PROGRESSIVE DIAMETRICALLY OPPOSITE SEQUENCE USING TORQUE WRENCHES AT SETTINGS RECOMMENDED BY THE MANUFACTURER. WHERE DISSIMILAR FLANGES ARE CONNECTED, AN INSULATING CONNECTION SHALL BE PROVIDED.
- ALL JOINTS SHALL BE WATERTIGHT AND FREE FROM LEAKS. EACH LEAK WHICH IS DISCOVERED WITHIN THE CORRECTION PERIOD STIPULATED IN THE GENERAL PROVISIONS SHALL BE REPAIRED BY AND AT THE EXPENSE OF THE CONTRACTOR.
- ALL CONTRACTOR INSTALLED PIPE, FITTINGS, VALVES, PIPE JOINTS, AND OTHER MATERIALS WHICH ARE FOUND TO BE DEFECTIVE SHALL BE REMOVED AND REPLACED WITH NEW AND ACCEPTABLE MATERIALS, AND THE AFFECTED PORTION OF THE PIPING RETESTED BY AND AT THE EXPENSE OF THE CONTRACTOR.
- FLEXIBLE COUPLINGS AND FLANGE ADAPTERS SHALL BE DESIGNED TO RELIEVE STRESS IN PIPELINES DUE TO THERMAL EXPANSION/CONTRACTION, DIFFERENTIAL SETTLEMENT OR MISALIGNMENT AND MECHANICAL VIBRATION. FLEXIBLE COUPLINGS SHALL CONSIST OF A SLEEVE WHICH SHALL FIT OVER THE ENDS OF THE TWO PIPE SECTIONS TO BE JOINED. THE COUPLING SHALL FORM A WATER TIGHT SEAL BY COMPRESSING RESILIENT WEDGE-SHAPED GASKETS BETWEEN THE ENDS OF THE SLEEVE AND THE PIPE SECTIONS. THE GASKETS SHALL BE COMPRESSED BY TWO RETAINER RINGS BOLTED TO ONE ANOTHER ON THE OUTSIDE OF THE COUPLING SLEEVE. FLANGE ADAPTERS SHALL BE EQUIVALENT TO FLEXIBLE COUPLINGS EXCEPT THAT ONE RETAINER RING AND GASKET SHALL BE REPLACED WITH A FLANGED CONNECTION ON THE COUPLING SLEEVE.
- ALL VALVES SHALL HAVE THE MANUFACTURER AND SIZE OF THE VALVE VISIBLY CAST ON THE BODY OR ON A PLATE ATTACHED TO THE BODY OF THE VALVE. VALVES AND REQUIRED OPERATING APPURTENANCES SHALL BE THE PRODUCT OF THE SAME MANUFACTURER. VALVE SEALS SHALL BE ABLE TO PROVIDE TIGHT CLOSURE AND PREVENT METAL-TO-METAL CONTACT. VALVES SHALL OPEN RIGHT.
- VALVE COMPONENTS SHALL WITHSTAND THE ENVIRONMENTAL CONDITIONS AND PROVIDE CONTINUOUS TROUBLE-FREE SERVICE.
- ALL MATERIALS AND WORKMANSHIP FOR SANITARY SEWER CONSTRUCTION SHALL CONFORM TO THE LATEST LINCOLN COUNTY STANDARDS AND SANITARY SEWER CONSTRUCTION DETAILS AND TECHNICAL SPECIFICATIONS, CDPHE AND ALL OTHER APPLICABLE AGENCIES.
- ALL DIRECT BURY SEWER MAINS SHALL BE PVC, ASTM D-3034, SDR35 OR APPROVED EQUAL, UNLESS OTHERWISE NOTED.
- SEWER LINES SHALL BE 10 FEET FROM WATER LINES EXCEPT WHEN CROSSING EACH OTHER. FOR SEWER LINES THAT CROSS LESS THAN 1 1/2 FEET VERTICALLY FROM WATER LINES, THE CLOSEST SANITARY SEWER JOINT SHALL BE A MINIMUM OF 6 FEET FROM THE CROSSING.
- ALL MANHOLES SHALL BE WATER TIGHT PRECAST CONCRETE, A MINIMUM OF 48 INCH IN DIAMETER WITH CONCENTRIC CONE, 24 INCH CAST IRON RING (8" DEPTH) AND COVER, UNLESS OTHERWISE SPECIFIED. CONCRETE ADJUSTMENT RINGS SHALL BE USED FOR ADJUSTMENT TO MATCH FINAL SURFACE ELEVATIONS AND SET IN MASTIC TO OBTAIN A WATER TIGHT SEAL. CONCRETE ADJUSTMENT RINGS SHALL BE 4" MINIMUM IN DEPTH TO ELIMINATE MULTIPLE JOINTS.
- SEWER RIM ELEVATIONS AND INVERTS SHOWN ARE APPROXIMATE ONLY AND ARE NOT TO BE TAKEN AS FINAL ELEVATIONS.
- THE CONTRACTOR TO VERIFY THE HORIZONTAL AND VERTICAL LOCATION OF ALL TIE IN POINTS AND INVERTS PRIOR TO CONSTRUCTION AND PROVIDE THE DATA TO THE TOWN ENGINEER.
- PIPE BEDDING SHALL BE CLASS "B" AND SHALL CONFORM TO ASTM C-33 OR

- D-448 GRADATION NO. 6 OR NO. 67. SQUEEGEE BEDDING IS PREFERRED. BEDDING DEPTH SHALL BE 6" UNDER AND AROUND THE SIDES OF THE PIPE AND 12" OVER THE PIPE. CONSOLIDATION IN PIPE ZONE SHALL BE BY HAND TAMPING.
- AT LEAST 5 DAYS PRIOR TO THE START OF CONSTRUCTION, A PRE-CONSTRUCTION MEETING WILL BE HELD AT THE TOWN'S OFFICE AND ATTENDED BY THE CONTRACTOR AND REPRESENTATIVES OF THE OTHER APPROVING AGENCIES. IT WILL BE THE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE TOWN ENGINEER TO SCHEDULE THIS MEETING.
- THE CONTRACTOR WILL IDENTIFY THE HORIZONTAL AND VERTICAL LOCATION OF ALL EXISTING UTILITIES PRIOR TO CONSTRUCTION. THE CONTRACTOR WILL REPORT ANY DISCREPANCIES TO THE ENGINEER IMMEDIATELY AND PRIOR TO CONSTRUCTION.
- THE CONTRACTOR SHALL MAINTAIN ONE COMPLETE SET OF APPROVED DRAWINGS ON THE CONSTRUCTION SITE AT ALL TIMES WHEREON HE WILL RECORD ANY APPROVED DEVIATIONS IN THE CONSTRUCTION FROM THE APPROVED DRAWINGS AS WELL AS THE LOCATIONS AND DEPTHS OF ALL EXISTING UTILITIES. THESE FIELD RECORD DRAWINGS SHALL BE KEPT UP TO DATE AT ALL TIMES AND SHALL BE AVAILABLE FOR INSPECTION BY THE OWNER'S REPRESENTATIVE UPON REQUEST.
- ALL MANHOLES SHALL HAVE SHAPED INVERTS.
- ALL SEWER LINES SHALL BE TESTED IN ACCORDANCE WITH THE TECHNICAL SPECIFICATIONS PRIOR TO INITIAL ACCEPTANCE OR ANY CONNECTION TO AN EXISTING SEWER LINE. THE MAXIMUM "BELLY" ON LOW SPOTS IN THE NEW SEWER MAIN SHALL NOT EXCEED 3/8 INCHES.
- ALUMINUM FOIL WARNING TAPE SHALL BE USED FOR ALL NEW DIRECT BURY SEWER MAINS. THE TAPE WILL BE INSTALLED 2' BELOW FINISHED GRADE. TAPE MUST BE GREEN IN COLOR.
- FERNCO STRONGBACK RC SERIES PIPE COUPLINGS WILL BE REQUIRED FOR PIPE AND LATERAL SERVICES.
- ALL BARREL SECTIONS OF MANHOLES SHALL BE GROUTED INSIDE AT JOINTS.
- SHOULD TRENCH DE-WATERING BECOME NECESSARY, THE CONTRACTOR WILL OBTAIN ALL REQUIRED PERMITS AND SUPPLY THE PUMPS REQUIRED AT NO ADDITIONAL COST TO THE OWNER.
- THE OPENING OR CHANNEL IN THE MANHOLE MUST BE NO LESS THAN THE DIAMETER OF THE PIPE, AND NO LESS THAN THE MANHOLE DIAMETER MINUS 4 INCHES IN LENGTH TO ACCOMMODATE EQUIPMENT NECESSARY TO MAINTAIN THE SEWER LINE.
- ALL MANHOLE AND SANITARY SEWER MAIN TESTING SHALL BE WITNESSED BY A REPRESENTATIVE OF THE TOWN. A MINIMUM OF 24 HOURS ADVANCED NOTICE IS REQUIRED PRIOR TO TESTING.
- ALL MANHOLE/VAULT EXTERIOR JOINTS SHALL BE WRAPPED IN 12-INCH WIDE CONSEAL CS 212 OR APPROVED EQUIVALENT.
- MANHOLE/VAULT BARREL SECTIONS WILL REQUIRE AN EXTERIOR COATING OF TNEC SERIES 46-46S OR APPROVED EQUIVALENT.
- ALL PRECAST CONCRETE SHALL BE 4,000 PSI MINIMUM STRENGTH.
- ALL EXISTING PIPING INTO EXISTING MANHOLES MUST BE RECONNECTED IN NEW MANHOLES.
- WHERE FILL IS REQUIRED BY THE DRAWINGS, THE EXISTING VEGETATION AND TOPSOIL SHALL BE FULLY REMOVED AND THE SURFACE SCARIFIED PER THE SPECIFICATIONS TO PROVIDE FOR ADEQUATE BONDING OF THE FILL.
- FILL SHALL BE PLACED TO MATCH THE CONTOURS SHOWN ON THE DRAWINGS. ALL BERM CONSTRUCTION AND OVERLOT GRADING SHALL BE UNDERTAKEN SUCH THAT THE CORNERS ARE ROUNDED AND BLENDED INTO THE EXISTING TOPOGRAPHY. NEW ELEVATION CONTOURS INDICATE FINAL SURFACE ELEVATIONS.
- GRADING OF THE WASTEWATER TREATMENT PLANT SITE TOGETHER WITH THE GRADING AROUND MANHOLES AND STRUCTURES THAT HAVE THEIR RINGS AND COVERS INSTALLED ABOVE GRADE SHALL BE FINALIZED SUCH THAT ALL AREAS DRAIN FREELY AWAY FROM THE TREATMENT CELLS AND STRUCTURES. COORDINATE WITH THE ENGINEER AND OWNER TO ENSURE THAT THIS CONDITION IS MET.
- ALL EQUIPMENT AND MATERIAL IS TO BE INSTALLED PER THE MANUFACTURER'S RECOMMENDATIONS AND REQUIREMENTS. ALL EQUIPMENT STARTUP SHALL BE PROVIDED BY A MANUFACTURER APPROVED FIELD REPRESENTATIVE. MANUFACTURER FIELD TRAINING FOR THE OPERATIONS STAFF SHALL ALSO BE PROVIDED AT EITHER THE TIME OF STARTUP OR AT ANOTHER TIME AS APPROVED BY THE OPERATOR.
- THE CONTRACTOR SHALL FURNISH AND INSTALL 12" X 24" SIGNS AS DIRECTED BY THE ENGINEER ON THE PERIMETER FENCING. THE GENERAL SPACING IS 200-FT CENTERS. THE SIGNS SHALL BE MADE FROM 20 GAUGE ALUMINUM SHEET METAL WITH A PAINTED WHITE BACKGROUND AND RED LETTERING. THE SIGNS SHALL READ AS FOLLOWS:  
  
**ANGER -- KEEP OUT  
WASTEWATER TREATMENT FACILITY**
- THE BASE BID ON THE PROJECT INCLUDES A BID ITEM CALLING FOR FURNISHING AND INSTALLING 6-INCHES OF SAND OVER THE BOTTOM OF THE NEW CELLS. THE SAND IS BEING INSTALLED TO MAINTAIN THE INTEGRITY OF THE LINER WHEN MINIMAL TO NO WATER IS CONTAINED WITHIN THE CELL. THE CONTRACTOR WILL NEED TO USE **EXTREME CARE** IN THE PLACEMENT OF THE MATERIAL TO MAINTAIN THE INTEGRITY OF THE NEW LINER. ANY TEARS OR DAMAGE TO THE LINER SHALL BE REPAIRED AT THE CONTRACTOR'S EXPENSE.

**CIVIL/ARCHITECTURAL/PROCESS SYMBOLS LIBRARY**



**ABBREVIATIONS**

ARVB	AIR RELIEF VACUUMBREAKER VALVE	MH	MANHOLE
BEG	BELOW EXISTING GRADE	N	NORTH
BFV	BUTTERFLY VALVE	NE	NORTHEAST
CL	CENTERLINE	NW	NORTHWEST
CMP	CORRUGATED METAL PIPE	OH	OVERHEAD
DIA. OR Ø	DIAMETER	PVC	POLYVINYL CHLORIDE
E	EAST	RAD OR R	RADIUS
EA	EACH	RPP	REINFORCED POLYPROPYLENE
ELEC	ELECTRICAL LINE	S	SOUTH
EOA	EDGE OF ASPHALT	SE	SOUTHEAST
EXIST. OR EX.	EXISTING	SW	SOUTHWEST
INV	INVERT	T.O.P.	TOP OF PIPE
L.P.	LOW POINT	UON	UNLESS OTHERWISE NOTED
FM	FORCE MAIN		

12687 W. CEDAR DRIVE, SUITE 300  
LAKEWOOD, CO 80226

720.749.4165  
WWW.ELEMENTENGINEERING.NET

BY	XXX						
DATE	07/17						
REVISIONS	DESCRIPTION						
NO.	DESCRIPTION NO. 1						
1							

WASTEWATER TREATMENT PLANT

GENERAL NOTES

TOWN OF RAMAH  
113 S. COMMERCIAL STREET  
RAMAH, CO 80852

FOR AND ON BEHALF OF  
ELEMENT ENGINEERING, LLC

DATE  
OCTOBER 2022

JOB NUMBER  
0043.0001

SCALE  
NTS

EDITION  
PERMITTING

SHEET  
C2 OF C27

**SEWER BYPASS PUMPING**

1. IF SEWAGE BYPASS PUMPING IS NECESSARY, THE CONTRACTOR WILL SUPPLY AND MONITOR THE PUMP DURING THE ENTIRE PUMPING PERIOD. A BACK-UP PUMP WILL BE ONSITE FOR USE IF NECESSARY. BYPASS HOSE SHALL BE PROTECTED FROM TRAFFIC DAMAGE USING APPROVED APPARATUS. FOR ALL SEWAGE BYPASS PUMPING, THE CONTRACTOR WILL HAVE CONTINUOUS ON SITE MONITORING OF PUMPING OPERATIONS.
2. FURNISH ALL LABOR, MATERIALS, EQUIPMENT, AND INCIDENTALS REQUIRED TO MAINTAIN CONTINUOUS AND RELIABLE WASTEWATER SERVICE IN ALL WASTEWATER LINES DURING CONSTRUCTION.
3. DURING VARIOUS PHASES OF THE WORK, IT WILL BE NECESSARY TO CONSTRUCT AND MAINTAIN TEMPORARY BYPASS SEWERS TO MAINTAIN CONTINUOUS AND RELIABLE WASTEWATER FLOW IN ALL PIPES, INCLUDING INDIVIDUAL SERVICE CONNECTIONS. VARIOUS PHASES OF THE WORK THAT SHALL REQUIRE THE IMPLEMENTATION OF TEMPORARY BYPASS SEWERS INCLUDING, BUT ARE NOT LIMITED TO, SEWER MAIN AND MANHOLE REPLACEMENT, TRENCHLESS REHABILITATION OF EXISTING SEWERS, AND PIPELINE INSPECTION.
4. CONTRACTOR SHALL CONSTRUCT AND MAINTAIN ALL TEMPORARY BYPASS SEWERS AND BE RESPONSIBLE FOR ALL BYPASS PUMPING OF SEWAGE THAT MAY BE REQUIRED TO PREVENT BACKING UP OF SEWAGE AND ALLOW APPROPRIATE CONDITIONS FOR PROPER INSPECTION, REHABILITATION, REPLACEMENT OR RECONNECTIONS TO EXISTING SEWERS. THE CONTRACTOR SHALL IMMEDIATELY REMOVE AND DISPOSE OF ALL OFFENSIVE MATTER SPILLED DURING THE BYPASS PUMPING AT HIS OWN EXPENSE. THE CONTRACTOR SHALL ALSO BE RESPONSIBLE FOR PAYING ANY FINES IMPOSED AS A RESULT OF SPILLS OR OVERFLOWS THAT OCCUR AS A RESULT OF THE BYPASS PUMPING OPERATIONS.
5. CONTRACTOR SHALL PROVIDE A REDUNDANT BYPASS PUMP, INTAKE AND DISCHARGE CONDUIT, AND OTHER EQUIPMENT NECESSARY TO PROVIDE CONTINUOUS WASTEWATER FLOW AND PREVENT THE BACKING UP OF SEWAGE IN THE CASE OF EMERGENCIES AT ALL TIMES.
6. WHERE NO ALTERNATE SANITARY SEWER ROUTE IS AVAILABLE OR WHEN TWENTY-FOUR HOURS OF STORAGE IS NOT FEASIBLE, REDUNDANT BYPASS PUMPING SHALL BE INSTALLED.
7. PRIMARY BYPASS PUMPS SHALL BE CRITICALLY SILENCED WHEN USED IN RESIDENTIAL SETTINGS OR AREAS WHERE EXCESSIVE NOISE LEVELS WOULD CREATE A DISTURBANCE. REDUNDANT BYPASS PUMPING DOES NOT HAVE TO BE CRITICALLY SILENCED.
8. THE CONTRACTOR SHALL SUBMIT TO THE ENGINEER A SCHEDULE TO COMPLETE THE WORK. IT WILL INCLUDE THE SEQUENCING AND COORDINATION OF CONNECTIONS TO EXISTING SEWERS, PIPELINE INSPECTION, TRENCHLESS REHABILITATION AND TESTING OF EXISTING SEWERS, AND THE HANDLING OF WASTEWATER FLOW DURING CONSTRUCTION. THE SCHEDULE OF WORK SHALL ALSO BE REVIEWED AND APPROVED BY THE OPERATOR IN RESPONSIBLE CHARGE (ORC).
9. THE DESIGN, INSTALLATION, AND OPERATION OF THE TEMPORARY PUMPING SYSTEM SHALL BE THE CONTRACTOR'S RESPONSIBILITY. THE CONTRACTOR SHALL EITHER DEMONSTRATE, OR EMPLOY THE SERVICES OF A SUBCONTRACTOR WHO CAN DEMONSTRATE, TO THE ENGINEER AND ORC THAT HE SPECIALIZES IN THE DESIGN AND OPERATION OF TEMPORARY BYPASS PUMPING SYSTEMS.
10. THE CONTRACTOR SHALL PREPARE A SPECIFIC, DETAILED DESCRIPTION OF THE PROPOSED PUMPING SYSTEM (BYPASS PUMPING PLAN). THE BYPASS PUMPING PLAN SHALL BE SUBMITTED AND APPROVED PRIOR TO THE MOBILIZATION OF ANY OF THE EQUIPMENT INCLUDED IN THE BYPASS PUMPING PLAN. THE BYPASS PUMPING PLAN SHALL OUTLINE ALL PROVISIONS AND PRECAUTIONS TO BE TAKEN BY THE CONTRACTOR REGARDING HANDLING OF EXISTING WASTEWATER FLOWS. THIS BYPASS PUMPING PLAN MUST BE SPECIFIC AND COMPLETE, INCLUDING SUCH ITEMS AS SCHEDULES, LOCATIONS, CAPACITIES OF EQUIPMENT, MATERIALS, AND ALL OTHER INCIDENTAL ITEMS NECESSARY AND/OR REQUIRED TO ENSURE PROPER PROTECTION OF THE FACILITIES, INCLUDING PROTECTION OF THE ACCESS AND BYPASS PUMPING LOCATIONS FOR DAMAGE DUE TO THE DISCHARGE FLOWS, AND COMPLIANCE WITH THE REQUIREMENTS AND PERMIT CONDITIONS SPECIFIED HEREIN. NO CONSTRUCTION SHALL BEGIN UNTIL ALL PROVISIONS AND REQUIREMENTS HAVE BEEN REVIEWED AND ACCEPTED BY THE ENGINEER AND ORC. THE PLAN SHALL INCLUDE BUT NOT LIMITED TO THE FOLLOWING DETAILS:
  - A. SEWER PLUGGING METHOD AND TYPES OF PLUGS.
  - B. SIZE OF SUCTION AND DISCHARGE HOSE OR PIPING.
  - C. BYPASS PUMP SIZES (ONE STANDBY PUMP WILL BE REQUIRED AT EACH LOCATION IN CASE OF A PUMP FAILURE), CAPACITIES, AND NUMBER OF EACH SIZE TO BE PROVIDED ON-SITE INCLUDING ALL PRIMARY, SECONDARY, AND SPARE PUMPING UNITS.
  - D. METHOD OF PROTECTING DISCHARGE MANHOLES OR STRUCTURES FROM EROSION AND DAMAGE.
  - E. SECTIONS SHOWING SUCTION AND DISCHARGE PIPE DEPTH, EMBEDMENT, SELECT FILL AND SPECIAL BACKFILL, IF COVER IS NECESSARY.
  - F. METHOD OF NOISE CONTROL FOR EACH PUMP AND ANY ADDITIONAL EQUIPMENT THAT IS INCLUDED IN THE BYPASS PUMPING PLAN.
  - G. SCHEDULE FOR INSTALLATION OF AND MAINTENANCE OF BYPASS PUMPING LINES.
  - H. PLAN INDICATING LOCATION OF BYPASS PUMPING PIPE LOCATIONS.
  - I. CONTRACTORS PLAN FOR PROVIDING CONTINUOUS MONITORING OF THE BYPASS PUMPING OPERATION AS WELL AS THE MONITORING PERSONS' QUALIFICATIONS.
11. THE CONTRACTOR SHALL SUPPLY PUMPS, CONDUITS, POWER, AND OTHER EQUIPMENT TO DIVERT THE FLOW OF SEWAGE AROUND THE SECTION IN WHICH

WORK IS TO BE PERFORMED. THE BYPASS SYSTEM SHALL BE OF SUFFICIENT CAPACITY TO HANDLE THE WASTEWATER FLOWS. IT IS THE INTENT OF THESE SPECIFICATIONS TO REQUIRE THE CONTRACTOR TO ESTABLISH ADEQUATE BYPASS PUMPING AS REQUIRED REGARDLESS OF THE FLOW CONDITION.

12. THE CONTRACTOR SHALL PERFORM LEAKAGE AND PRESSURE TESTS OF THE BYPASS PUMPING DISCHARGE PIPING USING CLEAN WATER PRIOR TO THE ACTUAL OPERATION. THE PRESSURE AND LEAKAGE TEST SHALL BE CONDUCTED AT ONE-AND-A-HALF TIMES THE MAXIMUM PRESSURE THE SYSTEM WILL EXPERIENCE BASED ON THE APPROVED BYPASS PUMPING PLAN FOR A PERIOD OF TWO HOURS. NO LEAKAGE IS PERMITTED DURING THIS TEST. THE ENGINEER WILL BE GIVEN 24 HOURS NOTICE PRIOR TO TESTING. IN ADDITION, THE CONTRACTOR SHALL DEMONSTRATE THAT THE PUMPING SYSTEM IS IN GOOD WORKING ORDER AND IS SUFFICIENTLY SIZED TO SUCCESSFULLY HANDLE FLOWS BY PERFORMING A TEST RUN FOR A PERIOD OF 24 HOURS PRIOR TO BEGINNING THE WORK.
13. THE CONTRACTOR SHALL BE REQUIRED TO REPAIR, AT HIS OWN EXPENSE, ANY DAMAGE TO PUBLIC OR PRIVATE PROPERTY CAUSED BY HIS OPERATIONS.
14. SHOULD DAMAGE OF ANY KIND OCCUR TO THE EXISTING SEWERS, THE CONTRACTOR SHALL, AT HIS OWN EXPENSE MAKE REPAIRS TO THE SATISFACTION OF THE ENGINEER AND THE ORC.
15. THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE AUTHORITY SHOULD A SANITARY SEWER OVERFLOW (SSO) OCCUR AND TAKE THE NECESSARY ACTION TO CLEAN UP AND DISINFECT THE SPILLAGE TO THE SATISFACTION OF THE AUTHORITY AND/OR OTHER GOVERNMENTAL AGENCY. IF SEWAGE IS SPILLED ONTO PUBLIC OR PRIVATE PROPERTY, THE CONTRACTOR SHALL WASH DOWN, CLEAN UP, AND DISINFECT THE SPILLAGE TO THE SATISFACTION OF THE PROPERTY OWNER, AUTHORITY, AND/OR OTHER GOVERNMENTAL AGENCY.
16. THE CONTRACTOR SHALL NOT BE PERMITTED TO OVERFLOW, BYPASS, PUMP OR BY ANY OTHER MEANS CONVEY DRAINAGE TO ANY LAND, STREET, STORM DRAIN OR WATER COURSE.
17. THE CONTRACTOR SHALL CEASE BYPASS PUMPING OPERATIONS AND RETURN FLOWS TO THE NEW AND/OR EXISTING SEWER WHEN DIRECTED BY THE OWNER. DURING BYPASSING, NO WASTEWATER SHALL BE LEAKED, DUMPED, OR SPILLED IN OR ONTO ANY AREA OUTSIDE THE EXISTING WASTEWATER SYSTEM. WHEN BYPASS OPERATIONS ARE COMPLETE, ALL BYPASS PIPING SHALL BE FLUSHED WITH FRESH WATER AND DRAINED INTO THE WASTEWATER SYSTEM PRIOR TO DISASSEMBLY.
18. CONTRACTOR MUST TAKE CARE TO PREVENT DAMAGE TO EXISTING STRUCTURES. DISCHARGE PIPING TO GRAVITY SEWER SYSTEMS SHALL BE DESIGNED IN SUCH A MANNER AS TO PREVENT DISCHARGE FROM CONTACTING MANHOLE WALLS OR BENCHING AND FULL DISCHARGE SHALL GO INTO DOWNSTREAM PIPE WITH AS MINIMAL TURBULENCE AS POSSIBLE. CONTRACTOR IS RESPONSIBLE FOR ANY DAMAGE TO MANHOLES. IT MAY BE NECESSARY TO REMOVE THE MANHOLE CONE TO PROVIDE SUFFICIENT SPACE FOR THE BYPASS PIPING. IF THIS IS REQUIRED, THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE TO EXISTING MANHOLE COMPONENTS.
19. THE 24-HOUR MONITORING PERSON SHALL BE PROPERLY TRAINED, EXPERIENCED, AND MECHANICALLY QUALIFIED SUCH THAT THEY CAN QUICKLY AND EFFECTIVELY ADDRESS ANY POTENTIAL EMERGENCY AND NON-EMERGENCY SITUATIONS ASSOCIATED WITH THE PUMPS AND BYPASS PUMPING SYSTEM THAT MUST REMAIN IN OPERATION FOR AN EXTENDED PERIOD.

**BACKFILLING GENERAL**

- A. ALL TRENCHES SHALL BE BACKFILLED AFTER PIPES, FITTINGS AND APPURTENANCES HAVE BEEN INSTALLED, INSPECTED AND APPROVED BY THE TOWN ENGINEER.
- B. WHENEVER A COMPACTION REQUIREMENT VALUE IS SPECIFIED HEREIN, THE OPTIMUM MOISTURE CONTENT AND STANDARD PROCTOR DENSITY SHALL BE DETERMINED IN ACCORDANCE WITH AASHTO T-99 FOR NINETY-FIVE PERCENT (95%).

**DENSITY REQUIREMENTS IN TRENCH**

THE CONTRACTOR SHALL OBTAIN A STANDARD PROCTOR DENSITY OF NINETY-FIVE (95%) STANDARD PROCTOR FOR THE TOTAL DEPTH OF ALL TRENCHES IN OPEN FIELDS AND IN DEDICATED ROWS. BACKFILLING SHALL BE DONE WITH GOOD SOUND EARTH, SAND OR GRAVEL, AND NO BITUMINOUS PAVEMENT, CONCRETE, ROCK OR OTHER LUMPY MATERIAL SHALL BE USED IN THE BACKFILL UNLESS THESE MATERIALS ARE SCATTERED AND DO NOT EXCEED SIX INCHES (6") IN ANY DIMENSION AND ARE NOT PLACED WITHIN ONE FOOT OF THE 2-1/2' LIMIT. MATERIAL OF PERISHABLE, SPONGY OR OTHERWISE IMPROPER NATURE SHALL NOT BE USED IN BACKFILLING AND NO MATERIAL GREATER THAN FOUR INCHES (4") IN ANY DIMENSION SHALL BE PLACED WITHIN ONE FOOT (1') OF ANY PIPE, MANHOLE OR STRUCTURE. BACKFILLING SHALL BE ACCOMPLISHED IN THE ZONE IN LAYERS NOT TO EXCEED TWO FEET (2') OR AS RECOMMENDED BY TESTER. ALL BACKFILL MATERIAL SHALL BE SUBJECT TO THE APPROVAL OF THE TOWN ENGINEER.

**COMPACTED FILL**

COMPACTION SHALL BE DONE BY USE OF VIBRATORY EQUIPMENT, TAMPING ROLLERS, PNEUMATIC TIRE ROLLERS OR OTHER MECHANICAL TAMPERS OF THE TYPE AND SIZE APPROVED BY THE TOWN ENGINEER. HAND TAMPERS SHALL BE USED AROUND ALL MANHOLES, VALVE BOXES, AND ANY SURFACE STRUCTURE. THE BACKFILL SHALL BE PLACED IN HORIZONTAL LAYERS OF SUCH DEPTHS AS ARE CONSIDERED PROPER FOR THE TYPE OF COMPACTING EQUIPMENT BEING USED IN RELATION TO THE BACKFILL MATERIAL BEING PLACED. EACH LAYER

SHALL BE EVENLY SPREAD, PROPERLY MOISTENED AND COMPACTED. ANY DAMAGE TO THE PIPE AS A RESULT OF CONTRACTOR'S OPERATION SHALL BE REPAIRED AND/OR REPLACED.

**COMPACTION TESTS**

COMPACTION TESTS WILL BE TAKEN BY AN APPROVED TESTING LABORATORY AT LOCATIONS DESIGNATED BY THE TOWN ENGINEER. ALL EXPENSES INVOLVED IN THESE TESTS WILL BE BORNE BY THE CONTRACTOR. RESULTS OF THE TESTS WILL BE MADE AVAILABLE TO THE TOWN ENGINEER IMMEDIATELY AND COPIES OF TEST RESULTS WILL BE SUPPLIED TO THE TOWN ENGINEER ONCE PER WEEK. A FINAL TYPED BOUND COPY OF FINAL TEST RESULTS MUST BE SUBMITTED TO THE TOWN ENGINEER AT THE END OF THE PROJECT. IN ALL CASES WHERE THE TESTS INDICATE COMPACTION LESS THAN THAT REQUIRED IN THESE STANDARDS, ADDITIONAL COMPACTION AND TESTS WILL BE REQUIRED UNTIL THESE SPECIFICATIONS ARE MET. PROBATIONARY ACCEPTANCE OF THE LINES BY THE TOWN WILL BE CONTINGENT UPON SATISFACTORY COMPACTION RESULTS. NO HYDROSTATIC TESTING OF THE WATER MAIN WILL BE ALLOWED UNTIL SATISFACTORY COMPACTION IS OBTAINED. FREQUENCY OF TESTING WILL BE AS FOLLOWS:

- A. ONE (1) TEST AT EVERY ABOVE GROUND APPURTENANCE (I.E. VALVE BOX, MANHOLE) AT TWO-FOOT (2.0') INCREMENTS.
- B. ONE (1) TEST EVERY TWO HUNDRED (200) LF OF MAINLINE TRENCH AT TWO-FOOT (2.0') INCREMENTS BEGINNING TWO FEET (2') ABOVE PIPE TO FINAL GRADE AND ONE TEST AT FINAL GRADE.
- C. SEE TECHNICAL SECTION 02200 FOR EMBANKMENT TESTING REQUIREMENTS.

**FENCE**

1. AT EACH LOCATION WHERE AN ELECTRIC TRANSMISSION, DISTRIBUTION, OR SECONDARY LINE CROSSES A FENCE, THE CONTRACTOR SHALL FURNISH AND INSTALL A GROUND CONFORMING TO ARTICLE 250 OF THE NATIONAL ELECTRIC CODE. A GROUND SHALL ALSO BE INSTALLED A MAXIMUM OF EVERY 500 FT ALONG THE FENCE. THE GROUND ROD SHALL BE A MINIMUM DIAMETER OF 1/2 IN AND 8 FT IN LENGTH, AND DRIVEN AT LEAST 7 1/2 FT INTO THE GROUND. THE ROD SHALL BE CONNECTED TO EACH WIRE WITH A MINIMUM AWG NO. 8 STRANDED COPPER WIRE. GROUNDING WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF THE FENCE.
2. H (HEIGHT OF FABRIC) SHALL BE AS SHOWN ON THE PLANS. FABRIC IS AVAILABLE IN THE FOLLOWING HEIGHTS: 36 IN, 42 IN, 60 IN, 72 IN, 84 IN, 96 IN, 108 IN, 120 IN, AND 144 IN.
3. CHAIN LINK FENCE SHALL CONFORM TO AASHTO M 181.
4. CHAIN LINK FABRIC SHALL BE 2 IN MESH NO. 9 GAGE GALVANIZED OR ALUMINUM COATED WIRE SECURELY FASTENED TO TENSION WIRE, LINE POSTS, RAILS, BRACES AND STRETCHER BARS SPACE AS SHOWN. WIRE FASTENERS AND TIE CLIPS SHALL BE NO. 11 GAGE (W&M) GALVANIZED STEEL WIRE OR NO. 7 GAGE (B&S) ALUMINUM WIRE, AND HOG RINGS SHALL BE NO. 9 GAGE, ALL IN CONFORMANCE WITH ASTM F 626.
5. STEEL POSTS, RAILS AND GATE FRAMES SHALL CONFORM TO AASHTO M 181 TYPE 1, GRADE 1 OR GRADE 2.
6. AT THE CONTRACTOR'S OPTION, PIPE USED FOR CONSTRUCTION SHALL CONFORM TO THE DIMENSIONS AND WEIGHTS FOR ORDINARY PIPE PER CDOT.
7. TENSION WIRE SHALL BE CONTINUOUS BETWEEN END OR CORNER POST AND LINE BRACE POST. A TURNBUCKLE OR OTHER APPROVED TIGHTENING DEVICE SHALL BE USED FOR EACH CONTINUOUS SPAN OF TENSION WIRE.
8. TENSION WIRE SHALL CONFORM TO AASHTO M 181.
9. CONCRETE FOOTINGS SHALL HAVE TOPS CROWNED AT GROUND LEVEL AND SHALL BE CLASS B. CONCRETE WITH LIGHTWEIGHT AGGREGATE CONFORMING TO AASHTO M 195, MAY BE SUBSTITUTED.
10. TERMINATION OF FENCE AT BRIDGES OR OTHER STRUCTURES SHALL BE AS SHOWN ON THE PLANS.
11. CHAIN LINK FABRIC UP TO 5 FT HIGH SHALL BE KNUCKLED AT THE TOP AND BOTTOM SELVAGES.
12. FENCE MAY BE CONSTRUCTED WITH EITHER ROUND PIPE OR ROLL-FORMED STEEL COMPONENTS. THE CONTRACTOR SHALL STATE AT THE PROCONSTRUCTION CONFERENCE, THE TYPE OF CONSTRUCTION AND TYPE OF LINE POST TO BE USED THROUGHOUT THE PROJECT.
13. THE CONTRACTOR SHALL BE RESPONSIBLE FOR RE-ESTABLISHING DISTURBED OR DESTROYED SURVEY MONUMENTS TO THE APPROPRIATE ACCURACY.




12687 W. CEDAR DRIVE, SUITE 300  
LAKEWOOD, CO 80226  
720.749.4165  
WWW.ELEMENTENGINEERING.NET


NO.	DESCRIPTION	DATE	BY
1	DESCRIPTION NO. 1	01/17	XXX

REVISIONS	DESCRIPTION

WASTEWATER TREATMENT PLANT
GENERAL NOTES
TOWN OF RAMA 113 S. COMMERCIAL STREET RAMA, CO 80832
FOR AND ON BEHALF OF ELEMENT ENGINEERING, LLC
DATE OCTOBER 2022
JOB NUMBER 0043.0001
SCALE NTS
EDITION PERMITTING
SHEET C3 OF C27



DESIGN SUMMARY		
PERMITTED DESIGN FLOW	0.015	MGD
PERMITTED ORGANIC LOADING	32	LBS/DAY
LIFT STATION PERMITTED FLOW	42	GPM
TOTAL BOTTOM OF POND AREA	310,000	SF
TOTAL TOP OF POND AREA	372,049	SF



NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
 PROCESS FLOW DIAGRAM  
 & HYDRAULIC PROFILE  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF

FOR AND ON BEHALF OF  
 ELEMENT ENGINEERING, LLC


DATE  
 OCTOBER 2022

JOB NUMBER  
 0043.0001

SCALE  
 NTS



EDITION  
 PERMITTING

SHEET  
 C4 OF C27



LEGEND	
●	FOUND MONUMENT AS DESCRIBED
●	SET 18" #5 REBAR WITH 1 1/2" ALUMINUM CAP "FLATIRONS SURV 16406"
(AM)	AS MEASURED AT TIME OF SURVEY
(C)	CALCULATED FROM RECORD AND AS MEASURED INFORMATION
(P)	AS PER THE PLAT OF ~PLAT NAME~
(R)	AS PER RECORD INFORMATION
▨	CONCRETE
▨	EDGE OF ASPHALT
▨	GRAVEL
▨	FENCE
—	SIGN / MARKER
⊗	DECIDUOUS TREE (TRUNK DIAMETER/DRIP LINE RADIUS)
⊗	CONIFEROUS TREE (TRUNK DIAMETER/DRIP LINE RADIUS)
—	WATER LINE
⊗	WATER VALVE
⊗	WATER METER
⊗	WELL
⊗	FIRE HYDRANT
—	IRRIGATION LINE
—	SANITARY SEWER LINE (8" PVC)
⊗	SANITARY SEWER MANHOLE
—	ELECTRIC LINE
⊗	TRANSFORMER
EM	ELECTRIC METER
EP	ELECTRICAL PANEL
EV	ELECTRIC VAULT/BOX
⊗	LIGHT POLE

LEGEND	
—	OVERHEAD UTILITY LINE
⊗	UTILITY POLE
—	GUY WIRE
—	CABLE TV LINE
⊗	CABLE/FIBEROPTIC VAULT
—	FIBEROPTIC LINE
—	GAS LINE
—	TELEPHONE LINE
⊗	TELEPHONE MANHOLE
⊗	TELEPHONE RISER
⊗	UNIDENTIFIED MANHOLE
⊗	UNIDENTIFIED VAULT
MB	MAILBOX
○	POST



**SURVEY INFORMATION**


COORDINATE DATUM: COORDINATES ON THIS PROJECT ARE FOR THE EXCLUSIVE USE FOR THE CONSTRUCTION OF THIS PROJECT AND ARE CONSIDERED PROJECT COORDINATES ONLY. PROJECT COORDINATES ARE MODIFIED COLORADO STATE PLANE CENTRAL ZONE NAD83 COORDINATES. PLEASE CONTACT B.L. LAMAN, brad@interstatesurveygroup.com, FOR ANY QUESTIONS ABOUT CONTROL POINTS ON THIS PROJECT.

ELEVATIONS ARE BASED ON NAVD88, DERIVED FROM AN OPUS SOLUTION.

CONTRACTOR TO VERIFY SURVEY INFORMATION AND REPORT ANY DISCREPANCIES BETWEEN SURVEY AND FIELD INFORMATION TO OWNER AND ENGINEER.

OBSERVATIONS WERE COLLECTED USING GPS RTK BETWEEN SEPTEMBER 20, 2021 AND OCTOBER 7, 2021.

NO RIGHT-OF-WAY DOCUMENTATION WAS FOUND FOR HWY 24 AND RAMAH ROAD EAST INTERSECTION. THE APPROXIMATE RIGHT-OF-WAY SHOWN WAS ESTABLISHED USING, AND BEST FIT TO, FOUND MONUMENTS



NO	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT

TOPOGRAPHIC SURVEY


TOWN OF RAMAH  
113 S. COMMERCIAL STREET  
RAMAH, CO 80832

FOR AND ON BEHALF OF ELEMENT ENGINEERING, LLC
DATE OCTOBER 2022
JOB NUMBER 0043.0001
SCALE 1" = 100'
EDITION
PERMITTING
SHEET C5 OF C27

**ELEMENT ENGINEERING LLC**

720.749.4165  
WWW.ELEMENTENGINEERING.NET

12687 W. CEDAR DRIVE, SUITE 300  
LAFLETT, CO 80226



NO.	REVISIONS	DATE	BY

WASTEWATER TREATMENT PLANT  
**TOPOGRAPHIC SURVEY**  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832


FOR AND ON BEHALF OF  
 ELEMENT ENGINEERING, LLC  
 DATE  
**OCTOBER 2022**  
 JOB NUMBER  
**0043.0001**  
 SCALE  
**1" = 100'**  
 EDITION  
**PERMITTING**  
 SHEET  
 C6 OF C27



NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
PROPOSED IMPROVEMENTS,  
CONST. PHASING, AND DEMO  
TOWN OF RAMAH  
113 S. COMMERCIAL STREET  
RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF  
  
FOR AND ON BEHALF OF  
ELEMENT ENGINEERING, LLC  
DATE  
OCTOBER 2022  
JOB NUMBER  
0043.0001  
SCALE  
NTS  
EDITION  
PERMITTING  
SHEET  
C7 OF C27




**DECOMMISSION AND ABANDON EXISTING SEPTIC TANK**  
REMOVE EXISTING TANK DECK AND BIOSOLIDS. DISPOSE OF BIOSOLIDS PER CDPHE REQUIREMENTS. FILL REMAINING TANK CAVITY TO MATCH SURROUNDING GRADE.

DECOMMISSION EXISTING WASTEWATER LAGOON  
SEE NOTES THIS SHEET

PROPERTY OWNER:  
TOWN OF RAMAH


- CONSTRUCTION PHASING NOTES**
- CONSTRUCT EVAPORATIVE PONDS
    - GRADE SITE
    - INSTALL PIPING AND STRUCTURES AT EVAPORATION POND SITE
    - INSTALL SYNTHETIC POND LINERS AND ASSOCIATED EQUIPMENT AND BALLAST
  - CONSTRUCT FORCE MAIN
    - CONSTRUCT LIFT STATION
    - CONSTRUCT/INSTALL LIFT STATION WET WELL, VALVE VAULT, AND OVERFLOW TANK WITH ASSOCIATED PIPING AND EQUIPMENT
  - CONSTRUCT GRAVITY SEWER TO DIRECT WASTEWATER TO NEW LIFT STATION.
  - COMPLETE TESTING AND STARTUP OF LIFT STATION, FORCE MAIN, AND EVAPORATION PONDS.
  - TIE IN ALL PROPOSED STRUCTURES AND PIPING. COMPLETE TESTING AND STARTUP OF PROPOSED SYSTEM.
  - COMPLETED EXISTING LAGOON AND SEPTIC TANK DECOMMISSIONING AS NOTED ON THIS SHEET.
- EXISTING LAGOON DECOMMISSIONING NOTES**
- REMOVE AND DISPOSE OF BIOSOLIDS FROM THE LAGOON PER CDPHE REQUIREMENTS.
  - LAGOON CLOSEOUT SHALL CONSIST OF REMOVAL OF ALL STANDING WASTEWATER, ALL BIOSOLIDS, ANY RESIDUES OF WASTEWATER TREATMENT, AND ALL INFRASTRUCTURE.
  - ADDITIONALLY, CLOSEOUT SHALL INCLUDE LEVELING OF EXISTING EMBANKMENTS INTO POND AFTER REMOVAL OF BIOSOLIDS AND RESEEDING OF THE AREA. PRIOR TO RESEEDING, THE CONTRACTOR SHALL SUBMIT THE PROPOSED SEED MIXTURE FOR APPROVAL.





**NOTES:**

- LIFT STATION AND MANHOLE INVERTS SHALL BE FIELD VERIFIED AND FIELD CORED
- ALL WORK AND EQUIPMENT TO STAY WITHIN ROW. CONTRACTOR TO INSTALL TEMPORARY CONSTRUCTION FENCE ALONG ROW AT LIFT STATION SITE.



**ELEMENT ENGINEERING LLC**  
 12687 W. CEDAR DRIVE, SUITE 300  
 LAKEWOOD, CO 80226  
 720.749.4165  
 WWW.ELEMENTENGINEERING.NET

NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
**LIFT STATION YARD PIPING**  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832



PREPARED UNDER THE DIRECT SUPERVISION OF

DATE	OCTOBER 2022
JOB NUMBER	0043.0001
SCALE	1" = 10'
EDITION	
<b>PERMITTING</b>	
SHEET	C8 OF C27


NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT
<b>LIFT STATION SITE PLAN</b>
TOWN OF RAMAH 113 S. COMMERCIAL STREET RAMAH, CO 80832

FOR AND ON BEHALF OF ELEMENT ENGINEERING, LLC
DATE OCTOBER 2022
JOB NUMBER 0043.0001
SCALE 1" = 10'
EDITION
<b>PERMITTING</b>
SHEET C9 OF C27



GRADE NOTES:  
 1. FINAL GRADE SHALL BE RETURNED TO EXISTING GRADE ELEVATION




A  
C10 LIFT STATION & VALVE VAULT PROFILE VIEW  
1/2" = 1'

LIFT STATION DESIGN POINT: 42 GPM  
 ADJUST KNIFE GATE TO CREATE ARTIFICIAL SYSTEM HEAD TO ALLOW DESIGN POINT OPERATION (APPROX 99 FT TDH)

INFLUENT PUMP & MOTOR INFORMATION	
PUMP MAKE	FLYGT SUBMERSIBLE GRINDER
PUMP MODEL	MP 3085 HT
DISCHARGE DIAMETER	2 IN
IMPELLER DIAMETER	150 MM
RATED POWER	4 HP
FREQUENCY	60 HZ
RATED VOLTAGE	230 V
NO. POLES	2
RATED CURRENT	9.9 AMP
STARTING CURRENT	62.0 AMP
RATED SPEED	3445 RPM

PUMP CURVE	
FLOW (GPM)	TDH (FT)
0	124
5	121
10	118
15	115
20	113
25	110
30	107
35	104
40	100
42	99
45	96
50	92
55	87
60	81
65	73



B  
C10 LIFT STATION & VALVE VAULT PLAN VIEW  
1/2" = 1'

LIFT STATION NOTES:  
 1. DISCHARGE CL MUST BE AT LEAST 18" FROM BOTTOM OF VALVE VAULT  
 2. DISCHARGE CL OF VAULT MUST EQUAL DISCHARGE CL OF ORDERED STATION  
 3. ALL BOLT PENETRATIONS THRU WALLS MUST BE SEALED WITH SILICONE SEALANT  
 4. ALL 2-INCH FORCE MAIN PIPING SHALL BE SCHD 80 PVC  
 5. ALL 3-INCH FORCE MAIN PIPING SHALL BE IPSS DR-13.5 HDPE  
 6. ALL 8-INCH GRAVITY PIPING SHALL BE SDR 35 PVC  
 7. PIPE COATING/COLORING AND LABELING PER SPECIFICATIONS  
 8. PIPE AND STRUCTURE PRESSURE TESTING PER SPECIFICATIONS  
 9. PIPE FITTINGS SHALL MATCH PIPE REQUIREMENTS INCLUDING INTERIOR COATING  
 10. FLOATS SHALL BE PLACED AS FAR AWAY FROM THE INFLUENT INVERT AS ALLOWABLE BASED ON THE GEOMETRY OF THE BASIN. THE PUMP OFF FLOAT SHALL BE LOCATED AT THE FURTHEST ALLOWABLE POSITION. FLOATS SHALL BE LOCATED IN INCREASING HEIGHT AS THEY GET CLOSER TO THE INVERT. FLOAT LOCATIONS SHOWN ON THESE PLANS ARE FOR ILLUSTRATIVE PURPOSES ONLY.

NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
 LIFT STATION DETAILS  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832


FOR AND ON BEHALF OF  
 ELEMENT ENGINEERING, LLC  
 DATE  
 OCTOBER 2022  
 JOB NUMBER  
 0043.0001  
 SCALE  
 AS SHOWN  
 EDITION  
 PERMITTING  
 SHEET  
 C10 OF C27

**LIFT STATION CONSTRUCTION NOTES:**


1. CONTRACTOR TO SUBMIT A CONSTRUCTION PHASING PLAN TO ENGINEER FOR APPROVAL PRIOR TO BEGINNING CONSTRUCTION. AN EXAMPLE CONSTRUCTION PHASING PLAN IS AS FOLLOWS:
  - 1.1. CONSTRUCT THE PROPOSED LIFT STATION INCLUDING INSTALLING ALL PUMPS, RAILS, PANELS, ETC.
  - 1.2. CONSTRUCT ALL YARD PIPING UP TO THE PROPOSED TIE IN LOCATIONS.
  - 1.3. TEST THE PROPOSED LIFT STATION PUMPS AND EQUIPMENT.
  - 1.4. INSTALL PROPOSED SANITARY SEWER MANHOLE.
  - 1.5. COMPLETE CONSTRUCTION OF ALL YARD PIPING. FINALIZE GRADING AND INSTALLATION OF ALL REQUIRED CONCRETE, BOLLARDS, ETC.
2. BYPASS PUMPING WILL BE REQUIRED DURING CONSTRUCTION. THE CONTRACTOR MUST SUBMIT A BYPASS PUMPING PLAN TO THE ENGINEER FOUR (4) WORKING DAYS PRIOR TO BEGINNING BYPASS PUMPING. NO BYPASS PUMPING SHALL BE ALLOWED UNTIL THE BYPASS PUMPING PLAN IS APPROVED BY THE ENGINEER IN WRITING. THE BYPASS PUMPING PLAN SHALL INCLUDE THE FOLLOWING ITEMS AT A MINIMUM:
  - 2.1. NUMBER OF PUMPS PROVIDED
  - 2.2. BASIC LAYOUT OF BYPASS PUMPS AND PIPE
  - 2.3. BYPASS PUMPING STAFFING PLAN
  - 2.4. EMERGENCY RESPONSE PLAN INCLUDING EMERGENCY CONTACT NUMBERS SHOULD A SANITARY SEWER OVERFLOW (SSO) OCCUR. NOTE THAT ANY REPORTING AND FINES RELATING TO A SSO SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
3. CONTRACTOR TO LOCATE ALL PROPOSED TIE IN LOCATIONS TO VERIFY DEPTH AND LOCATION. CONTRACTOR TO PROVIDE ANY MATERIALS, FITTINGS, BENDS AND PIPE NECESSARY TO TIE INTO EXISTING PIPES AND STRUCTURES. ANY DISCREPANCIES IN TIE IN LOCATIONS SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE ENGINEER.
4. PUMPS, RAILS, FLOATS, VALVES AND ALL ANCILLARY EQUIPMENT SHALL BE INSTALLED PER MANUFACTURER RECOMMENDATIONS AND SPECIFICATIONS.
6. AN ADDITIONAL 5 FEET OF WIRE FROM THE CONTROL BOX TO THE FLOATS SHALL BE ASSUMED TO ENSURE SLACK IN THE WIRE.
7. VENT PIPING SHALL BE 4-INCH DUCTILE IRON COATED YELLOW WITH EXTERIOR RATED EPOXY COATING PRODUCT. SECURE NO. 24 MESH IN OPENING. INSTALL CARBON CANISTER FOR ODOR CONTROL.
8. ALL CONCRETE STRUCTURES SHALL BE PRE-CAST. ALL HATCHES SHALL BE CAST INTO THE MANHOLE TOP.
9. PUMP STARTUP AND TRAINING TO BE COMPLETED BY A MANUFACTURER TRAINED AND APPROVED REPRESENTATIVE.
10. PUMP TESTING SHALL BE COMPLETED WITH CLEAN WATER WHICH MAY BE OBTAINED FROM THE TOWN. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ANY CONSTRUCTION WATER DISCHARGE PERMITS NECESSARY.
11. FOUR (4) HOURS OF OPERATOR TRAINING SHALL BE INCLUDED DURING PUMP STARTUP AND AUTO-DIALER STARTUP. ALL STARTUP AND TRAINING COSTS SHALL BE AT THE CONTRACTOR'S EXPENSE.
12. CONTRACTOR IS RESPONSIBLE FOR PROTECTING EXISTING EQUIPMENT AND STRUCTURES FROM DAMAGE. ANY DAMAGE WILL BE REPAIRED AT THE CONTRACTOR'S EXPENSE IN A MANNER ACCEPTABLE TO THE TOWN.
13. ALL MANHOLE CORES AND PENETRATIONS SHALL BE FIELD CORED AFTER VERIFYING EXISTING UTILITY INFORMATION.
14. CONTRACTOR TO POTHOLE ALL UTILITY CROSSINGS PRIOR TO CONSTRUCTION.

**LIFT STATION EXCAVATION AND BALLASTING NOTES:**

1. PRE-PACKAGED LIFT STATION:
  - 1.1. EXCAVATION AREA SHALL PROVIDE ADEQUATE WORKING ROOM AROUND THE PUMP STATION. SEE PUMP STATION INSTALLATION, CARE AND MAINTENANCE MANUAL FOR HANDLING, INSTALLATION, AND BALLASTING INSTRUCTIONS.
  - 1.2. CONCRETE BALLAST DESIGN SHALL BE SUFFICIENT TO RESIST HEAD PRESSURE AND SOIL LOADING WITH PUMP STATION COMPLETELY EMPTY AND WATER TO GRADE. THE DETAIL SHOWN HEREIN SATISFIES THIS CONDITION.
  - 1.3. DO NOT LET CONCRETE FREE FALL TO BOTTOM OF HOLE MORE THAN 3 TO 4 FEET. PLACE CONCRETE USING A TREMMY CHUTE TO HELP PRECLUDE SEGREGATION OF AGGREGATE FROM THE MATRIX. ENSURE THAT CONCRETE FLOWS UNDER THE FIBERGLASS ANTI-FLOTATION FLANGE. CONSOLIDATE CONCRETE WITH PROPER VIBRATION PER THE RECOMMENDED PRACTICE OF ACI 318-05 SECTION 5.10.
  - 1.4. BACKFILL AND COMPACTION SHALL MEET OR EXCEED THE REQUIREMENTS SET FORTH IN THE INSTALLATION, CARE, AND MAINTENANCE MANUAL FOR THE PACKAGE PUMP STATION.
  - 1.5. SLINGING, INSTALLATION, AND HANDLING SHALL FOLLOW ALL MANUFACTURERS REQUIREMENTS.



1  
C11 LIFT STATION BALLAST AND BACKFILL DETAILS  
1/2" = 1'




2  
C11 VALVE VAULT BALLAST AND BACKFILL DETAILS  
1/2" = 1'

GRADE NOTES:  
1. FINAL GRADE SHALL BE RETURNED TO EXISTING GRADE ELEVATION


NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
LIFT STATION NOTES & BALLASTING  
TOWN OF RAMAH  
113 S. COMMERCIAL STREET  
RAMAH, CO 80832


PREPARED UNDER THE DIRECT SUPERVISION OF  
FOR AND ON BEHALF OF  
ELEMENT ENGINEERING, LLC  
DATE  
OCTOBER 2022  
JOB NUMBER  
0043.0001  
SCALE  
AS SHOWN  
EDITION  
PERMITTING  
SHEET  
C11 OF C27



**A**  
C12 OVERFLOW PLAN VIEW  
1/4" = 1'



**C**  
C12 OVERFLOW SIDE VIEW  
1/4" = 1'



**B**  
C12 OVERFLOW PROFILE VIEW  
1/4" = 1'



NOTE: ALL EQUIPMENT SHOWN IN OVERFLOW PROFILE VIEW PROVIDED BY MANUFACTURER

8-FT DIAMETER 6,000 GALLON TANK	
QTY	DESCRIPTION
1	4" NPT SERVICE FITTING
1	8" DIA PVC INLET HORIZONTAL PIPE
1	23 1/2" IS FIBERGLASS ACCESS OPENING WITH 23 1/2" OD ALIGNMENT RING
1	24" DIA X 48" HIGH PVC RISER WITH FRP LID WITH GASKET
2	LIFTING LUG (10" X 8") 25", 25"
2	16-FT PREFABRICATED CONCRETE DEADMENT
2	HOLD DOWN STRAP


NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
**OVERFLOW DETAILS**  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF  
 FOR AND ON BEHALF OF  
 ELEMENT ENGINEERING, LLC  
 DATE  
 OCTOBER 2022  
 JOB NUMBER  
 0043.0001  
 SCALE  
 AS SHOWN  
 EDITION  
 PERMITTING  
 SHEET  
 C12 OF C27



- NOTES:**
1. INSTALL 3" IPS DR-13.5 HDPE FORCE MAIN TO MAINTAIN 5-FT TO 6-FT BURY DEPTH WITH TRACER WIRE. INSTALL VERTICAL BENDS AS NECESSARY.
  2. MAXIMUM ALLOWABLE JOINT DEFLECTION = 1"
  3. PIPE DEFLECTION SHALL ONLY BE ALLOWED AT JOINTS. NO BENDING OF THE PIPE SHALL BE ALLOWED.
  4. AVOID HIGH POINTS IN THE FORCE MAIN WHERE POSSIBLE. AIR VAC VAULTS SHALL BE REQUIRED AT ALL HIGH POINTS.
  5. CONTRACTOR TO SURVEY AND MARK ACCESS EASEMENT, DISCUSS UTILITIES EASEMENTS, AND FINAL PROPERTY BOUNDARY.
  6. ALL WORK IN EL PASO COUNTY RIGHT-OF-WAY SHALL FOLLOW EL PASO COUNTY UTILITY PERMIT REQUIREMENTS. CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS PRIOR TO BEGINNING WORK.
  7. CONTRACTOR TO REMOVE TREES AND BRUSH AND HAUL AWAY MATERIAL AS NECESSARY THROUGH WORK AREAS. DO NOT REMOVE OR DISTURB TREES UNNECESSARILY.
  8. CONTRACTOR TO POTHOLE UTILITIES AT ALL CROSSINGS.
  9. MAINTAIN 18-INCH MINIMUM VERTICAL SEPARATION AT ALL UTILITY CROSSINGS




HORIZ. SCALE: 1" = 40'  
VERT. SCALE: 1" = 4'


NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
**FORCE MAIN PLAN & PROFILE 0+00 - 6+00**  
TOWN OF RAMAH  
113 S. COMMERCIAL STREET  
RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF  
FOR AND ON BEHALF OF  
ELEMENT ENGINEERING, LLC  
DATE: OCTOBER 2022  
JOB NUMBER: 0043.0001  
SCALE: 1" = 40'  
EDITION: PERMITTING  
SHEET: C13 OF C27



- NOTES:**
1. INSTALL 3" IPS DR-13.5 HDPE FORCE MAIN TO MAINTAIN 5-FT TO 6-FT BURY DEPTH WITH TRACER WIRE. INSTALL VERTICAL BENDS AS NECESSARY.
  2. MAXIMUM ALLOWABLE JOINT DEFLECTION = 1"
  3. PIPE DEFLECTION SHALL ONLY BE ALLOWED AT JOINTS. NO BENDING OF THE PIPE SHALL BE ALLOWED.
  4. AVOID HIGH POINTS IN THE FORCE MAIN WHERE POSSIBLE. AIR VAC VAULTS SHALL BE REQUIRED AT ALL HIGH POINTS.
  5. CONTRACTOR TO SURVEY AND MARK ACCESS EASEMENT, DISCUSS UTILITIES EASEMENTS, AND FINAL PROPERTY BOUNDARY.
  6. ALL WORK IN EL PASO COUNTY RIGHT-OF-WAY SHALL FOLLOW EL PASO COUNTY UTILITY PERMIT REQUIREMENTS. CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS PRIOR TO BEGINNING WORK.
  7. CONTRACTOR TO REMOVE TREES AND BRUSH AND HAUL AWAY MATERIAL AS NECESSARY THROUGH WORK AREAS. DO NOT REMOVE OR DISTURB TREES UNNECESSARILY.
  8. CONTRACTOR TO POT HOLE UTILITIES AT ALL CROSSINGS.
  9. MAINTAIN 18-INCH MINIMUM VERTICAL SEPARATION AT ALL UTILITY CROSSINGS



HORIZ. SCALE: 1" = 40'  
VERT. SCALE: 1" = 4'

NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
**FORCE MAIN PLAN & PROFILE 6+00 - 16+00**  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF  
 FOR AND ON BEHALF OF  
 ELEMENT ENGINEERING, LLC  
 DATE: OCTOBER 2022  
 JOB NUMBER: 0043.0001  
 SCALE: 1" = 40'  
 EDITION: PERMITTING  
 SHEET: C14 OF C27




NO.	DATE	DESCRIPTION



WASTEWATER TREATMENT PLANT  
**FORCE MAIN PLAN & PROFILE**  
 16+00 - 27+00  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF

DATE	OCTOBER 2022
JOB NUMBER	0043.0001
SCALE	AS SHOWN
EDITION	
PERMITTING	
SHEET	C15 OF C27



- NOTES:
1. INSTALL 3" IPS DR-13.5 HDPE FORCE MAIN TO MAINTAIN 5-FT TO 6-FT BURY DEPTH WITH TRACER WIRE. INSTALL VERTICAL BENDS AS NECESSARY.
  2. MAXIMUM ALLOWABLE JOINT DEFLECTION = 1"
  3. PIPE DEFLECTION SHALL ONLY BE ALLOWED AT JOINTS. NO BENDING OF THE PIPE SHALL BE ALLOWED.
  4. AVOID HIGH POINTS IN THE FORCE MAIN WHERE POSSIBLE. AIR VAC VAULTS SHALL BE REQUIRED AT ALL HIGH POINTS.
  5. CONTRACTOR TO SURVEY AND MARK ACCESS EASEMENT, DISCUSS UTILITIES EASEMENTS, AND FINAL PROPERTY BOUNDARY.
  6. ALL WORK IN EL PASO COUNTY RIGHT-OF-WAY SHALL FOLLOW EL PASO COUNTY UTILITY PERMIT REQUIREMENTS. CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS PRIOR TO BEGINNING WORK.
  7. CONTRACTOR TO REMOVE TREES AND BRUSH AND HAUL AWAY MATERIAL AS NECESSARY THROUGH WORK AREAS. DO NOT REMOVE OR DISTURB TREES UNNECESSARILY.
  8. CONTRACTOR TO POTHOLE UTILITIES AT ALL CROSSINGS.
  9. MAINTAIN 18-INCH MINIMUM VERTICAL SEPARATION AT ALL UTILITY CROSSINGS










NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
FORCE MAIN PLAN &  
PROFILE 27+00 - 38+00  
TOWN OF RAMAH  
113 S. COMMERCIAL STREET  
RAMAH, CO 80832

PERMITTED UNDER THE DIRECT SUPERVISION OF  
DATE: OCTOBER 2022  
JOB NUMBER: 0043.0001  
SCALE: 1" = 40'  
EDITION:  
PERMITTING  
SHEET: C16 OF C27



- NOTES:
1. INSTALL 3" IPS DR-13.5 HDPE FORCE MAIN TO MAINTAIN 5-FT TO 6-FT BURY DEPTH WITH TRACER WIRE. INSTALL VERTICAL BENDS AS NECESSARY.
  2. MAXIMUM ALLOWABLE JOINT DEFLECTION = 1"
  3. PIPE DEFLECTION SHALL ONLY BE ALLOWED AT JOINTS. NO BENDING OF THE PIPE SHALL BE ALLOWED.
  4. AVOID HIGH POINTS IN THE FORCE MAIN WHERE POSSIBLE. AIR VAC VAULTS SHALL BE REQUIRED AT ALL HIGH POINTS.
  5. CONTRACTOR TO SURVEY AND MARK ACCESS EASEMENT, DISCUSS UTILITIES EASEMENTS, AND FINAL PROPERTY BOUNDARY.
  6. ALL WORK IN EL PASO COUNTY RIGHT-OF-WAY SHALL FOLLOW EL PASO COUNTY UTILITY PERMIT REQUIREMENTS. CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS PRIOR TO BEGINNING WORK.
  7. CONTRACTOR TO REMOVE TREES AND BRUSH AND HAUL AWAY MATERIAL AS NECESSARY THROUGH WORK AREAS. DO NOT REMOVE OR DISTURB TREES UNNECESSARILY.
  8. CONTRACTOR TO POTHOLE UTILITIES AT ALL CROSSINGS.
  9. MAINTAIN 18-INCH MINIMUM VERTICAL SEPARATION AT ALL UTILITY CROSSINGS





HORIZ. SCALE: 1" = 40'  
VERT. SCALE: 1" = 4'



GRAPHIC SCALE  
(IN FEET)  
1 INCH = 40 FT

- NOTES:
1. INSTALL 3" IPS DR-13.5 HDPE FORCE MAIN TO MAINTAIN 5-FT TO 6-FT BURY DEPTH WITH TRACER WIRE. INSTALL VERTICAL BENDS AS NECESSARY.
  2. MAXIMUM ALLOWABLE JOINT DEFLECTION = 1"
  3. PIPE DEFLECTION SHALL ONLY BE ALLOWED AT JOINTS. NO BENDING OF THE PIPE SHALL BE ALLOWED.
  4. AVOID HIGH POINTS IN THE FORCE MAIN WHERE POSSIBLE. AIR VAC VAULTS SHALL BE REQUIRED AT ALL HIGH POINTS.
  5. CONTRACTOR TO SURVEY AND MARK ACCESS EASEMENT, DISCUSS UTILITIES EASEMENTS, AND FINAL PROPERTY BOUNDARY.
  6. ALL WORK IN EL PASO COUNTY RIGHT-OF-WAY SHALL FOLLOW EL PASO COUNTY UTILITY PERMIT REQUIREMENTS. CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS PRIOR TO BEGINNING WORK.
  7. CONTRACTOR TO REMOVE TREES AND BRUSH AND HAUL AWAY MATERIAL AS NECESSARY THROUGH WORK AREAS. DO NOT REMOVE OR DISTURB TREES UNNECESSARILY.
  8. CONTRACTOR TO POTHOLE UTILITIES AT ALL CROSSINGS.
  9. MAINTAIN 18-INCH MINIMUM VERTICAL SEPARATION AT ALL UTILITY CROSSINGS




HORIZ. SCALE: 1" = 40'  
VERT. SCALE: 1" = 4'

NO.	DATE	BY	DESCRIPTION


WASTEWATER TREATMENT PLANT  
FORCE MAIN PLAN &  
PROFILE 38+00 - 46+75  
TOWN OF RAMAH  
113 S. COMMERCIAL STREET  
RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF

DATE	OCTOBER 2022
JOB NUMBER	0043.0001
SCALE	1" = 40'
EDITION	
PERMITTING	
SHEET	C17 OF C27




**A**  
18 INFLUENT BAR SCREEN PLAN  
3/4" = 1'



**B**  
18 INFLUENT BAR SCREEN PROFILE  
3/4" = 1'


GATE TABLE				
GATE NUMBER	GATE TYPE	MOUNTING TYPE	CHANNEL DIMENSIONS (H' X W')	NOTES
1	MANUAL STOP GATE	FE	3'-6" X 1'-6"	
2	MANUAL STOP GATE	FE	3'-6" X 1'-6"	
3	MANUAL STOP GATE	FE	3'-6" X 1'	EMERGENCY OVERFLOW WEIR
4	MANUAL STOP GATE	FE	3'-6" X 1'	EMERGENCY OVERFLOW WEIR

FE FRAME EMBEDDED INSIDE CHANNEL  
H HEIGHT  
W WIDTH




- NOTES:
- STOP GATES TO BE MANUFACTURED BY PLASTI-FAB OR ENGINEER APPROVED EQUAL
  - SEE PLANS FOR OPENING AND GATE DIMENSIONS
  - STOP GATE IS SANDWICH CONSTRUCTION W/ FRP SKINS, FOAM CORE, AND INTERNAL STRUCTURAL STEEL
  - STOP GATE COLOR IS GREY
  - RESIN: MCWHORTER 712-3765
  - GUIDE FRAME IS PULTRUDED FRP (VINYL-ESTER)
  - ALL JOINTS ARE BONDED WITH PLEXUS MA-300
  - ALL HARDWARE MATERIAL IS T-304 S/S
  - APPROXIMATE WEIGHT OF GATE ALONE IS 14 LBS


**1**  
18 STOP GATE DETAIL  
NTS



**2**  
18 MANUAL BAR SCREEN SECTION  
NTS



**3**  
18 MANUAL BAR SCREEN FRONT VIEW  
NTS



**4**  
18 MANUAL BAR SCREEN TOP VIEW  
NTS


REVISIONS	BY	DATE	DESCRIPTION

WASTEWATER TREATMENT PLANT  
INFLUENT SCREEN DETAILS


TOWN OF RAMAH  
113 S. COMMERCIAL STREET  
RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF


DATE	OCTOBER 2022
JOB NUMBER	0043.0001
SCALE	AS SHOWN
EDITION	PERMITTING
SHEET	C18 OF C27



**A** INFLUENT SPLITTER STRUCTURE AND INFLEUNT PIPING PLAN  
C21 1/4" = 1'



**B** INFLUENT SPLITTER STRUCTURE PROFILE  
C21 1/2" = 1'



**C** OVERFLOW PIPING  
C21 1" = 60'

NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
SPLITTER BOX & POND  
OVERFLOW PIPING  
TOWN OF RAMAH  
113 S. COMMERCIAL STREET  
RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF  
FOR AND ON BEHALF OF  
ELEMENT ENGINEERING, LLC  
DATE  
OCTOBER 2022  
JOB NUMBER  
0043.0001  
SCALE  
AS SHOWN  
EDITION  
PERMITTING  
SHEET  
C19 OF C27

NOTES:  
 1. CONTRACTOR TO STRIP TOP 6" OF EXISTING MATERIAL AND VEGETATION AND DISPOSE OF OFF-SITE.

CURVE TABLE					
CURVE	LENGTH	RADIUS	DELTA	CHORD BEARING	CHORD
C1	65.97'	42.00'	90°00'00"	N43°52'52"E	59.50'
C2	65.97'	42.00'	90°00'00"	S46°07'08"E	59.50'
C3	49.59'	56.00'	50°44'10"	S25°22'05"E	47.98'
C4	66.76'	42.50'	90°00'00"	S45°00'00"E	60.10'
C5	65.97'	42.00'	90°00'00"	S43°52'52"W	59.50'
C6	65.97'	42.00'	90°00'00"	S46°07'08"W	59.50'
C7	65.97'	42.00'	90°00'00"	S43°52'52"W	59.50'
C8	65.97'	42.00'	90°00'00"	S46°07'08"W	59.50'
C9	65.97'	42.00'	90°00'00"	S46°07'08"W	59.50'

ESTIMATED CUT/FILL QUANTITIES  
 CUT: 49,781 CY  
 FILL: 38,341 CY (1.15 COMPACTION FACTOR)  
 TOP SOIL REMOVAL: 9,916 CY

ESTIMATED POND LINER  
 POND LINER: 402,446 SF



28 LF 24" CORRUGATED HDPE CULVERT AT PONDS ENTRANCE.  
 15' WIDE ACCESS ROAD TO PONDS  
 INSTALL 16' WIDE BARB WIRE GATE, ADD CROSS BRACE POST ON EACH SIDE

15' SITE ACCESS ROAD  
 INSTALL 16' WIDE GATE TO PONDS

START OF DRAINAGE SWALE (DS)  
 SLOPE 1% TO SOUTH

INFLUENT STRUCTURE  
 SEE SHEET C21




END OF DRAINAGE SWALE (DS)  
 SLOPE 1% TO THE EAST




NO.	DATE	BY	DESCRIPTION

WASTEWATER TREATMENT PLANT  
 HORIZONTAL CONTROL &  
 GRADING  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832


FOR AND ON BEHALF OF  
 ELEMENT ENGINEERING, LLC  
 DATE  
 OCTOBER 2022  
 JOB NUMBER  
 0043.0001  
 SCALE  
 1" = 60'  
 EDITION  
 PERMITTING  
 SHEET  
 C20 OF C27




HORIZ. SCALE: 1" = 60'  
VERT. SCALE: 1" = 12'



HORIZ. SCALE: 1" = 60'  
VERT. SCALE: 1" = 12'



HORIZ. SCALE: 1" = 60'  
VERT. SCALE: 1" = 12'





HORIZ. SCALE: 1" = 60'  
VERT. SCALE: 1" = 12'

NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
**POND GRADING PROFILES**  
TOWN OF RAMAH  
113 S. COMMERCIAL STREET  
RAMAH, CO 80832

FOR AND ON BEHALF OF  
ELEMENT ENGINEERING, LLC  
DATE  
OCTOBER 2022  
JOB NUMBER  
0043.0001  
SCALE  
1" = 100'  
EDITION  
PERMITTING  
SHEET  
C21 OF C27

ELEVATIONS TABLE			
NUMBER	MINIMUM ELEVATION	MAXIMUM ELEVATION	COLOR
1	-11.98	-7.62	Red
2	-7.62	-5.76	Grey
3	-5.76	-3.40	Yellow
4	-3.40	-1.76	Light Green
5	-1.76	-0.23	Green
6	-0.23	0.00	Cyan
7	0.00	1.64	Blue
8	1.64	4.11	Dark Blue
9	4.11	7.28	Dark Purple
10	7.28	12.90	Purple



INSTALL APPROXIMATELY 2,900.1 L.F. 6-FT TALL CHAIN LINK FENCE

OUTER ACCESS ROAD

28 LF 24" CORRUGATED HDPE CULVERT AT PONDS ENTRANCE.

15' WIDE ACCESS ROAD TO PONDS

INSTALL 16' WIDE GATE TO PONDS

INSTALL 16' WIDE BARB WIRE GATE, ADD CROSS BRACE POST ON EACH SIDE

START OF DRAINAGE SWALE (DS) SLOPE 1% TO SOUTH

END OF DRAINAGE SWALE (DS) SLOPE 1% TO THE EAST

WEST ACCESS ROAD

CENTER ACCESS ROAD

OUTER ACCESS ROAD

CONSTRUCTION SITE ACCESS

COUNTY ROAD (E. RAMAH ROAD) 60' ROW

COUNTY ROAD (RAMAH ROAD E.) 60' ROW

NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT  
**CUT & FILL PLAN**  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF

FOR AND ON BEHALF OF  
 ELEMENT ENGINEERING, LLC

DATE  
**OCTOBER 2022**

JOB NUMBER  
**0043.0001**

SCALE

EDITION  
**PERMITTING**

SHEET  
**C22** OF **C27**

LINER AND VENT INFORMATION

LINER MATERIAL: 45-MIL FPP-R (FLEXIBLE REINFORCED POLYPROPYLENE) OR 45-MIL LLDPE-R (LINEAR LOW DENSITY REINFORCED POLYETHYLENE)

AIR/GAS VENT STRIP: DIMPLED STRIP AT 45-FT ON CENTER BOTH DIRECTIONS (SEE DETAIL)

AIR/GAS VENTS: ON SIDE SLOPE WITH EACH VENT STRIP (SEE DETAIL)

SPECIFICATIONS: SEE TECHNICAL SPECIFICATIONS FOR SPECIFIC MATERIAL PROPERTIES AND REQUIREMENTS.

NOTES:

- CONTRACTOR TO REMOVE ANY DIRT AND DEBRIS WHICH MAY DAMAGE LINER SYSTEM. ANY DEBRIS GREATER THAN 3/8" DIAMETER TO BE REMOVED PRIOR TO INSTALLATION.
- CONTRACTOR RESPONSIBLE FOR LOCATION AND PROTECTION OF ALL UTILITIES PRIOR TO AND DURING CONSTRUCTION.
- AIR/GAS VENTING STRIP TO BE INSTALLED AFTER SUBGRADE IS COMPACTED AND AT FINAL GRADE.
- CONTRACTOR TO FOLLOW ALL MANUFACTURER'S RECOMMENDATIONS FOR HAULING, STOCKPILING, STAGING, UNLOADING, AND INSTALLATION OF LINER SYSTEM.
- PROTECT EXISTING ASPHALT, STRUCTURES, AND CURB AND GUTTER FROM DAMAGE. THE CONTRACTOR WILL BE HELD RESPONSIBLE FOR ANY DAMAGE TO EXISTING INFRASTRUCTURE.
- PRIOR TO INSTALLATION OF LINER, ENGINEER'S REPRESENTATIVE SHALL APPROVE THE INSTALLATION OF AIR/GAS VENTING STRIPS.
- PRIOR TO INSTALLATION OF BALLAST, ENGINEER'S REPRESENTATIVE SHALL APPROVE THE LINER AND AIR/GAS VENT.
- AIR/GAS VENTING STRIP TO MEET THE FOLLOWING SPECIFICATIONS:
  - STRUCTURE: SIMPLED STRIP
  - POLYMER: PS
  - THICKNESS: 1-INCH
  - THRU-FLOW: YES
  - COMPRESSIVE STRENGTH (ASTM D 1621): 9,500 PSF
  - FLOW (ASTM D 4716): 30 GPM/FT
  - FABRIC/BACKING: CORE ENCAPSULATED W/ 4 OZ NW
  - WIDTH: 12-INCH
- INSTALL AIR/GAS VENT 6-INCHES BELOW CREST OF LINER ABOVE EACH AIR/GAS VENTING STRIP. SEE DETAILS FOR INSTALLATION INFORMATION.
- ENGINEER AND LINER MANUFACTURER REPRESENTATIVE TO APPROVE SUBGRADE PREPARATION PRIOR TO LINER INSTALLATION.
- LINER AND MESH UNDER-LINER TO BE INSTALLED BY MANUFACTURER CERTIFIED INSTALLATION TECHNICIANS.
- RESTORE AND RE-SEED SITE PER SPECIFICATIONS.
- BALLAST INSTALLATION REQUIREMENTS (PER POND)


TOE OF SLOPE WILL REQUIRE PERMANENT TOE BALLAST IN THE FORM OF UV RESISTANT SAND TUBES. TOE BALLAST MINIMUM REQUIREMENTS ARE ONE 45 KG SAND TUBE SPACED 5.2 M CENTER TO CENTER ALONG THE TOE OR APPROXIMATELY 80 BALLAST TUBES ALONG THE TOE. IN ADDITION, ALL SLOPE AREAS OF THE CONTAINMENT SHOULD BE BALLASTED ON THE SLOPE WITH A MINIMUM OF 3 SAND TUBES PER CABLE SUPPORTED STRING WITH RESTRAINING CABLE TIE-OFF AT THE TOP OF SLOPE WITHIN THE ANCHOR TRENCH. SPACING OF BALLAST TUBE STRINGS SHOULD BE AT 10.2 M (33.5 FT) INTERVALS ALONG THE INSIDE SLOPE WHICH RESULTS IN APPROXIMATELY 40 BALLAST STRINGS AND 120 BALLAST TUBES. FOR THE BOTTOM OPEN AREA, THE TUBES SHALL BE PLACED IN OFFSET STRINGS PARALLEL TO THE POND LONG DIMENSION OR WIDTH DIMENSION IN SO FAR AS PRACTICAL BUT POSITIONED TO APPROXIMATE ONE TUBE PER 16.4 SQM (176 SF) OR A TOTAL OF 430 BOTTOM SAND TUBES. TOTAL NUMBER OF SAND TUBES PER POND IS ESTIMATED TO BE 630.

SUMMARY BALLAST TUBES PER POND

3H:1V SLOPES	120 (40 BALLAST STRINGS WITH 3 EACH)
TOE OF SLOPE	80 (2 BALLAST TUBES BETWEEN SLOPE TUBES)
BOTTOM	430 (1 BALLAST TUBE PER 16.4 SQM)
TOTAL	630

POND DIMENSION INFORMATION

POND BOTTOM SURFACE AREA (PER POND):	103,333 SF (2.37 ACRES)	RADIUS OF CORNER AT BOTTOM:	20-FT
POND TOP SURFACE AREA (PER POND):	124,016 SF (2.85 ACRES)	RADIUS OF CORNER AT TOP:	35-FT
ASSUMED SLUDGE DEPTH:	6-INCHES	WIDTH OF POND AT BOTTOM:	228-FT
MAX OPERATING WATER LEVEL:	3-FEET	LENGTH OF POND AT BOTTOM:	455-FT
FREEBOARD:	2-FEET	WIDTH OF POND AT TOP:	258-FT
SIDE SLOPE RATIO:	3:1	LENGTH OF POND AT TOP:	485-FT
POND LENGTH TO WIDTH RATIO:	2:1	ROADWAY WIDTH:	15-FT
NO. PONDS	3		





NO.	REVISIONS	DESCRIPTION	DATE	BY


WASTEWATER TREATMENT PLANT  
**POND DETAILS**  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832

PREPARED UNDER THE DIRECT SUPERVISION OF  
 FOR AND ON BEHALF OF  
 ELEMENT ENGINEERING, LLC  
 DATE: OCTOBER 2022  
 JOB NUMBER: 0043.0001  
 SCALE: 1" = 60'  
 EDITION: PERMITTING  
 SHEET: C23 OF C27






**A**  
C24 EVAPORATIVE PONDS DRAINAGE PLAN  
1" = 60'



**C**  
C24 DRAINAGE SWALE ELEV PROFILES  
NTS






**B**  
C24 DRAINAGE SWALE AND OUTLET  
1" = 40'





NO.	REVISIONS	DESCRIPTION	DATE	BY

WASTEWATER TREATMENT PLANT &  
DRAINAGE SWALE PLAN &  
PROFILE


TOWN OF RAMAH 113 S. COMMERCIAL STREET RAMAH, CO 80832	
PREPARED UNDER THE DIRECT SUPERVISION OF	
FOR AND ON BEHALF OF ELEMENT ENGINEERING, LLC	
DATE	OCTOBER 2022
JOB NUMBER	0043.0001
SCALE	AS SHOWN
EDITION	PERMITTING
SHEET	C24 OF C27



NOTE: MANHOLE/VAULT BARREL SECTIONS WILL REQUIRE AN EXTERIOR COATING OF TNEMC SERIES 46-465 OR APPROVED EQUIVALENT IF GROUNDWATER IS ENCOUNTERED IN THE TRENCH.



NO.	REVISIONS	DATE	BY



**ROD DIAMETER, GRADE & LENGTH OF RESTRAINED PIPE**







PIPE SIZE 4" AND LESS	6"	8"	12"	16"	20"	24"
FITTING	D L G D L G D L G D L G D L G D L G	D L G D L G D L G D L G D L G D L G	D L G D L G D L G D L G D L G D L G	D L G D L G D L G D L G D L G D L G	D L G D L G D L G D L G D L G D L G	D L G D L G D L G D L G D L G D L G
90° BEND, TEE, PLUG, VALVE	MS 3/4" 50'	MS 3/4" 71'	MS 3/4" 94'	MS 3/4" 104'	MS 1" 173'	MS 1 1/2" 212'
45° BEND	MS 3/4" 25'	MS 3/4" 35'	MS 3/4" 46'	MS 3/4" 66'	MS 1" 104'	MS 1 1/2" 122'
22 1/2° BEND	MS 3/4" 12'	MS 3/4" 17'	MS 3/4" 23'	MS 3/4" 32'	MS 1" 41'	MS 1 1/2" 50'
11 1/4° BEND	-	-	MS 3/4" 7'	MS 3/4" 10'	MS 1" 13'	MS 1 1/2" 15'

**TOWN OF RAMAH**

**LENGTH OF RESTRAINED PIPE**

SCALE: NONE DATE: OCTOBER 2022

REVISED:



**ELEMENT ENGINEERING LLC**  
 12687 W. CEDAR DRIVE, SUITE 300  
 LAKEWOOD, CO 80228  
 720.749.4165  
 WWW.ELEMENTENGINEERING.NET

NO.	REVISIONS	DESCRIPTION	DATE	BY


FOR AND ON BEHALF OF  
 ELEMENT ENGINEERING, LLC

DATE: OCTOBER 2022  
 JOB NUMBER: 0043.0001  
 SCALE: NTS  
 EDITION: PERMITTING

FOR AND ON BEHALF OF  
 TOWN OF RAMAH  
 113 S. COMMERCIAL STREET  
 RAMAH, CO 80832

WASTEWATER TREATMENT PLANT  
 GENERAL DETAILS

SHEET 26 OF 27




TOWN OF RAMAH

**TYPICAL LINER ANCHOR TRENCH**

SCALE: NONE DATE: OCTOBER 2022

REVISED:




TOWN OF RAMAH

**TYPICAL PIPE BOOT**

SCALE: NONE DATE: OCTOBER 2022

REVISED:




TOWN OF RAMAH

**PIPE BOLLARD DETAIL**

SCALE: NONE DATE: OCTOBER 2022

REVISED:




TOWN OF RAMAH

**LINER AIR/GAS VENT**

SCALE: NONE DATE: OCTOBER 2022

REVISED:




TOWN OF RAMAH

**GRATING SCHEDULE AND CONNECTION DETAILS**

SCALE: NONE DATE: OCTOBER 2022

REVISED:




TOWN OF RAMAH

**TYPICAL POLYPROPYLENE LINER FIELD SEAM DETAIL**

SCALE: NONE DATE: OCTOBER 2022

REVISED:




TOWN OF RAMAH

**BOOT TO PIPE CONNECTION**

SCALE: NONE DATE: OCTOBER 2022

REVISED:



TOWN OF RAMAH

**GRATING SUPPORT AT CONCRETE**

SCALE: NONE DATE: OCTOBER 2022

REVISED:

NO.	REVISIONS	DESCRIPTION	DATE	BY