



SIGN PANEL

CLASS I

- .100 6062-T6 Aluminum with Anodize Coating
- 3M 3930 Series High Intensity Prismatic Sheeting
- 3M 1170 Series Electro-Cut Film
- 3M 880 Process Color Ink

- PRODUCTS**
- Steel Wire Rope
- Pe Strand
- Cable Tie Out
- Chain
- Chain Assemblies
- Anchor Chain & Anchor
- Frame Hook
- G80 Hook
- Regular Hook
- Miscellaneous Hook
- Link
- Ring
- Load Binder
- Turnbuckle
- Eye Bolt
- Shackle
- Wire Rope Clip
- Thimble
- Snap Hook
- Sleeve
- Small Anchor
- Buckle
- Metal Hook
- Pulley and Block
- Other

◀ STEEL WIRE ROPE ▶
Previous *Next*

- HOME
- ABOUT
- CATALOGUE
- CONTACT

**SPECIFICATION: ASTM A 475
 HOT DIP GALVANIZED STRANDS , CLASS A**



Nominal Diameter	Construction	Nominal Diameter Of Wires	Approx Weight			Min Breaking Strength		Weight Of Zine Coating(Grade A)	
			lb/ft	kg/1000'	High Strength	Extra High Strength	oz/sq.ft	g/sq.m	
in		in			lb	lb			
1/8	1x7	0.041	0.032	14.5	1,330	1,830	0.40	122	
5/32	1x7	0.052	0.051	23	2,140	2,940	0.40	122	
3/16	1x7	0.062	0.073	33	2,850	3,990	0.50	153	
7/32	1x7	0.072	0.098	45	3,850	5,400	0.50	153	
1/4	1x7	0.080	0.121	55	4,750	6,650	0.60	183	
9/32	1x7	0.093	0.164	74	6,400	8,950	0.70	214	
5/16	1x7	0.109	0.205	93	8,000	11,200	0.80	244	
3/8	1x7	0.120	0.273	124	10,800	15,400	0.80	244	
7/16	1x7	0.145	0.399	181	14,500	20,800	0.90	275	
1/2	1x7	0.165	0.517	235	18,800	26,900	0.90	275	
9/16"	1x7	.188	0.671	304	24,500	35,000	1.00	305	
1/2	1x19	0.100	0.504	229	19,100	26,700	0.70	214	
9/16	1x19	0.113	0.637	289	24,100	33,700	0.80	244	
5/8	1x19	0.125	0.796	362	28,100	40,200	0.85	259	

Provide sketch showing where each size is being used