

September 20, 2019



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
COLORADO SPRINGS, CO 80907
PHONE (719) 531-5599
FAX (719) 531-5238

Tech Contractors
3575 Kenyon Street, Ste 200
San Diego, California 92110

Attn: Raul Guzman

Re: Soil, Geology and Geologic Hazard Evaluation
Meridian Ranch – Rolling Hills Ranch, Filings 1 through 4
SE of Sunrise Ridge Drive and Rex Road
El Paso County, Colorado

Dear Mr. Guzman:

As requested, personnel of Entech Engineering, Inc. have investigated the above referenced site to evaluate the conditions with respect to geology and geologic hazards affecting development of the site. The subsurface soil conditions were investigated by Entech Engineering, Inc., Test Boring Logs (Appendix A) and Summary of Laboratory Testing Results are included with this report.

The project consists of single-family residential development on an approximate 250-acre site. The site lies in El Paso County, Colorado, approximately 4 miles north of Falcon, Colorado. The approximate location of the site is shown on the Vicinity Location Map, Figure 1.

The topography of the site is gently to moderately sloping rolling hills that generally slope in a southeasterly direction. Minor drainages exist on the site that trend in south-southeasterly directions. The drainages were dry at the time of this investigation. The site lies in portions of S½ of Section 20, and Northern portion of Section 29 Township 12 South, Range 64 West of the 6th Principal Meridian in El Paso County, Colorado. The site is currently vacant. The Site Plan/Proposed Grading is presented in Figure 3.

Forty-nine test borings were drilled on the site as a part of a Subsurface Soil Investigation dated July 15, 2019, (Reference 1). The Test Boring Logs are included in Appendix A. Laboratory Test Results are summarized in Table 1. Information from this report was used evaluating the site.

The scope of this report includes a geologic analysis/evaluation of the site utilizing published geologic data, available subsurface soils information and site-specific mapping of major geologic features, and identification of geologic hazards with respect to the development with recommended mitigation techniques. The Natural Resource Conservation Service (NRCS), previously the Soil Conservation Service (SCS) Survey was also reviewed to evaluate the site.

Tech Contractors
Soil, Geology and Geologic Hazard Evaluation
Meridian Ranch – Rolling Hills Ranch, Filing Nos. 1 – 4
SE of Sunrise Ridge Drive and Rex Road
El Paso County, Colorado

SOIL AND GEOLOGIC CONDITIONS

Soil Survey

The Natural Resource Conservation Service (NRCS) (Reference 2, Figure 3), previously the Soil Conservation Service (Reference 3) has mapped two soil types on the site. Complete descriptions of the soils are presented in Appendix B. In general, the soils consist of gravelly, sandy loam and sandy loam. The soils are described as follows:

| <u>Type</u> | <u>Description</u> |
|-------------|---|
| 19 | Columbine gravelly sand loam, 0-3% slopes |
| 83 | Stapleton sandy loam, 3-8% slopes |

Soils

The soils encountered in the test borings from Subsurface Soil Investigation consisted of slightly silty to silty sand, clayey sand, and clean sand overlying slightly silty to silty sandstone, clayey to very clayey sandstone with interbedded layers of sandy to very sandy claystone. The upper soils were encountered at medium dense to dense states and moist conditions. The upper sands have low expansion potential, however, the claystone and very clayey sandstone have moderate to high expansion potential.

Groundwater

Groundwater was encountered at depths ranging from 2 to 23 feet in thirty-eight of the test borings drilled on this site (Reference 1). Areas of potentially seasonal shallow and seasonal shallow groundwater have been mapped on the site and are discussed later in this report. Fluctuations in groundwater conditions may occur due to variations in rainfall or other factors not readily apparent at this time. Isolated sand layers within the soil profile can carry water in the subsurface. Contractors should be cognizant of the potential for the occurrence of subsurface water features during construction.

Geology

Approximately 16 miles west of the site is a major structural feature known as the Rampart Range Fault. This fault marks the boundary between the Great Plains Physiographic Province and the Southern Rocky Mountain Province. The site exists within a large structural feature known as the Denver Basin. Bedrock in the area is typically gently dipping in a northwesterly direction (Reference 4). The bedrock underlying the site consists of the Dawson Arkose Formation of Tertiary Age. The Dawson Formation typically consists of coarse-grained arkosic sandstone with interbedded layers of fine-grained sandstone, siltstone or claystone. Overlying the Dawson are deposits of alluvial, residual, and man-made soils.

Tech Contractors
Soil, Geology and Geologic Hazard Evaluation
Meridian Ranch – Rolling Hills Ranch, Filing Nos. 1 – 4
SE of Sunrise Ridge Drive and Rex Road
El Paso County, Colorado

The geology of the site was evaluated using the *Geologic Map of the Falcon Quadrangle*, by Morgan and White in 2012, (Reference 5, Figure 4). The geology of the site is indicated in Figure 5. Five mappable units were identified on this site which are described as follows:

- Qaf** **Artificial Fill of Quaternary Age:** These are man-made fill deposits associated with recent on-site grading and stockpiles.
- Qal** **Recent Alluvium of Quaternary Age:** These are recent stream deposits associated with the defined drainages on site. They generally consist of silty to clayey sands and may contain highly organic soil.
- Qa₂** **Alluvium Two of Quaternary Age:** These are water deposited as stream terrace deposits that typically consist of silty to clayey sands and may contain clay layers. The Alluvium two correlates with the Piney Creek Alluvium.
- Qa₃** **Alluvium Three of Quaternary Age:** These are water deposited as stream terrace deposits that typically consist of silty to clayey sands and may contain clay layers. The Alluvium Three correlates with the Broadway Alluvium.
- Tda** **Dawson Arkose Formation of Tertiary Age:** The Dawson Formation typically consists of arkosic sandstone with interbedded fine-grained sandstone, siltstone and claystone. Overlying this formation is a variable layer of residual soil. The residual soils were derived from the in-situ weathering of the bedrock materials on-site. These soils consisted of silty sands and may contain layers of sandy clays.

ENGINEERING GEOLOGIC HAZARDS

Mapping has been performed on this site to identify areas where various geologic conditions exist of which developers should be cognizant during the planning, design and construction stages should new construction be proposed. The engineering geologic hazards identified on this site include artificial fill, potentially seasonal shallow groundwater areas, and shallow groundwater areas (Figure 6). Areas of shallow bedrock will also be encountered on this site. These hazards and recommended mitigation techniques are discussed as follows:

Artificial Fill

An area of fill was mapped on the site in the northeastern portion associated with a dam, and in the north central portion that is associated with a large fill pile that is considered uncontrolled, and areas of fill may exist that are not mapped due to on-going site grading.

Mitigation: It is anticipated the uncontrolled fill piles will be removed during site grading. Any uncontrolled fill encountered beneath foundations should be removed and recompacted at a minimum of 95% of its maximum Modified Proctor Dry Density, ASTM D-1557.

Tech Contractors
Soil, Geology and Geologic Hazard Evaluation
Meridian Ranch – Rolling Hills Ranch, Filing Nos. 1 – 4
SE of Sunrise Ridge Drive and Rex Road
El Paso County, Colorado

Loose Soils

Loose soils were encountered in some of the borings drilled on site. Loose soils if encountered beneath the foundation or floor slabs will require mitigation.

Mitigation: Should loose soils be encountered beneath foundations or floor slabs, mitigation will be necessary. Overexcavation and recompaction at a minimum of 95% of its maximum Modified Proctor Dry Density, ASTM D-1557 is a suitable mitigation, which is common in the area. An overexcavation depth of 2 to 3 feet is anticipated for loose soils.

Expansive Soils

Expansive soils were encountered in some of the test borings drilled on-site. These occurrences are typically sporadic; therefore, none have been indicated on the maps. These clays and claystones, if encountered beneath foundations, can cause differential movement in the structure foundation. These occurrences should be identified and dealt with on an individual basis.

Mitigation: Should expansive soils be encountered beneath the foundation, mitigation will be necessary. Mitigation of expansive soils will require special foundation design. Overexcavation and replacement with non-expansive soils at a minimum of 95% of its maximum Modified Proctor Dry Density, ASTM D-1557 is a suitable mitigation, which is common in the area. Another alternative in areas of highly expansive soils is the use of drilled pier foundation systems. Typical minimum pier depths are on the order of 25 feet and requiring penetration into the bedrock material a minimum of 4 to 6 feet, depending upon building loads. Floor slabs on expansive soils should be expected to experience movement. Overexcavation and replacement has been successful in minimizing slab movements. The use of structural floors should be considered for basement construction on highly expansive clays. Final recommendations should be determined after additional investigation of each building site.

Potentially Seasonal Shallow and Seasonal Shallow Groundwater Area

Drainages are located along the western, northern and southeastern portions of the site. In these areas, the potential for periodically high subsurface moisture conditions and frost heave potential exists. In these areas, the potential exists for shallow groundwater during high moisture periods. The drainages will be avoided or regraded during site development, and the seasonal shallow groundwater area will be avoided by the proposed development.

Mitigation: Foundations must have a minimum 30-inch depth for frost protection. In areas where high subsurface moisture conditions are anticipated periodically, subsurface perimeter drains are recommended to help prevent the intrusion of water into areas below grade. It is anticipated much of these areas would be filled during site grading further raising foundations above the groundwater level. Any grading in these areas should be done to direct surface flow around construction to avoid areas of ponded water. All organic material would be completely removed prior to fill placement. Specific recommendations concerning the affects of groundwater on site

Tech Contractors
Soil, Geology and Geologic Hazard Evaluation
Meridian Ranch – Rolling Hills Ranch, Filing Nos. 1 – 4
SE of Sunrise Ridge Drive and Rex Road
El Paso County, Colorado

grading and construction are included in the Subsurface Soil Investigation (Reference 1). Further investigation will be necessary to determine the groundwater depth after final grading. The site does not lie within any floodplain zones according to the FEMA Map No. 08041CO552G, dated December 7, 2018 (Figure 7, Reference 6). Exact locations of floodplain and specific drainage studies are beyond the scope of this report. Finished floor levels must be located a minimum of one foot above floodplain levels.

RELEVANCE OF GEOLOGIC CONDITIONS TO LAND USE PLANNING

As mentioned, the proposed development will be single-family residential. The existing geologic and engineering geologic conditions will impose some constraints on development and construction. The geologic conditions on the site include artificial fill, expansive or loose soils, and potentially seasonal shallow groundwater areas which can be satisfactorily mitigated through proper engineering design and construction practices or regrading and avoidance.

The upper granular soils encountered in the borings drilled on the site were generally encountered at medium dense to very dense states. Loose or uncontrolled fill soils, if encountered in roads or beneath foundations, will require recompaction. Expansive layers may also be encountered in the soil on this site. Expansive soils, if encountered, will require special foundation design. These soils will not prohibit development.

An area of fill was mapped on the site in the northeastern portion that is associated with the road and pond embankment, and a large fill pile is located in the northern portion of the site. Other minor areas associated with small fill piles that are considered uncontrolled, and areas of fill may exist. It is anticipated the fill piles would be removed during site grading. Any uncontrolled fill encountered beneath foundations and floor slabs will require removal and recompaction at a minimum of 95% of its maximum Modified Proctor Dry Density, ASTM D-1557.

Areas of shallow bedrock will be encountered on this site. Shallow bedrock will likely be encountered in those areas mapped as Tda-Dawson Formation, or Soil Types 2 or 3 on Figure 2. Bedrock depths are indicated on Table 2 and in Figures 3 and 6. Difficult excavation should be anticipated in areas of shallow bedrock. Higher allowable bearing capacities will also be expected in areas of shallow bedrock.

Groundwater was encountered at 2 to 23 feet in the thirty-eight of the forty-nine test borings. Groundwater depths are indicated on Table 2. Areas of potentially seasonal shallow and seasonally shallow groundwater have been mapped on this site. (Figure 6). These areas can be avoided by construction or are being regraded. Specific recommendations concerning the effects of groundwater on site grading and construction are discussed in the Subsurface Soil Investigation (Reference 1). The site should not be affected by any delineated 100-year FEMA floodplains (Figure 7, Reference 6).

Tech Contractors
Soil, Geology and Geologic Hazard Evaluation
Meridian Ranch – Rolling Hills Ranch, Filing Nos. 1 – 4
SE of Sunrise Ridge Drive and Rex Road
El Paso County, Colorado

In summary, the site granular soils will likely provide suitable support for roads and shallow foundations. The geologic conditions encountered on site can be mitigated with proper engineering and construction practices. Specific recommendations have been made in the Subsurface Soil Investigation (Reference 1).

CLOSURE

It should be pointed out that because of the nature of data obtained by random sampling of such variable nonhomogeneous materials as soil and rock, it is important that we be informed of any differences observed between surface and subsurface conditions encountered in construction and those assumed in the body of this report. Construction and design personnel should be made familiar with the contents of this report. Specific site recommendations have been made in the Preliminary Subsurface Soil Investigation (Reference 1). Specific construction and foundation recommendations will be provided when investigations are completed for new construction after overlot grading.

This report has been prepared for Tech Contractors for application to the proposed development in accordance with generally accepted geologic, soil and engineering practices. No other warranty expresses or implied is made.

We trust that this report has provided you with all the information that you required. Should you have any questions or require additional information, please do not hesitate to contact us.

Respectfully Submitted,

ENTECH ENGINEERING, INC.



Logan L. Langford, P. G.
Engineering Geologist

LLL/hg

Encl.Entech Job No. 190300
AAprojects/2019/190300 sg&ghs

Reviewed by:



Joseph C. Good
President



Tech Contractors
Soil, Geology and Geologic Hazard Evaluation
Meridian Ranch – Rolling Hills Ranch, Filing Nos. 1 – 4
SE of Sunrise Ridge Drive and Rex Road
El Paso County, Colorado

BIBLIOGRAPHY

1. Entech Engineering, Inc., July 15, 2019. *Preliminary Subsurface Soil Investigation, Meridian Ranch – Rolling Hills Ranch, Filing Nos. 1 – 4, El Paso County, Colorado*. Entech Job No. 190300.
2. Natural Resources Conservation Service. September 23, 2016. *Web Soil Survey*. United States Department of Agriculture. <http://websoilsurvey.sc.egov.usda.gov>.
3. United States Department of Agriculture Soil Conservation Service. June, 1981. *Soil Survey of El Paso County Area, Colorado*.
4. Scott, Glenn R.; Taylor, Richard B.; Epis, Rudy C. and Wobus, Reinhard A. 1978. *Geologic Structure Map of the Pueblo 1° x 2° Quadrangle, South-Central Colorado*. Sheet 2. US Geological Survey. Map I-1022.
5. Morgan, Matthew L. and White, Jonathan L. 2012. *Falcon Quadrangle Geologic Map, El Paso County, Colorado*. Colorado Geological Survey. Open-File Report 12-05.
6. Federal Emergency Management Agency. December 7, 2018. *Flood Insurance Rate Maps for the City of Colorado Springs, Colorado*. Map Number 08041CO552G.

FIGURES

TABLE 1

SUMMARY OF LABORATORY TEST RESULTS

CLIENT TECH CONTRACTORS
 PROJECT ROLLING HILLS
 JOB NO. 190300

| SOIL TYPE | TEST BORING NO. | DEPTH (FT) | WATER (%) | DRY DENSITY (PCF) | PASSING NO. 200 SIEVE (%) | LIQUID LIMIT (%) | PLASTIC INDEX (%) | SULFATE (WT %) | AASHTO CLASS. | FHA SWELL (PSF) | SWELL/CONSOL (%) | UNIFIED CLASS. | SOIL DESCRIPTION |
|-----------|-----------------|------------|-----------|-------------------|---------------------------|------------------|-------------------|----------------|---------------|-----------------|------------------|----------------|---------------------------|
| 1 | 6 | 2-3 | | | 8.1 | NV | NP | <0.01 | A-1-b | | | SM-SW | SAND, SLIGHTLY SILTY |
| 1 | 8 | 5 | | | 6.1 | | | | | | | SM-SW | SAND, SLIGHTLY SILTY |
| 1 | 10 | 5 | | | 14.0 | 29 | 16 | 0.01 | A-2-6 | | | SC | SAND, CLAYEY |
| 1 | 11 | 2-3 | | | 15.2 | | | | | 370 | | SM | SAND, SILTY |
| 1 | 2 | 2-3 | | | 8.4 | | | | | | | SM-SW | SAND, SLIGHTLY SILTY |
| 1 | 23 | 2-3 | | | 17.0 | NV | NP | 0.00 | A-1-b | | | SM | SAND, SILTY |
| 1 | 24 | 2-3 | | | 18.0 | | | | | | | SM | SAND, SILTY |
| 1 | 32 | 10 | | | 15.6 | | | | | | | SM | SAND SILTY |
| 1 | 27 | 5 | | | 48.3 | | | | | 460 | | SC | SAND, VERY CLAYEY |
| 1 | 1 | 2-3 | | | 4.7 | NV | NP | | A-1-b | | | SW | SAND |
| 1 | 5 | 2-3 | | | 13.3 | 26 | 10 | | A-2-4 | | | SC | SAND, CLAYEY |
| 1 | 13 | 2-3 | | | 4.8 | | | | | | | SW | SAND |
| 1 | 14 | 5 | | | 13.2 | NV | NP | | A-1-b | | | SM | SAND, SILTY |
| 1 | 16 | 5 | | | 5.9 | | | | | 70 | | SM-SW | SAND, SLIGHTLY SILTY |
| 1 | 19 | 2-3 | 10.0 | 112.9 | 34.7 | | | | | | -1.2 | SM | SAND, SILTY |
| 1 | 26 | 5 | | | 11.5 | NV | NP | | A-1-b | | | SM-SW | SAND, SLIGHTLY SILTY |
| 1 | 28 | 2-3 | | | 4.9 | NV | NP | | A-1-b | | | SW | SAND |
| 1 | 30 | 2 | | | 12.1 | | | | | | | SC | SAND, CLAYEY |
| 1 | 30 | 3 | | | | | | | | 2970 | | CL | CLAY, SANDY |
| 1 | 30 | 5 | | | 6.9 | | | | | | | SM-SW | SAND, SLIGHTLY SILTY |
| 1 | 31 | 5 | | | 5.4 | | | | | | | SM-SW | SAND, SLIGHTLY SILTY |
| 1 | 38 | 2-3 | | | 8.6 | NV | NP | | A-1-b | | | SM-SW | SAND, SLIGHTLY SILTY |
| 1 | 39 | 5 | | | 17.8 | | | | | | | SM | SAND, SILTY |
| 1 | 42 | 5 | | | 19.6 | | | | | | | SM | SAND, SILTY |
| 1 | 43 | 2-3 | | | 6.0 | NV | NP | | A-1-b | | | SM-SW | SAND, SLIGHTLY SILTY |
| 1 | 47 | 2-3 | | | 20.7 | | | | | 220 | | SM | SAND, SILTY |
| 1 | 49 | 5 | | | 7.3 | | | | | | | SM-SW | SAND, SLIGHTLY SILTY |
| 2 | 7 | 10 | | | 18.6 | 32 | 14 | | A-2-6 | | | SC | SANDSTONE, CLAYEY |
| 2 | 17 | 10 | | | 7.3 | NV | NP | | A-1-b | | | SM-SW | SANDSTONE, SLIGHTLY SILTY |
| 2 | 18 | 5 | | | 14.2 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 20 | 5 | | | 17.1 | 37 | 20 | | A-2-6 | | | SC | SANDSTONE, CLAYEY |
| 2 | 21 | 10 | | | 12.5 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 41 | 10 | | | 16.0 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 44 | 10 | | | 14.3 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 6 | 20 | | | 38.9 | 26 | 13 | <0.01 | A-6 | | | SC | SANDSTONE, VERY CLAYEY |
| 2 | 9 | 15 | | | 17.5 | NV | NP | <0.01 | A-1-b | | | SM | SANDSTONE, SILTY |

TABLE 1 (cont.)

| SOIL TYPE | TEST BORING NO. | DEPTH (FT) | WATER (%) | DRY DENSITY (PCF) | PASSING NO. 200 SIEVE (%) | LIQUID LIMIT (%) | PLASTIC INDEX (%) | SULFATE (WT %) | AASHTO CLASS. | FHA SWELL (PSF) | SWELL/ CONSOL (%) | UNIFIED CLASS. | SOIL DESCRIPTION |
|-----------|-----------------|------------|-----------|-------------------|---------------------------|------------------|-------------------|----------------|---------------|-----------------|-------------------|----------------|---------------------------|
| 2 | 12 | 10 | | | 15.5 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 3 | 5 | | | 26.1 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 37 | 5 | 11.4 | 116.5 | 35.4 | | | 0.00 | | | -0.4 | SC | SANDSTONE, CLAYEY |
| 2 | 40 | 10 | | | 12.3 | NV | NP | <0.01 | A-1-b | | | SM | SANDSTONE, SILTY |
| 2 | 25 | 15 | | | 28.7 | NV | NP | | A-2-4 | | | SM | SANDSTONE, SILTY |
| 2 | 23 | 10 | | | 11.6 | | | | | | | SM-SW | SANDSTONE, SLIGHTLY SILTY |
| 2 | 35 | 5 | | | 10.1 | | | | | | | SM-SW | SANDSTONE, SLIGHTLY SILTY |
| 2 | 27 | 10 | | | 16.2 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 1 | 15 | | | 15.5 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 4 | 20 | 9.3 | 110.3 | 20.3 | 29 | 12 | | A-2-6 | | -1.9 | SC | SANDSTONE, CLAYEY |
| 2 | 5 | 25 | | | 48.5 | 31 | 14 | | A-6 | | | SC | SANDSTONE, VERY CLAYEY |
| 2 | 14 | 20 | | | 17.8 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 15 | 15 | | | 19.9 | | | | | | | SC | SANDSTONE, CLAYEY |
| 2 | 20 | 20 | 7.4 | 84.0 | 49.7 | 28 | 14 | | A-6 | | 3.2 | SC | SANDSTONE, VERY CLAYEY |
| 2 | 21 | 25 | | | 21.2 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 28 | 15 | | | 28.3 | 41 | 17 | | A-2-6 | | | SC | SANDSTONE, CLAYEY |
| 2 | 29 | 10 | 4.5 | 119.9 | 49.6 | | | | | | -0.4 | SC | SANDSTONE, VERY CLAYEY |
| 2 | 39 | 15 | | | 41.1 | | | | | | | SC | SANDSTONE, VERY CLAYEY |
| 2 | 45 | 20 | | | 13.4 | | | | | | | SM | SANDSTONE, SILTY |
| 2 | 46 | 15 | | | 45.5 | | | | | | | SC | SANDSTONE, VERY CLAYEY |
| 3 | 19 | 5 | | | 65.1 | | | | | | | CL | CLAYSTONE, SANDY |
| 3 | 15 | 10 | 7.2 | 126.8 | 56.1 | | | | | | 1.0 | CL | CLAYSTONE, VERY SANDY |
| 3 | 16 | 20 | 9.5 | 120.5 | 58.8 | | | | | | 0.0 | CL | CLAYSTONE, VERY SANDY |
| 3 | 22 | 10 | 12.7 | 99.3 | 54.2 | 34 | 15 | | A-6 | | | CL | CLAYSTONE, VERY SANDY |
| 3 | 38 | 15 | | | 59.6 | 34 | 17 | | A-6 | | | CL | CLAYSTONE, VERY SANDY |
| 3 | 48 | 20 | 12.5 | 103.3 | 51.1 | | | | | | -0.7 | CL | CLAYSTONE, VERY SANDY |
| 3 | 36 | 15 | | | 59.7 | | | | | | | CL | CLAYSTONE, VERY SANDY |
| 3 | 24 | 5 | | | 63.6 | | | | | 90 | | CL | CLAYSTONE, SANDY |
| 3 | 34 | 10 | 11.5 | 114.3 | 56.0 | | | | | | 0.7 | CL | CLAYSTONE, VERY SANDY |
| 3 | 33 | 10 | 16.5 | 115.0 | 80.8 | 42 | 20 | | A-7-6 | | 2.5 | CL | CLAYSTONE, SANDY |

Table 2: Summary of Test Borings and Water Measurements*

| Test Boring No. | Depth of Boring (ft.) | Depth to Bedrock (ft.) | Depth to Groundwater (ft.) | Cut & Fill** (-/+ , ft.) | Estimated Ground Elevation | Estimated Groundwater Elevation |
|----------------------------|----------------------------------|---------------------------------------|---|---|---|--|
| 1 | 20.0 | 9.0 | 9.0 | 0 to -2 | 7021.3 | 7012.3 |
| 2 | 25.0 | 9.0 | 13.0 | -2 to -4 | 7031.5 | 7018.5 |
| 3 | 25.0 | 1.0 | 15.0 | -2 to -4 | 7032.3 | 7017.3 |
| 4 | 20.0 | 1.0 | dry | -2 to -4 | 7044.0 | dry |
| 5 | 25.0 | 4.0 | 14.0 | -2 to -4 | 7044.8 | 7030.8 |
| 6 | 25.0 | 14.0 | 10.0 | 0 to +2 | 7054.7 | 7044.7 |
| 7 | 20.0 | 1.0 | 16.5 | +2 to +4 | 7058.6 | 7042.6 |
| 8 | 20.0 | 9.0 | 13.0 | 0 to -2 | 7060.1 | 7047.1 |
| 9 | 20.0 | 14.0 | 10.0 | +4 to +6 | 7069.7 | 7059.7 |
| 10 | 20.0 | 14.0 | 14.0 | 0 to -2 | 7077.5 | 7063.5 |
| 11 | 20.0 | 9.0 | 9.0 | 0 to +2 | 7071.6 | 7062.6 |
| 12 | 20.0 | 9.0 | 14.0 | 0 to -2 | 7087.3 | 7073.3 |
| 13 | 20.0 | 9.0 | 14.0 | 0 to -2 | 7092.0 | 7078.0 |
| 14 | 25.0 | 14.0 | 18.5 | -6 to -8 | 7105.3 | 7086.8 |
| 15 | 20.0 | 9.0 | 18.0 | 0 to -2 | 7108.4 | 7090.4 |
| 16 | 25.0 | 9.0 | 16.0 | 0 to -2 | 7110.9 | 7094.9 |
| 17 | 20.0 | 1.0 | 17.5 | 0 to -2 | 7121.7 | 7104.2 |
| 18 | 20.0 | 4.0 | dry | 0 to +2 | 7120.7 | dry |
| 19 | 20.0 | 4.0 | dry | +2 to +4 | 7126.5 | dry |
| 20 | 20.0 | 1.0 | dry | outside cut/fill | 7125.4 | dry |
| 21 | 25.0 | 1.0 | 10.0 | -6 to -8 | 7105.7 | 7095.7 |
| 22 | 20.0 | 4.0 | 18.5 | -6 to -8 | 7106.0 | 7087.5 |
| 23 | 20.0 | 9.0 | dry | +2 to +4 | 7092.3 | dry |
| 24 | 25.0 | 4.0 | 2.0 | 0 to +2 | 7072.9 | 7070.9 |


Table 2: (Continued)

| Test Boring No. | Depth of Boring (ft.) | Depth to Bedrock (ft.) | Depth to Groundwater (ft.) | Cut & Fill** (-/+ , ft.) | Est. Ground Elevation | Estimated Groundwater Elevation |
|----------------------------|----------------------------------|---------------------------------------|---|---|--------------------------------------|--|
| 25 | 20.0 | 1.0 | 12.0 | 0 to +2 | 7068.8 | 7056.8 |
| 26 | 20.0 | 1.0 | 17.0 | -6 to -8 | 7049.2 | 7032.2 |
| 27 | 20.0 | 9.0 | 8.0 | 0 to +2 | 7071.2 | 7063.2 |
| 28 | 20.0 | 9.0 | 13.5 | 0 to -2 | 7082.9 | 7069.4 |
| 29 | 25.0 | 4.0 | 12.0 | outside cut/fill | 7084.4 | 7072.4 |
| 30 | 20.0 | 10.0 | 8.0 | 0 to +2 | 7066.7 | 7058.7 |
| 31 | 20.0 | 14.0 | dry | 0 to -2 | 7057.5 | dry |
| 32 | 25.0 | 14.0 | 13.0 | 0 to -2 | 7045.4 | 7032.4 |
| 33 | 25.0 | 9.0 | 7.0 | 0 to -2 | 7052.7 | 7045.7 |
| 34 | 20.0 | 1.0 | 9.0 | +2 to +4 | 7042.0 | 7033.0 |
| 35 | 20.0 | 3.0 | dry | 0 to -2 | 7065.4 | dry |
| 36 | 25.0 | 1.0 | 23.0 | -6 to -8 | 7049.4 | 7026.4 |
| 37 | 20.0 | 1.0 | dry | -2 to -4 | 7038.8 | dry |
| 38 | 25.0 | 12.0 | 10.0 | -6 to -8 | 7032.4 | 7022.4 |
| 39 | 20.0 | 9.0 | 4.0 | -6 to -8 | 7032.5 | 7028.5 |
| 40 | 20.0 | 9.0 | 10.0 | +12 to +14 | 7032.1 | 7022.1 |
| 41 | 20.0 | 1.0 | 17.0 | outside cut/fill | 7039.1 | 7022.1 |
| 42 | 25.0 | 9.0 | 14.0 | outside cut/fill | 7046.0 | 7032.0 |
| 43 | 25.0 | 4.0 | 19.0 | outside cut/fill | 7049.0 | 7030.0 |
| 44 | 20.0 | 1.0 | dry | outside cut/fill | 7064.0 | dry |
| 45 | 25.0 | 4.0 | 11.0 | outside cut/fill | 7072.1 | 7061.1 |
| 46 | 25.0 | 4.0 | 22.0 | outside cut/fill | 7065.0 | 7043.0 |
| 47 | 20.0 | 1.0 | dry | outside cut/fill | 7058.7 | dry |
| 48 | 20.0 | 1.0 | dry | outside cut/fill | 7047.6 | dry |
| 49 | 25.0 | 14.0 | 12.0 | outside cut/fill | 7029.5 | 7017.5 |

* - Measurement taken subsequent to drilling

** - Cut and Fill estimates based on map provided by the client

TABLES



ENTECH
ENGINEERING, INC.
505 ELKTON DRIVE
COLORADO SPRINGS, CO. 80907 (719) 531-5599

VICINITY MAP
MERIDIAN RANCH - ROLLING HILLS RANCH
FILINGS 1 - 4
EL PASO COUNTY, CO.
FOR: TECH CONTRACTORS

DRAWN:
LLL


DATE:
9/18/19

CHECKED:

DATE:

JOB NO.:
190300

FIG NO.:
1



ENTECH
ENGINEERING, INC.
505 ELKTON DRIVE
COLORADO SPRINGS, CO. 80907 (719) 531-5599

USGS MAP
MERIDIAN RANCH - ROLLING HILLS RANCH
FILINGS 1 - 4
EL PASO COUNTY, CO.
FOR: TECH CONTRACTORS

DRAWN:
LLL


DATE:
9/18/19

CHECKED:

DATE:

JOB NO.:
190300

FIG NO.:
2




| | |
|-------------|----------|
| DATE | 9/16/19 |
| SCALE | AS SHOWN |
| DR NO | 1000300 |
| TRAILER NO. | 3 |
| CHECKED | |
| DESIGNED | |

SITE PLAN/PROPOSED GRADING
MERIDIAN RANCH - ROLLING HILLS RANCH
FILINGS 1 - 4
EL PASO COUNTY, CO.
FOR: TECH CONTRACTORS



ENTECH
ENGINEERING, INC.
505 ELKTON DRIVE
COLORADO SPRINGS, CO. 80907 (719) 531-5599

| | |
|-------------|--|
| REVISION BY | |
| | |
| | |
| | |
| | |
| | |



ENTECH
ENGINEERING, INC.
505 ELKTON DRIVE
COLORADO SPRINGS, CO. 80907 (719) 531-5599

SOIL SURVEY MAP
MERIDIAN RANCH - ROLLING HILLS RANCH
FILINGS 1 - 4
EL PASO COUNTY, CO.
FOR: TECH CONTRACTORS

DRAWN:
LLL


DATE:
9/18/19

CHECKED:

DATE:

JOB NO.:
190300

FIG NO.:
4



ENTECH
ENGINEERING, INC.
505 ELKTON DRIVE
COLORADO SPRINGS, CO. 80907 (719) 531-5599

FALCON QUADRANGLE GEOLOGIC MAP
MERIDIAN RANCH - ROLLING HILLS RANCH
FILINGS 1 - 4
EL PASO COUNTY, CO.
FOR: TECH CONTRACTORS

DRAWN:
LLL


DATE:
9/18/19

CHECKED:

DATE:

JOB NO.:
190300

FIG NO.:
5



LEGEND:

Qa-1 Artificial Fill of Holocene Age:
man-made fill deposits

Qa-1 Recent Alluvium of Holocene Age:
recent water deposited materials

Qa-2 Alluvium Two of early Holocene Age:
stream terrace deposited sands (Piney Creek Alluvium)

Qa-3 Alluvium Three of Pleistocene Age:
stream terrace deposited sands (Broadway Alluvium)

Tda Dawson Arkose of Tertiary Age:
arkosic sandstone with siltstone and claystone lenses

psw potential seasonal shallow groundwater area

sw seasonal shallow groundwater area

TB-1 Approximate Test Boring Location (Depth to Bedrock)



ENTECH
ENGINEERING, INC.
505 ELKTON DRIVE
COLORADO SPRINGS, CO. 80907 (719) 531-5599

FEMA FLOODPLAIN MAP
MERIDIAN RANCH - ROLLING HILLS RANCH
FILINGS 1 - 4
EL PASO COUNTY, CO.
FOR: TECH CONTRACTORS

DRAWN:
LLL

DATE:
9/18/19

CHECKED:

DATE:

JOB NO.:
190300

FIG NO.:
7

APPENDIX A: Test Boring Logs

TEST BORING NO. 1
 DATE DRILLED 6/19/2019
 Job # 190300

TEST BORING NO. 2
 DATE DRILLED 3/11/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 9', 6/19/19

3" TOP SOIL SAND, CLEAN TO SILTY, FINE TO COARSE GRAINED, TAN, MEDIUM DENSE, MOIST

SANDSTONE, SILTY, FINE TO COARSE GRAINED, TAN, VERY DENSE, MOIST TO WET

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 14 | 8.3 | 1 |
| 5 | | | 23 | 7.0 | 1 |
| 10 | | | 50 9" | 12.4 | 2 |
| 15 | | | 50 10" | 11.9 | 2 |
| 20 | | | 50 7" | 12.7 | 2 |

REMARKS

WATER @ 13', 3/11/19

SAND, GRAVELLY, SLIGHTLY SILTY, FINE TO COARSE GRAINED, BROWN, MEDIUM DENSE, MOIST

SANDSTONE, SILTY, FINE TO COARSE GRAINED, TAN TO GRAY BROWN, VERY DENSE, MOIST TO WET

CLAYSTONE, SANDY, GRAY BROWN, HARD, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 22 | 12.5 | 1 |
| 5 | | | 28 | 9.3 | 1 |
| 10 | | | 50 10" | 7.8 | 2 |
| 15 | | | 50 9" | 14.6 | 2 |
| 20 | | | 50 9" | 11.9 | 3 |
| 25 | | | 50 6" | 12.4 | 3 |



**ENTECH
 ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE

CHECKED: *a*

DATE

3/11/19

JOB NO:
 190300

FIG NO:
 A- 1

TEST BORING NO. 3
 DATE DRILLED 3/11/2019
 Job # 190300

TEST BORING NO. 4
 DATE DRILLED 6/7/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 15', 3/11/19

SAND, SILTY, TAN
 SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, TAN, VERY
 DENSE, MOIST

SANDSTONE, CLAYEY, FINE TO
 MEDIUM GRAINED, GRAY
 BROWN, VERY DENSE, MOIST
 TO WET



| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 1 | 1.1 | | | | 1 |
| 2 | | | 50 11" | 4.4 | 2 |
| 3 | | | 50 8" | 7.3 | 2 |
| 4 | | | | | |
| 5 | | | | | |
| 6 | | | | | |
| 7 | | | | | |
| 8 | | | | | |
| 9 | | | | | |
| 10 | | | 50 4" | 11.4 | 2 |
| 11 | | | | | |
| 12 | | | | | |
| 13 | | | | | |
| 14 | | | | | |
| 15 | | | 50 6" | 11.6 | 2 |
| 16 | | | | | |
| 17 | | | | | |
| 18 | | | | | |
| 19 | | | | | |
| 20 | | | 50 8" | 30.4 | 2 |
| 21 | | | | | |
| 22 | | | | | |
| 23 | | | | | |
| 24 | | | | | |
| 25 | | | 50 3" | 24.1 | 2 |

REMARKS

DRY TO 20', 6/7/19

6" TOP SOIL, SAND, SILTY, TAN
 SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, TAN, VERY
 DENSE, MOIST

FINE GRAINED LENSES

CLAYSTONE, SANDY, TAN,
 HARD, MOIST

SANDSTONE, CLAYEY, FINE
 TO COARSE GRAINED, TAN,
 VERY DENSE, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 1 | 1.1 | | | | 1 |
| 2 | | | 50 7" | 7.8 | 2 |
| 3 | | | 50 7" | 5.7 | 2 |
| 4 | | | | | |
| 5 | | | | | |
| 6 | | | | | |
| 7 | | | | | |
| 8 | | | | | |
| 9 | | | | | |
| 10 | | | 50 6" | 8.7 | 2 |
| 11 | | | | | |
| 12 | | | | | |
| 13 | | | | | |
| 14 | | | | | |
| 15 | | | 50 9" | 17.0 | 3 |
| 16 | | | | | |
| 17 | | | | | |
| 18 | | | | | |
| 19 | | | | | |
| 20 | | | 50 5" | 8.4 | 2 |



**ENTECH
 ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *h*

DATE: 7/1/19

JOB NO.:
 190300

FIG NO.:
 A- 2

TEST BORING NO. 5
 DATE DRILLED 5/29/2019
 Job # 190300

TEST BORING NO. 6
 DATE DRILLED 3/7/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 14', 5/29/19

3" TOP SOIL SAND, CLAYEY,
 FINE TO COARSE GRAINED,
 TAN, MEDIUM DENSE, MOIST

SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, TAN,
 DENSE TO MEDIUM DENSE,
 MOIST

CLAYSTONE, SANDY, GRAY
 BROWN, HARD, MOIST

SANDSTONE, VERY CLAYEY,
 FINE GRAINED, GRAY BROWN,
 VERY DENSE, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| | | | 14 | 9.6 | 1 |
| 5 | | | 40 | 5.4 | 2 |
| 10 | | | 50 6" | 9.3 | 2 |
| 15 | | | 50 5" | 6.5 | 2 |
| 20 | | | 50 4" | 13.8 | 3 |
| 25 | | | 50 7" | 14.6 | 2 |

REMARKS

WATER @ 10', 3/7/19

6" TOP SOIL, SAND, SLIGHTLY
 SILTY, FINE TO COARSE GRAINED
 BROWN TO TAN, MEDIUM DENSE
 TO LOOSE, MOIST TO WET

WEATHERED TO FORMATIONAL
 SANDSTONE, CLAYEY TO VERY
 CLAYEY, FINE TO COARSE
 GRAINED, GRAY BROWN, DENSE
 TO VERY DENSE, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| | | | 28 | 2.4 | 1 |
| 5 | | | 21 | 4.2 | 1 |
| 10 | | | 9 | 15.7 | 1 |
| 15 | | | 48 | 13.3 | 2 |
| 20 | | | 50 10" | 11.7 | 2 |
| 25 | | | 45 | 15.4 | 2 |



**ENTECH
 ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *L*

DATE: 7/1/19

JOB NO.:
 190300

FIG NO
 A- 3

TEST BORING NO. 7
 DATE DRILLED 5/29/2019
 Job # 190300

TEST BORING NO. 8
 DATE DRILLED 3/7/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 16.5', 5/29/19

6" TOPSOIL, SAND, SILTY, TAN
 WEATHERED SANDSTONE,
 SILTY, FINE TO COARSE
 GRAINED, DENSE, MOIST

SANDSTONE, CLAYEY TO
 SILTY, FINE TO COARSE
 GRAINED, TAN, VERY DENSE,
 MOIST TO WET

FINE GRAINED LENSES

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 4.5 | | | | | |
| 4.5 | | | 46 | 4.8 | 1 |
| 5 | | | 45 | 9.0 | 2 |
| 10 | | | 50 6" | 8.1 | 2 |
| 15 | | | 50 3" | 10.7 | 2 |
| 20 | | | 50 6" | 11.1 | 2 |

REMARKS

WATER @ 13', 3/7/19

6" TOPSOIL, SAND, SLIGHTLY
 SILTY, FINE TO COARSE GRAINED,
 BROWN, MEDIUM DENSE, MOIST

SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, TAN, VERY
 DENSE, MOIST TO WET

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 4.5 | | | | | |
| 4.5 | | | 23 | 4.1 | 1 |
| 5 | | | 11 | 6.0 | 1 |
| 10 | | | 50 9" | 8.5 | 2 |
| 15 | | | 50 7" | 17.8 | 2 |
| 20 | | | 50 6" | 16.6 | 2 |



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE

CHECKED *L*

DATE 7/1/19

JOB NO.
 190300

FIG NO.
 A- 4

TEST BORING NO. 9
 DATE DRILLED 3/7/2019
 Job # 190300

TEST BORING NO. 10
 DATE DRILLED 3/7/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

| REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type | REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|--|------------|--------|---------|----------------|----------------|-----------|---|------------|--------|---------|----------------|----------------|-----------|
| WATER @ 10', 3/7/19 | | | | | | | WATER @ 14', 3/7/19 | | | | | | |
| 6" TOPSOIL, SAND, SILTY, FINE TO COARSE GRAINED, BROWN, MEDIUM DENSE, DRY TO MOIST | 5 | * | | 16 | 2.7 | 1 | 6" TOPSOIL, SAND, SILTY TO CLAYEY, FINE TO COARSE GRAINED, TAN, MEDIUM DENSE, MOIST | 5 | * | | 26 | 6.2 | 1 |
| | 11 | | | 11 | 6.6 | 1 | | 19 | | | 7.8 | 1 | |
| SAND, CLAYEY, FINE TO COARSE GRAINED, GRAY BROWN, LOOSE, WET | 10 | | | 5 | 18.0 | 1 | | 27 | | | 12.4 | 1 | |
| | 15 | | | 50 | 8.7 | 2 | SANDSTONE, CLAYEY, FINE TO COARSE GRAINED, BROWN, VERY DENSE TO DENSE, WET | 15 | | | 50 | 12.5 | 2 |
| | 20 | | | 50 | 10.9 | 2 | WEATHERED ZONE | 20 | | | 45 | 13.8 | 2 |
| | | | | 6" | | | | | | | | | |



**ENTECH
ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *h*

DATE: 7/1/19

JOB NO
190300

FIG NO
A- 5

TEST BORING NO. 11
 DATE DRILLED 3/7/2019
 Job # 190300

TEST BORING NO. 12
 DATE DRILLED 3/7/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

| REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type | REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|---|------------|--------|---------|----------------|----------------|-----------|---|------------|--------|---------|----------------|----------------|-----------|
| WATER @ 9', 3/7/19 | | | | | | | WATER @ 14', 3/7/19 | | | | | | |
| SAND, SILTY, FINE TO COARSE GRAINED, TAN, LOOSE TO MEDIUM DENSE, VERY MOIST | 5 | | | 7 | 21.3 | 1 | 6" TOP SOIL, SAND, SILTY, FINE TO COARSE GRAINED, BROWN, LOOSE TO MEDIUM DENSE, MOIST | 5 | | | 6 | 3.6 | 1 |
| | 5 | | | 16 | 15.1 | 1 | | 5 | | | 23 | 8.6 | 1 |
| SANDSTONE, SILTY, FINE TO COARSE GRAINED, TAN, VERY DENSE, WET | 10 | | | 50 11" | 17.5 | 2 | WEATHERED TO FORMATIONAL SANDSTONE, SILTY, FINE TO COARSE GRAINED, BROWN, DENSE TO VERY DENSE, MOIST TO WET | 10 | | | 36 | 11.3 | 2 |
| | 15 | | | 50 8" | 12.6 | 2 | CLAYEY LENSES | 15 | | | 50 11" | 20.2 | 2 |
| | 20 | | | 50 7" | 12.7 | 2 | | 20 | | | 50 7" | 12.8 | 2 |



**ENTECH
 ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED:

DATE
 7/1/19

JOB NO.:
 190300

FIG NO.:
 A- 6

TEST BORING NO. 13
 DATE DRILLED 5/29/2019
 Job # 190300

TEST BORING NO. 14
 DATE DRILLED 5/29/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 14', 5/29/19

6" TOP SOIL, SAND, CLEAN TO SILTY, FINE TO COARSE GRAINED, TAN, LOOSE TO MEDIUM DENSE, MOIST

WEATHERED TO FORMATIONAL SANDSTONE, SILTY, FINE TO COARSE GRAINED, TAN, DENSE TO VERY DENSE, MOIST TO WET



| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 11 | 1.4 | 1 |
| | | | 14 | 6.3 | 1 |
| 10 | | | 45 | 8.4 | 2 |
| 15 | | | 48 | 8.9 | 2 |
| 20 | | | 50 | 11.5 | 2 |
| | | | 5" | | |

REMARKS

WATER @ 18.5', 5/29/19

6" TOP SOIL, SAND, SILTY, FINE TO COARSE GRAINED, TAN, LOOSE TO MEDIUM DENSE, DRY TO MOIST

FINE GRAINED LENSES

SANDSTONE, SILTY, FINE TO COARSE GRAINED, TAN, VERY DENSE, MOIST TO WET



| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 13 | 1.8 | 1 |
| | | | 7 | 2.3 | 1 |
| 10 | | | 24 | 9.1 | 1 |
| 15 | | | 50 | 6.7 | 2 |
| | | | 11" | | |
| 20 | | | 50 | 10.6 | 2 |
| | | | 11" | | |
| 25 | | | 50 | 12.6 | 2 |
| | | | 9" | | |



**ENTECH
ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *h*

DATE: 7/1/19

JOB NO:
190300

FIG NO:
A- 7

TEST BORING NO. 15
 DATE DRILLED 5/29/2019
 Job # 190300

TEST BORING NO. 16
 DATE DRILLED 5/29/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 18', 5/29/19

6" TOPSOIL SAND, SILTY, TAN
 WEATHERED SANDSTONE,
 SILTY, FINE TO COARSE
 GRAINED, TAN, DENSE,
 MOIST

CLAYSTONE, VERY SANDY,
 GRAY BROWN, HARD, MOIST

SANDSTONE, CLAYEY, FINE
 TO COARSE GRAINED, TAN,
 VERY DENSE, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 0 | | | | | 1 |
| 1 | | | 43 | 3.2 | 2 |
| 2 | | | 34 | 9.9 | 2 |
| 3 | | | | | |
| 4 | | | | | |
| 5 | | | | | |
| 6 | | | | | |
| 7 | | | | | |
| 8 | | | | | |
| 9 | | | | | |
| 10 | | | 50 | 11.4 | 3 |
| 11 | | | 7" | | |
| 12 | | | | | |
| 13 | | | | | |
| 14 | | | | | |
| 15 | | | 50 | 11.0 | 2 |
| 16 | | | 4" | | |
| 17 | | | | | |
| 18 | | | | | |
| 19 | | | | | |
| 20 | | | 50 | 14.2 | 2 |
| 21 | | | 11" | | |



REMARKS

WATER @ 16', 5/29/19

6" TOPSOIL, SAND, SLIGHTLY
 SILTY, FINE TO COARSE
 GRASINED, TAN, MEDIUM
 DENSE, DRY

SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, TAN, VERY
 DENSE, MOIST

CLAYSTONE, VERY SANDY,
 BROWN, HARD, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 0 | | | | | |
| 1 | | | | | |
| 2 | | | 11 | 1.2 | 1 |
| 3 | | | | | |
| 4 | | | 21 | 1.8 | 1 |
| 5 | | | | | |
| 6 | | | | | |
| 7 | | | | | |
| 8 | | | | | |
| 9 | | | | | |
| 10 | | | 50 | 7.0 | 2 |
| 11 | | | 9" | | |
| 12 | | | | | |
| 13 | | | | | |
| 14 | | | | | |
| 15 | | | 50 | 8.3 | 2 |
| 16 | | | 6" | | |
| 17 | | | | | |
| 18 | | | | | |
| 19 | | | | | |
| 20 | | | 50 | 15.0 | 3 |
| 21 | | | | | |
| 22 | | | | | |
| 23 | | | | | |
| 24 | | | | | |
| 25 | | | B | 8.9 | 3 |



B - BOUNCE



**ENTECH
 ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED:

DATE: 7/1/19

JOB NO.:
 190300

FIG NO.:
 A- 8

TEST BORING NO. 17
 DATE DRILLED 5/29/2019
 Job # 190300

TEST BORING NO. 18
 DATE DRILLED 6/7/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 17.5', 5/29/19
 6" TOPSOIL, SAND, SILTY, TAN
 SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, TAN,
 VERY DENSE, DRY TO MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 0 | 4" | | | | 1 |
| 1 | | | 50 | 1.7 | 2 |
| 2 | | | 10" | | |
| 3 | | | 50 | 1.8 | 2 |
| 4 | | | 8" | | |
| 5 | | | | | |
| 6 | | | | | |
| 7 | | | | | |
| 8 | | | | | |
| 9 | | | | | |
| 10 | | | 50 | 6.9 | 2 |
| 11 | | | 6" | | |
| 12 | | | | | |
| 13 | | | | | |
| 14 | | | | | |
| 15 | | | 50 | 8.0 | 2 |
| 16 | | | 7" | | |
| 17 | | | | | |
| 18 | | | | | |
| 19 | | | | | |
| 20 | | | 50 | 10.1 | 2 |
| 21 | | | 6" | | |



REMARKS

DRY TO 20', 6/7/19
 6" TOPSOIL, SAND, SILTY,
 FINE TO COARSE GRAINED,
 BROWN, MEDIUM DENSE, DRY
 WEATHERED TO FORMATIONAL
 SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, TAN,
 DENSE TO VERY DENSE, MOIST
 FINE GRAINED LENSES

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 0 | 4" | | | | |
| 1 | | | | | |
| 2 | | | 12 | 2.7 | 1 |
| 3 | | | | | |
| 4 | | | | | |
| 5 | | | 42 | 5.0 | 2 |
| 6 | | | | | |
| 7 | | | | | |
| 8 | | | | | |
| 9 | | | | | |
| 10 | | | 50 | 8.9 | 2 |
| 11 | | | 6" | | |
| 12 | | | | | |
| 13 | | | | | |
| 14 | | | | | |
| 15 | | | 50 | 4.9 | 2 |
| 16 | | | 7" | | |
| 17 | | | | | |
| 18 | | | | | |
| 19 | | | | | |
| 20 | | | 50 | 7.0 | 2 |
| 21 | | | 6" | | |



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *h*

DATE: 7/1/19

JOB NO.:
 190300

FIG NO.:
 A- 9

TEST BORING NO. 19
 DATE DRILLED 6/7/2019
 Job # 190300

TEST BORING NO. 20
 DATE DRILLED 5/30/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

| REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type | REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|---|------------|--------|---------|----------------|----------------|-----------|---|------------|--------|---------|----------------|----------------|-----------|
| DRY TO 20', 6/7/19 | | | | | | | DRY TO 20', 5/30/19 CAVED TO 19', 6/6/19, DRY | | | | | | |
| 6" TOP SOIL, SAND, SILTY, FINE TO COARSE GRAINED, GRAY BROWN, MEDIUM DENSE, MOIST | | | | 21 | 7.8 | 1 | 6" TOP SOIL, SAND, SILTY, TAN SANDSTONE, SILTY TO CLAYEY, FINE TO COARSE GRAINED, TAN, VERY DENSE, DRY TO MOIST | | | | 50 | 4.8 | 2 |
| CLAYSTONE, SANDY, GRAY BROWN, HARD, MOIST | 5 | | | 50 9" | 10.9 | 3 | | 5 | | | 50 9" | 8.6 | 2 |
| SANDSTONE, SILTY, FINE TO COARSE GRAINED, TAN, VERY DENSE, MOIST | 10 | | | 50 8" | 7.8 | 2 | | 10 | | | 50 9" | 6.5 | 2 |
| | 15 | | | 50 8" | 5.7 | 2 | CLAYSTONE, SANDY, GRAY BROWN, HARD, MOIST | 15 | | | 50 7" | 10.4 | 3 |
| | 20 | | | 50 6" | 8.9 | 2 | SANDSTONE, VERY CLAYEY, FINE TO COARSE GRAINED, BROWN, VERY DENSE, MOIST | 20 | | | 50 2" | 8.0 | 2 |



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *W*

DATE: 7/1/19

JOB NO.
 190300

FIG NO.
 A- 10

TEST BORING NO. 21
 DATE DRILLED 5/30/2019
 Job # 190300

TEST BORING NO. 22
 DATE DRILLED 4/25/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

| REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type | REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|---|------------|--------|---------|----------------|----------------|-----------|---|------------|--------|-----------|----------------|----------------|-----------|
| WATER @ 18', 5/30/19 | | | | | | | WATER @ 18.5', 6/6/19 | | | | | | |
| WATER @ 10', 6/6/19 | | | | | | | | | | | | | |
| 6" TOPSOIL, SAND, SILTY, TAN WEATHERED SANDSTONE, SILTY, FINE TO COARSE GRAINED, TAN, DENSE, MOIST | 0 | 1-1 | | 40 | 3.0 | 1 | 6" TOPSOIL, SAND, SILTY, FINE TO COARSE GRAINED, TAN, MEDIUM DENSE, MOIST | 0 | 1-1 | | 25 | 7.2 | 1 |
| | 5 | | | 42 | 6.2 | 2 | SANDSTONE, SILTY, FINE TO COARSE GRAINED, TAN, VERY DENSE, MOIST | 5 | | 50 10" | 6.3 | 2 | 2 |
| 6/6/19 SANDSTONE, SILTY, FINE TO COARSE GRAINED, BROWN, VERY DENSE, MOIST | 10 | | | 50 10" | 6.5 | 2 | CLAYSTONE, VERY SANDY, TAN, HARD, MOIST | 10 | | 50 8" | 12.1 | 3 | 3 |
| CLAYSTONE, SANDY, GRAY BROWN, HARD, MOIST | 15 | | | 50 | 13.1 | 3 | SANDSTONE, SILTY, FINE TO COARSE GRAINED, BROWN, VERY DENSE, MOIST | 15 | | 50 6" | 3.4 | 2 | 2 |
| 5/30/19 SANDSTONE LENSE | 20 | | | 50 | 12.3 | 3 | | 20 | | 50 6" | 9.7 | 2 | 2 |
| SANDSTONE, SILTY, FINE TO COARSE GRAINED, GRAY BROWN, VERY DENSE, MOIST | 25 | | | 50 6" | 8.8 | 2 | | | | | | | |



**ENTECH
ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE

CHECKED: *h*

DATE 7/1/19

JOB NO:
190300

FIG NO:
A- 11

TEST BORING NO. 23
 DATE DRILLED 3/12/2019
 Job # 190300

TEST BORING NO. 24
 DATE DRILLED 3/12/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

DRY TO 20', 3/12/19
 6" TOPSOIL, SAND, SILTY, FINE
 TO COARSE GRAINED, TAN,
 LOOSE, MOIST

SANDSTONE, SLIGHTLY SILTY,
 FINE TO COARSE GRAINED,
 BROWN, VERY DENSE, MOIST
 CLAYSTONE, SANDY, BLUE
 GRAY, HARD, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 0 | | | | | |
| 4 | | | 4 | 3.3 | 1 |
| 5 | | | 7 | 4.5 | 1 |
| 10 | | | 50 10" | 12.1 | 2 |
| 15 | | | 50 8" | 12.5 | 3 |
| 20 | | | 50 11" | 13.3 | 3 |

REMARKS

WATER @ 9', 3/12/19
 WATER @ 2', 6/6/19

6" TOPSOIL, SAND, SILTY, FINE
 TO COARSE GRAINED, TAN,
 DENSE, MOIST 6/6/19
 CLAYSTONE, SANDY, TAN,
 HARD, MOIST
 3/12/19
 SANDSTONE, CLAYEY, FINE
 TO COARSE GRAINED, BROWN,
 VERY DENSE, WET

CLAYSTONE, SANDY, BLUE
 GRAY, HARD, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 0 | | | | | |
| 4 | | | 45 | 11.4 | 1 |
| 5 | | | 50 7" | 16.8 | 3 |
| 10 | | | 50 11" | 21.0 | 2 |
| 15 | | | 50 7" | 8.3 | 2 |
| 20 | | | 50 9" | 10.4 | 2 |
| 25 | | | 50 5" | 16.1 | 3 |



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN

DATE:

CHECKED: *h*

DATE: 7-12-19

JOB NO.:
 190300

FIG NO.:
 A- 12

TEST BORING NO. 25
 DATE DRILLED 3/12/2019
 Job # 190300

TEST BORING NO. 26
 DATE DRILLED 6/7/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 12', 7/9/19

SAND, SILTY, TAN
 SANDSTONE, CLAYEY TO SILTY,
 FINE TO COARSE GRAINED, TAN
 TO GRAY BROWN, VERY DENSE,
 MOIST TO WET

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 1 | 1-1 | | | | 1 |
| 2 | | | 50 3" | 9.4 | 2 |
| 5 | | | 50 9" | 8.6 | 2 |
| 10 | | | 50 7" | 6.6 | 2 |
| 15 | | | 50 11" | 17.0 | 2 |
| 20 | | | 50 5" | 14.6 | 2 |



REMARKS

WATER @ 11', 7/9/19

6" TOP SOIL, SAND, SILTY, TAN
 SANDSTONE, SLIGHTLY
 SILTY TO SILTY, FINE TO
 COARSE GRAINED, BROWN
 TO TAN, VERY DENSE, MOIST
 TO WET

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 1 | 1-1 | | | | 1 |
| 2 | | | 50 7" | 5.5 | 2 |
| 5 | | | 50 6" | 4.2 | 2 |
| 10 | | | 50 7" | 6.4 | 2 |
| 15 | | | 50 6" | 10.3 | 2 |
| 20 | | | 50 5" | 11.5 | 2 |



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *h*

DATE:

7.12.19

JOB NO.:
 190300

FIG NO
 A- 13

TEST BORING NO. 27
 DATE DRILLED 3/12/2019
 Job # 190300

TEST BORING NO. 28
 DATE DRILLED 4/25/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

| REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type | REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|--|------------|--------|---------|----------------|----------------|-----------|---|------------|--------|---------|----------------|----------------|-----------|
| WATER @ 18', 3/12/19 WATER @ 8', 6/6/19 | | | | | | | WATER @ 13.5', 4/25/19 | | | | | | |
| 6" TOPSOIL SAND, SILTY, FINE TO COARSE GRAINED, BROWN, MEDIUM DENSE, DRY | | | | 22 | 2.7 | 1 | 6" TOPSOIL, SAND, SILTY TO CLEAN, FINE TO COARSE GRAINED, TAN, MEDIUM DENSE, DRY TO MOIST | | | | 18 | 2.4 | 1 |
| SAND, VERY CLAYEY, FINE TO COARSE GRAINED, BROWN, MEDIUM DENSE, MOIST | 5 | | | 23 | 13.6 | 1 | | 5 | | | 26 | 5.2 | 1 |
| 6/6/2019 | | | | | | | | | | | | | |
| SANDSTONE, SILTY, FINE TO COARSE GRAINED, BROWN, VERY DENSE, MOIST | 10 | | | 50 8" | 8.7 | 2 | SANDSTONE, SILTY TO CLAYEY, FINE TO COARSE GRAINED, BROWN, VERY DENSE, MOIST TO WET | 10 | | | 50 11" | 7.7 | 2 |
| | | | | | | | | | | | | | |
| 3/12/2019 | | | | | | | | | | | | | |
| CLAYSTONE, SANDY, BROWN, HARD, MOIST | 15 | | | 50 7" | 9.6 | 2 | | 15 | | | 50 6" | 17.1 | 2 |
| | | | | | | | | | | | | | |
| | 20 | | | 50 6" | 15.9 | 3 | | 20 | | | 50 5" | 8.1 | 2 |



**ENTECH
ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *h*

DATE: 7.12.19

JOB NO.:
190300

FIG NO.:
A- 14

TEST BORING NO. 29
 DATE DRILLED 5/30/2019
 Job # 190300

TEST BORING NO. 30
 DATE DRILLED 4/25/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

| REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type | REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|---|------------|--------|---------|----------------|----------------|-----------|--|------------|--------|---------|----------------|----------------|-----------|
| WATER @ 19', 5/30/19 WATER @ 12', 6/11/19 | | | | | | | WATER @ 8', 4/25/19 | | | | | | |
| 6" TOPSOIL, SAND, SILTY, FINE TO COARSE GRAINED, TAN, MEDIUM DENSE, MOIST | | | | 20 | 6.6 | 1 | 6" TOPSOIL, SAND, SILTY TO SLIGHTLY SILTY WITH CLAY LENSES, FINE TO COARSE GRAINED, TAN, MEDIUM DENSE TO DENSE, DRY TO MOIST | | | 10 | 1.7 | 1 | |
| SANDSTONE, SILTY, FINE TO COARSE GRAINED, BROWN, VERY DENSE, MOIST | 5 | | | 50 11" | 8.5 | 2 | | 5 | | 30 | 4.4 | 1 | |
| SANDSTONE, CLAYEY TO VERY CLAYEY, FINE TO COARSE GRAINED, GRAY BROWN, VERY DENSE, MOIST | 10 | | | 50 6" | 11.2 | 2 | | 10 | | 39 | 9.5 | 1 | |
| 6/6/19 | 15 | | | 50 6" | 7.7 | 2 | | 15 | | 50 | 12.8 | 2 | |
| 5/30/2019 | 20 | | | 50 6" | 9.0 | 2 | B - BOUNCE | 20 | | B | | | 2 |
| FINE GRAINED LENSES | 25 | | | 50 6" | 15.4 | 2 | | | | | | | |



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *[Signature]*

DATE:

7.12.19

JOB NO.
 190300

FIG NO.
 A- 15

TEST BORING NO. 31
 DATE DRILLED 5/29/2019
 Job # 190300

TEST BORING NO. 32
 DATE DRILLED 3/12/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

| REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type | REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|---|------------|--------|---------|----------------|----------------|-----------|--|------------|--------|---------|----------------|----------------|-----------|
| DRY TO 20', 5/29/19 | | | | | | | WATER @ 13', 3/12/19 | | | | | | |
| 6" TOP SOIL, SAND, SLIGHTLY SILTY, FINE TO COARSE GRAINED, TAN, DENSE, DRY TO MOIST | | * | | | | | 6" TOP SOIL, SAND, SILTY, FINE TO COARSE GRAINED, BROWN, LOOSE TO MEDIUM DENSE, DRY TO MOIST | | * | | | | |
| | 5 | | | 32 | 2.0 | 1 | | 5 | | 5 | 1.4 | 1 | |
| | | | | 30 | 3.0 | 1 | | | | 6 | 1.3 | 1 | |
| | 10 | | | 34 | 9.8 | 1 | | 10 | | 11 | 10.7 | 1 | |
| CLAYSTONE, SANDY, BLUE GRAY, HARD, MOIST | 15 | | | 50 | 14.8 | 3 | SANDSTONE, CLAYEY, FINE TO COARSE GRAINED, GRAY BROWN, VERY DENSE, MOIST | 15 | | 50 | 11.8 | 2 | |
| | | | | 11" | | | | | | 10" | | | |
| | 20 | | | 50 | 14.7 | 3 | | 20 | | 50 | 11.0 | 2 | |
| | | | | 7" | | | | | | 7" | | | |
| | | | | | | | CLAYSTONE, SANDY, BLUE GRAY, HARD, MOIST | 25 | | 50 | 14.8 | 3 | |
| | | | | | | | | | | 8" | | | |



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *h*

DATE: 7/12/19

JOB NO.:
 190300

FIG NO.:
 A- 16

TEST BORING NO. 33
 DATE DRILLED 3/12/2019
 Job # 190300

TEST BORING NO. 34
 DATE DRILLED 3/12/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 17', 3/12/19
 WATER @ 7', 6/6/19

6" TOPSOIL, SAND, SILTY, FINE
 TO COARSE GRAINED, BROWN,
 MEDIUM DENSE, DRY TO MOIST

6/6/2019

WEATHERED TO FORMATIONAL
 CLAYSTONE, SANDY, GRAY
 BROWN, VERY STIFF TO HARD,
 MOIST

3/12/2019

SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, BROWN,
 VERY DENSE, VERY MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 13 | 2.4 | 1 |
| | | | 15 | 4.1 | 1 |
| 10 | | | 45 | 17.4 | 3 |
| 15 | | | 50 9" | 13.1 | 3 |
| 20 | | | 50 8" | 18.0 | 3 |
| 25 | | | 50 5" | 14.3 | 2 |

REMARKS

WATER @ 9', 3/12/19

6" TOPSOIL, SAND, SILTY, BROWN
 SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, BROWN,
 VERY DENSE, MOIST

CLAYSTONE, VERY SANDY,
 GRAY BROWN, HARD, MOIST

SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, GRAY
 BROWN, VERY DENSE, MOIST

CLAYSTONE, SANDY, BLUE GRAY,
 HARD, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 50 7" | 6.1 | 2 |
| | | | 50 10" | 8.2 | 2 |
| 10 | | | 50 9" | 12.8 | 3 |
| 15 | | | 50 5" | 9.7 | 2 |
| 20 | | | 50 5" | 15.9 | 3 |



**ENTECH
 ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *[Signature]*

DATE:

7/12/19

JOB NO.:
 190300

FIG NO.:
 A- 17

TEST BORING NO. 35
 DATE DRILLED 3/12/2019
 Job # 190300

TEST BORING NO. 36
 DATE DRILLED 3/11/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

DRY TO 20', 3/12/19

6" TOPSOIL SAND, SILTY, FINE
 TO COARSE GRAINED, TAN,
 DENSE, MOIST
 SANDSTONE, SLIGHTLY SILTY
 TO SILTY, FINE TO COARSE
 GRAINED, BROWN, VERY DENSE,
 MOIST

CLAYSTONE, SANDY, BLUE GRAY,
 HARD, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 48 | 3.6 | 1 |
| 5 | | | 50 | 6.0 | 2 |
| 10 | | | 50 9" | 8.9 | 2 |
| 15 | | | 50 | 9.7 | 2 |
| 20 | | | 50 6" | 11.7 | 3 |

REMARKS

WATER @ 13.5', 7/9/19

SAND, SILTY, TAN
 SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, TAN, VERY
 DENSE, MOIST

CLAYSTONE, VERY SANDY, BLUE
 GRAY, HARD, MOIST

SANDSTONE, CLAYEY, FINE TO
 COARSE GRAINED, GRAY BROWN
 TO BROWN, VERY DENSE,
 MOIST TO WET

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 1 | | | 50 7" | 3.1 | 2 |
| 5 | | | 50 6" | 3.7 | 2 |
| 10 | | | 50 6" | 10.9 | 2 |
| 15 | | | 50 6" | 12.2 | 3 |
| 20 | | | 50 10" | 13.4 | 2 |
| 25 | | | 50 7" | 16.8 | 2 |



**ENTECH
 ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE

CHECKED:

DATE 7/12/19

JOB NO
 190300

FIG NO
 A- 18

TEST BORING NO. 37
 DATE DRILLED 3/12/2019
 Job # 190300

TEST BORING NO. 38
 DATE DRILLED 6/7/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

| REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type | REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|----------------------------|------------|--------|---------|----------------|----------------|-----------|------------------------------|------------|--------|---------|----------------|----------------|-----------|
| DRY TO 20', 3/12/19 | | | | | | | WATER @ 18', 7/9/19 | | | | | | |
| SAND, SILTY, BROWN | | 1.1 | | | | 1 | 6" TOP SOIL, SAND, GRAVELLY, | | 1.1 | | | | |
| CLAYSTONE, SANDY, BROWN, | | | | 50 | 11.6 | 3 | SILTY TO SLIGHTLY SILTY, | | | | 4 | 1.7 | 1 |
| HARD, MOIST | | | | 11" | | | FINE TO COARSE GRAINED, | | | | | | |
| | 5 | | | 50 | 10.1 | 2 | BROWN, LOOSE TO MEDIUM | 5 | | | 12 | 0.7 | 1 |
| SANDSTONE, CLAYEY, FINE TO | | | | 10" | | | DENSE, MOIST | | | | | | |
| COARSE GRAINED, TAN, VERY | | | | | | | | | | | | | |
| DENSE, MOIST | | | | | | | | | | | | | |
| | 10 | | | 50 | 11.3 | 2 | | 10 | | | * | 7.6 | 1 |
| | | | | 7" | | | | | | | | | |
| | 15 | | | 50 | 9.2 | 2 | CLAYSTONE, SANDY, BROWN, | 15 | | | * | 19.1 | 3 |
| | | | | 7" | | | MOIST | | | | | | |
| | 20 | | | 50 | 9.3 | 2 | | 20 | | | 50 | 12.1 | 2 |
| | | | | 6" | | | SANDSTONE, SILTY, FINE TO | | | | 5" | | |
| | | | | | | | COARSE GRAINED, BROWN, | | | | | | |
| | | | | | | | VERY DENSE, MOIST | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | CLAYSTONE, SANDY, BLUE | 25 | | | B | 9.4 | 3 |
| | | | | | | | GRAY, HARD, MOIST | | | | | | |

* - BULK SAMPLE TAKEN

B - BOUNCE



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *L*

DATE: 7/12/19

JOB NO:
 190300

FIG NO:
 A- 19

TEST BORING NO. 39
 DATE DRILLED 5/29/2019
 Job # 190300

TEST BORING NO. 40
 DATE DRILLED 3/12/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

| REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type | REMARKS | Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|--|------------|--------|---------|----------------|----------------|-----------|--|------------|--------|---------|----------------|----------------|-----------|
| WATER @ 11', 7/9/19 | | | | | | | WATER @ 10', 3/12/19 | | | | | | |
| 6" TOPSOIL, SAND, SILTY, FINE TO COARSE GRAINED, TAN, MEDIUM DENSE, MOIST TO WET | | * | | | | | 6" TOPSOIL, SAND, SILTY, FINE TO COARSE GRAINED, TAN, DENSE TO MEDIUM DENSE, MOIST | | * | | | | |
| | 5 | | | 13 | 10.7 | 1 | | 5 | | | 32 | 4.8 | 1 |
| | | | | 21 | 11.7 | 1 | | | | | 27 | 6.2 | 1 |
| CLAYSTONE, SANDY, GRAY BROWN, HARD, MOIST | 10 | | | 50 | 10.2 | 3 | SANDSTONE, SILTY, FINE TO COARSE GRAINED, GRAY BROWN, VERY DENSE, MOIST TO WET | 10 | | | 50 9" | 12.9 | 2 |
| SANDSTONE, VERY CLAYEY, FINE TO COARSE GRAINED, BROWN, WET | 15 | | | * | 14.8 | 2 | CLAYEY LENSES | 15 | | | 50 8" | 12.9 | 2 |
| CLAYSTONE, SANDY, BROWN, WET | 20 | | | * | 18.4 | 3 | | 20 | | | 50 9" | 15.2 | 2 |

* - BULK SAMPLE TAKEN



**ENTECH
ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED *L*

DATE 7/12/19

JOB NO.
190300

FIG NO
A- 20

TEST BORING NO. 41
 DATE DRILLED 6/7/2019
 Job # 190300

TEST BORING NO. 42
 DATE DRILLED 3/12/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 17', 6/7/19

6" TOP SOIL, SAND, SILTY, TAN
 SANDSTONE, SILTY, FINE
 TO COARSE GRAINED, BROWN,
 VERY DENSE, MOIST
 CLAYSTONE, SANDY, BROWN,
 HARD, MOIST

SANDSTONE, CLAYEY TO
 SILTY, FINE TO COARSE
 GRAINED, BROWN, VERY
 DENSE, MOIST TO WET

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 50 7" | 5.2 | 1 |
| 5 | | | 50 6" | 10.3 | 3 |
| 10 | | | 50 6" | 10.1 | 2 |
| 15 | | | 50 7" | 11.9 | 2 |
| 20 | | | 50 6" | 15.5 | 2 |



REMARKS

WATER @ 14', 6/7/19

6" TOP SOIL, SAND, CLAYEY,
 FINE TO COARSE GRAINED,
 BROWN, MEDIUM DENSE,
 MOIST

SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, BROWN,
 VERY DENSE, MOIST TO WET

CLAYEY LENSES

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 10 | 9.2 | 1 |
| 5 | | | 29 | 7.8 | 1 |
| 10 | | | 50 10" | 10.0 | 2 |
| 15 | | | 50 6" | 10.2 | 2 |
| 20 | | | 50 6" | 9.3 | 2 |
| 25 | | | 50 6" | 14.0 | 2 |



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED:

DATE 7/12/19

JOB NO. 190300

FIG NO. A- 21

TEST BORING NO. 43
 DATE DRILLED 5/30/2019
 Job # 190300

TEST BORING NO. 44
 DATE DRILLED 5/30/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 19', 5/30/19

6" TOPSOIL, SAND, SLIGHTLY
 SILTY, FINE TO COARSE
 GRAINED, TAN, MEDIUM
 DENSE, MOIST
 WEATHERED SANDSTONE,
 SILTY, FINE TO COARSE
 GRAINED, BROWN, DENSE,
 MOIST

CLAYSTONE, SANDY, GRAY
 BROWN, HARD, MOIST

SANDSTONE, CLAYEY, FINE
 TO COARSE GRAINED, TAN,
 VERY DENSE, MOIST

CLAYSTONE, SANDY, BLUE GRAY
 HARD, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 14 | 3.4 | 1 |
| 5 | | | 32 | 8.3 | 2 |
| 10 | | | 50 7" | 14.1 | 3 |
| 15 | | | 50 8" | 12.5 | 3 |
| 20 | | | 50 5" | 12.2 | 2 |
| 25 | | | 50 6" | 16.8 | 3 |

REMARKS

DRY TO 20', 5/30/19

6" TOPSOIL, SAND, SILTY, TAN
 WEATHERED SANDSTONE,
 SILTY, FINE TO COARSE
 GRAINED, TAN, DENSE, MOIST
 CLAYEY LENSES

SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, BROWN,
 VERY DENSE, MOIST

CLAYEY LENSES

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 1 | | | | | 1 |
| | | | 32 | 3.0 | 2 |
| 5 | | | 35 | 10.3 | 2 |
| 10 | | | 50 11" | 9.8 | 2 |
| 15 | | | 50 8" | 8.8 | 2 |
| 20 | | | 50 7" | 10.6 | 2 |



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED:

DATE: 5/31/19

JOB NO:
 190300

FIG NO:
 A- 22

TEST BORING NO. 45
DATE DRILLED 5/30/2019
Job # 190300

TEST BORING NO. 46
DATE DRILLED 5/30/2019
CLIENT TECH CONTRACTORS
LOCATION ROLLING HILLS

REMARKS

WATER @ 13', 5/30/19
WATER @ 11', 6/6/19
6" TOP SOIL, SAND, CLAYEY,
FINE TO COARSE GRAINED,
BROWN, MEDIUM DENSE,
MOIST
SANDSTONE, SILTY TO
CLAYEY, FINE TO COARSE
GRAINED, TAN, VERY DENSE,
MOIST TO WET

6/6/2019

5/30/2019

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 22 | 11.2 | 1 |
| | | | 50 | 6.9 | 2 |
| | | | 5" | | |
| 10 | | | 50 | 9.0 | 2 |
| | | | 11" | | |
| 15 | | | 50 | 8.7 | 2 |
| | | | 7" | | |
| 20 | | | 50 | 13.4 | 2 |
| | | | 8" | | |
| 25 | | | 50 | 13.4 | 2 |
| | | | 7" | | |

REMARKS

WATER @ 22', 5/30/19
6" TOP SOIL, SAND, CLAYEY,
FINE TO COARSE GRAINED,
LIGHT BROWN, MEDIUM DENSE,
MOIST
SANDSTONE, CLAYEY TO
VERY CLAYEY, FINE TO COARSE
GRAINED, TAN TO GRAY BROWN,
VERY DENSE, MOIST

CLAYSTONE, SANDY, GRAY
BROWN, HARD, MOIST

SANDSTONE, CLAYEY, FINE
TO COARSE GRAINED,
GRAY BROWN, VERY DENSE,
MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 10 | 14.2 | 1 |
| | | | 50 | 7.9 | 2 |
| | | | 11" | | |
| 10 | | | 50 | 7.9 | 2 |
| | | | 6" | | |
| 15 | | | 50 | 8.4 | 2 |
| | | | 6" | | |
| 20 | | | 50 | 12.9 | 3 |
| | | | 6" | | |
| 25 | | | 50 | 14.3 | 2 |
| | | | 6" | | |



**ENTECH
ENGINEERING, INC.**

505 ELKTON DRIVE
COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE

CHECKED:

DATE

JOB NO:
190300

FIG NO:
A- 23

TEST BORING NO. 47
 DATE DRILLED 5/30/2019
 Job # 190300

TEST BORING NO. 48
 DATE DRILLED 6/7/2019
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

DRY TO 20', 5/30/19

6" TOPSOIL, SAND, SILTY, TAN
 SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, BROWN,
 VERY DENSE, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 50 9" | 9.0 | 1 |
| | | | 50 10" | 8.7 | 2 |
| 10 | | | 50 10" | 9.4 | 2 |
| 15 | | | 50 10" | 8.8 | 2 |
| 20 | | | 50 7" | 8.5 | 2 |

REMARKS

DRY TO 20', 6/7/19
 CAVED TO 14', 7/9/19, DRY

6" TOPSOIL, SAND, SILTY, TAN
 SANDSTONE, CLAYEY TO
 SILTY, FINE TO COARSE
 GRAINED, BROWN, VERY DENSE,
 MOIST

CLAYSTONE, SANDY, BROWN,
 HARD, MOIST

SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, TAN,
 VERY DENSE, MOIST

CLAYSTONE, VERY SANDY,
 GRAY BROWN, HARD, MOIST

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 32 | 8.9 | 2 |
| | | | 27 | 7.8 | 2 |
| 10 | | | 50 9" | 9.6 | 3 |
| 15 | | | 50 8" | 5.4 | 2 |
| 20 | | | 50 9" | 9.4 | 3 |



ENTECH
ENGINEERING, INC.

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *h*

DATE:

7/22/19

JOB NO.
 190300

FIG NO.
 A- 24

TEST BORING NO. 49
 DATE DRILLED 6/7/2019
 Job # 190300

TEST BORING NO.
 DATE DRILLED
 CLIENT TECH CONTRACTORS
 LOCATION ROLLING HILLS

REMARKS

WATER @ 12', 6/7/19
 6" TOPSOIL, SAND, SLIGHTLY
 SILTY TO SILTY, FINE TO
 COARSE GRAINED, TAN,
 MEDIUM DENSE TO DENSE,
 MOIST

SANDSTONE, SILTY, FINE TO
 COARSE GRAINED, TAN, VERY
 DENSE, MOIST TO WET

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | 15 | 5.2 | 1 |
| 5 | | | 20 | 10.3 | 1 |
| 10 | | | 33 | 10.1 | 1 |
| 15 | | | 50 9" | 11.9 | 2 |
| 20 | | | 50 6" | 15.5 | 2 |
| 25 | | | 50 5" | 15.5 | 2 |

REMARKS

| Depth (ft) | Symbol | Samples | Blows per foot | Watercontent % | Soil Type |
|------------|--------|---------|----------------|----------------|-----------|
| 5 | | | | | |
| 10 | | | | | |
| 15 | | | | | |
| 20 | | | | | |
| 25 | | | | | |



**ENTECH
 ENGINEERING, INC.**

505 ELKTON DRIVE
 COLORADO SPRINGS, COLORADO 80907

TEST BORING LOG

DRAWN:

DATE:

CHECKED: *L*

DATE:

7/12/19

JOB NO.:
 190300

FIG NO.:
 A- 25

APPENDIX B: Soil Survey Descriptions

El Paso County Area, Colorado

19—Columbine gravelly sandy loam, 0 to 3 percent slopes

Map Unit Setting

National map unit symbol: 367p
Elevation: 6,500 to 7,300 feet
Mean annual precipitation: 14 to 16 inches
Mean annual air temperature: 46 to 50 degrees F
Frost-free period: 125 to 145 days
Farmland classification: Not prime farmland

Map Unit Composition

Columbine and similar soils: 85 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Columbine

Setting

Landform: Flood plains, fan terraces, fans
Down-slope shape: Linear
Across-slope shape: Linear
Parent material: Alluvium

Typical profile

A - 0 to 14 inches: gravelly sandy loam
C - 14 to 60 inches: very gravelly loamy sand

Properties and qualities

Slope: 0 to 3 percent
Depth to restrictive feature: More than 80 inches
Natural drainage class: Well drained
Runoff class: Very low
Capacity of the most limiting layer to transmit water (Ksat): High to very high (5.95 to 19.98 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: Very low (about 2.5 inches)

Interpretive groups

Land capability classification (irrigated): 4e
Land capability classification (nonirrigated): 6e
Hydrologic Soil Group: A
Ecological site: Gravelly Foothill (R049BY214CO)
Hydric soil rating: No

Minor Components

Fluvaquentic haplaquolls

Percent of map unit:
Landform: Swales

Hydric soil rating: Yes

Pleasant

Percent of map unit:

Landform: Depressions

Hydric soil rating: Yes

Other soils

Percent of map unit:

Hydric soil rating: No

Data Source Information

Soil Survey Area: El Paso County Area, Colorado

Survey Area Data: Version 16, Sep 10, 2018

El Paso County Area, Colorado

83—Stapleton sandy loam, 3 to 8 percent slopes

Map Unit Setting

National map unit symbol: 369z
Elevation: 6,500 to 7,300 feet
Mean annual precipitation: 14 to 16 inches
Mean annual air temperature: 46 to 48 degrees F
Frost-free period: 125 to 145 days
Farmland classification: Not prime farmland

Map Unit Composition

Stapleton and similar soils: 80 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Stapleton

Setting

Landform: Hills
Landform position (three-dimensional): Side slope
Down-slope shape: Linear
Across-slope shape: Linear
Parent material: Sandy alluvium derived from arkose

Typical profile

A - 0 to 11 inches: sandy loam
Bw - 11 to 17 inches: gravelly sandy loam
C - 17 to 60 inches: gravelly loamy sand

Properties and qualities

Slope: 3 to 8 percent
Depth to restrictive feature: More than 80 inches
Natural drainage class: Well drained
Runoff class: Low
Capacity of the most limiting layer to transmit water (Ksat): High
(2.00 to 6.00 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: Low (about 4.7 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 3e
Hydrologic Soil Group: B
Ecological site: Gravelly Foothill (R049BY214CO)
Hydric soil rating: No

Minor Components

Pleasant

Percent of map unit:

Landform: Depressions

Hydric soil rating: Yes

Fluvaquentic haplaquolls

Percent of map unit:

Landform: Swales

Hydric soil rating: Yes

Other soils

Percent of map unit:

Hydric soil rating: No

Data Source Information

Soil Survey Area: El Paso County Area, Colorado

Survey Area Data: Version 16, Sep 10, 2018