

**ADDENDUM TO THE  
FINAL DRAINAGE REPORT  
FOR  
HOMESTEAD AT STERLING RANCH FILING NO. 2**

**EPCD File No. SF-19-004**

**Prepared For:**

**SR Land, LLC  
20 Boulder Crescent, Suite 210  
Colorado Springs, CO 80903**

**August 18, 2020  
Project No. 25188.00**

**Prepared By:  
JR Engineering, LLC  
5475 Tech Center Drive, Suite 235  
Colorado Springs, CO 80919  
719-593-2593**

**ADDENDUM TO THE FINAL DRAINAGE REPORT FOR HOMESTEAD AT  
STERLING RANCH FILING NO. 2**

**ENGINEER'S STATEMENT:**

The attached drainage plan and report were prepared under my direction and supervision and are correct to the best of my knowledge and belief. Said drainage report has been prepared according to the criteria established by El Paso County for drainage reports and said report is in conformity with the master plan of the drainage basin. I accept responsibility for any liability caused by any negligent acts, errors, or omissions on my part in preparing this report.

---

Mike Bramlett, Colorado P.E. # 32314  
For and On Behalf of JR Engineering, LLC

**DEVELOPER'S STATEMENT:**

I, the developer, have read and will comply with all of the requirements specified in this drainage report and plan.

Business Name: SR Land, LLC

By: \_\_\_\_\_

Title: \_\_\_\_\_

Address: 20 Boulder Crescent, Suite 210  
Colorado Springs, CO 80903

**El Paso County:**

Filed in accordance with the requirements of the El Paso County Land Development Code, Drainage Criteria Manual, Volumes 1 and 2 and Engineering Criteria Manual, as amended.

---

Jennifer Irvine, P.E.  
County Engineer/ ECM Administrator

---

Date

Conditions:



**ADDENDUM TO THE FINAL DRAINAGE REPORT FOR HOMESTEAD AT  
STERLING RANCH FILING NO. 2**

**Table of Contents**

PURPOSE..... 1  
PROPOSED DRAINAGE CHARACTERISTICS ..... 1  
    Detailed Drainage Discussion (Design Points)..... 1  
    Water Quality Provisions..... 2  
    Construction Cost opinion – homestead at sterling ranch fil. no. 2..... 3

REVISED APPENDIX MATERIALS  
SF-3 Minor Basins X1, X2, W1, & Y1  
SF-3 Major Basins X1, X2, W1, & Y1  
MHFD Detention workbook Sand Filter 1  
MHFD Detention workbook Sand Filter 2  
Proposed basin map (limited to Basins X1, X2, W1, & Y1)

# ADDENDUM TO THE FINAL DRAINAGE REPORT FOR HOMESTEAD AT STERLING RANCH FILING NO. 2

## PURPOSE

---

This document is an Addendum to the Final Drainage Report for Homestead at Sterling Ranch Filing No. 2. The purpose of this report is to update the approved “Final Drainage Report for Homestead at Sterling Ranch Filing No. 2”. The scope of the updates included in this addendum are limited to proposed Basins W1, X1, X2, & Y1. More specifically, this Addendum proposes to replace the proposed individual lot Sand Filters for lots 13-24, 28-35, and 36-41 with two common Sand Filters, one to serve basin X1, lots 36-41, and one to serve basins W1, X2, & Y1, lots 13-24 & 28-35.

The text below replaces the original corresponding text from the Final Drainage Report for Homestead at Sterling Ranch Filing No. 2. The revised sections of the original report are marked in the table of contents below, and also crossed out/highlighted in the attached original report. Crossed out text is replaced and highlighted text is modified or discussed further herein.

## PROPOSED DRAINAGE CHARACTERISTICS

---

### DETAILED DRAINAGE DISCUSSION (DESIGN POINTS)

**BASIN X1** (0.78 acres), consists of proposed residential backyards of lots 36-41 along the eastern boundary of the site with runoff coefficients of 0.22 for the 5 year and 0.46 for the 100 year. Runoff in this basin will be directed via backyard swales towards the rear of the lots where it will be collected in a 12” Nyoplast Drain Basin w/ a 12” dome grate placed in the rear southwest corner of each lot. The 12” Nyoplast Drain Basins are sized to collect all flows ( $Q_5 = 0.8$  cfs,  $Q_{100} = 2.8$  cfs) in both the 5 and 100 year storms. Collected flows will then be piped to a proposed full-spectrum sand filter, with a 12-hour drain time and a 4” perforated underdrain. The treated flows from the sand filter will be discharged via an outlet structure to the adjacent Sand Creek.

**BASIN X2** (1.04 acres), consists of proposed residential backyards of lots 28-35 along the southern boundary of the site with runoff coefficients of 0.22 for the 5 year and 0.46 for the 100 year. Runoff in this basin will be directed via backyard swales towards the rear of the lots where it will be collected in a 12” Nyoplast Drain Basin w/ a 12” dome grate placed in the rear southwest corner of each lot (DP2). The 12” Nyoplast Drain Basins are sized to collect all flows ( $Q_5 = 1.1$  cfs,  $Q_{100} = 3.7$  cfs) in both the 5 and 100 year storms. Collected flows will then be piped west via 12” HDPE pipe following the rear lot lines towards DP3.1, where flows in the pipe combine with collected flows from Basin W1.

**BASIN W1** (0.86 acres), consists of proposed residential backyards of lots 19-24 along the southeastern boundary of the site with runoff coefficients of 0.22 for the 5 year and 0.46 for the 100 year. Runoff in this basin will be directed via backyard swales towards the rear of the lots where it



## **ADDENDUM TO THE FINAL DRAINAGE REPORT FOR HOMESTEAD AT STERLING RANCH FILING NO. 2**

will be collected in a 12" Nyoplast Drain Basin w/ a 12" dome grate placed in the rear corner of each lot (DP3). The 12" Nyoplast Drain Basins are sized to collect all flows ( $Q_5 = 0.9$  cfs,  $Q_{100} = 3.1$  cfs) in both the 5 and 100 year storms. Collected flows will then be piped southwest via 12" HDPE pipe following the rear lot lines towards DP3.1, where flows in the pipe combine with collected flows from Basin X2 ( $Q_5 = 1.5$  cfs,  $Q_{100} = 5.5$  cfs).

Flows in the pipe at DP3.1 are then piped to DP4.1 where they combine with collected flows from Basin Y1 ( $Q_5 = 2.1$  cfs,  $Q_{100} = 7.5$  cfs).

**BASIN Y1** (0.84 acres), consists of proposed residential backyards of lots 13-18 along the southeastern boundary of the site with runoff coefficients of 0.22 for the 5 year and 0.46 for the 100 year. Runoff in this basin will be directed via backyard swales towards the rear of the lots where it will be collected in a 12" Nyoplast Drain Basin w/ a 12" dome grate placed in the rear corner of each lot (DP4). The 12" Nyoplast Drain Basins are sized to collect all flows ( $Q_5 = 0.8$  cfs,  $Q_{100} = 3.0$  cfs) in both the 5 and 100 year storms. Collected flows will then be piped southwest via 12" HDPE pipe following the rear lot lines to a proposed full spectrum sand filter at DP4.1, where flows combine with collected flows from Basin X2 and W1 ( $Q_5 = 2.1$  cfs,  $Q_{100} = 7.5$  cfs).

The basin characteristics, hydrologic parameters, runoff and rational calcs for Basins X1, X2, W1, and Y1 have remained consistent with the approved Final Drainage Report for Homestead at Sterling Ranch Filing No. 2. However, the routing of the basins has changed and therefore revised SF-3 forms are included in the appendix section of this report. A revised basin map, showing the changes within the above described basins is also attached to this report.

### **WATER QUALITY PROVISIONS**

Runoff produced within the residential backyard lots, of Basin X1 will be conveyed in backyard swales, collected in drain basins and directed to a full-spectrum sand filter (sand filter 1). The treated flows will be collected by private storm sewer systems and discharged into the Sand Creek Channel. Sand filter basin 1 is designed to provide 0.01 ac-ft of water quality storage (WQCV), 0.025 ac-feet of excess urban runoff volume (EURV) and 0.03 ac-ft of 100-year storage for a total design volume of 0.065 ac-ft. Sand filter basin 1 was designed to have a 12 hour WQCV drain time and a peak outflow for the 100 year design storm of 0.3 cfs. The sand filter will outfall via an orifice controlled 12" HDPE pipe and FES directly to the adjacent Sand Creek channel. Sand filter basin 1 will also include a 4" perforated underdrain system and emergency overflow spillway designed to pass the peak 100-yr flow rate with one foot of freeboard above the design water surface elevation. The peak discharge rate of the proposed sand filter is at or below the historic flows for the basin which it serves.

Runoff produced within the residential backyard lots, of Basins X2, W1, and Y1 will be conveyed in backyard swales, collected in drain basins and directed to a full-spectrum sand filter (sand filter 2). The treated flows will be collected by private storm sewer systems and discharged, ultimately, into



## **ADDENDUM TO THE FINAL DRAINAGE REPORT FOR HOMESTEAD AT STERLING RANCH FILING NO. 2**

the Sand Creek Channel. The sand filter will outfall via an orifice controlled 12” HDPE pipe that is directly connected to the existing 60” RCP storm sewer outfall pipe of existing “Pond 4”.

Sand filter basin 2 is designed to provide 0.035 ac-ft of water quality storage (WQCV), 0.095 ac-feet of excess urban runoff volume (EURV) and 0.107 ac-ft of 100-year storage for a total design volume of 0.238 ac-ft. Sand filter basin 2 was designed to have a 12 hour WQCV drain time and a peak outflow for the 100 year design storm of 1.8 cfs. The sand filter will outfall via an orifice controlled 12” HDPE pipe directly connected to the existing 60” RCP pipe to the south that serves as the outfall to “Pond 4” constructed with Sterling Ranch Filing No. 1. Sand filter basin 2 will also include a 4” perforated underdrain system and emergency overflow spillway designed to pass the peak 100-yr flow rate with one foot of freeboard above the design water surface elevation. The peak discharge rate of the proposed sand filter is at or below the historic flows for the basins which it serves.

Both proposed sand filters are contained within existing Tract D, of the Homestead at Sterling Ranch Filing No. 2 development. The proposed sand filter facilities are to be privately maintained by the Sterling Ranch Metropolitan District. Access to maintain these sand filter basins is from the regional trail along sand creek.

The proposed sand filters were sized using the MHFD Detention workbook and printouts are included in the Hydraulic Calculations section of this report.

### **CONSTRUCTION COST OPINION – HOMESTEAD AT STERLING RANCH FIL. NO. 2**

Drainage improvements are planned with the development of Homestead at Sterling Ranch Filing No. 2. A majority of the construction costs have been accounted for in the “Master Development Drainage Report for Sterling Ranch Filing Nos. 1&2, and Final Drainage Report for Sterling Ranch Filing No.1” prepared by MS Civil Consultants, dated April 2017. Any additional improvements and costs are listed below.

The following list of drainage improvements is Non-Reimbursable. The Reimbursable facilities are outlined in the Sterling Ranch Filing No. 1 Final Drainage Report and Sterling Ranch MDDP. Refer to the MDDP for Sterling Ranch Cost and Fee Analysis Report (February 2019).

**ADDENDUM TO THE FINAL DRAINAGE REPORT FOR HOMESTEAD AT  
STERLING RANCH FILING NO. 2**

Item	Description	Quantity Prev	Quantity Now	Unit	Unit Cost	Cost
1	18" RCP	31	31	LF	\$ 40	\$ 1,240
2	24" RCP	127	127	LF	\$ 50	\$ 6,350
3	30" RCP	998	998	LF	\$ 85	\$ 84,830
4	36" RCP	8	8	LF	\$ 105	\$ 840
5	42" RCP	699	699	LF	\$ 185	\$ 129,315
6	24" FES	1	1	EA	\$ 750	\$ 750
8	42" FES	1	1	EA	\$ 1,250	\$ 1,250
9	5.0'x4.5' CDOT Type R Sump Inlet	1	1	EA	\$ 4,000	\$ 4,000
10	10' CDOT Type R Sump Inlet	4	4	EA	\$ 4,700	\$ 18,800
11	15' CDOT Type R At-Grade Inlet	2	2	EA	\$ 6,000	\$ 12,000
12	4.0' Type II MH	1	1	EA	\$ 3,500	\$ 3,500
13	5.0' Type II MH	2	2	EA	\$ 4,000	\$ 8,000
14	6.0' Type II MH	1	1	EA	\$ 4,500	\$ 4,500
17	5.0'x6.0' MH	2	2	EA	\$ 6,500	\$ 13,000
18	5.5'x5.5' MH	1	1	EA	\$ 6,500	\$ 6,500
19	Headwall/Wingwall	1	1	EA	\$ 6,000	\$ 6,000
20	Full Spectrum Det. Pond 1	1	1	EA	\$ 15,000	\$ 15,000
21	FSD Pond 1 Outlet Structure	1	1	EA	\$ 12,600	\$ 12,600
22	Ind. Lot Sand filter	26	0	EA	\$ 2,000	\$ -
23	18" Drain basin MH	27	0	EA	\$ 1,000	\$ -
24	12" Storm pipe	1,658	2,433	LF	\$ 26	\$ 63,258
25	12" Nyloplast Drain basin w/ 12" dome grate	0	28	EA	\$ 1,000	\$ 28,000
26	Sand Filter Basin 1	0	1	LS	\$ 4,000	\$ 4,000
27	Sand Filter Basin 2	0	1	LS	\$ 6,000	\$ 6,000
28	12" FES	0	4	EA	\$ 350	\$ 1,400
<b>TOTAL</b>						<b>\$ 431,133</b>

**ADDENDUM TO THE FINAL DRAINAGE REPORT FOR HOMESTEAD AT  
STERLING RANCH FILING NO. 2**

**REVISED APPENDIX MATERIALS**

**STANDARD FORM SF-3**  
**STORM DRAINAGE SYSTEM DESIGN**  
(RATIONAL METHOD PROCEDURE)

Project Name: Homestead at Sterling Ranch Filing No. 2

Project No.: 2000-5188.

Calculated By: REB

Checked By: \_\_\_\_\_

Date: 8/18/20

Subdivision: Homestead at Sterling Ranch Filing No. 2

Location: Colorado Springs

Design Storm: 5-Year

STREET	Design Point	DIRECT RUNOFF							TOTAL RUNOFF				PIPE				TRAVEL TIME			REMARKS
		Basin ID	Area (Ac)	Runoff Coeff.	t <sub>c</sub> (min)	C*A (Ac)	I (in/hr)	Q (cfs)	t <sub>c</sub> (min)	C*A (ac)	I (in/hr)	Q (cfs)	Q <sub>pipe</sub> (cfs)	C*A (ac)	Slope (%)	Pipe Size (inches)	Length (ft)	Velocity (fps)	t <sub>c</sub> (min)	
	1	X1	0.78	0.22	7.3	0.17	4.60	0.8				0.8	0.17	2.0	18	250	2.6	1.6	Runoff from Basin X1, collected by private 12" Nyoplast Drain Basins, Piped via 12" HDPE to pvt. Full-spectrum sand filter @ DP1.1	
	2	X2	1.04	0.22	7.3	0.23	4.60	1.1				1.1	0.23	2.0	12	950	3.1	5.1	Runoff from Basin X2, collected by private 12" Nyoplast Drain Basins, Piped via 12" HDPE to DP3.1	
	3	W1	0.86	0.22	7.3	0.19	4.60	0.9				0.9	0.19	2.0	12	250	2.8	1.5	Runoff from Basin W1, collected by private 12" Nyoplast Drain Basins, Piped via 12" HDPE to DP3.1	
	3.1							13.9	0.42	3.64	1.5								Combined flow in private 12" HDPE pipe @ DP3.1, piped to private full-spectrum sand filter @ DP-4.1	
	4	Y1	0.84	0.22	7.3	0.18	4.60	0.8				0.8	0.18	2.0	12	350	3.0	1.9	Runoff from Basin Y1, collected by private 12" Nyoplast Drain Basins, Piped via 12" HDPE to DP4.1	
	4.1							15.8	0.60	3.44	2.1								Combined flow in private 12" HDPE pipe @ DP4.1, inflow to proposed private full-spectrum sand filter	

Notes:

Street and Pipe C\*A values are determined by Q/i using the catchment's intensity value.

All pipes are private and RCP unless otherwise noted. Pipe size shown in table column.

**STANDARD FORM SF-3**  
**STORM DRAINAGE SYSTEM DESIGN**  
(RATIONAL METHOD PROCEDURE)

**Subdivision:** Homestead at Sterling Ranch Filing No. 2  
**Location:** Colorado Springs  
**Design Storm:** 100-Year

**Project Name:** Homestead at Sterling Ranch Filing No. 2  
**Project No.:** 2000-5188.  
**Calculated By:** REB  
**Checked By:**  
**Date:** 8/18/20

Description	Design Point	DIRECT RUNOFF						TOTAL RUNOFF				PIPE				TRAVEL TIME			REMARKS
		Basin ID	Area (ac)	Runoff Coeff.	t <sub>c</sub> (min)	C*A (ac)	I (in/hr)	Q (cfs)	t <sub>c</sub> (min)	C*A (ac)	I (in/hr)	Q (cfs)	Q <sub>pipe</sub> (cfs)	C*A (ac)	Slope (%)	Pipe Size (inches)	Length (ft)	Velocity (fps)	
	1	X1	0.78	0.46	7.3	0.36	7.72	2.8				2.8	0.36	1.5	12	250	3.2	1.3	Runoff from Basin X1, collected by private 12" Nyoplast Drain Basins, Piped via 12" HDPE to pvt. Full-spectrum sand filter @ DP1.1
	2	X2	1.04	0.46	7.3	0.48	7.72	3.7				3.7	0.48	1.5	12	950	3.5	4.5	Runoff from Basin X2, collected by private 12" Nyoplast Drain Basins, Piped via 12" HDPE to DP3.1
	3	W1	0.86	0.46	7.3	0.40	7.72	3.1				3.1	0.40	1.5	12	250	3.3	1.2	Runoff from Basin W1, collected by private 12" Nyoplast Drain Basins, Piped via 12" HDPE to DP3.1
	3.1							13.1	0.88	6.26	5.5								Combined flow in private 12" HDPE pipe @ DP3.1, piped to private full-spectrum sand filter @ DP-4.1
	4	Y1	0.84	0.46	7.3	0.39	7.72	3.0				3.0	0.39	1.5	12	350	3.3	1.8	Runoff from Basin Y1, collected by private 12" Nyoplast Drain Basins, Piped via 12" HDPE to DP4.1
	4.1							14.8	1.27	5.94	7.5								Combined flow in private 12" HDPE pipe @ DP4.1, inflow to proposed private full-spectrum sand filter



Notes:  
Street and Pipe C\*A values are determined by Q/I using the catchment's intensity value.  
All pipes are private and RCP unless otherwise noted. Pipe size shown in table column.





# DETENTION BASIN STAGE-STORAGE TABLE BUILDER

*MHFD-Detention, Version 4.00 (December 2019)*




# DETENTION BASIN OUTLET STRUCTURE DESIGN

MHFD-Detention, Version 4.00 (December 2019)

**Project:** Homestead at Sterling Ranch Filing No. 2

**Basin ID:** Sand Filter - Basin X1



**Example Zone Configuration (Retention Pond)**

	Estimated Stage (ft)	Estimated Volume (ac-ft)	Outlet Type
Zone 1 (WQCV)	0.27	0.010	Filtration Media
Zone 2 (EURV)	0.82	0.025	Circular Orifice
Zone 3 (100-year)	1.35	0.030	Circular Orifice
Total (all zones)		0.065	

**User Input:** Orifice at Underdrain Outlet (typically used to drain WQCV in a Filtration BMP)

Underdrain Orifice Invert Depth = 2.10 ft (distance below the filtration media surface)  
 Underdrain Orifice Diameter = 0.50 inches

**Calculated Parameters for Underdrain**  
 Underdrain Orifice Area = 0.0 ft<sup>2</sup>  
 Underdrain Orifice Centroid = 0.02 feet

**User Input:** Orifice Plate with one or more orifices or Elliptical Slot Weir (typically used to drain WQCV and/or EURV in a sedimentation BMP)

Invert of Lowest Orifice = N/A ft (relative to basin bottom at Stage = 0 ft)  
 Depth at top of Zone using Orifice Plate = N/A ft (relative to basin bottom at Stage = 0 ft)  
 Orifice Plate: Orifice Vertical Spacing = N/A inches  
 Orifice Plate: Orifice Area per Row = N/A inches

**Calculated Parameters for Plate**  
 WQ Orifice Area per Row = N/A ft<sup>2</sup>  
 Elliptical Half-Width = N/A feet  
 Elliptical Slot Centroid = N/A feet  
 Elliptical Slot Area = N/A ft<sup>2</sup>

**User Input:** Stage and Total Area of Each Orifice Row (numbered from lowest to highest)

	Row 1 (optional)	Row 2 (optional)	Row 3 (optional)	Row 4 (optional)	Row 5 (optional)	Row 6 (optional)	Row 7 (optional)	Row 8 (optional)
Stage of Orifice Centroid (ft)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Orifice Area (sq. inches)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

	Row 9 (optional)	Row 10 (optional)	Row 11 (optional)	Row 12 (optional)	Row 13 (optional)	Row 14 (optional)	Row 15 (optional)	Row 16 (optional)
Stage of Orifice Centroid (ft)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Orifice Area (sq. inches)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

**User Input:** Vertical Orifice (Circular or Rectangular)

	Zone 2 Circular	Zone 3 Circular	
Invert of Vertical Orifice =	0.29	0.87	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Vertical Orifice =	0.87	1.42	ft (relative to basin bottom at Stage = 0 ft)
Vertical Orifice Diameter =	0.50	4.00	inches

**Calculated Parameters for Vertical Orifice**  
 Vertical Orifice Area = 0.00 ft<sup>2</sup>  
 Vertical Orifice Centroid = 0.02 feet

**User Input:** Overflow Weir (Dropbox with Flat or Sloped Gate and Outlet Pipe OR Rectangular/Trapezoidal Weir (and No Outlet Pipe))

	Not Selected	Not Selected	
Overflow Weir Front Edge Height, Ho =	N/A	N/A	ft (relative to basin bottom at Stage = 0 ft)
Overflow Weir Front Edge Length =	N/A	N/A	feet
Overflow Weir Gate Slope =	N/A	N/A	H:V
Horiz. Length of Weir Sides =	N/A	N/A	feet
Overflow Gate Open Area % =	N/A	N/A	%, gate open area/total area
Debris Clogging % =	N/A	N/A	%

**Calculated Parameters for Overflow Weir**  
 Height of Gate Upper Edge, H<sub>t</sub> = N/A feet  
 Overflow Weir Slope Length = N/A feet  
 Gate Open Area / 100-yr Orifice Area = N/A  
 Overflow Gate Open Area w/o Debris = N/A ft<sup>2</sup>  
 Overflow Gate Open Area w/ Debris = N/A ft<sup>2</sup>

**User Input:** Outlet Pipe w/ Flow Restriction Plate (Circular Orifice, Restrictor Plate, or Rectangular Orifice)

	Not Selected	Not Selected	
Depth to Invert of Outlet Pipe =	N/A	N/A	ft (distance below basin bottom at Stage = 0 ft)
Circular Orifice Diameter =	N/A	N/A	inches

**Calculated Parameters for Outlet Pipe w/ Flow Restriction Plate**  
 Outlet Orifice Area = N/A ft<sup>2</sup>  
 Outlet Orifice Centroid = N/A feet  
 Half-Central Angle of Restrictor Plate on Pipe = N/A radians

**User Input:** Emergency Spillway (Rectangular or Trapezoidal)

Spillway Invert Stage = 2.50 ft (relative to basin bottom at Stage = 0 ft)  
 Spillway Crest Length = 10.00 feet  
 Spillway End Slopes = 4.00 H:V  
 Freeboard above Max Water Surface = 1.50 feet

**Calculated Parameters for Spillway**  
 Spillway Design Flow Depth = 0.12 feet  
 Stage at Top of Freeboard = 4.12 feet  
 Basin Area at Top of Freeboard = 0.09 acres  
 Basin Volume at Top of Freeboard = 0.17 acre-ft




## Routed Hydrograph Results

*The user can override the default CUHP hydrographs and runoff volumes by entering new values in the Inflow Hydrographs table (Columns W through AF).*

	WQCV	EURV	2 Year	5 Year	10 Year	25 Year	50 Year	100 Year	500 Year
Design Storm Return Period	0.53	1.07	1.19	1.50	1.75	2.00	2.25	2.52	3.14
One-Hour Rainfall Depth (in)	0.010	0.035	0.033	0.049	0.063	0.083	0.099	0.119	0.160
CUHP Runoff Volume (acre-ft)	0.010	0.035	0.033	0.049	0.063	0.083	0.099	0.119	0.160
Inflow Hydrograph Volume (acre-ft)	0.0	0.0	0.1	0.2	0.2	0.4	0.6	0.7	1.0
CUHP Predevelopment Peak Q (cfs)	0.0	0.0	0.07	0.20	0.31	0.58	0.72	0.93	1.30
OPTIONAL Override Predevelopment Peak Q (cfs)	0.0	0.0							
Predevelopment Unit Peak Flow, q (cfs/acre)	0.1	0.4	0.4	0.5	0.7	0.9	1.1	1.3	1.8
Peak Inflow Q (cfs)	0.0	0.0	0.0	0.0	0.1	0.2	0.3	0.3	0.4
Peak Outflow Q (cfs)	N/A	N/A	N/A	0.3	0.5	0.5	0.5	0.5	0.4
Ratio Peak Outflow to Predevelopment Q	Filtration Media	Vertical Orifice 1	Vertical Orifice 1	Vertical Orifice 2	Vertical Orifice 2	Vertical Orifice 2	Vertical Orifice 2	Vertical Orifice 2	Vertical Orifice 2
Structure Controlling Flow	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Max Velocity through Gate 1 (fps)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Max Velocity through Gate 2 (fps)	12	34	33	41	41	41	41	41	40
Time to Drain 97% of Inflow Volume (hours)	13	35	34	42	43	43	43	44	44
Time to Drain 99% of Inflow Volume (hours)	0.22	0.76	0.72	0.99	1.13	1.29	1.43	1.63	2.00
Maximum Ponding Depth (ft)	0.04	0.05	0.05	0.05	0.06	0.06	0.06	0.07	0.08
Area at Maximum Ponding Depth (acres)	0.008	0.031	0.030	0.044	0.052	0.061	0.070	0.083	0.110
Maximum Volume Stored (acre-ft)									

# DETENTION BASIN OUTLET STRUCTURE DESIGN

*MHFD-Detention, Version 4.00 (December 2019)*



S-A-V-D Chart Axis Override	X-axis	Left Y-Axis	Right Y-Axis
minimum bound			
maximum bound			

# DETENTION BASIN OUTLET STRUCTURE DESIGN

Outflow Hydrograph Workbook Filename: \_\_\_\_\_

## Inflow Hydrographs

The user can override the calculated inflow hydrographs from this workbook with inflow hydrographs developed in a separate program.


Time Interval	SOURCE	CUHP	CUHP	CUHP	CUHP	CUHP	CUHP	CUHP	CUHP	CUHP
	TIME	WQCV [cfs]	EURV [cfs]	2 Year [cfs]	5 Year [cfs]	10 Year [cfs]	25 Year [cfs]	50 Year [cfs]	100 Year [cfs]	500 Year [cfs]
5.00 min	0:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01
	0:15:00	0.01	0.03	0.03	0.04	0.05	0.04	0.05	0.04	0.06
	0:20:00	0.03	0.09	0.10	0.13	0.16	0.09	0.11	0.12	0.16
	0:25:00	0.07	0.26	0.24	0.37	0.49	0.23	0.28	0.31	0.50
	0:30:00	0.10	0.37	0.34	0.52	0.65	0.70	0.84	0.96	1.31
	0:35:00	0.11	0.38	0.35	0.53	0.66	0.88	1.05	1.26	1.68
	0:40:00	0.10	0.36	0.34	0.50	0.63	0.94	1.12	1.33	1.76
	0:45:00	0.09	0.33	0.31	0.46	0.59	0.91	1.07	1.31	1.74
	0:50:00	0.09	0.31	0.29	0.43	0.55	0.88	1.04	1.26	1.67
	0:55:00	0.08	0.29	0.27	0.40	0.51	0.81	0.96	1.19	1.57
	1:00:00	0.08	0.27	0.25	0.37	0.48	0.75	0.89	1.12	1.49
	1:05:00	0.07	0.25	0.24	0.35	0.45	0.70	0.83	1.07	1.42
	1:10:00	0.07	0.23	0.21	0.32	0.42	0.63	0.76	0.97	1.29
	1:15:00	0.06	0.21	0.19	0.30	0.40	0.57	0.69	0.86	1.16
	1:20:00	0.05	0.19	0.18	0.27	0.36	0.51	0.61	0.75	1.01
	1:25:00	0.05	0.17	0.16	0.24	0.32	0.45	0.54	0.65	0.88
	1:30:00	0.05	0.16	0.15	0.23	0.30	0.40	0.48	0.58	0.77
	1:35:00	0.04	0.15	0.14	0.21	0.28	0.36	0.43	0.52	0.69
	1:40:00	0.04	0.14	0.13	0.20	0.26	0.33	0.39	0.46	0.62
	1:45:00	0.04	0.13	0.13	0.18	0.24	0.30	0.35	0.42	0.56
	1:50:00	0.04	0.12	0.12	0.17	0.22	0.27	0.32	0.38	0.51
	1:55:00	0.03	0.11	0.11	0.15	0.20	0.25	0.29	0.34	0.45
	2:00:00	0.03	0.10	0.10	0.14	0.18	0.22	0.26	0.30	0.40
	2:05:00	0.03	0.08	0.08	0.12	0.15	0.19	0.22	0.25	0.34
	2:10:00	0.02	0.07	0.07	0.09	0.12	0.15	0.18	0.21	0.28
	2:15:00	0.02	0.05	0.06	0.08	0.10	0.12	0.14	0.16	0.22
	2:20:00	0.01	0.04	0.04	0.06	0.08	0.09	0.11	0.13	0.17
	2:25:00	0.01	0.03	0.03	0.05	0.06	0.07	0.08	0.09	0.12
	2:30:00	0.01	0.03	0.03	0.04	0.05	0.05	0.06	0.07	0.09
	2:35:00	0.01	0.02	0.02	0.03	0.04	0.04	0.05	0.05	0.07
	2:40:00	0.01	0.02	0.02	0.03	0.03	0.03	0.04	0.04	0.06
	2:45:00	0.00	0.02	0.02	0.02	0.03	0.03	0.03	0.03	0.04
	2:50:00	0.00	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.03
	2:55:00	0.00	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02
	3:00:00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.02
	3:05:00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
	3:10:00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
	3:15:00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01
	3:20:00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01
	3:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01
	3:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
4:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:15:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:20:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:15:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:20:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
6:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	





# DETENTION BASIN STAGE-STORAGE TABLE BUILDER

MHFD-Detention, Version 4.00 (December 2019)






# DETENTION BASIN OUTLET STRUCTURE DESIGN

MHFD-Detention, Version 4.00 (December 2019)

**Project:** Homestead at Sterling Ranch Filling No. 2

**Basin ID:** Sand Filter - Basins Y1, W1, X2



**Example Zone Configuration (Retention Pond)**

	Estimated Stage (ft)	Estimated Volume (ac-ft)	Outlet Type
Zone 1 (WQCV)	0.41	0.035	Filtration Media
Zone 2 (EURV)	1.32	0.095	Circular Orifice
Zone 3 (100-year)	2.14	0.107	Circular Orifice
Total (all zones)		0.238	

**User Input:** Orifice at Underdrain Outlet (typically used to drain WQCV in a Filtration BMP)

Underdrain Orifice Invert Depth =  ft (distance below the filtration media surface)  
 Underdrain Orifice Diameter =  inches

**Calculated Parameters for Underdrain**

Underdrain Orifice Area =  ft<sup>2</sup>  
 Underdrain Orifice Centroid =  feet

**User Input:** Orifice Plate with one or more orifices or Elliptical Slot Weir (typically used to drain WQCV and/or EURV in a sedimentation BMP)

**Calculated Parameters for Plate**

Invert of Lowest Orifice =  ft (relative to basin bottom at Stage = 0 ft)  
 Depth at top of Zone using Orifice Plate =  ft (relative to basin bottom at Stage = 0 ft)  
 Orifice Plate: Orifice Vertical Spacing =  inches  
 Orifice Plate: Orifice Area per Row =  inches

WQ Orifice Area per Row =  ft<sup>2</sup>  
 Elliptical Half-Width =  feet  
 Elliptical Slot Centroid =  feet  
 Elliptical Slot Area =  ft<sup>2</sup>

**User Input:** Stage and Total Area of Each Orifice Row (numbered from lowest to highest)

	Row 1 (optional)	Row 2 (optional)	Row 3 (optional)	Row 4 (optional)	Row 5 (optional)	Row 6 (optional)	Row 7 (optional)	Row 8 (optional)
Stage of Orifice Centroid (ft)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Orifice Area (sq. inches)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

	Row 9 (optional)	Row 10 (optional)	Row 11 (optional)	Row 12 (optional)	Row 13 (optional)	Row 14 (optional)	Row 15 (optional)	Row 16 (optional)
Stage of Orifice Centroid (ft)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Orifice Area (sq. inches)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

**User Input:** Vertical Orifice (Circular or Rectangular)

**Calculated Parameters for Vertical Orifice**

	Zone 2 Circular	Zone 3 Circular	
Invert of Vertical Orifice =	<input type="text" value="0.60"/>	<input type="text" value="1.75"/>	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Vertical Orifice =	<input type="text" value="1.73"/>	<input type="text" value="2.62"/>	ft (relative to basin bottom at Stage = 0 ft)
Vertical Orifice Diameter =	<input type="text" value="0.80"/>	<input type="text" value="12.00"/>	inches

Vertical Orifice Area =  ft<sup>2</sup>  
 Vertical Orifice Centroid =  feet

**User Input:** Overflow Weir (Dropbox with Flat or Sloped Gate and Outlet Pipe OR Rectangular/Trapezoidal Weir (and No Outlet Pipe))

**Calculated Parameters for Overflow Weir**

	Not Selected	Not Selected	
Overflow Weir Front Edge Height, H <sub>o</sub> =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	ft (relative to basin bottom at Stage = 0 ft)
Overflow Weir Front Edge Length =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	feet
Overflow Weir Gate Slope =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	H:V
Horiz. Length of Weir Sides =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	feet
Overflow Gate Open Area % =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	%, gate open area/total area
Debris Clogging % =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	%

	Not Selected	Not Selected	
Height of Gate Upper Edge, H <sub>t</sub> =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	feet
Overflow Weir Slope Length =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	feet
Gate Open Area / 100-yr Orifice Area =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	
Overflow Gate Open Area w/o Debris =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	ft <sup>2</sup>
Overflow Gate Open Area w/ Debris =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	ft <sup>2</sup>

**User Input:** Outlet Pipe w/ Flow Restriction Plate (Circular Orifice, Restrictor Plate, or Rectangular Orifice)

**Calculated Parameters for Outlet Pipe w/ Flow Restriction Plate**

	Not Selected	Not Selected	
Depth to Invert of Outlet Pipe =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	ft (distance below basin bottom at Stage = 0 ft)
Circular Orifice Diameter =	<input type="text" value="N/A"/>	<input type="text" value="N/A"/>	inches

Outlet Orifice Area =  ft<sup>2</sup>  
 Outlet Orifice Centroid =  feet  
 Half-Central Angle of Restrictor Plate on Pipe =  radians

**User Input:** Emergency Spillway (Rectangular or Trapezoidal)

**Calculated Parameters for Spillway**

Spillway Invert Stage =  ft (relative to basin bottom at Stage = 0 ft)  
 Spillway Crest Length =  feet  
 Spillway End Slopes =  H:V  
 Freeboard above Max Water Surface =  feet

Spillway Design Flow Depth =  feet  
 Stage at Top of Freeboard =  feet  
 Basin Area at Top of Freeboard =  acres  
 Basin Volume at Top of Freeboard =  acre-ft




**Routed Hydrograph Results**

*The user can override the default CUHP hydrographs and runoff volumes by entering new values in the Inflow Hydrographs table (Columns W through AF).*

	WQCV	EURV	2 Year	5 Year	10 Year	25 Year	50 Year	100 Year	500 Year
Design Storm Return Period	0.53	1.07	1.19	1.50	1.75	2.00	2.25	2.52	3.14
One-Hour Rainfall Depth (in)	0.035	0.131	0.124	0.181	0.232	0.302	0.358	0.429	0.574
CUHP Runoff Volume (acre-ft)	0.035	0.131	0.124	0.181	0.232	0.302	0.358	0.429	0.574
Inflow Hydrograph Volume (acre-ft)	0.0	0.0	0.2	0.6	0.9	1.7	2.1	2.7	3.8
CUHP Predevelopment Peak Q (cfs)	0.0	0.0							
OPTIONAL Override Predevelopment Peak Q (cfs)	0.0	0.0							
Predevelopment Unit Peak Flow, q (cfs/acre)	0.00	0.00	0.08	0.22	0.34	0.61	0.77	0.99	1.38
Peak Inflow Q (cfs)	0.4	1.5	1.4	2.1	2.7	3.7	4.4	5.2	6.9
Peak Outflow Q (cfs)	0.0	0.1	0.1	0.1	0.2	0.7	1.1	1.8	2.8
Ratio Peak Outflow to Predevelopment Q	N/A	N/A	N/A	0.1	0.2	0.4	0.5	0.7	0.7
Structure Controlling Flow	Filtration Media	Vertical Orifice 1	Vertical Orifice 1	Vertical Orifice 1	Vertical Orifice 2	Vertical Orifice 2	Vertical Orifice 2	Vertical Orifice 2	N/A
Max Velocity through Gate 1 (fps)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Max Velocity through Gate 2 (fps)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Time to Drain 97% of Inflow Volume (hours)	12	36	34	45	51	51	50	50	48
Time to Drain 99% of Inflow Volume (hours)	12	37	35	47	52	53	53	53	52
Maximum Ponding Depth (ft)	0.33	1.23	1.17	1.62	1.94	2.20	2.35	2.53	2.75
Area at Maximum Ponding Depth (acres)	0.09	0.12	0.11	0.13	0.14	0.15	0.15	0.16	0.16
Maximum Volume Stored (acre-ft)	0.027	0.119	0.113	0.168	0.210	0.247	0.269	0.296	0.331

# DETENTION BASIN OUTLET STRUCTURE DESIGN

*MHFD-Detention, Version 4.00 (December 2019)*



S-A-V-D Chart Axis Override	X-axis	Left Y-Axis	Right Y-Axis
minimum bound			
maximum bound			

# DETENTION BASIN OUTLET STRUCTURE DESIGN



Outflow Hydrograph Workbook Filename: \_\_\_\_\_

## Inflow Hydrographs

The user can override the calculated inflow hydrographs from this workbook with inflow hydrographs developed in a separate program.

Time Interval	SOURCE	CUHP	CUHP	CUHP	CUHP	CUHP	CUHP	CUHP	CUHP	CUHP
	TIME	WQCV [cfs]	EURV [cfs]	2 Year [cfs]	5 Year [cfs]	10 Year [cfs]	25 Year [cfs]	50 Year [cfs]	100 Year [cfs]	500 Year [cfs]
5.00 min	0:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.04
	0:15:00	0.03	0.14	0.12	0.19	0.23	0.16	0.20	0.19	0.28
	0:20:00	0.12	0.40	0.42	0.55	0.69	0.41	0.48	0.51	0.71
	0:25:00	0.29	1.12	1.01	1.55	2.05	1.00	1.19	1.33	2.06
	0:30:00	0.40	1.54	1.42	2.13	2.66	2.87	3.44	3.91	5.31
	0:35:00	0.41	1.54	1.44	2.13	2.64	3.56	4.23	5.04	6.70
	0:40:00	0.39	1.44	1.37	1.99	2.47	3.72	4.39	5.22	6.89
	0:45:00	0.35	1.32	1.24	1.82	2.28	3.53	4.17	5.08	6.70
	0:50:00	0.32	1.21	1.13	1.67	2.08	3.36	3.97	4.82	6.35
	0:55:00	0.29	1.11	1.04	1.53	1.92	3.05	3.60	4.47	5.90
	1:00:00	0.27	1.02	0.96	1.41	1.79	2.79	3.31	4.19	5.54
	1:05:00	0.25	0.93	0.88	1.29	1.65	2.56	3.04	3.94	5.21
	1:10:00	0.22	0.85	0.79	1.17	1.52	2.28	2.72	3.47	4.61
	1:15:00	0.20	0.76	0.70	1.05	1.40	2.02	2.40	3.02	4.03
	1:20:00	0.18	0.69	0.63	0.96	1.29	1.75	2.09	2.58	3.45
	1:25:00	0.17	0.64	0.59	0.89	1.18	1.56	1.86	2.25	3.02
	1:30:00	0.16	0.60	0.55	0.82	1.07	1.39	1.66	1.98	2.66
	1:35:00	0.15	0.55	0.51	0.77	0.98	1.25	1.48	1.76	2.35
	1:40:00	0.14	0.50	0.48	0.69	0.89	1.11	1.32	1.55	2.07
	1:45:00	0.13	0.45	0.45	0.62	0.81	0.99	1.17	1.36	1.82
	1:50:00	0.12	0.40	0.41	0.55	0.72	0.87	1.03	1.18	1.57
	1:55:00	0.10	0.35	0.36	0.48	0.64	0.76	0.89	1.01	1.34
	2:00:00	0.09	0.30	0.31	0.42	0.54	0.65	0.76	0.85	1.13
	2:05:00	0.07	0.24	0.24	0.33	0.43	0.50	0.59	0.65	0.87
	2:10:00	0.05	0.19	0.19	0.26	0.34	0.37	0.43	0.48	0.64
	2:15:00	0.04	0.15	0.15	0.21	0.28	0.29	0.33	0.36	0.49
	2:20:00	0.04	0.12	0.13	0.17	0.23	0.22	0.26	0.28	0.38
	2:25:00	0.03	0.10	0.10	0.14	0.19	0.18	0.21	0.21	0.29
	2:30:00	0.02	0.08	0.09	0.11	0.15	0.14	0.16	0.16	0.22
	2:35:00	0.02	0.07	0.07	0.09	0.12	0.11	0.13	0.12	0.17
	2:40:00	0.02	0.05	0.06	0.07	0.10	0.09	0.10	0.09	0.13
	2:45:00	0.01	0.04	0.05	0.06	0.08	0.07	0.08	0.07	0.09
	2:50:00	0.01	0.03	0.04	0.05	0.06	0.05	0.06	0.05	0.07
	2:55:00	0.01	0.03	0.03	0.04	0.05	0.04	0.05	0.04	0.06
	3:00:00	0.01	0.02	0.02	0.03	0.04	0.03	0.04	0.03	0.05
	3:05:00	0.01	0.02	0.02	0.02	0.03	0.03	0.03	0.03	0.04
	3:10:00	0.00	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.03
	3:15:00	0.00	0.01	0.01	0.01	0.01	0.01	0.02	0.01	0.02
	3:20:00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
	3:25:00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01
	3:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:15:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:20:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:15:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:20:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00





Sand Filter 2 - Emergency Spillway Riprap Sizing




Figure 12-21. Embankment protection details and rock sizing chart (adapted from Arapahoe County)




# HOMESTEAD AT STERLING RANCH FILING NO. 2

## COUNTY OF EL PASO, STATE OF COLORADO

### PROPOSED DRAINAGE MAP (ADDENDUM)


Tributary Sub-basin	Area (acres)	Percent Impervious	C <sub>s</sub>	C <sub>100</sub>	t <sub>c</sub> (min)	Q <sub>s</sub> (cfs)	Q <sub>100</sub> (cfs)
X1	0.78	25%	0.22	0.46	7.3	0.8	2.8
X2	1.04	25%	0.22	0.46	7.3	1.1	3.7
W1	0.86	25%	0.22	0.46	7.3	0.9	3.1
Y1	0.84	25%	0.22	0.46	7.3	0.8	3.0

DP	Q <sub>5</sub>	Q <sub>100</sub>
	Total	Total
1	0.8	2.8
2	1.1	3.1
3	0.9	3.0
3.1	1.5	5.5
4	0.8	3.0
4.1	2.1	7.5



#### LEGEND

- BASIN ID  
A: SUB-BASIN DESIGNATION  
B: AREA (AC)  
C: 5 YEAR STORM COEFFICIENT  
D: 100 YEAR STORM COEFFICIENT
- DRAINAGE DISCHARGE DESIGN POINT
- PROPOSED FLOW DIRECTION
- HISTORIC FLOW DIRECTION
- EXISTING DRAINAGE BASIN
- PROPOSED DRAINAGE BASIN
- EXISTING STORM SEWER
- PROPOSED STORM SEWER



100 50 0 100  
ORIGINAL SCALE: 1" = 100'

PROPOSED DRAINAGE MAP  
(ADDENDUM)  
HOMESTEAD AT STERLING RANCH FILING NO. 2  
JOB NO. 25188.00  
08/18/2020  
SHEET 1 OF 1



Centennial 303-740-9393 • Colorado Springs 719-593-2593  
Fort Collins 970-491-9888 • www.jrengineering.com

X:\25188\000\addendum\Homestead 2 Sanfil Filter\CAD\Proposed Drainage Map.dwg, PROPOSED DRAINAGE, 8/18/2020 12:56:44 PM, CS



**FINAL DRAINAGE REPORT FOR  
HOMESTEAD AT STERLING RANCH  
FILING NO.2**

**EL PASO COUNTY, COLORADO**

March 2020

Prepared for:  
**SR Land, LLC**  
**20 Boulder Crescent, Suite 210**  
**Colorado Springs, CO 80903**

Prepared by:



102 E. Pikes Peak, Suite 500  
Colorado Springs, CO 80903  
(719) 955-5485


Project #09-007  
SF-19-004

**FINAL DRAINAGE REPORT FOR  
HOMESTEAD AT STERLING RANCH FILING NO. 2**

**DRAINAGE PLAN STATEMENTS**

**ENGINEERS STATEMENT**

The attached drainage plan and report was prepared under my direction and supervision and are correct to the best of my knowledge and belief. Said drainage report has been prepared according to the criteria established by the County for drainage reports and said report is in conformity with the master plan of the drainage basin. I accept responsibility for any liability caused by any negligent acts, errors or omissions on my part in preparing this report.



\_\_\_\_\_  
Virgil A. Sanchez, P.E. #37160  
For and on Behalf of M&S Civil Consultants, Inc

**DEVELOPER'S STATEMENT**

I, the developer have read and will comply with all the requirements specified in this drainage report and plan.

BY: James Morley  
James F Morley

TITLE: Manager  
DATE: 3-31-2020

ADDRESS: SR Land, LLC  
20 Boulder Crescent, Suite 210  
Colorado Springs, CO 80903

**EL PASO COUNTY'S STATEMENT**

Filed in accordance with the requirements of El Paso County Land Development Code, Drainage Criteria Manual Volumes 1 and 2, and the Engineering Criteria Manual, as amended.

BY: \_\_\_\_\_ DATE: \_\_\_\_\_

Jennifer Irvine, P.E.  
County Engineer / ECM Administrator



**FINAL DRAINAGE REPORT FOR  
HOMESTEAD AT STERLING RANCH FILING NO. 2**

**TABLE OF CONTENTS**

<b>PURPOSE</b>	<b>4</b>
GENERALLOCATIONANDDESCRIPTION	4
SOILS	4
HYDROLOGICCALCULATIONS	4
HYDRAULICCALCULATIONS	5
FLOODPLAINSTATEMENT	5
DRAINAGECRITERIA	5
FOUR STEP PROCESS	5
EXISTINGDRAINAGECONDITIONS	6
<b>PROPOSEDDRAINAGECHARACTERISTICS</b>	<b>6</b>
CHANNEL IMPROVEMENTS	9
<b>WATER QUALITY PROVISIONS</b>	<b>9</b>
EROSIONCONTROL	10
<b>CONSTRUCTION COST OPINION</b>	<b>10</b>
DRAINAGE & BRIDGE FEES	11
STERLING RANCH FIL. NO.1 - SIA	11
SUMMARY	12
REFERENCES	13

**APPENDIX**

VicinityMap  
SoilsMap  
FIRMPanelW/Revised LOMR  
**HydrologicCalculations**  
**HydraulicCalculations**  
**DrainageMaps**

# FINAL DRAINAGE REPORT FOR HOMESTEAD AT STERLING RANCH FILING NO. 2

## PURPOSE

Additional language added in Addendum above

This document is the Final Drainage Report for Homestead at Sterling Ranch Filing No. 2. This report was previously discussed, as a preliminary drainage report, in the “Master Development Drainage Report for Sterling Ranch Filing Nos. 1&2, and Final Drainage Report for Sterling Ranch Filing No.1” prepared by MS Civil Consultants, dated April 2017. The purpose of this document is to identify and analyze the on and offsite drainage patterns and to ensure that post development runoff is routed through the site safely and in a manner that satisfies the requirements set forth by the El Paso County Drainage Criteria Manual. The following report is an analysis of the drainage for Homestead at Sterling Ranch Filing No. 2, single family lots, onsite and offsite drainage.

## GENERAL LOCATION AND DESCRIPTION

Homestead at Sterling Ranch Filing No. 2 is located in the SE  $\frac{1}{4}$  of the NW  $\frac{1}{4}$ , the SW  $\frac{1}{4}$  of the NE  $\frac{1}{4}$ , and the NW  $\frac{1}{4}$  of the NE  $\frac{1}{4}$  of Section 33, Township 12 South, Range 65 West of the 6<sup>th</sup> Principal Meridian, and the NE  $\frac{1}{4}$  of the SW  $\frac{1}{4}$  of Section 33, Township 12 South, Range 65 West of the 6<sup>th</sup> Principal Meridian within unincorporated El Paso County, Colorado. The site is bound on the south by an existing detention pond, to the north by Briargate Parkway and to the east by Sand Creek. Existing Dines Boulevard runs along the western site boundary. An existing residential development, Homestead at Sterling Ranch Filing No. 1, bounds the site to the west and a future commercial parcel bounds the site to the northwest. Sterling Ranch lies within the Sand Creek Drainage Basin. Flows from this site are tributary to Sand Creek.

Homestead at Sterling Ranch Filing No. 2 consists of 29.658 acres and is presently undeveloped. Vegetation is sparse, consisting of native grasses. Existing site terrain generally slopes from north to southwest at grade rates that vary between 2% and 6%.

Land use for Homestead at Sterling Ranch Filing No. 2 is currently listed as AG (Grazing Land). Improvements proposed for the site include paved streets, trails, a full spectrum detention pond, and utilities as normally constructed for a residential development.

## SOILS

Soils for this project are delineated by the map in the appendix as Pring Coarse Sandy Loam (71) and is characterized as Hydrologic Soil Types "B". Soils in the study area are shown as mapped by S.C.S. in the "Soils Survey of El Paso County Area". Vegetation is sparse, consisting of native grasses and weeds.

## HYDROLOGIC CALCULATIONS

Hydrologic calculations were performed using the El Paso County and City of Colorado Storm Drainage Design Criteria manual and where applicable the Urban Storm Drainage Criteria Manual. The Rational Method was used to estimate stormwater runoff anticipated from design storms with 5-year and 100-year recurrence intervals.

## HYDRAULIC CALCULATIONS

Hydraulic calculations were estimated using the Manning's Formula and the methods described in the El Paso County and City of Colorado Springs Storm Drainage Design Criteria manual. The relevant data sheets can be found in the "Master Development Drainage Report for Sterling Ranch Filing Nos. 1&2, and Final Drainage Report for Sterling Ranch Filing No.1" prepared by MS Civil Consultants, dated April 2017 and in the appendix of this report.

## FLOODPLAIN STATEMENT

No portion of this site is within a designated F.E.M.A. floodplain as determined by the Federal Emergency Management Agency (FEMA) Flood Insurance Rate Map (FIRM) Panel No. 08041C0533G, effective date December 7, 2018. An annotated FIRM Panel is included in the Appendix.

## DRAINAGE CRITERIA

This drainage analysis has been prepared in accordance with the current City of Colorado Springs/El Paso County Drainage Criteria Manual, Volumes I & II, dated November 1991, including subsequent updates. El Paso County has also adopted Chapter 6 and Section 3.2.1 of Chapter 13 in the City of Colorado Springs & El Paso County Drainage Criteria Manual Volumes I and II, dated May 2014. (Appendix I of the El Paso County's Engineering Criteria Manual (ECM), 2008). In addition to the ECM, the Urban Storm Drainage Criteria Manuals, Volumes 1-3, published by the Urban Drainage and Flood Control District (Volumes 1 & 2 dated January 2016, Volume 3 dated November 2010 and updates. Calculations were performed to determine runoff quantities for the 5-year and 100-year frequency storms for developed conditions using the Rational Method. July 2019 ECM updated for MS4 permit.

## FOUR STEP PROCESS

**Step 1 Employ Runoff Reduction Practices.** Roof drains will be directed to side yard swales and as possible to grass lined swales to aid in minimizing direct connection of impervious surfaces.

**Step 2 Implement BMPs that provide a water quality capture volume with slow release.** – An existing Full Spectrum Detention Facility (see Sterling Ranch Filing Nos. 1&2 MDDP, Pond 4) was planned and constructed to handle tributary flows for the southwest portion of the site. All remaining tributary areas from the site will be treated in a proposed temporary Full Spectrum Detention Facility, Interim Pond 1. Both ponds will incorporate water quality capture volumes that are intended to slowly drain in 40 hours and excess urban runoff volumes that are intended to drain within 72 hours.

**Step 3 Stabilize streams.** – With the full spectrum detention facilities in place, the runoff from the proposed residential development will be reduced to predevelopment conditions. The developed discharge from the site is less than existing and therefore is not anticipated to have negative effects on downstream drainageways. Additionally, the Sand Creek Channel will be reinforced with selected areas of rip rap bank protection, vegetative slope stabilization, check structures and drop structures.

**Step 4 Consider need for Industrial and Commercial BMPs.** – No industrial or commercial land uses are proposed with this development. The proposed residential development area will implement a Stormwater Management Plan (SWMP) incorporating proper housekeeping procedures. Onsite drainage will be routed through proposed private temporary Full Spectrum Detention Facility (FSD), Interim Pond 1, to minimize introduction of contaminants to the county's public drainage systems.

## EXISTING DRAINAGE CONDITIONS

The Homestead at Sterling Ranch Filing No. 2 site consists of 29.658 acres and is situated west of the Sand Creek Watershed. This area was previously studied in the "Sand Creek Drainage Basin Planning Study" (DBPS) prepared by Kiowa Corporation, revised March 1996. More recently the area was studied in the "Master Development Drainage Report for Sterling Ranch Filing Nos. 1&2, and Final Drainage Report for Sterling Ranch Filing No.1" prepared by MS Civil Consultants, dated April 2017 (henceforth referred to as "Sterling Ranch Filing Nos. 1&2 MDDP").

See the Historic conditions map, the Homestead at Sterling Ranch Filing No. 2 site lies within the Basin EX-4 ( $Q_5 = 71$  cfs,  $Q_{100} = 352$  cfs) and is a 330 acre area of land located on the western portion of the site, including the Sand Creek channel. A portion of this basin extends off-site to the northwest of Vollmer Road, and at the time this map was created was undeveloped property. Runoff from the basin generally travels from north to south until it reaches the northern boundary of the site, being conveyed in the Sand Creek channel. Homestead at Sterling Ranch Filing No. 2 and the surrounding areas, with the exception of the existing Barbarick Subdivision; have already been graded during the overlot of the subdivision. Please refer to the Sterling Ranch Filing Nos. 1&2 MDDP by MS Civil Consultants for information on existing conditions and overlot drainage patterns. A copy of the historic and existing conditions map has been provided in the appendix.

## PROPOSED DRAINAGE CHARACTERISTICS

### General Concept Drainage Discussion

The following is a description of the onsite basins, offsite bypass flows and the overall drainage characteristics for the development of Sterling Ranch Filing No. 2. The development of Sterling Ranch Filing No. 2 consists of residential streets and cul-de-sacs, proposed storm drainage improvements, and lots located within the filing boundary. The proposed development results in drainage patterns and flow values that are the same or less than those in the Sterling Ranch Filing Nos. 1&2 MDDP. Surface flow is designated as Design Points (DP). The following DPs and Basins were determined using the Rational Method since this method offers a more conservative approach to drainage. It should be noted that all calculations and drainage basins have been revised to reflect the new criteria updates by the El Paso County/City of Colorado Springs Drainage Criteria Manual. For comparison, the **asterisk (\*)** symbol in the detailed drainage discussions below represents each Basin or Design Point as labeled in the Sterling Ranch Filing Nos. 1&2 MDDP. Asterisk symbols on the Proposed Drainage Map in the appendix also represent Basins, Design Points and Pipe Runs as presented in the Sterling Ranch Filing Nos. 1&2 MDDP.

### Detailed Drainage Discussion (Design Points)

**DP2\***, 5.39 acres, consists of Basin B\* planned residential lots and streets with runoff coefficients of 0.38 for the 5-year and 0.55 for the 100-year. Developed runoff of  $Q_5=8.0$  cfs and  $Q_{100}=19.3$  cfs has been calculated for DP2\*. The surface runoff is routed via overlot grading and planned swales to two existing 15' CDOT Type R at-grade inlets. The flows are routed east via a 36" RCP to DP5.

**DP3\***, 2.92 acres, consists of Basin C\* residential lots within Homestead at Sterling Ranch Filing No. 1, and streets with runoff coefficients of 0.38 for the 5-year and 0.55 for the 100-year. Developed runoff of  $Q_5=4.2$  cfs and  $Q_{100}=10.1$  cfs has been calculated for DP3\*. The surface runoff is routed via overlot grading and proposed swales to an existing 5' CDOT type R sump inlet. The flows captured by the inlet are routed to existing Detention Pond 4.

**DP4\***, 9.36 acres, consists of Basin D\* and Basin E\* residential lots within Homestead at Sterling Ranch Filing No. 1 and streets with runoff coefficients of 0.38 for the 5-year and 0.55 for the 100-year and Basin F\* (Dines Boulevard) with runoff coefficients of 0.90 for the 5-year and 0.96 for the 100-year. Developed runoff of Q5=16.1 cfs and Q100=36.7 cfs has been calculated for DP4. The surface runoff is routed via overlot grading and curb and gutter to DP4\* which will be collected by a 15' CDOT type R at-grade inlet. The intercepted flow (Q5=13.3 cfs and Q100=20.0 cfs) will combine with flows from DP3\* and be routed east via a 30" RCP (PR6\*, Q5=16.8 cfs and Q100=29.4 cfs) to existing Detention Pond 4.

**DP5\***, 0.80 acres, consists of Basin G\* residential lots with runoff coefficients of 0.22 for the 5-year and 0.46 for the 100-year, Basin H\* existing Dines Boulevard, with runoff coefficients of 0.90 for the 5-year and 0.96 for the 100-year and flowby from Sterling Ranch Filing Nos. 1&2 MDDP DP4\*. Developed runoff of Q5=4.2 and Q100=19.7 cfs has been calculated for DP5\*. The surface runoff is routed via overlot grading and curb and gutter to DP5\* which is collected by an existing 15' CDOT type R at-grade inlet. DP5\* has an intercepted flow of (Q5=4.2 cfs and Q100=14.7 cfs) and of flowby of (Q5=0.0 cfs and Q100=5.0 cfs). Flowby from DP5\* continues on to Pond FSD13, east of Dines Boulevard. See, Sterling Ranch Filing MDDP Proposed Hydrologic Conditions Map.

**DP6\***, 4.68 acres, consists of Sterling Ranch Filing Nos. 1&2 MDDP Basins J\* and K\* planned residential lots with runoff coefficients of 0.22 for the 5-year and 0.46 for the 100-year, Sterling Ranch Filing Nos. 1&2 MDDP Basin I\* (Wheatland Drive) and Basin L\* (Dines Boulevard) with runoff coefficients of 0.90 for the 5-year and 0.96 for the 100-year. Developed runoff of Q5=14.1 cfs and Q100=26.7 cfs has been calculated for DP6\*. The surface runoff is routed via overlot grading and curb and gutter to DP6\* which is collected by an existing 15' CDOT type R at-grade inlet. DP6\* has an intercepted flow of (Q5=12.1 cfs and Q100=17.2 cfs) and of flowby of (Q5=2.0 cfs and Q100=9.5 cfs). Flowby from DP6\* continues on to Pond FSD13, east of Dines Boulevard. See, Sterling Ranch Filing MDDP Proposed Hydrologic Conditions Map.

**DP7**, 4.42 acres, consists of Basin P proposed residential lots with runoff coefficients of 0.38 for the 5-year and 0.55 for the 100-year. Developed runoff of Q5=5.7 and Q100=13.8 cfs has been calculated for DP7. Surface runoff is routed via overlot grading and curb and gutter to DP7 which is collected by a proposed 10' CDOT type R sump inlet. Flows captured by the proposed 10' CDOT type R sump inlet are routed to existing Detention Pond 4 by proposed RCP storm sewer. The flows from DP7 were anticipated in the sizing of Pond 4 per the Sterling Ranch Filing No. 1 Final Drainage Report.

**DP8**, 3.78, acres, consists of Basin Q proposed residential lots with runoff coefficients of 0.38 for the 5-year and 0.55 for the 100-year. Developed runoff of Q5=4.9 and Q100=11.8 cfs has been calculated for DP8. Surface runoff is routed via overlot grading and curb and gutter to DP8 which is collected by a proposed 10' CDOT type R sump inlet. Flows captured by the proposed 10' CDOT type R sump inlet are routed to existing Detention Pond 4 by proposed RCP storm sewer. The flows from DP8 were anticipated in the sizing of Pond 4 per the Sterling Ranch Filing No. 1 Final Drainage Report.

**DP9**, acres, consists of Basin R proposed residential lots with runoff coefficients of 0.38 for the 5-year and 0.55 for the 100-year. Developed runoff of Q5=2.2 and Q100=5.4 cfs has been calculated for DP9. Surface runoff is routed via overlot grading and curb and gutter to DP9 which is collected by a proposed 5' CDOT type R sump inlet. Flows captured by the proposed 10' CDOT type R sump inlet combine with captured flows contributed from Design Points 7 & 8 and are routed to existing Detention Pond 4 by Pipe Run 4 (Q5=12.4 and Q100=30.1 cfs). Pipe Run 4 connects to existing Sterling Ranch Filing Nos. 1&2 MDDP Pipe Run 10\* (Q5=12.5 and Q100=30.4 cfs) and is discharged into the forebay of existing Detention Pond 4. Flows contributed to the forebay of existing Pond 4 are approximately equal to those anticipated by the MDDP, therefore Pond 4 has the capacity for SWQ and Full Spectrum Detention for these flows.

**DP10**, 9.14, acres, consists of Basin T proposed residential lots with runoff coefficients of 0.30 for the 5-year and 0.50 for the 100-year. Developed runoff of Q5=9.4 and Q100=15.6 cfs has been calculated for

DP10. Surface runoff is routed via overlot grading and curb and gutter to DP10 which is collected by a proposed 15' CDOT type R at-grade inlet. DP10 has an intercepted flow of (Q5=9.1 cfs and Q100=12.7cfs) and of flowby of (Q5=0.3cfs and Q100=2.9cfs). Flows captured by the proposed 15' CDOT type R at-grade inlet are routed southwest to the proposed full spectrum detention Pond 1 by proposed RCP storm sewer.

**DP11**, 1.48, acres, consists of Basin V1 proposed residential lots with runoff coefficients of 0.38 for the 5-year and 0.55 for the 100-year. Developed runoff of Q5=1.9 and Q100=15.6 cfs has been calculated for DP11. Surface runoff is routed via overlot grading and curb and gutter to DP11 which is collected by a proposed 15' CDOT type R at-grade inlet. DP11 has an intercepted flow of (Q5=1.9cfs and Q100=12.7cfs) and of flowby of (Q5=0.0cfs and Q100=2.9cfs). Flows captured by the proposed 15' CDOT type R at-grade inlet are routed southwest to the proposed full spectrum detention Pond 1 by proposed RCP storm sewer.

**DP12**, 4.50, acres, consists of Basin U proposed residential lots with runoff coefficients of 0.38 for the 5-year and 0.55 for the 100-year and flowby from DP10. Developed runoff of Q5=6.2cfs and Q100=17.2 cfs has been calculated for DP12. Surface runoff is routed via overlot grading and curb and gutter to DP12 which is collected by a proposed 10' CDOT type R sump inlet. Flows captured by the proposed 10' CDOT type R sump inlet are routed to the proposed full spectrum detention Pond 1 by proposed RCP storm sewer.

**DP13**, 0.83, acres, consists of Basin V2 proposed residential lots with runoff coefficients of 0.38 for the 5-year and 0.55 for the 100-year and flowby from DP11. Developed runoff of Q5=1.2 and Q100=5.9cfs has been calculated for DP13. Surface runoff is routed via overlot grading and curb and gutter to DP13 which is collected by a proposed modified 5' length by 4.5' wide CDOT type R sump inlet.

**DP14**, 0.56, acres, consists of Basin W3 proposed full spectrum detention Pond 1 with runoff coefficients of 0.08 for the 5-year and 0.35 for the 100-year and contributed flow from pipe run 9. Developed runoff of Q5=19.6cfs and Q100=52.4cfs has been calculated for DP14. All flows captured by inlets at Design Points DP10, DP11, DP12 and DP13 are routed by Pipe Run 9 (PR9, Q5=17.9 and Q100=47.1 cfs) to the forebay in Pond 1 and combine with surface runoff within Basin W1. An outlet structure with an orifice plate and restrictor plate regulates release rates and provides treatment to all flows tributary to DP14. See the Water Quality Provisions discussion in this report for more information on Pond 1.

Basins labeled on the Proposed Drainage Map marked with a "\*", were previously analyzed and shown in the Final Drainage report for Sterling Ranch Filing No. 1. These basins are; B\*, C\*, D\*, E\*, F\*, G\*, H\*, I\*, L\*, & S\*. They are shown on the Proposed Drainage Map for continuity. Basins K & J additionally contribute to Design Points 3, 4, 5 & 6. Therefore, the inlets sizing at these design points has been verified.

### Detailed Drainage Discussion (Drainage Basins)

~~**Basins X1, X2, W1, and Y1** (0.78, 1.04, 0.86 and 0.084 acres respectively), consists of proposed residential backyard lots located along the eastern boundary of the site with runoff coefficients of 0.22 for the 5-year and 0.46 for the 100-year. Developed runoff of (Q5=0.8, 1.1, 0.2, and 0.8 cfs and Q100=2.8, 3.7, 1.7, and 3.0 cfs respectively has been calculated for the basins. Runoff produced within the residential backyard lots, of Basins X1, X2, W1 and Y1 will be conveyed in backyard swales and as sheet flow to a Sand Filter Basin within each lot. The treated flows will be collected by private storm sewer systems and discharged into the Sand Creek Channel. A 20' wide typical drainage easement is provided within the lots to accommodate the BMP's. The facilities constructed are to be privately maintained by the Sterling Ranch metro district.~~

**Basins X, W2, and Y** (0.22, 0.26, and 0.09 acres respectively), consists primarily of vegetated tracts and portion of residential backyards that will discharge as sheet flow to the Sand Creek Channel. The developed flow rates from Basins X, W2, and Y are Q5=0.2, 0.1, 0.1 cfs and Q100=0.8, 0.8, and 0.3 respectively. The total combined developed area being discharge to the channel is less than one acre. It

is not practicable to provide WQCV for these areas, as stated earlier in this paragraph, areas consists primarily of vegetated tracts with no development.

## **CHANNEL IMPROVEMENTS**

Slope grading and intermittent channel bank lining has been proposed for portions of the developable areas adjacent to Sand Creek to protect the developed lots and prevent excessive erosion until the DBPS recommended Sand Creek Channel improvements are installed. The proposed slope grading is intended to reduce outer bankgrades and bring uniformity to areas where significant riling and destabilization has occurred. Proposed channel stabilization improvements includes placement of soil riprap and turf reinforcement matting along embankment toes and along embankment slopes, both of which will function to retain soils and vegetation during heavy rains or larger flood flow events. All disturbed areas, not hardscaped will be re-vegetated with native species grasses, per El Paso County erosion control standards. Storm sewer outfalls into Sand Creek shall be protected by low-tailwater riprap basins. The outfall protection is shown on the accompanying drainage map in the appendix. Refer to the Homestead Filing No.2 Grading and Erosion Control Plans for riprap and turf reinforcement map placement and construction details.

Permanently installed check structures and rip-rap channel lining will be installed within Sand Creek Channel to handle the runoff from fully developed Sterling Ranch and up-gradient watershed in accordance with the Sand Creek DBPS. A discussion regarding the timing of these channel improvements is provided in a subsequent paragraph titled Sterling Ranch Filing No. 1 Subdivision Improvement agreement which follows the Construction Costs segment of this report. Financial Assurance shall be posted for the proposed Sand Creek Channel Improvements and Bank Stabilization (Slope Protection and grade control structures).

## **WATER QUALITY PROVISIONS**

The proposed Full Spectrum Detention Facility, Pond 1 functions to provide detention storage and water quality facility for runoff produced onsite from tributary Basins T, U, V1, V2 and W3. This water quality facility is designed to treat 0.245 ac-ft of water quality storage (WQCV), 0.741 ac-feet of excess urban runoff volume (EURV) and 1.331 ac-ft of 100-year storage. A rolled erosion control blanketed emergency spillway, concrete forebay, trickle channel and outlet structure, and gravel maintenance access road has been designed for Pond 1.

A 24" RCP pipe extending from the proposed modified 6'x2.9' CDOT Type D sump inlet (see Design Point 13) will convey discharge from the pond to Sand Creek. Runoff discharged to Sand Creek is anticipated to reach peak flow rates of  $Q_5=0.7$  cfs and  $Q_{100}=23.4$  cfs. A soil riprap stilling basin has been provided at the termination of the pipe to arrest erosion.

~~Runoff produced within the residential backyard lots, of Basins X1, X2, W1 and Y1 will be conveyed in backyard swales and as sheet flow to a Sand Filter Basin within each lot. The treated flows will be collected by private storm sewer systems and discharged into the Sand Creek Channel. This water quality facility, for each Sand Filter Basin, is designed to treat 0.001 ac-ft of water quality storage (WQCV), 0.005 ac-feet of excess urban runoff volume (EURV) and 0.014 ac-ft of 100-year storage. A 20' wide typical drainage easement is provided within the lots to accommodate the BMP's. The facilities constructed are to be privately maintained by the Sterling Ranch Metropolitan District. Access to maintain these sand filter basins is from the regional trail along sand creek.~~

The WQCV and EURV required for the site has been determined using the guidelines set forth in the City of Colorado Springs/El Paso County Drainage Criteria Manual - Volume II. Refer to the water quality

facility sizing calculations located within the appendix of this report(see UD-Detention Worksheet in appendix).

As previously discussed, refer to Sterling Ranch Filing Nos. 1&2 MDDP for additional information regarding existing FSD Pond 4. The previously approved FSD Pond was constructed with the Sterling Ranch Filing No. 1 construction drawings in 2018-2019.

## EROSION CONTROL

It is the policy of the El Paso County that a grading and erosion control plan be submitted with the drainage report. EPC approved “Early Grading Plan for Sterling Ranch Phase I Onsite Grading & Erosion Control”, November 18, 2015. And “Early Grading Plan for Sterling Ranch Phase I Offsite Grading & Erosion Control”, December 3, 2015. Grading and Erosion control operations are currently underway (July 2019). Grading and Erosion Control will cease with the final development of the site in the next 6-12 months.

## CONSTRUCTION COST OPINION – HOMESTEAD AT STERLING RANCH FIL. NO. 2

**Drainage Facilities:** Updated Cost Opinion included in Addendum above

Drainage improvements are planned with the development of Homestead at Sterling Ranch Filing No. 2. A majority of the construction costs have been accounted for in the “Master Development Drainage Report for Sterling Ranch Filing Nos. 1&2, and Final Drainage Report for Sterling Ranch Filing No.1” prepared by MS Civil Consultants, dated April 2017. Any additional improvements and costs are listed below.

The following list of drainage improvements are **Non-Reimbursable**. The Reimbursable facilities are outlined in the Sterling Ranch Filing No. 1 Final Drainage Report and Sterling Ranch MDDP. Refer to the MDDP for Sterling Ranch Cost and Fee Analysis Report (February 2019).

<del>Item</del>	<del>Description</del>	<del>Quantity</del>	<del>Unit Cost</del>	<del>Cost</del>
<del>1.</del>	<del>18" RCP</del>	<del>31 LF</del>	<del>\$40 /LF</del>	<del>\$1,240.00</del>
<del>2.</del>	<del>24" RCP</del>	<del>127 LF</del>	<del>\$50 /LF</del>	<del>\$6,350.00</del>
<del>3.</del>	<del>30" RCP</del>	<del>998 LF</del>	<del>\$85 /LF</del>	<del>\$84,830.00</del>
<del>4.</del>	<del>36" RCP</del>	<del>8 LF</del>	<del>\$105 /LF</del>	<del>\$840.00</del>
<del>5.</del>	<del>42" RCP</del>	<del>699 LF</del>	<del>\$185 /LF</del>	<del>\$129,315.00</del>
<del>6.</del>	<del>24" FES</del>	<del>1 EA</del>	<del>\$750 /EA</del>	<del>\$750.00</del>
<del>8.</del>	<del>42" FES</del>	<del>1 EA</del>	<del>\$1,250 /EA</del>	<del>\$1,250.00</del>
<del>9.</del>	<del>5.0'x4.5' CDOT Type R Sump Inlet</del>	<del>1 EA</del>	<del>\$4,000 /EA</del>	<del>\$4,000.00</del>
<del>10.</del>	<del>10' CDOT Type R Sump Inlet</del>	<del>4 EA</del>	<del>\$4,700 /EA</del>	<del>\$18,800.00</del>
<del>11.</del>	<del>15' CDOT Type R At-Grade Inlet</del>	<del>2 EA</del>	<del>\$6,000 /EA</del>	<del>\$12,000.00</del>
<del>12.</del>	<del>4.0' Type II MH</del>	<del>1 EA</del>	<del>\$3,500 /EA</del>	<del>\$3,500.00</del>
<del>13.</del>	<del>5.0' Type II MH</del>	<del>2 EA</del>	<del>\$4,000 /EA</del>	<del>\$8,000.00</del>
<del>14.</del>	<del>6.0' Type II MH</del>	<del>1 EA</del>	<del>\$4,500 /EA</del>	<del>\$4,500.00</del>
<del>17.</del>	<del>5.0'x6.0' MH</del>	<del>2 EA</del>	<del>\$6,500 /EA</del>	<del>\$13,000.00</del>
<del>18.</del>	<del>5.5'x5.5' MH</del>	<del>1 EA</del>	<del>\$6,500 /EA</del>	<del>\$6,500.00</del>
<del>19.</del>	<del>Headwall/Wingwall</del>	<del>1 EA</del>	<del>\$6,000 /EA</del>	<del>\$6,000.00</del>
<del>20.</del>	<del>Full Spectrum Det. Pond 1</del>	<del>1 EA</del>	<del>\$15,000 /EA</del>	<del>\$15,000.00</del>



<del>21.</del>	<del>FSD Pond 1 Outlet Structure</del>	<del>1</del>	<del>EA</del>	<del>\$12,600</del>	<del>/EA</del>	<del>\$12,600.00</del>
<del>22.</del>	<del>Ind. Lot Sand Filter Basins w/6" Pipe</del>	<del>26</del>	<del>EA</del>	<del>\$2,000</del>	<del>/EA</del>	<del>\$52,000.00</del>
<del>23.</del>	<del>18" Drain Basin Manholes w/Lids</del>	<del>27</del>	<del>EA</del>	<del>\$1,000</del>	<del>/EA</del>	<del>27,000.00</del>
<del>24.</del>	<del>12" ADS Pipe</del>	<del>1,658</del>		<del>\$26</del>	<del>/LF</del>	<del>43,108.00</del>
<b>Total \$</b>						<b><del>\$450,583.00</del></b>

The following list of drainage improvements are **Reimbursable** for the improvements to the Sand Creek Channel adjacent to Homestead at Sterling Ranch Filing No.2. The reimbursement is up to the amount as shown in the DBPS or as adjusted through the City/EPC Drainage Board.

**Sand Creek Channel Improvements**

Item	Description	Quantity	Unit Cost	Cost
1.	Rip Rap Protection	390 Ton	\$80 /Ton	\$31,200.00
2.	Drop/Check Structures	5 EA	\$75,000 /EA	\$375,000.00
3.	Slope Stabilization Blankets	7,435 SY	\$6 /SY	\$44,610.00
<b>Total</b>				<b>\$450,810.00</b>

**DRAINAGE & BRIDGE FEES – HOMESTEAD AT STERLING RANCH FIL. NO. 2**

This site is within the Sand Creek Drainage Basin. The 2019 Drainage and Bridge Fees per El Paso County for the HOMESTEAD AT STERLING RANCH FILING NO. 2 site are as follows:

Per Homestead at Sterling Ranch Filing No. 2 Plat – **Total Area 29.658 Acres**

**HOMESTEAD AT STERLING RANCH FILING NO. 2 FEES:**

<b>Drainage Fees:</b>	29.658	x	46%	\$	18,940.00	=	\$	258,392.36
<b>Bridge Fees:</b>	29.658	x	46%	\$	5,559.00	=	\$	75,839.66
<b>Total</b>								<b>\$ 334,232.02</b>

**STERLING RANCH FILING NO. 1 - SUBDIVISION IMPROVEMENTS AGREEMENT**

Sterling Ranch Filing No. 1 final plat and SIA has been recorded, and addressed the following drainage improvements Not located/and located in the Sand Creek Channel. The following SIA paragraphs outlined drainage for Sterling Ranch in the following manner;

*2. **Drainage and Landscaping Tracts:** Improvements on Tracts A, B, F, H, I, J, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z, AA and CC as identified on the final plat of Filing No. 1 will be completed to the satisfaction of the County and District and, upon said completion, the improvements will be dedicated to and accepted by the District. Improvements on Tract D (Sand Creek) will be completed to the satisfaction of the County and upon said completion; the improvements will be dedicated to and accepted by the County. The ownership and maintenance of storm drain facilities and structures not located on the foregoing tracts shall be determined as follows. All storm pipes shall be owned and maintained by the District except where located in County road rights of way (see Paragraph 5 below), in which case the County shall own and maintain the storm drain facilities and structures, including but not limited to, inlets and manholes. A typical cross section describing the ownership and maintenance responsibilities of drainage improvements within County rights of way is attached as Exhibit C hereto.*

**7. *Timing of Construction and Acceptance:***

*a. **Drainage Improvements Not Located in Sand Creek Channel:** Except as set forth below in subsection 6.b. (drainage improvements located in Sand Creek Channel), all drainage improvements described in Exhibit A and constructed within the Drainage and Landscaping Tracts identified in paragraph 2 above shall be completed by the*

*Subdivider and District, meeting all applicable standards for preliminary acceptance, prior to the recording of the first replat of Tracts C, E, G, K or BB. In the event that a portion of the drainage improvements are not completed prior to the recording of the first replat, then prior to such recording collateral sufficient in the opinion of the County to assure completion of the improvements must be posted by the Subdivider and a deadline by which such drainage improvements shall be completed shall be established by written agreement.*

*b. **Drainage Improvements Located in Sand Creek Channel (Tract D):** The District agrees that it will construct or cause the construction of all drainage improvements to be located in Tract D as well as future tracts within Sterling Ranch containing the Sand Creek Channel in accordance with the following:*

*i. Bank stabilization of the Sand Creek channel shall be required prior to any replats or other final plats adjacent to the channel. The design and installation of said improvements shall be accomplished and guaranteed through the normal subdivision review and collateralization process.*

*ii. Other drainage improvements in Tract D and future tracts containing the Sand Creek Channel, such as drop structures, check structures and similar stabilization or protection improvements, will be designed and constructed by the District with the final construction drawings to be approved by the County no later than the final platting of the 700<sup>th</sup> single family lot within the boundaries of the approved Sterling Ranch Sketch Plan and the completion of all said improvements no later than the 800<sup>th</sup> single family lot with the boundaries of the approved Sterling Ranch Sketch Plan.*

*iii. In order to assure completion of the drainage improvements required in Subsection 6.b.ii above as well as a fair apportionment of the costs of said drainage improvements amongst adjacent Sterling Ranch subdividers, the District agrees to establish a Sand Creek Channel Drainage Fee to be paid into a District Escrow Fund by adjacent subdividers at the time of final platting. The amount of the fee shall be a minimum of One Thousand Dollars (\$1,000.00) per single family lot. The details of the proposed Sand Creek Channel Drainage Fee and the District Escrow Fund shall be agreed to by the parties in advance of the submittal of the first replat of or subdivision of the Master Pad Sites or other property located within Sterling Ranch.*

A full copy of the recorded SIA is located in the files of El Paso County and EPC Clerk and Records office under Reception No. 218714151

## **SUMMARY**


Development of this site will not adversely affect the surrounding development per this final drainage report with no negative impacts to the neighboring developments. The existing and proposed drainage facilities will adequately convey, detain and route runoff from tributary and onsite flows to the Sand Creek Drainage channel. Full Spectrum Detention and Water Quality Ponds will be used to discharge developed flows into Sand Creek per the Urban Drainage criteria flow rates, which are at or less than the historic flow. Care will be taken during construction to accommodate overland flow routes onsite and temporary drainage conditions. The development of the HOMESTEAD AT STERLING RANCH FILING NO. 2 project(s) shall not adversely affect adjacent or downstream property.

## REFERENCES

- 1.) "El Paso County and City of Colorado Springs Drainage Criteria Manual, Vol I & II".
- 2.) "Urban Storm Drainage Criteria Manuals, Volumes 1-3"
- 3.) NRSC Web Soil Survey Map for El Paso County. <http://websoilsurvey.nrcs.usda.gov>
- 4.) Flood Insurance Rate Map (FIRM), Federal Emergency Management Agency, Effective date December 7, 2018.
- 5.) "Sand Creek Drainage Basin Planning Study" (DBPS) prepared by Kiowa Corporation, revised March 1996
- 6.) "Sterling Ranch-Phase 1 Offsite Grading, Early Grading & Erosion Control Plans", prepared by M&S Civil Consultants, Inc., dated November 2015
- 7.) "Sterling Ranch-Phase 1 Onsite Grading, Early Grading & Erosion Control Plans", prepared by M&S Civil Consultants, Inc., dated November 2015
- 8.) "Master Development Drainage Report for Sterling Ranch Filing Nos. 1&2 and Final Drainage Report for Sterling Ranch Filing No. 1", prepared by M&S Civil Consultants, Inc., dated April 2017
- 9.) "Sterling Ranch Filing Nos. 1&2 MDDP" prepared by MS Civil Consultants, Inc., dated October 2018.

## **APPENDIX**

**VICINITY MAP**




# VICINITY MAP


N.T.S.

**SOILS MAP**

Hydrologic Soil Group—El Paso County Area, Colorado




Map Scale: 1:4,430 if printed on A portrait (8.5" x 11") sheet.





### MAP LEGEND

**Area of Interest (AOI)**









 Area of Interest (AOI)

**Soils**

**Soil Rating Polygons**





-  A
-  A/D
-  B
-  B/D
-  C
-  C/D
-  D
-  Not rated or not available

**Soil Rating Lines**

-  A
-  A/D
-  B
-  B/D
-  C
-  C/D
-  D
-  Not rated or not available

**Soil Rating Points**






-  A
-  A/D
-  B
-  B/D

-  C
-  C/D
-  D
-  Not rated or not available

**Water Features**

 Streams and Canals

**Transportation**

-  Rails
-  Interstate Highways
-  US Routes
-  Major Roads
-  Local Roads

**Background**

 Aerial Photography

### MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:24,000.

**Warning:** Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service  
 Web Soil Survey URL:  
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: El Paso County Area, Colorado  
 Survey Area Data: Version 15, Oct 10, 2017

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: May 22, 2016—Mar 9, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

## Hydrologic Soil Group

Map unit symbol	Map unit name	Rating	Acres in AOI	Percent of AOI
71	Pring coarse sandy loam, 3 to 8 percent slopes	B	29.0	100.0%
<b>Totals for Area of Interest</b>			<b>29.0</b>	<b>100.0%</b>

### Description

Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The soils in the United States are assigned to four groups (A, B, C, and D) and three dual classes (A/D, B/D, and C/D). The groups are defined as follows:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

If a soil is assigned to a dual hydrologic group (A/D, B/D, or C/D), the first letter is for drained areas and the second is for undrained areas. Only the soils that in their natural condition are in group D are assigned to dual classes.

### Rating Options


*Aggregation Method:* Dominant Condition

*Component Percent Cutoff: None Specified*

*Tie-break Rule: Higher*

**FIRM PANEL W/ REVISED LOMR**

**EL PASO COUNTY  
UNINCORPORATED AREAS  
080059**



**SITE**

- Legend**
- 1% annual chance (100-Year) Floodplain
  - 1% annual chance (100-Year) Floodway
  - 0.2% annual chance (500-Year) Floodplain



**NATIONAL FLOOD INSURANCE PROGRAM**

**FIRM**  
FLOOD INSURANCE RATE MAP

**EL PASO COUNTY,  
COLORADO AND  
INCORPORATED  
AREAS**

**PANEL 535 OF 1300**  
(SEE MAP INDEX FOR PANELS NOT PRINTED)

**CONTAINS:**

COMMUNITY	NUMBER PANEL SUFFIX
EL PASO COUNTY, UNINCORPORATED AREAS 080059	0335 F

**REVISED TO  
REFLECT LOMR  
EFFECTIVE: July 23, 2009**

**MAP NUMBER  
08041C0535 F**

**EFFECTIVE DATE:  
MARCH 17, 1997**

Federal Emergency Management Agency

**NOTE: MAP AREA SHOWN ON  
THIS PANEL IS LOCATED WITHIN  
TOWNSHIP 12 SOUTH, RANGE 65  
WEST AND TOWNSHIP 13 SOUTH,  
RANGE 65 WEST.**

**AREA REVISED  
BY LOMR DATED  
DECEMBER 07, 2005**

# National Flood Hazard Layer FIRMette



38°58'7.45"N

104°40'35.20"W



USGS The National Map: Orthoimagery. Data refreshed October, 2017.



38°57'39.48"N

## Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

SPECIAL FLOOD HAZARD AREAS		Without Base Flood Elevation (BFE) Zone A, V, A99
		With BFE or Depth Zone AE, AO, AH, VE, AR
		Regulatory Floodway
OTHER AREAS OF FLOOD HAZARD		0.2% Annual Chance Flood Hazard, Areas of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile Zone X
		Future Conditions 1% Annual Chance Flood Hazard Zone X
		Area with Reduced Flood Risk due to Levee. See Notes. Zone X
		Area with Flood Risk due to Levee Zone D
OTHER AREAS		NO SCREEN Area of Minimal Flood Hazard Zone X
		Effective LOMRs
GENERAL STRUCTURES		Area of Undetermined Flood Hazard Zone D
		Channel, Culvert, or Storm Sewer
		Levee, Dike, or Floodwall
OTHER FEATURES		20.2 Cross Sections with 1% Annual Chance
		17.5 Water Surface Elevation
		Coastal Transect
		Base Flood Elevation Line (BFE)
		Limit of Study
		Jurisdiction Boundary
MAP PANELS		Coastal Transect Baseline
		Profile Baseline
		Hydrographic Feature
		Digital Data Available
		No Digital Data Available
		Unmapped



The pin displayed on the map is an approximate point selected by the user and does not represent an authoritative property location.

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on 1/23/2019 at 7:09:44 PM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.

104°39'57.74"W



Questions concerning the VERTCON process may be mailed to [NGS](#)

---

Latitude: 38.964784

Longitude: 104.67180

NGVD 29 height:

Datum shift (NAVD 88 minus NGVD 29): 1.196 meter

1.196 meters = 3.92 feet

NAVD88 - 3.92 feet = NGVD29

## **STORM 4 Outfall to Sand Creek Channel**

Cross Section DE = 7071.8 NAVD88

7071.8 NAVD88 - 3.92 feet = 7067.88 NGVD29

## **HYDROLOGIC CALCULATIONS**



# HOMESTEAD AT STERLING RANCH FILING NO. 2

## FINAL DRAINAGE REPORT

### (Area Drainage Summary)

From Area Runoff Coefficient Summary				OVERLAND				STREET / CHANNEL FLOW				Time of Travel (T <sub>t</sub> )		INTENSITY **		TOTAL FLOWS	
BASIN	AREA TOTAL (Acres)	C <sub>5</sub>	C <sub>100</sub>	C <sub>5</sub>	Length (ft)	Height (ft)	T <sub>C</sub> (min)	Length (ft)	Slope (%)	Velocity (fps)	T <sub>t</sub> (min)	TOTAL (min)	CHECK (min)	I <sub>5</sub> (in/hr)	I <sub>100</sub> (in/hr)	Q <sub>5</sub> (c.f.s.)	Q <sub>100</sub> (c.f.s.)
		<small>From DCM Table 5-1</small>															
<b>Proposed Area Drainage Summary</b>																	
<b>ONSITE BASINS</b>																	
<b>J</b>	0.43	0.22	0.46	0.22	90	1.8	12.0	0	2.0%	3.0	0.0	12.0	10.5	4.1	6.8	<b>0.4</b>	<b>1.3</b>
<b>K</b>	0.61	0.22	0.46	0.22	75	1.5	10.9	0	2.0%	3.0	0.0	10.9	10.4	4.1	6.8	<b>0.5</b>	<b>1.9</b>
<b>P</b>	4.42	0.38	0.55	0.38	100	2	10.3	1100	2.5%	3.0	6.0	16.4	16.7	3.4	5.7	<b>5.7</b>	<b>13.8</b>
<b>Q</b>	3.78	0.38	0.55	0.38	100	2	10.3	1100	2.5%	3.0	6.0	16.4	16.7	3.4	5.7	<b>4.9</b>	<b>11.8</b>
<b>R</b>	1.57	0.38	0.55	0.38	100	2	10.3	450	1.6%	3.0	2.5	12.8	13.1	3.8	6.3	<b>2.2</b>	<b>5.4</b>
<b>T</b>	9.14	0.30	0.50	0.30	100	2	11.5	942	2.1%	3.0	5.2	16.7	15.8	3.4	5.8	<b>9.4</b>	<b>26.4</b>
<b>U</b>	4.50	0.38	0.55	0.38	100	2	10.3	457	1.5%	3.0	2.5	12.9	13.1	3.8	6.3	<b>6.4</b>	<b>15.6</b>
<b>VI</b>	1.48	0.38	0.55	0.38	100	2	10.3	600	2.0%	3.0	3.3	13.6	13.9	3.7	6.2	<b>2.1</b>	<b>5.0</b>
<b>V2</b>	0.83	0.38	0.55	0.38	100	2	10.3	360	1.6%	3.0	2.0	12.3	12.6	3.8	6.4	<b>1.2</b>	<b>2.9</b>
<b>W1</b>	0.86	0.22	0.46	0.22	80	6	7.3	0	0.0%	2.3	0.0	7.3	10.4	4.6	7.7	<b>0.9</b>	<b>3.1</b>
<b>W2</b>	0.26	0.08	0.35	0.08	35	8	3.9	0	0.3%	2.3	0.0	5.0	10.2	5.2	8.7	<b>0.1</b>	<b>0.8</b>
<b>W3</b>	0.56	0.08	0.35	0.08	35	8	3.9	160	0.5%	2.3	1.2	5.1	11.1	5.2	8.7	<b>0.2</b>	<b>1.7</b>
<b>X</b>	0.22	0.22	0.46	0.22	80	6	7.3	0	2.5%	2.3	0.0	7.3	10.4	4.6	7.7	<b>0.2</b>	<b>0.8</b>
<b>XI</b>	0.78	0.22	0.46	0.22	80	6	7.3	0	2.5%	2.3	0.0	7.3	10.4	4.6	7.7	<b>0.8</b>	<b>2.8</b>
<b>X2</b>	1.04	0.22	0.46	0.22	80	6	7.3	0	2.5%	2.3	0.0	7.3	10.4	4.6	7.7	<b>1.1</b>	<b>3.7</b>
<b>Y</b>	0.09	0.22	0.46	0.22	80	6	7.3	0	2.5%	2.3	0.0	7.3	10.4	4.6	7.7	<b>0.1</b>	<b>0.3</b>
<b>Y1</b>	0.84	0.22	0.46	0.22	80	6	7.3	0	2.5%	2.3	0.0	7.3	10.4	4.6	7.7	<b>0.8</b>	<b>3.0</b>
<b>Y2</b>	0.21	0.22	0.46	0.22	80	6	7.3	0	2.5%	2.3	0.0	7.3	10.4	4.6	7.7	<b>0.2</b>	<b>0.7</b>
<b>OFFSITE BASINS*</b>																	
<b>B*</b>	5.39	0.38	0.55	0.38	60	1.2	8.0	1381	2.8%	3.0	7.6	16.3	18.0	3.4	5.7	<b>8.0</b>	<b>19.3</b>
<b>C*</b>	2.92	0.38	0.55	0.38	100	1.2	12.2	411	3.0%	3.0	2.3	14.5	12.8	3.8	6.3	<b>4.2</b>	<b>10.1</b>
<b>D*</b>	2.90	0.38	0.55	0.38	100	2	10.3	245	2.1%	3.0	1.3	11.7	11.9	3.9	6.5	<b>4.3</b>	<b>10.4</b>
<b>E*</b>	5.34	0.38	0.55	0.38	100	2	10.3	61	3.3%	3.0	0.3	10.7	10.9	4.0	6.8	<b>8.2</b>	<b>19.9</b>
<b>F*</b>	1.12	0.90	0.96	0.90	10	0.2	0.9	1525	2.8%	3.0	8.4	9.3	18.5	4.2	7.1	<b>4.3</b>	<b>7.7</b>
<b>G*</b>	0.61	0.22	0.46	0.22	100	2	12.6	0	2.2%	3.0	0.0	12.6	10.6	4.0	6.8	<b>0.5</b>	<b>1.9</b>
<b>H*</b>	0.19	0.90	0.96	0.90	10	0.2	0.9	280	2.1%	3.0	1.5	5.0	11.6	5.2	8.7	<b>0.9</b>	<b>1.6</b>
<b>I*</b>	2.10	0.90	0.96	0.90	10	0.2	0.9	1082	2.5%	3.0	5.9	6.9	16.1	4.7	7.9	<b>8.9</b>	<b>15.9</b>
<b>L*</b>	1.54	0.90	0.96	0.90	10	0.2	0.9	1805	2.1%	3.0	9.9	10.8	20.1	4.0	6.7	<b>5.6</b>	<b>10.0</b>
<b>S*</b>	1.97	0.08	0.35	0.08	60	10	5.6	270	0.5%	2.3	2.0	7.6	11.8	4.5	7.6	<b>0.7</b>	<b>5.3</b>

\* For detailed information on Desing Points, Basins, Flowby, or Pipe Runs see Sterling Ranch Filing Nos. 1&2 MDDP prepared by MS Civil Consultants, dated April 2017

\*\* Intensity equations assume a minimum travel time of 5 minutes.

Calculated by: ET/CMN  
 Date: 1/14/2020  
 Checked by: VAS

**HOMESTEAD AT STERLING RANCH FILING NO. 2**  
**FINAL DRAINAGE REPORT**  
**(Basin Routing Summary)**

<i>From Area Runoff Coefficient Summary</i>				<b>OVERLAND</b>				<b>PIPE / CHANNEL FLOW</b>				<b>Time of Travel (T<sub>t</sub>)</b>	<b>INTENSITY **</b>		<b>TOTAL FLOWS</b>		<b>COMMENTS</b>
<b>DESIGN POINT</b>	<b>CONTRIBUTING BASINS</b>	CA <sub>5</sub>	CA <sub>100</sub>	C <sub>5</sub>	Length (ft)	Height (ft)	T <sub>C</sub> (min)	Length (ft)	Slope (%)	Velocity (fps)	T <sub>t</sub> (min)	<b>TOTAL</b> (min)	I <sub>5</sub>	I <sub>100</sub>	Q <sub>5</sub>	Q <sub>100</sub>	
													(in/hr)	(in/hr)	(c.f.s.)	(c.f.s.)	
<b>PROPOSED DRAINAGE BASIN ROUTING SUMMARY</b>																	
2*	B*	2.34	3.39									16.3	3.4	5.7	8.0	19.3	(2) EX. 15' AT-GRADE INLETS
3*	C*	1.11	1.61									12.8	3.8	6.3	4.2	10.1	EX. 6' SUMP INLET
4*	D*, E*, F*	4.14	5.61									11.7	3.9	6.5	16.1	36.7	EX. 15' AT-GRADE INLET
5*	G*, H*, FLOWBY DP4*	1.07	3.02									11.7	3.9	6.5	4.2	19.7	EX. 15' AT-GRADE INLET
6*	I*, J, K, L*	3.50	3.97									10.8	4.0	6.7	14.1	26.7	EX. 15' AT-GRADE INLET
7	P	1.68	2.43									16.4	3.4	5.7	5.7	13.8	PROP. 10' SUMP INLET
8	Q	1.44	2.08									16.4	3.4	5.7	4.9	11.8	PROP. 10' SUMP INLET
9	R	0.60	0.86									12.8	3.8	6.3	2.2	5.4	PROP. 10' SUMP INLET
10	T	2.74	2.69									15.8	3.4	5.8	9.4	15.6	PROP. 15' AT-GRADE INLET Total CA100=3.86 Split Between DP10 & DP11 For Crown Overflow
11	VI	0.56	2.69									15.8	3.4	5.8	1.9	15.6	PROP. 15' AT-GRADE INLET Total CA100=3.86 Split Between DP10 & DP11 For Crown Overflow
12	U, FLOWBY DP10	1.80	2.98									15.8	3.4	5.8	6.2	17.2	PROP. 10' SUMP INLET
13	V2, FLOWBY DP11	0.32	0.96									13.6	3.7	6.2	1.2	5.9	PROP. MODIFIED 5'x4.5' SUMP INLET
14	W3, PR9	5.35	8.52									13.6	3.7	6.2	19.6	52.4	CUMULATIVE DETENTION POND

\* For detailed information on Desing Points, Basins, Flowby, or Pipe Runs see Sterling Ranch Filing Nos. 1&2 MDDP prepared by MS Civil Consultants, dated April 2017

\*\* Intensity equations assume a minimum travel time of 5 minutes.

Calculated by: ET/CMN  
 Date: 1/14/2020  
 Checked by: VAS

**HOMESTEAD AT STERLING RANCH FILING NO. 2**  
**DRAINAGE CALCULATIONS**  
**(Storm Sewer Routing Summary)**

PIPE RUN	Contributing Pipes/Design Points	Equivalent CA <sub>5</sub>	Equivalent CA <sub>100</sub>	Maximum T <sub>C</sub>	Intensity**		Flow		PIPE SIZE
					I <sub>5</sub>	I <sub>100</sub>	Q <sub>5</sub>	Q <sub>100</sub>	
1	DP7	1.68	2.43	16.4	3.4	5.7	5.7	13.8	24" RCP
2	DP8	1.44	2.08	16.4	3.4	5.7	4.9	11.8	18" RCP
3	PR1, PR2	3.12	4.51	16.4	3.4	5.7	10.6	25.7	24" RCP
4	DP9, PR3	3.71	5.37	17.0	3.3	5.6	12.4	30.1	30" RCP
5	DP10	2.64	2.20	15.8	3.4	5.8	9.1	12.7	18" RCP
6	DP11	0.55	2.20	15.8	3.4	5.8	1.9	12.7	18" RCP
7	PR5, PR6	3.19	4.39	16.0	3.4	5.7	10.9	25.3	30" RCP
8	DP12	1.80	2.98	15.8	3.4	5.8	6.2	17.2	24" RCP
9	DP13, PR7, PR8	5.31	8.33	16.6	3.4	5.7	17.9	47.1	42" RCP
10	UD-Detention_v3.07						0.7	23.4	Outlet Structure & 18" CMP
11	Pipe Run continued from MDDP DP15* to Sand Creek. Flow values are that of MDDP Pipe Run 15* (PR15*).						42.1	76.8	42" RCP
<del>12</del>	<del>Lots 36-41</del>						<del>0.0</del>	<del>1.3</del>	<del>12" ADS</del>
<del>13</del>	<del>Lots 28-35</del>						<del>0.0</del>	<del>1.6</del>	<del>12" ADS</del>
<del>14</del>	<del>Lots 19-24</del>						<del>0.0</del>	<del>1.5</del>	<del>12" ADS</del>
<del>15</del>	<del>Lots 13-18</del>						<del>0.0</del>	<del>1.4</del>	<del>12" ADS</del>

\* For detailed information on Desing Points, Basins, Flowby, or Pipe Runs see Sterling Ranch Filing Nos. 1&2 MDDP prepared by MS Civil Consultants, dated April 2017

\*\* Intensity equations assume a minimum travel time of 5 minutes.

DP - Design Point  
EX - Existing Design Point

FB- Flow By from Design Point  
INT- Intercepted Flow from Design Point

Calculated by: CMN  
Date: 1/14/2020  
Checked by: VAS

Updated SF-3 routing for Basins X1, X2, W1, & Y1 included in Addendum above.


## **HYDRAULIC CALCULATIONS**

<i>Weighted Percent Imperviousness of FSD Pond 1</i>				
<i>Contributing Basins</i>	<i>Area (Acres)</i>	<i>C<sub>s</sub></i>	<i>Impervious % (I)</i>	<i>(Acres)*(I)</i>
<i>T</i>	9.14	0.30	40	365.60
<i>U</i>	4.50	0.38	53	238.50
<i>V1</i>	1.48	0.38	53	78.44
<i>V2</i>	0.83	0.38	53	43.99
<i>W1</i>	0.56	0.08	2	1.12
<b><i>Totals</i></b>	<b>16.51</b>			<b>727.65</b>
<b><i>Imperviousness of FSD Pond 1</i></b>	<b>44.1</b>	<b>%</b>		

**DETENTION BASIN STAGE-STORAGE TABLE BUILDER**

UD-Detention, Version 3.07 (February 2017)

Project: **Homestead At Sterling Ranch Filings Nos. 2**  
 Basin ID: **FSD Pond 1**



**Example Zone Configuration (Retention Pond)**

**Required Volume Calculation**

Selected BMP Type =	<b>EDB</b>		
Watershed Area =	16.51	acres	
Watershed Length =	875	ft	
Watershed Slope =	0.020	ft/ft	
Watershed Imperviousness =	44.10%	percent	
Percentage Hydrologic Soil Group A =	0.0%	percent	
Percentage Hydrologic Soil Group B =	100.0%	percent	
Percentage Hydrologic Soil Groups C/D =	0.0%	percent	
Desired WQC Drain Time =	40.0	hours	
Location for 1-hr Rainfall Depths =	User Input		
Water Quality Capture Volume (WQCv) =	0.262	acre-feet	Optional User Override 1-Hr Precipitation
Excess Urban Runoff Volume (EURV) =	0.771	acre-feet	
2-yr Runoff Volume (P1 = 1.19 in.) =	0.614	acre-feet	1.19 inches
5-yr Runoff Volume (P1 = 1.5 in.) =	0.847	acre-feet	1.50 inches
10-yr Runoff Volume (P1 = 1.75 in.) =	1.177	acre-feet	1.75 inches
25-yr Runoff Volume (P1 = 2 in.) =	1.710	acre-feet	2.00 inches
50-yr Runoff Volume (P1 = 2.25 in.) =	2.073	acre-feet	2.25 inches
100-yr Runoff Volume (P1 = 2.52 in.) =	2.550	acre-feet	2.52 inches
500-yr Runoff Volume (P1 = 0 in.) =	0.000	acre-feet	inches
Approximate 2-yr Detention Volume =	0.574	acre-feet	
Approximate 5-yr Detention Volume =	0.795	acre-feet	
Approximate 10-yr Detention Volume =	1.075	acre-feet	
Approximate 25-yr Detention Volume =	1.190	acre-feet	
Approximate 50-yr Detention Volume =	1.247	acre-feet	
Approximate 100-yr Detention Volume =	1.412	acre-feet	


**Stage-Storage Calculation**

Zone 1 Volume (WQCv) =	0.262	acre-feet	
Zone 2 Volume (EURV - Zone 1) =	0.508	acre-feet	
Zone 3 Volume (100-year - Zones 1 & 2) =	0.642	acre-feet	
Total Detention Basin Volume =	1.412	acre-feet	
Initial Surcharge Volume (SV) =	user	ft <sup>3</sup>	
Initial Surcharge Depth (ISD) =	user	ft	
Total Available Detention Depth (H <sub>total</sub> ) =	user	ft	
Depth of Trickle Channel (H <sub>TC</sub> ) =	user	ft	
Slope of Trickle Channel (S <sub>TC</sub> ) =	user	ft/ft	
Slopes of Main Basin Sides (S <sub>mb</sub> ) =	user	H:V	
Basin Length-to-Width Ratio (R <sub>lv</sub> ) =	user		
Initial Surcharge Area (A <sub>sv</sub> ) =	user	ft <sup>2</sup>	
Surcharge Volume Length (L <sub>sv</sub> ) =	user	ft	
Surcharge Volume Width (W <sub>sv</sub> ) =	user	ft	
Depth of Basin Floor (H <sub>100yr</sub> ) =	user	ft	
Length of Basin Floor (L <sub>100yr</sub> ) =	user	ft	
Width of Basin Floor (W <sub>100yr</sub> ) =	user	ft	
Area of Basin Floor (A <sub>100yr</sub> ) =	user	ft <sup>2</sup>	
Volume of Basin Floor (V <sub>100yr</sub> ) =	user	ft <sup>3</sup>	
Depth of Main Basin (H <sub>mb</sub> ) =	user	ft	
Length of Main Basin (L <sub>mb</sub> ) =	user	ft	
Width of Main Basin (W <sub>mb</sub> ) =	user	ft	
Area of Main Basin (A <sub>mb</sub> ) =	user	ft <sup>2</sup>	
Volume of Main Basin (V <sub>mb</sub> ) =	user	ft <sup>3</sup>	
Calculated Total Basin Volume (V <sub>total</sub> ) =	user	acre-feet	

Depth Increment =										
Stage - Storage Description	Stage (ft)	Optional Override Stage (ft)	Length (ft)	Width (ft)	Area (ft <sup>2</sup> )	Optional Override Area (ft <sup>2</sup> )	Area (acre)	Volume (ft <sup>3</sup> )	Volume (ac-ft)	
Top of Micropool	76.17	0.00				0	0.000			
	76.4	0.33				40	0.001	7	0.000	
	77	0.83				100	0.002	40	0.001	
	78.00	1.83				4,187	0.096	2,143	0.049	
	80.00	3.83				8,006	0.184	14,378	0.330	
	82.00	5.83				11,106	0.255	33,490	0.769	
	84.00	7.83				14,529	0.334	59,125	1.357	
	86.00	9.83				18,087	0.415	91,741	2.106	

# DETENTION BASIN STAGE-STORAGE TABLE BUILDER

UD-Detention, Version 3.07 (February 2017)




## Detention Basin Outlet Structure Design

UD-Detention, Version 3.07 (February 2017)

Project: \_\_\_\_\_

Basin ID: \_\_\_\_\_



	Stage (ft)	Zone Volume (ac-ft)	Outlet Type
Zone 1 (WQCV)	3.45	0.262	Orifice Plate
Zone 2 (EURV)	5.84	0.508	Orifice Plate
Zone 3 (100-year)	8.00	0.642	Weir&Pipe (Restrict)
<b>Total</b>		1.412	

**User Input: Orifice at Underdrain Outlet (typically used to drain WQCV in a Filtration BMP)**

Underdrain Orifice Invert Depth =  ft (distance below the filtration media surface)  
 Underdrain Orifice Diameter =  inches

**Calculated Parameters for Underdrain**

Underdrain Orifice Area =  ft<sup>2</sup>  
 Underdrain Orifice Centroid =  feet

**User Input: Orifice Plate with one or more orifices or Elliptical Slot Weir (typically used to drain WQCV and/or EURV in a sedimentation BMP)**

Invert of Lowest Orifice =  ft (relative to basin bottom at Stage = 0 ft)  
 Depth at top of Zone using Orifice Plate =  ft (relative to basin bottom at Stage = 0 ft)  
 Orifice Plate: Orifice Vertical Spacing =  inches  
 Orifice Plate: Orifice Area per Row =  sq. inches (diameter = 1-3/16 inches)

**Calculated Parameters for Plate**

WQ Orifice Area per Row =  ft<sup>2</sup>  
 Elliptical Half-Width =  feet  
 Elliptical Slot Centroid =  feet  
 Elliptical Slot Area =  ft<sup>2</sup>

**User Input: Stage and Total Area of Each Orifice Row (numbered from lowest to highest)**

	Row 1 (required)	Row 2 (optional)	Row 3 (optional)	Row 4 (optional)	Row 5 (optional)	Row 6 (optional)	Row 7 (optional)	Row 8 (optional)
Stage of Orifice Centroid (ft)	0.00	1.95	3.89					
Orifice Area (sq. inches)	1.19	1.19	1.19					
Stage of Orifice Centroid (ft)								
Orifice Area (sq. inches)								

**User Input: Vertical Orifice (Circular or Rectangular)**

	Not Selected	Not Selected	
Invert of Vertical Orifice =	N/A	N/A	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Vertical Orifice =	N/A	N/A	ft (relative to basin bottom at Stage = 0 ft)
Vertical Orifice Diameter =	N/A	N/A	inches

**Calculated Parameters for Vertical Orifice**

	Not Selected	Not Selected	
Vertical Orifice Area =	N/A	N/A	ft <sup>2</sup>
Vertical Orifice Centroid =	N/A	N/A	feet

**User Input: Overflow Weir (Dropbox) and Grate (Flat or Sloped)**

	Zone 3 Weir	Not Selected	
Overflow Weir Front Edge Height, Ho =	5.84	N/A	ft (relative to basin bottom at Stage = 0 ft)
Overflow Weir Front Edge Length =	6.00	N/A	feet
Overflow Weir Slope =	3.00	N/A	H:V (enter zero for flat grate)
Horiz. Length of Weir Sides =	2.91	N/A	feet
Overflow Grate Open Area % =	70%	N/A	%, grate open area/total area
Debris Clogging % =	50%	N/A	%

**Calculated Parameters for Overflow Weir**

	Zone 3 Weir	Not Selected	
Height of Grate Upper Edge, H <sub>1</sub> =	6.81	N/A	feet
Overflow Weir Slope Length =	3.07	N/A	feet
Grate Open Area / 100-yr Orifice Area =	7.21	N/A	should be ≥ 4
Overflow Grate Open Area w/o Debris =	12.88	N/A	ft <sup>2</sup>
Overflow Grate Open Area w/ Debris =	6.44	N/A	ft <sup>2</sup>

**User Input: Outlet Pipe w/ Flow Restriction Plate (Circular Orifice, Restrictor Plate, or Rectangular Orifice)**

	Zone 3 Restrictor	Not Selected	
Depth to Invert of Outlet Pipe =	0.25	N/A	ft (distance below basin bottom at Stage = 0 ft)
Outlet Pipe Diameter =	24.00	N/A	inches
Restrictor Plate Height Above Pipe Invert =	13.30	N/A	inches

**Calculated Parameters for Outlet Pipe w/ Flow Restriction Plate**

	Zone 3 Restrictor	Not Selected	
Outlet Orifice Area =	1.79	N/A	ft <sup>2</sup>
Outlet Orifice Centroid =	0.63	N/A	feet
Half-Central Angle of Restrictor Plate on Pipe =	1.68	N/A	radians

**User Input: Emergency Spillway (Rectangular or Trapezoidal)**

Spillway Invert Stage =  ft (relative to basin bottom at Stage = 0 ft)  
 Spillway Crest Length =  feet  
 Spillway End Slopes =  H:V  
 Freeboard above Max Water Surface =  feet

**Calculated Parameters for Spillway**

Spillway Design Flow Depth =  feet  
 Stage at Top of Freeboard =  feet  
 Basin Area at Top of Freeboard =  acres




**Routed Hydrograph Results**

	WQCV	EURV	2 Year	5 Year	10 Year	25 Year	50 Year	100 Year	500 Year
Design Storm Return Period =									
One-Hour Rainfall Depth (in) =	0.53	1.07	1.19	1.50	1.75	2.00	2.25	2.52	0.00
Calculated Runoff Volume (acre-ft) =	0.262	0.771	0.614	0.847	1.177	1.710	2.073	2.550	0.000
OPTIONAL Override Runoff Volume (acre-ft) =									
Inflow Hydrograph Volume (acre-ft) =	0.262	0.771	0.614	0.847	1.176	1.710	2.074	2.551	#N/A
Predevelopment Unit Peak Flow, q (cfs/acre) =	0.00	0.00	0.02	0.03	0.27	0.84	1.16	1.55	0.00
Predevelopment Peak Q (cfs) =	0.0	0.0	0.3	0.4	4.4	13.9	19.2	25.5	0.0
Peak Inflow Q (cfs) =	5.3	15.5	12.4	17.0	23.5	34.1	41.2	50.5	#N/A
Peak Outflow Q (cfs) =	0.1	0.2	0.2	0.7	6.0	15.8	22.3	23.4	#N/A
Ratio Peak Outflow to Predevelopment Q =	N/A	N/A	N/A	1.5	1.4	1.1	1.2	0.9	#N/A
Structure Controlling Flow =	Plate	Plate	Plate	Overflow Grate 1	Overflow Grate 1	Overflow Grate 1	Outlet Plate 1	Outlet Plate 1	#N/A
Max Velocity through Grate 1 (fps) =	N/A	N/A	N/A	0.0	0.4	1.2	1.7	1.8	#N/A
Max Velocity through Grate 2 (fps) =	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	#N/A
Time to Drain 97% of Inflow Volume (hours) =	39	69	62	71	69	66	63	61	#N/A
Time to Drain 99% of Inflow Volume (hours) =	40	73	65	76	75	74	73	72	#N/A
Maximum Ponding Depth (ft) =	3.35	5.72	5.08	5.96	6.44	6.91	7.15	7.75	#N/A
Area at Maximum Ponding Depth (acres) =	0.16	0.25	0.23	0.26	0.28	0.30	0.31	0.33	#N/A
Maximum Volume Stored (acre-ft) =	0.245	0.741	0.588	0.802	0.932	1.067	1.137	1.331	#N/A



# Detention Basin Outlet Structure Design

UD-Detention, Version 3.07 (February 2017)



S-A-V-D Chart Axis Override	X-axis	Left Y-Axis	Right Y-Axis
minimum bound			
maximum bound			



PROJECT: Homestead Piling No. 2  
DATE: \_\_\_\_\_

Micropool Surface Area

$$TIA = I \times A$$

$$(0.441 \times 1651)$$

$$TIA = 7.3 \sim 8.0$$

From Micropool Sizing Chart (SA) Micropool SA = 440 sf →

Tributary Area = 16.51 ac  
Imperviousness = 44.1%

Forebay Volume for F&D Pond

Tributary Area = 16.51 ac

Min. Forebay Volume = 3.0% of WQCV (WQFED T-5, EDB-4)

WQCV for F&D Pond = 0.262 ac-ft

$$\text{Total Volume Req'd} = 0.03 (0.262) \frac{43560}{1 \text{ ac-ft}} = 342 \text{ cf}$$

$$\text{Area} = 283 - 7 (\text{wall}) = 276 \text{ sf}$$

$$\begin{matrix} 276 & \times & 1.25 \text{ ht} & = & 345 & > & 342 & \text{ Forebay } 15" \text{ depth} \rightarrow \\ \text{(forebay area)} & & \text{(depth)} & & \text{(volume provided)} & & & \end{matrix}$$

Size notch in forebay to accommodate 2% of 100 yr. (WQFED T-5 EDB)

$$Q_{100} = 47.1 \text{ cfs} \Rightarrow 0.02 \times 47.1 = 0.94$$

$$\text{Using Ret. Weir Eqn. } Q = \frac{3.247 L \cdot H^{1.48} - 0.566 \cdot L^{1.9} H^{1.9}}{1 + 2L^{0.87}}$$

$$\text{Solve for } L = 2.6" \quad Q = 0.94$$

Use a 2.6" notch →

PROJECT: Homestead Filing No. 2

DATE: \_\_\_\_\_

Riprap Apron For Pond 1

Riprap Sizing

$Q_{100} = 47.1$  cfs (Pipe Run 9)

$D_c = 42" = 3.5'$

$\frac{Q}{D^{2.5}} < 6$  Then use Figure 9-38 (UDFCO Vol. 2)

$\frac{47.1}{(3.5)^{2.5}} = 2.05 < 6$  Therefore use Figure 9-38  
and  $\frac{1}{2} \sqrt{D_c} = 0.40 \phi \frac{Q}{D^{1.5}} = \frac{47.1}{(3.5)^{1.5}} = 7.19$


Use Type L  $D_{50} = 9"$

Riprap Depth

$T = 2 D_{50}$   
 $= 2(9")$   
 $T = 18" \text{ or } 1.5'$

Low Tailwater Riprap Basin

42" Pipe




### DETENTION BASIN STAGE-STORAGE TABLE BUILDER

UD-Detention, Version 3.07 (February 2017)

Project: **Homestead at Sterling Ranch Filing No.2**

Basin ID: **Lots 14, 15, 21-24, 41 Lot size 10,319 sq ft-15,049 sq ft**



#### Required Volume Calculation

Selected BMP Type =	<b>SF</b>	
Watershed Area =	0.18	acres
Watershed Length =	82	ft
Watershed Slope =	0.080	ft/ft
Watershed Imperviousness =	42.00%	percent
Percentage Hydrologic Soil Group A =	0.0%	percent
Percentage Hydrologic Soil Group B =	100.0%	percent
Percentage Hydrologic Soil Groups C/D =	0.0%	percent
Desired WQCV Drain Time =	12.0	hours
Location for 1-hr Rainfall Depths =	User Input	
Water Quality Capture Volume (WQCV) =	0.002	acre-feet
Excess Urban Runoff Volume (EURV) =	0.008	acre-feet
2-yr Runoff Volume (P1 = 1.19 in.) =	0.006	acre-feet
5-yr Runoff Volume (P1 = 1.5 in.) =	0.009	acre-feet
10-yr Runoff Volume (P1 = 1.75 in.) =	0.012	acre-feet
25-yr Runoff Volume (P1 = 2 in.) =	0.018	acre-feet
50-yr Runoff Volume (P1 = 2.25 in.) =	0.022	acre-feet
100-yr Runoff Volume (P1 = 2.52 in.) =	0.027	acre-feet
500-yr Runoff Volume (P1 = 0 in.) =	0.000	acre-feet
Approximate 2-yr Detention Volume =	0.006	acre-feet
Approximate 5-yr Detention Volume =	0.008	acre-feet
Approximate 10-yr Detention Volume =	0.011	acre-feet
Approximate 25-yr Detention Volume =	0.012	acre-feet
Approximate 50-yr Detention Volume =	0.013	acre-feet
Approximate 100-yr Detention Volume =	0.015	acre-feet

Note: L / W R  
L / W Ratio =

#### Stage-Storage Calculation

Zone 1 Volume (WQCV) =	0.002	acre-feet
Zone 2 Volume (EURV - Zone 1) =	0.006	acre-feet
Zone 3 Volume (100-year - Zones 1 & 2) =	0.007	acre-feet
Total Detention Basin Volume =	0.015	acre-feet
Initial Surcharge Volume (ISV) =	N/A	ft <sup>3</sup>
Initial Surcharge Depth (ISD) =	N/A	ft
Total Available Detention Depth (H <sub>Total</sub> ) =	user	ft
Depth of Trickle Channel (H <sub>TC</sub> ) =	N/A	ft
Slope of Trickle Channel (S <sub>TC</sub> ) =	N/A	ft/ft
Slopes of Main Basin Sides (S <sub>main</sub> ) =	user	H:V

Depth Increment = 0.5 ft

Stage - Storage Description	Stage (ft)	Optional Override Stage (ft)	Length (ft)	Width (ft)	Area (ft <sup>2</sup> )	Optional Override Area (ft <sup>2</sup> )	Area (acre)	Volume (ft <sup>3</sup> )	Volume (ac-ft)
Media Surface	--	0.00	--	--	--	77	0.002	--	--
7065.27	7065.5	0.50	--	--	--	152	0.003	56	0.001
7066	--	1.00	--	--	--	328	0.008	174	0.004
7066.50	--	1.50	--	--	--	543	0.012	390	0.009
7067.00	--	2.00	--	--	--	796	0.018	722	0.017
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--


Optional User Override 1-hr Precipitation		
1.19	inches	
1.50	inches	
1.75	inches	
2.00	inches	
2.25	inches	
2.52	inches	
	inches	



## Detention Basin Outlet Structure Design

UD-Detention, Version 3.07 (February 2017)

Project: Homestead at Sterling Ranch Filing No.2  
Basin ID: Lot 14, 15, 21-24, 41



Example Zone Configuration (Retention Pond)

	Stage (ft)	Zone Volume (ac-ft)	Outlet Type
Zone 1 (WQCV)	0.71	0.002	Filtration Media
Zone 2 (EURV)	1.41	0.006	Rectangular Orifice
Zone 3 (100-year)	1.90	0.007	Rectangular Orifice
		0.015	Total

User Input: Orifice at Underdrain Outlet (typically used to drain WQCV in a Filtration BMP)

Underdrain Orifice Invert Depth =	2.10	ft (distance below the filtration media surface)
Underdrain Orifice Diameter =	0.13	inches

Calculated Parameters for Underdrain

Underdrain Orifice Area =	0.0	ft <sup>2</sup>
Underdrain Orifice Centroid =	0.01	feet

User Input: Orifice Plate with one or more orifices or Elliptical Slot Weir (typically used to drain WQCV and/or EURV in a sedimentation BMP)

Invert of Lowest Orifice =	N/A	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Orifice Plate =	N/A	ft (relative to basin bottom at Stage = 0 ft)
Orifice Plate: Orifice Vertical Spacing =	N/A	inches
Orifice Plate: Orifice Area per Row =	N/A	inches

Calculated Parameters for Plate

WQ Orifice Area per Row =	N/A	ft <sup>2</sup>
Elliptical Half-Width =	N/A	feet
Elliptical Slot Centroid =	N/A	feet
Elliptical Slot Area =	N/A	ft <sup>2</sup>

User Input: Stage and Total Area of Each Orifice Row (numbered from lowest to highest)

	Row 1 (optional)	Row 2 (optional)	Row 3 (optional)	Row 4 (optional)	Row 5 (optional)	Row 6 (optional)	Row 7 (optional)	Row 8 (optional)
Stage of Orifice Centroid (ft)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Orifice Area (sq. inches)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

	Row 9 (optional)	Row 10 (optional)	Row 11 (optional)	Row 12 (optional)	Row 13 (optional)	Row 14 (optional)	Row 15 (optional)	Row 16 (optional)
Stage of Orifice Centroid (ft)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Orifice Area (sq. inches)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

User Input: Vertical Orifice (Circular or Rectangular)

	Zone 2 Rectangular	Zone 3 Rectangular	
Invert of Vertical Orifice =	0.71	1.41	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Vertical Orifice =	1.41	1.90	ft (relative to basin bottom at Stage = 0 ft)
Vertical Orifice Height =	2.00	2.00	inches
Vertical Orifice Width =	1.00	6.00	inches

Calculated Parameters for Vertical Orifice

	Zone 2 Rectangular	Zone 3 Rectangular	
Vertical Orifice Area =	0.01	0.08	ft <sup>2</sup>
Vertical Orifice Centroid =	0.08	0.08	feet

User Input: Overflow Weir (Dropbox) and Grate (Flat or Sloped)

	Not Selected	Not Selected	
Overflow Weir Front Edge Height, H <sub>o</sub> =	1.88	N/A	ft (relative to basin bottom at Stage = 0 ft)
Overflow Weir Front Edge Length =	1.00	N/A	feet
Overflow Weir Slope =	0.00	N/A	H:V (enter zero for flat grate)
Horiz. Length of Weir Sides =	1.00	N/A	feet
Overflow Grate Open Area % =	70%	N/A	% grate open area/total area
Debris Clogging % =	50%	N/A	%

Calculated Parameters for Overflow Weir

	Not Selected	Not Selected	
Height of Grate Upper Edge, H <sub>1</sub> =	1.88	N/A	feet
Over Flow Weir Slope Length =	1.00	N/A	feet
Grate Open Area / 100-yr Orifice Area =	N/A	N/A	should be ≥ 4
Overflow Grate Open Area w/o Debris =	0.70	N/A	ft <sup>2</sup>
Overflow Grate Open Area w/ Debris =	0.35	N/A	ft <sup>2</sup>

User Input: Outlet Pipe w/ Flow Restriction Plate (Circular Orifice, Restrictor Plate, or Rectangular Orifice)

	Not Selected	Not Selected	
Depth to Invert of Outlet Pipe =	N/A	N/A	ft (distance below basin bottom at Stage = 0 ft)
Circular Orifice Diameter =	N/A	N/A	inches

Calculated Parameters for Outlet Pipe w/ Flow Restriction Plate

	Not Selected	Not Selected	
Outlet Orifice Area =	N/A	N/A	ft <sup>2</sup>
Outlet Orifice Centroid =	N/A	N/A	feet
Half-Central Angle of Restrictor Plate on Pipe =	N/A	N/A	radians

User Input: Emergency Spillway (Rectangular or Trapezoidal)

Spillway Invert Stage =	1.90	ft (relative to basin bottom at Stage = 0 ft)
Spillway Crest Length =	2.00	feet
Spillway End Slopes =	4.00	H:V
Freeboard above Max Water Surface =	0.25	feet

Calculated Parameters for Spillway




Spillway Design Flow Depth =	0.14	feet
Stage at Top of Freeboard =	2.29	feet
Basin Area at Top of Freeboard =	0.02	acres

### Routed Hydrograph Results

	WQCV	EURV	2 Year	5 Year	10 Year	25 Year	50 Year	100 Year	500 Year
Design Storm Return Period =									
One-Hour Rainfall Depth (in) =	0.53	1.07	1.19	1.50	1.75	2.00	2.25	2.52	0.00
Calculated Runoff Volume (acre-ft) =	0.002	0.008	0.006	0.009	0.012	0.018	0.022	0.027	0.000
OPTIONAL Override Runoff Volume (acre-ft) =									
Inflow Hydrograph Volume (acre-ft) =	0.001	0.007	0.006	0.008	0.012	0.018	0.021	0.027	#N/A
Predevelopment Unit Peak Flow, q (cfs/acre) =	0.00	0.00	0.02	0.03	0.32	0.97	1.34	1.78	0.00
Predevelopment Peak Q (cfs) =	0.0	0.0	0.0	0.0	0.1	0.2	0.2	0.3	0.0
Peak Inflow Q (cfs) =	0.0	0.2	0.2	0.2	0.3	0.5	0.6	0.8	#N/A
Peak Outflow Q (cfs) =	0.0	0.0	0.0	0.0	0.1	0.2	0.3	0.3	#N/A
Ratio Peak Outflow to Predevelopment Q =	N/A	N/A	N/A	8.1	1.4	1.2	1.1	1.0	#N/A
Structure Controlling Flow =	Filtration Media	Vertical Orifice 1	Vertical Orifice 1	Vertical Orifice 1	Vertical Orifice 2	Vertical Orifice 2	Vertical Orifice 2	Vertical Orifice 2	#N/A
Max Velocity through Grate 1 (fps) =	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	#N/A
Max Velocity through Grate 2 (fps) =	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	#N/A
Time to Drain 97% of Inflow Volume (hours) =	12	40	40	39	38	35	33	30	#N/A
Time to Drain 99% of Inflow Volume (hours) =	12	43	43	43	43	42	41	40	#N/A
Maximum Ponding Depth (ft) =	0.27	1.17	1.01	1.24	1.47	1.62	1.72	1.88	#N/A
Area at Maximum Ponding Depth (acres) =	0.00	0.01	0.01	0.01	0.01	0.01	0.02	0.02	#N/A
Maximum Volume Stored (acre-ft) =	0.001	0.005	0.004	0.006	0.009	0.011	0.012	0.014	#N/A

# Detention Basin Outlet Structure Design

UD-Detention, Version 3.07 (February 2017)



S-A-V-D Chart Axis Override

	X-axis	Left Y-Axis	Right Y-Axis
minimum bound			
maximum bound			






## Detention Basin Outlet Structure Design

UD-Detention, Version 3.07 (February 2017)

Project: Homestead at Sterling Ranch Filing No.2

Basin ID: Lots 13, 16-20, 28-40 Lots size 7,800 sq-ft -9830 sq-ft



Example Zone Configuration (Retention Pond)

	Stage (ft)	Zone Volume (ac-ft)	Outlet Type
Zone 1 (WQCV)	0.40	0.002	Filtration Media
Zone 2 (EURV)	0.89	0.004	Rectangular Orifice
Zone 3 (100-year)	1.24	0.005	Rectangular Orifice
		0.010	Total

User Input: Orifice at Underdrain Outlet (typically used to drain WQCV in a Filtration BMP)

Underdrain Orifice Invert Depth =	2.10	ft (distance below the filtration media surface)
Underdrain Orifice Diameter =	0.13	inches

Calculated Parameters for Underdrain

Underdrain Orifice Area =	0.0	ft <sup>2</sup>
Underdrain Orifice Centroid =	0.01	feet

User Input: Orifice Plate with one or more orifices or Elliptical Slot Weir (typically used to drain WQCV and/or EURV in a sedimentation BMP)

Invert of Lowest Orifice =	N/A	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Orifice Plate =	N/A	ft (relative to basin bottom at Stage = 0 ft)
Orifice Plate: Orifice Vertical Spacing =	N/A	inches
Orifice Plate: Orifice Area per Row =	N/A	inches

Calculated Parameters for Plate

WQ Orifice Area per Row =	N/A	ft <sup>2</sup>
Elliptical Half-Width =	N/A	feet
Elliptical Slot Centroid =	N/A	feet
Elliptical Slot Area =	N/A	ft <sup>2</sup>

User Input: Stage and Total Area of Each Orifice Row (numbered from lowest to highest)

	Row 1 (optional)	Row 2 (optional)	Row 3 (optional)	Row 4 (optional)	Row 5 (optional)	Row 6 (optional)	Row 7 (optional)	Row 8 (optional)
Stage of Orifice Centroid (ft)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Orifice Area (sq. inches)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

	Row 9 (optional)	Row 10 (optional)	Row 11 (optional)	Row 12 (optional)	Row 13 (optional)	Row 14 (optional)	Row 15 (optional)	Row 16 (optional)
Stage of Orifice Centroid (ft)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Orifice Area (sq. inches)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

User Input: Vertical Orifice (Circular or Rectangular)

	Zone 2 Rectangular	Zone 3 Rectangular	
Invert of Vertical Orifice =	0.40	0.89	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Vertical Orifice =	0.89	1.24	ft (relative to basin bottom at Stage = 0 ft)
Vertical Orifice Height =	2.00	2.00	inches
Vertical Orifice Width =	1.00	3.50	inches

Calculated Parameters for Vertical Orifice

	Zone 2 Rectangular	Zone 3 Rectangular	
Vertical Orifice Area =	0.01	0.05	ft <sup>2</sup>
Vertical Orifice Centroid =	0.08	0.08	feet

User Input: Overflow Weir (Dropbox) and Grate (Flat or Sloped)

	Not Selected	Not Selected	
Overflow Weir Front Edge Height, H <sub>o</sub> =	1.24	N/A	ft (relative to basin bottom at Stage = 0 ft)
Overflow Weir Front Edge Length =	1.00	N/A	feet
Overflow Weir Slope =	0.00	N/A	H:V (enter zero for flat grate)
Horiz. Length of Weir Sides =	1.00	N/A	feet
Overflow Grate Open Area % =	70%	N/A	% grate open area/total area
Debris Clogging % =	50%	N/A	%

Calculated Parameters for Overflow Weir

	Not Selected	Not Selected	
Height of Grate Upper Edge, H <sub>t</sub> =	1.24	N/A	feet
Over Flow Weir Slope Length =	1.00	N/A	feet
Grate Open Area / 100-yr Orifice Area =	N/A	N/A	should be ≥ 4
Overflow Grate Open Area w/o Debris =	0.70	N/A	ft <sup>2</sup>
Overflow Grate Open Area w/ Debris =	0.35	N/A	ft <sup>2</sup>

User Input: Outlet Pipe w/ Flow Restriction Plate (Circular Orifice, Restrictor Plate, or Rectangular Orifice)

	Not Selected	Not Selected	
Depth to Invert of Outlet Pipe =	N/A	N/A	ft (distance below basin bottom at Stage = 0 ft)
Circular Orifice Diameter =	N/A	N/A	inches

Calculated Parameters for Outlet Pipe w/ Flow Restriction Plate

	Not Selected	Not Selected	
Outlet Orifice Area =	N/A	N/A	ft <sup>2</sup>
Outlet Orifice Centroid =	N/A	N/A	feet
Half-Central Angle of Restrictor Plate on Pipe =	N/A	N/A	radians

User Input: Emergency Spillway (Rectangular or Trapezoidal)

Spillway Invert Stage =	1.24	ft (relative to basin bottom at Stage = 0 ft)
Spillway Crest Length =	2.00	feet
Spillway End Slopes =	4.00	H:V
Freeboard above Max Water Surface =	0.25	feet

Calculated Parameters for Spillway




Spillway Design Flow Depth =	0.14	feet
Stage at Top of Freeboard =	1.63	feet
Basin Area at Top of Freeboard =	0.02	acres

### Routed Hydrograph Results

	WQCV	EURV	2 Year	5 Year	10 Year	25 Year	50 Year	100 Year	500 Year
Design Storm Return Period =									
One-Hour Rainfall Depth (in) =	0.83	1.07	1.19	1.50	1.75	2.00	2.25	2.52	0.00
Calculated Runoff Volume (acre-ft) =	0.002	0.006	0.004	0.006	0.008	0.012	0.015	0.018	0.000
OPTIONAL Override Runoff Volume (acre-ft) =									
Inflow Hydrograph Volume (acre-ft) =	0.001	0.005	0.004	0.006	0.008	0.012	0.014	0.018	#N/A
Predevelopment Unit Peak Flow, q (cfs/acre) =	0.00	0.00	0.02	0.03	0.28	0.88	1.21	1.61	0.00
Predevelopment Peak Q (cfs) =	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.2	0.0
Peak Inflow Q (cfs) =	0.0	0.1	0.1	0.1	0.2	0.3	0.3	0.4	#N/A
Peak Outflow Q (cfs) =	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.2	#N/A
Ratio Peak Outflow to Predevelopment Q =	N/A	N/A	N/A	10.1	1.4	1.1	1.0	0.9	#N/A
Structure Controlling Flow	Filtration Media	Vertical Orifice 1	Vertical Orifice 1	Vertical Orifice 1	Vertical Orifice 2	Vertical Orifice 2	Vertical Orifice 2	Vertical Orifice 2	#N/A
Max Velocity through Grate 1 (fps) =	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	#N/A
Max Velocity through Grate 2 (fps) =	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	#N/A
Time to Drain 97% of Inflow Volume (hours) =	12	31	31	30	29	28	27	25	#N/A
Time to Drain 99% of Inflow Volume (hours) =	12	32	32	32	33	32	32	31	#N/A
Maximum Ponding Depth (ft) =	0.20	0.65	0.58	0.71	0.91	1.05	1.10	1.21	#N/A
Area at Maximum Ponding Depth (acres) =	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	#N/A
Maximum Volume Stored (acre-ft) =	0.001	0.003	0.003	0.004	0.006	0.007	0.008	0.010	#N/A


# Detention Basin Outlet Structure Design

UD-Detention, Version 3.07 (February 2017)



S-A-V-D Chart Axis Override	X-axis	Left Y-Axis	Right Y-Axis
minimum bound			
maximum bound			


Scenario: 100 yr  
STRM 1 & 2



**Conduit FlexTable: Table - 1 STRM 1&2**

Label	Upstream Structure	Rise (ft)	Flow (cfs)	Flow / Capacity (Design) (%)	Length (Unified) (ft)	Velocity (ft/s)	Froude Number (Normal)	Depth (Normal) (ft)	Depth (Critical) (ft)
PR3	4' DIA TYPE II MH		25.70	62.7	213.1	8.82	1.432	1.43	1.73
PR4	10' CDOT TYPE R INLET		30.10	21.5	98.7	22.71	5.300	0.79	1.87
PR3	5' DIA TYPE II MH		25.70	58.4	254.1	9.31	1.557	1.37	1.73
PR2	10' CDOT TYPE R INLET		11.80	37.9	3.2	3.76	2.023	0.85	1.23
PR1	10' CDOT TYPE R INLET		13.80	26.6	27.2	13.97	3.425	0.70	1.34
Hydraulic Grade Line (In) (ft)	Hydraulic Grade Line (Out) (ft)	Headloss (ft)	Upstream Structure Hydraulic Grade Line (In) (ft)	Upstream Structure Velocity (In-Governing) (ft/s)	Upstream Structure Headloss Coefficient	Upstream Structure Headloss (ft)	Elevation Ground (Start) (ft)	Invert (Start) (ft)	Invert (Stop) (ft)
7,070.13	7,068.77	1.36	7,070.34	9.31	0.270	0.21	7,075.93	7,068.40	7,066.27
7,067.84	7,060.00	7.84	7,068.77	5.24	1.020	0.93	7,071.69	7,065.97	7,054.50
7,073.35	7,070.07	3.27	7,074.54	4.39	1.520	1.19	7,077.37	7,071.62	7,068.70
7,074.55	7,074.54	0.01	7,075.57	3.76	1.000	1.02	7,077.10	7,072.18	7,072.12
7,074.89	7,074.54	0.35	7,075.49	6.18	1.020	0.61	7,077.10	7,073.55	7,072.12

# STORM 1 - 100 YR




Elevation (ft)

7,078.00  
7,077.00  
7,076.00  
7,075.00  
7,074.00  
7,073.00  
7,072.00  
7,071.00  
7,070.00  
7,069.00  
7,068.00  
7,067.00  
7,066.00  
7,065.00  
7,064.00  
7,063.00  
7,062.00  
7,061.00  
7,060.00  
7,059.00  
7,058.00  
7,057.00  
7,056.00  
7,055.00  
7,054.00  
7,053.00  
7,052.00  
7,051.00

Station (ft)


0.0 20.0 40.0 60.0 80.0 100.0 120.0 140.0 160.0 180.0 200.0 220.0 240.0 260.0 280.0 300.0 320.0 340.0 360.0 380.0 400.0 420.0 440.0 460.0 480.0 500.0 520.0 540.0 560.0

### STORM 2 - 100 Yr



Scenario: 100 yr

Storm 3 incl ExHZ" SR1




**Conduit FlexTable: Table - 1 STRM 3 INCL 42" SR1**

Label	Upstream Structure	Rise (ft)	Flow (cfs)	Flow / Capacity (Design) (%)	Length (Unified) (ft)	Velocity (ft/s)	Froude Number (Normal)	Depth (Normal) (ft)	Depth (Critical) (ft)
PR11-3	EX. EPC TYPE I MH (SR Ranch FIL NO.1)		76.80	76.4	138.4	11.50	1.432	2.29	2.74
PR11-2	EPC TYPE I MH		76.80	47.5	50.8	16.58	2.541	1.70	2.74
PR11-1	EPC TYPE I MH		76.80	48.1	341.2	16.43	2.507	1.71	2.74
PR11	EPC TYPE I MH		76.80	23.9	155.1	27.41	5.244	1.16	2.74
EX 42"-5	EX CDOT TYPE D (SR RANCH FIL NO.1)		76.80	58.8	110.4	14.12	1.992	1.93	2.74
EX 42"-4	EX MH-12 (SR RANCH FIL NO.1)		76.80	47.3	235.2	16.64	2.553	1.69	2.74
Hydraulic Grade Line (In) (ft)	Hydraulic Grade Line (Out) (ft)	Headloss (ft)	Upstream Structure Hydraulic Grade Line (In) (ft)	Upstream Structure Velocity (In-Governing) (ft/s)	Upstream Structure Headloss Coefficient	Upstream Structure Headloss (ft)	Elevation Ground (Start) (ft)	Invert (Start) (ft)	Invert (Stop) (ft)
7,084.23	7,082.43	1.80	7,084.61	9.24	0.270	0.38	7,088.97	7,081.49	7,080.11
7,082.05	7,080.82	1.23	7,082.43	11.32	0.270	0.38	7,086.56	7,079.31	7,078.00
7,080.44	7,072.98	7.46	7,080.82	9.24	0.270	0.38	7,085.36	7,077.70	7,069.11
7,071.55	7,056.70	14.85	7,072.98	7.98	1.020	1.43	7,077.40	7,068.81	7,053.00
7,092.81	7,091.03	1.78	7,095.29	9.50	1.770	2.48	7,095.00	7,090.07	7,088.21
7,090.65	7,084.61	6.04	7,091.03	9.24	0.270	0.38	7,094.77	7,087.91	7,081.79




### STORM 3 INCL EX 42" SR1 - 100 Yr




Scenario: 100 yr

STRM 5,6,7




**Conduit FlexTable: Table - 1 STRM 5,6,7**

Label	Upstream Structure	Rise (ft)	Flow (cfs)	Flow / Capacity (Design) (%)	Length (Unified) (ft)	Velocity (ft/s)	Froude Number (Normal)	Depth (Normal) (ft)	Depth (Critical) (ft)
PR6	15' CDOT TYPE R INLET		12.70	85.5	2.5	7.19	1.674	1.07	1.34
PR5	15' CDOT TYPE R INLET		12.70	55.2	26.5	13.34	2.948	0.80	1.34
PR7	5' DIA TYPE II MH		25.30	49.2	475.5	10.43	1.867	1.24	1.71
PR9	5' CDOT TYPE R INLET		47.10	17.3	8.0	6.66	6.560	0.84	2.24
PR9-1	6' DIA TYPE II MH		47.10	42.6	34.9	4.90	1.755	1.60	2.14
PR8	10' CDOT TYPE R INLET		17.20	20.9	35.4	3.50	3.114	0.78	1.40
Hydraulic Grade Line (In) (ft)	Hydraulic Grade Line (Out) (ft)	Headloss (ft)	Upstream Structure Hydraulic Grade Line (In) (ft)	Upstream Structure Velocity (In-Governing) (ft/s)	Upstream Structure Headloss Coefficient	Upstream Structure Headloss (ft)	Elevation Ground (Start) (ft)	Invert (Start) (ft)	Invert (Stop) (ft)
7,090.47	7,090.43	0.04	7,091.28	7.19	1.020	0.82	7,093.41	7,088.59	7,088.54
7,091.15	7,090.43	0.72	7,092.07	7.62	1.020	0.92	7,093.57	7,089.81	7,088.54
7,089.25	7,084.94	4.31	7,090.43	7.19	1.520	1.17	7,093.68	7,087.54	7,080.07
7,084.06	7,084.02	0.04	7,084.94	3.50	1.280	0.88	7,086.36	7,079.57	7,078.23
7,083.85	7,083.77	0.08	7,084.02	6.66	0.470	0.18	7,086.18	7,077.73	7,077.31
7,085.01	7,084.94	0.06	7,085.34	3.50	1.770	0.34	7,086.34	7,081.49	7,080.07




# STORM 6 - 100 YR





**STORM 7 - 100 YR**



Label: 15' CDOOT TYPER INLET  
Type: Catch Basin  
ID: 116

Label: 5' DIA TYPE II MH  
Type: Manhole  
ID: 114

Label: 15' CDOOT TYPER INLET  
Type: Catch Basin  
ID: 118


Label: P66  
Type: Conduit  
ID: 117

Label: P65  
Type: Conduit  
ID: 119

Elevation (ft)

Station (ft)

# STRM 4 POND 1 OUTFALL INDEX MAP




**Conduit FlexTable: STRM 4 POND 1 7-30-19**

Label	ID	Upstream Structure	Flow (cfs)	Flow / Capacity (Design) (%)	Length (Unified) (ft)	Velocity (ft/s)	Froude Number (Normal)	Depth (Normal) (ft)	Depth (Critical) (ft)	Energy Grade Line (In) (ft)	Energy Grade Line (Out) (ft)	Hydraulic Grade Line (In) (ft)	Hydraulic Grade Line (Out) (ft)	Headloss (ft)	Upstream Structure Hydraulic Grade Line (In) (ft)
PR10	129	Outlet Structure (FSD Pond 1)	23.50	40.3	78.2	17.56	3.772	0.88	1.72	7,078.68	7,074.39	7,077.64	7,069.91	7.73	7,079.20
Upstream Structure Velocity (In-Governing) (ft/s)	Upstream Structure Headloss Coefficient	Upstream Structure Headloss (ft)	Elevation Ground (Start) (ft)	Invert (Start) (ft)	Invert (Stop) (ft)										
8.17	1.500	1.56	7,083.40	7,075.92	7,069.00										




# STORM 4 - 100 yr



**ALLOWABLE CAPACITY FOR ONE-HALF OF STREET (Minor & Major Storm)**

(Based on Regulated Criteria for Maximum Allowable Flow Depth and Spread)


Project: \_\_\_\_\_  
 Inlet ID: \_\_\_\_\_ Enter Your Project Name Here  
Inlet DP 7



<b>Gutter Geometry (Enter data in the blue cells)</b>							
Maximum Allowable Width for Spread Behind Curb	$T_{BACK} = $ <input style="width: 50px;" type="text" value="8.0"/> ft						
Side Slope Behind Curb (leave blank for no conveyance credit behind curb)	$S_{BACK} = $ <input style="width: 50px;" type="text" value="0.020"/> ft/ft						
Manning's Roughness Behind Curb (typically between 0.012 and 0.020)	$n_{BACK} = $ <input style="width: 50px;" type="text" value="0.020"/>						
Height of Curb at Gutter Flow Line	$H_{CURB} = $ <input style="width: 50px;" type="text" value="6.00"/> inches						
Distance from Curb Face to Street Crown	$T_{CROWN} = $ <input style="width: 50px;" type="text" value="17.0"/> ft						
Gutter Width	$W = $ <input style="width: 50px;" type="text" value="2.00"/> ft						
Street Transverse Slope	$S_X = $ <input style="width: 50px;" type="text" value="0.020"/> ft/ft						
Gutter Cross Slope (typically 2 inches over 24 inches or 0.083 ft/ft)	$S_W = $ <input style="width: 50px;" type="text" value="0.083"/> ft/ft						
Street Longitudinal Slope - Enter 0 for sump condition	$S_O = $ <input style="width: 50px;" type="text" value="0.000"/> ft/ft						
Manning's Roughness for Street Section (typically between 0.012 and 0.020)	$n_{STREET} = $ <input style="width: 50px;" type="text" value="0.020"/>						
Max. Allowable Spread for Minor & Major Storm	<table border="1" style="width: 100%; text-align: center;"> <tr> <th style="width: 50%;">Minor Storm</th> <th style="width: 50%;">Major Storm</th> <th style="width: 10%;"></th> </tr> <tr> <td><math>T_{MAX} = </math> <input style="width: 50px;" type="text" value="17.0"/></td> <td><input style="width: 50px;" type="text" value="17.0"/></td> <td>ft</td> </tr> </table>	Minor Storm	Major Storm		$T_{MAX} = $ <input style="width: 50px;" type="text" value="17.0"/>	<input style="width: 50px;" type="text" value="17.0"/>	ft
Minor Storm	Major Storm						
$T_{MAX} = $ <input style="width: 50px;" type="text" value="17.0"/>	<input style="width: 50px;" type="text" value="17.0"/>	ft					
Max. Allowable Depth at Gutter Flowline for Minor & Major Storm	<table border="1" style="width: 100%; text-align: center;"> <tr> <th style="width: 50%;">Minor Storm</th> <th style="width: 50%;">Major Storm</th> <th style="width: 10%;"></th> </tr> <tr> <td><math>d_{MAX} = </math> <input style="width: 50px;" type="text" value="5.1"/></td> <td><input style="width: 50px;" type="text" value="7.8"/></td> <td>inches</td> </tr> </table>	Minor Storm	Major Storm		$d_{MAX} = $ <input style="width: 50px;" type="text" value="5.1"/>	<input style="width: 50px;" type="text" value="7.8"/>	inches
Minor Storm	Major Storm						
$d_{MAX} = $ <input style="width: 50px;" type="text" value="5.1"/>	<input style="width: 50px;" type="text" value="7.8"/>	inches					
Check boxes are not applicable in SUMP conditions	<input type="checkbox"/> <span style="margin-left: 100px;"><input type="checkbox"/></span>						
<b>MINOR STORM Allowable Capacity is based on Depth Criterion</b>							
<b>MAJOR STORM Allowable Capacity is based on Depth Criterion</b>							
Q <sub>allow</sub> =	<table border="1" style="width: 100%; text-align: center;"> <tr> <th style="width: 50%;">Minor Storm</th> <th style="width: 50%;">Major Storm</th> <th style="width: 10%;"></th> </tr> <tr> <td><input style="width: 50px;" type="text" value="SUMP"/></td> <td><input style="width: 50px;" type="text" value="SUMP"/></td> <td>cfs</td> </tr> </table>	Minor Storm	Major Storm		<input style="width: 50px;" type="text" value="SUMP"/>	<input style="width: 50px;" type="text" value="SUMP"/>	cfs
Minor Storm	Major Storm						
<input style="width: 50px;" type="text" value="SUMP"/>	<input style="width: 50px;" type="text" value="SUMP"/>	cfs					

## INLET IN A SUMP OR SAG LOCATION

Version 4.05 Released March 2017




Design Information (Input)	MINOR	MAJOR	
Type of Inlet	CDOT Type R Curb Opening		
Local Depression (additional to continuous gutter depression 'a' from above)	3.00	3.00	inches
Number of Unit Inlets (Grate or Curb Opening)	2	2	
Water Depth at Flowline (outside of local depression)	5.1	7.8	inches
<b>Grate Information</b>	MINOR	MAJOR	<input checked="" type="checkbox"/> Override Depths
Length of a Unit Grate	N/A	N/A	feet
Width of a Unit Grate	N/A	N/A	feet
Area Opening Ratio for a Grate (typical values 0.15-0.90)	N/A	N/A	
Clogging Factor for a Single Grate (typical value 0.50 - 0.70)	N/A	N/A	
Grate Weir Coefficient (typical value 2.15 - 3.60)	N/A	N/A	
Grate Orifice Coefficient (typical value 0.60 - 0.80)	N/A	N/A	
<b>Curb Opening Information</b>	MINOR	MAJOR	
Length of a Unit Curb Opening	5.00	5.00	feet
Height of Vertical Curb Opening in Inches	6.00	6.00	inches
Height of Curb Orifice Throat in Inches	6.00	6.00	inches
Angle of Throat (see USDCM Figure ST-5)	63.40	63.40	degrees
Side Width for Depression Pan (typically the gutter width of 2 feet)	2.00	2.00	feet
Clogging Factor for a Single Curb Opening (typical value 0.10)	0.10	0.10	
Curb Opening Weir Coefficient (typical value 2.3-3.7)	3.60	3.60	
Curb Opening Orifice Coefficient (typical value 0.60 - 0.70)	0.67	0.67	
<b>Low Head Performance Reduction (Calculated)</b>	MINOR	MAJOR	
Depth for Grate Midwidth	N/A	N/A	ft
Depth for Curb Opening Weir Equation	0.26	0.48	ft
Combination Inlet Performance Reduction Factor for Long Inlets	0.48	0.74	
Curb Opening Performance Reduction Factor for Long Inlets	0.88	1.00	
Grated Inlet Performance Reduction Factor for Long Inlets	N/A	N/A	
<b>Total Inlet Interception Capacity (assumes clogged condition)</b>	MINOR	MAJOR	
<b>Q<sub>a</sub></b>	6.7	18.7	cfs
<b>Q<sub>PEAK REQUIRED</sub></b>	5.7	13.8	cfs

Inlet Capacity IS GOOD for Minor and Major Storms(>Q PEAK)

**ALLOWABLE CAPACITY FOR ONE-HALF OF STREET (Minor & Major Storm)**

(Based on Regulated Criteria for Maximum Allowable Flow Depth and Spread)


Project: \_\_\_\_\_  
 Inlet ID: \_\_\_\_\_ **Inlet DP 8**



Gutter Geometry (Enter data in the blue cells)							
Maximum Allowable Width for Spread Behind Curb	$T_{BACK} = 8.0$ ft						
Side Slope Behind Curb (leave blank for no conveyance credit behind curb)	$S_{BACK} = 0.020$ ft/ft						
Manning's Roughness Behind Curb (typically between 0.012 and 0.020)	$n_{BACK} = 0.020$						
Height of Curb at Gutter Flow Line	$H_{CURB} = 6.00$ inches						
Distance from Curb Face to Street Crown	$T_{CROWN} = 17.0$ ft						
Gutter Width	$W = 2.00$ ft						
Street Transverse Slope	$S_X = 0.020$ ft/ft						
Gutter Cross Slope (typically 2 inches over 24 inches or 0.083 ft/ft)	$S_W = 0.083$ ft/ft						
Street Longitudinal Slope - Enter 0 for sump condition	$S_O = 0.000$ ft/ft						
Manning's Roughness for Street Section (typically between 0.012 and 0.020)	$n_{STREET} = 0.020$						
Max. Allowable Spread for Minor & Major Storm	<table border="1"> <tr> <th>Minor Storm</th> <th>Major Storm</th> <th>ft</th> </tr> <tr> <td><math>T_{MAX} = 17.0</math></td> <td><math>T_{MAX} = 17.0</math></td> <td></td> </tr> </table>	Minor Storm	Major Storm	ft	$T_{MAX} = 17.0$	$T_{MAX} = 17.0$	
Minor Storm	Major Storm	ft					
$T_{MAX} = 17.0$	$T_{MAX} = 17.0$						
Max. Allowable Depth at Gutter Flowline for Minor & Major Storm	<table border="1"> <tr> <th>Minor Storm</th> <th>Major Storm</th> <th>inches</th> </tr> <tr> <td><math>d_{MAX} = 5.1</math></td> <td><math>d_{MAX} = 7.8</math></td> <td></td> </tr> </table>	Minor Storm	Major Storm	inches	$d_{MAX} = 5.1$	$d_{MAX} = 7.8$	
Minor Storm	Major Storm	inches					
$d_{MAX} = 5.1$	$d_{MAX} = 7.8$						
Check boxes are not applicable in SUMP conditions	<table border="1"> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> </tr> </table>	<input type="checkbox"/>	<input type="checkbox"/>				
<input type="checkbox"/>	<input type="checkbox"/>						
<b>MINOR STORM Allowable Capacity is based on Depth Criterion</b>							
<b>MAJOR STORM Allowable Capacity is based on Depth Criterion</b>							
	<table border="1"> <tr> <th>Minor Storm</th> <th>Major Storm</th> <th>cfs</th> </tr> <tr> <td><math>Q_{allow} = \text{SUMP}</math></td> <td><math>Q_{allow} = \text{SUMP}</math></td> <td></td> </tr> </table>	Minor Storm	Major Storm	cfs	$Q_{allow} = \text{SUMP}$	$Q_{allow} = \text{SUMP}$	
Minor Storm	Major Storm	cfs					
$Q_{allow} = \text{SUMP}$	$Q_{allow} = \text{SUMP}$						

## INLET IN A SUMP OR SAG LOCATION

Version 4.05 Released March 2017




Design Information (Input)	MINOR	MAJOR	
Type of Inlet	CDOT Type R Curb Opening		
Local Depression (additional to continuous gutter depression 'a' from above)	3.00	3.00	inches
Number of Unit Inlets (Grate or Curb Opening)	2	2	
Water Depth at Flowline (outside of local depression)	5.1	7.8	inches
<b>Grate Information</b>	MINOR	MAJOR	<input checked="" type="checkbox"/> Override Depths
Length of a Unit Grate	N/A	N/A	feet
Width of a Unit Grate	N/A	N/A	feet
Area Opening Ratio for a Grate (typical values 0.15-0.90)	N/A	N/A	
Clogging Factor for a Single Grate (typical value 0.50 - 0.70)	N/A	N/A	
Grate Weir Coefficient (typical value 2.15 - 3.60)	N/A	N/A	
Grate Orifice Coefficient (typical value 0.60 - 0.80)	N/A	N/A	
<b>Curb Opening Information</b>	MINOR	MAJOR	
Length of a Unit Curb Opening	5.00	5.00	feet
Height of Vertical Curb Opening in Inches	6.00	6.00	inches
Height of Curb Orifice Throat in Inches	6.00	6.00	inches
Angle of Throat (see USDCM Figure ST-5)	63.40	63.40	degrees
Side Width for Depression Pan (typically the gutter width of 2 feet)	2.00	2.00	feet
Clogging Factor for a Single Curb Opening (typical value 0.10)	0.10	0.10	
Curb Opening Weir Coefficient (typical value 2.3-3.7)	3.60	3.60	
Curb Opening Orifice Coefficient (typical value 0.60 - 0.70)	0.67	0.67	
<b>Low Head Performance Reduction (Calculated)</b>	MINOR	MAJOR	
Depth for Grate Midwidth	N/A	N/A	ft
Depth for Curb Opening Weir Equation	0.26	0.48	ft
Combination Inlet Performance Reduction Factor for Long Inlets	0.48	0.74	
Curb Opening Performance Reduction Factor for Long Inlets	0.88	1.00	
Grated Inlet Performance Reduction Factor for Long Inlets	N/A	N/A	
<b>Total Inlet Interception Capacity (assumes clogged condition)</b>	MINOR	MAJOR	
<b>Q<sub>a</sub></b>	6.7	18.7	cfs
Q <sub>PEAK REQUIRED</sub>	4.9	11.8	cfs

Inlet Capacity IS GOOD for Minor and Major Storms(>Q PEAK)

**ALLOWABLE CAPACITY FOR ONE-HALF OF STREET (Minor & Major Storm)**

(Based on Regulated Criteria for Maximum Allowable Flow Depth and Spread)


Project: \_\_\_\_\_  
 Inlet ID: \_\_\_\_\_ Enter Your Project Name Here  
Inlet DP 9



<b>Gutter Geometry (Enter data in the blue cells)</b>																	
Maximum Allowable Width for Spread Behind Curb	$T_{BACK} = $ <input style="width: 50px;" type="text" value="8.0"/> ft																
Side Slope Behind Curb (leave blank for no conveyance credit behind curb)	$S_{BACK} = $ <input style="width: 50px;" type="text" value="0.020"/> ft/ft																
Manning's Roughness Behind Curb (typically between 0.012 and 0.020)	$n_{BACK} = $ <input style="width: 50px;" type="text" value="0.020"/>																
Height of Curb at Gutter Flow Line	$H_{CURB} = $ <input style="width: 50px;" type="text" value="6.00"/> inches																
Distance from Curb Face to Street Crown	$T_{CROWN} = $ <input style="width: 50px;" type="text" value="17.0"/> ft																
Gutter Width	$W = $ <input style="width: 50px;" type="text" value="2.00"/> ft																
Street Transverse Slope	$S_X = $ <input style="width: 50px;" type="text" value="0.020"/> ft/ft																
Gutter Cross Slope (typically 2 inches over 24 inches or 0.083 ft/ft)	$S_W = $ <input style="width: 50px;" type="text" value="0.083"/> ft/ft																
Street Longitudinal Slope - Enter 0 for sump condition	$S_O = $ <input style="width: 50px;" type="text" value="0.000"/> ft/ft																
Manning's Roughness for Street Section (typically between 0.012 and 0.020)	$n_{STREET} = $ <input style="width: 50px;" type="text" value="0.020"/>																
Max. Allowable Spread for Minor & Major Storm	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;"></th> <th style="width: 25%; text-align: center;">Minor Storm</th> <th style="width: 25%; text-align: center;">Major Storm</th> <th style="width: 10%;"></th> </tr> </thead> <tbody> <tr> <td><math>T_{MAX} = </math></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="17.0"/></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="17.0"/></td> <td style="text-align: right;">ft</td> </tr> <tr> <td><math>d_{MAX} = </math></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="5.1"/></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="8.0"/></td> <td style="text-align: right;">inches</td> </tr> <tr> <td></td> <td style="text-align: center;"><input type="checkbox"/></td> <td style="text-align: center;"><input type="checkbox"/></td> <td></td> </tr> </tbody> </table>		Minor Storm	Major Storm		$T_{MAX} = $	<input style="width: 40px;" type="text" value="17.0"/>	<input style="width: 40px;" type="text" value="17.0"/>	ft	$d_{MAX} = $	<input style="width: 40px;" type="text" value="5.1"/>	<input style="width: 40px;" type="text" value="8.0"/>	inches		<input type="checkbox"/>	<input type="checkbox"/>	
	Minor Storm	Major Storm															
$T_{MAX} = $	<input style="width: 40px;" type="text" value="17.0"/>	<input style="width: 40px;" type="text" value="17.0"/>	ft														
$d_{MAX} = $	<input style="width: 40px;" type="text" value="5.1"/>	<input style="width: 40px;" type="text" value="8.0"/>	inches														
	<input type="checkbox"/>	<input type="checkbox"/>															
Max. Allowable Depth at Gutter Flowline for Minor & Major Storm																	
Check boxes are not applicable in SUMP conditions																	
<b>MINOR STORM Allowable Capacity is based on Depth Criterion</b>																	
<b>MAJOR STORM Allowable Capacity is based on Depth Criterion</b>																	
$Q_{allow} = $	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;"></th> <th style="width: 25%; text-align: center;">Minor Storm</th> <th style="width: 25%; text-align: center;">Major Storm</th> <th style="width: 10%;"></th> </tr> </thead> <tbody> <tr> <td></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="SUMP"/></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="SUMP"/></td> <td style="text-align: right;">cfs</td> </tr> </tbody> </table>		Minor Storm	Major Storm			<input style="width: 40px;" type="text" value="SUMP"/>	<input style="width: 40px;" type="text" value="SUMP"/>	cfs								
	Minor Storm	Major Storm															
	<input style="width: 40px;" type="text" value="SUMP"/>	<input style="width: 40px;" type="text" value="SUMP"/>	cfs														

## INLET IN A SUMP OR SAG LOCATION

Version 4.05 Released March 2017




Design Information (Input)	MINOR	MAJOR	
Type of Inlet	CDOT Type R Curb Opening		
Local Depression (additional to continuous gutter depression 'a' from above)	3.00	3.00	inches
Number of Unit Inlets (Grate or Curb Opening)	1	1	
Water Depth at Flowline (outside of local depression)	5.1	7.8	inches
<b>Grate Information</b>	MINOR	MAJOR	<input checked="" type="checkbox"/> Override Depths
Length of a Unit Grate	N/A	N/A	feet
Width of a Unit Grate	N/A	N/A	feet
Area Opening Ratio for a Grate (typical values 0.15-0.90)	N/A	N/A	
Clogging Factor for a Single Grate (typical value 0.50 - 0.70)	N/A	N/A	
Grate Weir Coefficient (typical value 2.15 - 3.60)	N/A	N/A	
Grate Orifice Coefficient (typical value 0.60 - 0.80)	N/A	N/A	
<b>Curb Opening Information</b>	MINOR	MAJOR	
Length of a Unit Curb Opening	5.00	5.00	feet
Height of Vertical Curb Opening in Inches	6.00	6.00	inches
Height of Curb Orifice Throat in Inches	6.00	6.00	inches
Angle of Throat (see USDCM Figure ST-5)	63.40	63.40	degrees
Side Width for Depression Pan (typically the gutter width of 2 feet)	2.00	2.00	feet
Clogging Factor for a Single Curb Opening (typical value 0.10)	0.10	0.10	
Curb Opening Weir Coefficient (typical value 2.3-3.7)	3.60	3.60	
Curb Opening Orifice Coefficient (typical value 0.60 - 0.70)	0.67	0.67	
<b>Low Head Performance Reduction (Calculated)</b>	MINOR	MAJOR	
Depth for Grate Midwidth	N/A	N/A	ft
Depth for Curb Opening Weir Equation	0.26	0.48	ft
Combination Inlet Performance Reduction Factor for Long Inlets	0.65	1.00	
Curb Opening Performance Reduction Factor for Long Inlets	1.00	1.00	
Grated Inlet Performance Reduction Factor for Long Inlets	N/A	N/A	
<b>Total Inlet Interception Capacity (assumes clogged condition)</b>	MINOR	MAJOR	
<b>Q<sub>a</sub></b>	3.7	9.0	cfs
Q <sub>PEAK REQUIRED</sub>	2.2	5.4	cfs

**Inlet Capacity IS GOOD for Minor and Major Storms(>Q PEAK)**

**ALLOWABLE CAPACITY FOR ONE-HALF OF STREET (Minor & Major Storm)**

(Based on Regulated Criteria for Maximum Allowable Flow Depth and Spread)

Project: \_\_\_\_\_  
 Inlet ID: \_\_\_\_\_ Enter Your Project Name Here  
Inlet DP 10




<b>Gutter Geometry (Enter data in the blue cells)</b>							
Maximum Allowable Width for Spread Behind Curb	T <sub>BACK</sub> = 8.0 ft						
Side Slope Behind Curb (leave blank for no conveyance credit behind curb)	S <sub>BACK</sub> = 0.020 ft/ft						
Manning's Roughness Behind Curb (typically between 0.012 and 0.020)	n <sub>BACK</sub> = 0.020						
Height of Curb at Gutter Flow Line	H <sub>CURB</sub> = 6.00 inches						
Distance from Curb Face to Street Crown	T <sub>CROWN</sub> = 17.0 ft						
Gutter Width	W = 2.00 ft						
Street Transverse Slope	S <sub>x</sub> = 0.020 ft/ft						
Gutter Cross Slope (typically 2 inches over 24 inches or 0.083 ft/ft)	S <sub>w</sub> = 0.083 ft/ft						
Street Longitudinal Slope - Enter 0 for sump condition	S <sub>o</sub> = 0.022 ft/ft						
Manning's Roughness for Street Section (typically between 0.012 and 0.020)	n <sub>STREET</sub> = 0.020						
Max. Allowable Spread for Minor & Major Storm	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <th style="padding: 2px;">Minor Storm</th> <th style="padding: 2px;">Major Storm</th> <th style="padding: 2px;">ft</th> </tr> <tr> <td style="text-align: center;">17.0</td> <td style="text-align: center;">17.0</td> <td></td> </tr> </table>	Minor Storm	Major Storm	ft	17.0	17.0	
Minor Storm	Major Storm	ft					
17.0	17.0						
Max. Allowable Depth at Gutter Flowline for Minor & Major Storm	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <th style="padding: 2px;">Minor Storm</th> <th style="padding: 2px;">Major Storm</th> <th style="padding: 2px;">inches</th> </tr> <tr> <td style="text-align: center;">5.1</td> <td style="text-align: center;">7.8</td> <td></td> </tr> </table>	Minor Storm	Major Storm	inches	5.1	7.8	
Minor Storm	Major Storm	inches					
5.1	7.8						
Allow Flow Depth at Street Crown (leave blank for no)	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="text-align: center;"><input type="checkbox"/></td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td style="padding-left: 10px;">check = yes</td> </tr> </table>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	check = yes			
<input type="checkbox"/>	<input checked="" type="checkbox"/>	check = yes					
<b>MINOR STORM Allowable Capacity is based on Depth Criterion</b>							
<b>MAJOR STORM Allowable Capacity is based on Depth Criterion</b>							
Minor storm max. allowable capacity GOOD - greater than the design flow given on sheet 'Inlet Management'	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <th style="padding: 2px;">Minor Storm</th> <th style="padding: 2px;">Major Storm</th> <th style="padding: 2px;">cfs</th> </tr> <tr> <td style="text-align: center;">9.4</td> <td style="text-align: center;">29.1</td> <td></td> </tr> </table>	Minor Storm	Major Storm	cfs	9.4	29.1	
Minor Storm	Major Storm	cfs					
9.4	29.1						
Major storm max. allowable capacity GOOD - greater than the design flow given on sheet 'Inlet Management'							



## INLET ON A CONTINUOUS GRADE

Version 4.05 Released March 2017




Design Information (Input)	MINOR	MAJOR	
Type of Inlet	CDOT Type R Curb Opening		
Local Depression (additional to continuous gutter depression 'a')	3.0	3.0	inches
Total Number of Units in the Inlet (Grate or Curb Opening)	1	1	
Length of a Single Unit Inlet (Grate or Curb Opening)	15.00	15.00	ft
Width of a Unit Grate (cannot be greater than W, Gutter Width)	N/A	N/A	ft
Clogging Factor for a Single Unit Grate (typical min. value = 0.5)	N/A	N/A	
Clogging Factor for a Single Unit Curb Opening (typical min. value = 0.1)	0.10	0.10	
<b>Street Hydraulics: OK - Q &lt; Allowable Street Capacity</b>			
Total Inlet Interception Capacity	9.1	12.7	cfs
Total Inlet Carry-Over Flow (flow bypassing inlet)	0.3	2.9	cfs
Capture Percentage = $Q_i/Q_c$ =	97	82	%

**ALLOWABLE CAPACITY FOR ONE-HALF OF STREET (Minor & Major Storm)**

(Based on Regulated Criteria for Maximum Allowable Flow Depth and Spread)


Project: \_\_\_\_\_  
 Inlet ID: \_\_\_\_\_ Enter Your Project Name Here  
Inlet DP 11



<b>Gutter Geometry (Enter data in the blue cells)</b>																	
Maximum Allowable Width for Spread Behind Curb	T <sub>BACK</sub> = <input style="width: 50px;" type="text" value="8.0"/> ft																
Side Slope Behind Curb (leave blank for no conveyance credit behind curb)	S <sub>BACK</sub> = <input style="width: 50px;" type="text" value="0.020"/> ft/ft																
Manning's Roughness Behind Curb (typically between 0.012 and 0.020)	n <sub>BACK</sub> = <input style="width: 50px;" type="text" value="0.020"/>																
Height of Curb at Gutter Flow Line	H <sub>CURB</sub> = <input style="width: 50px;" type="text" value="6.00"/> inches																
Distance from Curb Face to Street Crown	T <sub>CROWN</sub> = <input style="width: 50px;" type="text" value="17.0"/> ft																
Gutter Width	W = <input style="width: 50px;" type="text" value="2.00"/> ft																
Street Transverse Slope	S <sub>x</sub> = <input style="width: 50px;" type="text" value="0.020"/> ft/ft																
Gutter Cross Slope (typically 2 inches over 24 inches or 0.083 ft/ft)	S <sub>w</sub> = <input style="width: 50px;" type="text" value="0.083"/> ft/ft																
Street Longitudinal Slope - Enter 0 for sump condition	S <sub>o</sub> = <input style="width: 50px;" type="text" value="0.022"/> ft/ft																
Manning's Roughness for Street Section (typically between 0.012 and 0.020)	n <sub>STREET</sub> = <input style="width: 50px;" type="text" value="0.020"/>																
Max. Allowable Spread for Minor & Major Storm	<table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th style="text-align: center;">Minor Storm</th> <th style="text-align: center;">Major Storm</th> <th></th> </tr> </thead> <tbody> <tr> <td style="text-align: right;">T<sub>MAX</sub> =</td> <td style="text-align: center;"><input style="width: 50px;" type="text" value="17.0"/></td> <td style="text-align: center;"><input style="width: 50px;" type="text" value="17.0"/></td> <td style="text-align: right;">ft</td> </tr> <tr> <td style="text-align: right;">d<sub>MAX</sub> =</td> <td style="text-align: center;"><input style="width: 50px;" type="text" value="5.1"/></td> <td style="text-align: center;"><input style="width: 50px;" type="text" value="7.8"/></td> <td style="text-align: right;">inches</td> </tr> <tr> <td></td> <td style="text-align: center;"><input type="checkbox"/></td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td style="text-align: right;">check = yes</td> </tr> </tbody> </table>		Minor Storm	Major Storm		T <sub>MAX</sub> =	<input style="width: 50px;" type="text" value="17.0"/>	<input style="width: 50px;" type="text" value="17.0"/>	ft	d <sub>MAX</sub> =	<input style="width: 50px;" type="text" value="5.1"/>	<input style="width: 50px;" type="text" value="7.8"/>	inches		<input type="checkbox"/>	<input checked="" type="checkbox"/>	check = yes
	Minor Storm	Major Storm															
T <sub>MAX</sub> =	<input style="width: 50px;" type="text" value="17.0"/>	<input style="width: 50px;" type="text" value="17.0"/>	ft														
d <sub>MAX</sub> =	<input style="width: 50px;" type="text" value="5.1"/>	<input style="width: 50px;" type="text" value="7.8"/>	inches														
	<input type="checkbox"/>	<input checked="" type="checkbox"/>	check = yes														
Max. Allowable Depth at Gutter Flowline for Minor & Major Storm																	
Allow Flow Depth at Street Crown (leave blank for no)																	
<b>MINOR STORM Allowable Capacity is based on Depth Criterion</b>																	
<b>MAJOR STORM Allowable Capacity is based on Depth Criterion</b>																	
	<table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th style="text-align: center;">Minor Storm</th> <th style="text-align: center;">Major Storm</th> <th></th> </tr> </thead> <tbody> <tr> <td style="text-align: right;">Q<sub>allow</sub> =</td> <td style="text-align: center;"><input style="width: 50px;" type="text" value="9.4"/></td> <td style="text-align: center;"><input style="width: 50px;" type="text" value="29.1"/></td> <td style="text-align: right;">cfs</td> </tr> </tbody> </table>		Minor Storm	Major Storm		Q <sub>allow</sub> =	<input style="width: 50px;" type="text" value="9.4"/>	<input style="width: 50px;" type="text" value="29.1"/>	cfs								
	Minor Storm	Major Storm															
Q <sub>allow</sub> =	<input style="width: 50px;" type="text" value="9.4"/>	<input style="width: 50px;" type="text" value="29.1"/>	cfs														
Minor storm max. allowable capacity GOOD - greater than the design flow given on sheet 'Inlet Management' Major storm max. allowable capacity GOOD - greater than the design flow given on sheet 'Inlet Management'																	

## INLET ON A CONTINUOUS GRADE

Version 4.05 Released March 2017




Design Information (Input)	MINOR	MAJOR	
Type of Inlet	CDOT Type R Curb Opening		
Local Depression (additional to continuous gutter depression 'a')	3.0	3.0	inches
Total Number of Units in the Inlet (Grate or Curb Opening)	1	1	
Length of a Single Unit Inlet (Grate or Curb Opening)	15.00	15.00	ft
Width of a Unit Grate (cannot be greater than W, Gutter Width)	N/A	N/A	ft
Clogging Factor for a Single Unit Grate (typical min. value = 0.5)	N/A	N/A	
Clogging Factor for a Single Unit Curb Opening (typical min. value = 0.1)	0.10	0.10	
<b>Street Hydraulics: OK - Q &lt; Allowable Street Capacity</b>			
Total Inlet Interception Capacity	1.9	12.7	cfs
Total Inlet Carry-Over Flow (flow bypassing inlet)	0.0	2.9	cfs
Capture Percentage = $Q_i/Q_c$ =	100	82	%

**ALLOWABLE CAPACITY FOR ONE-HALF OF STREET (Minor & Major Storm)**

(Based on Regulated Criteria for Maximum Allowable Flow Depth and Spread)


Project: \_\_\_\_\_  
 Inlet ID: \_\_\_\_\_ Enter Your Project Name Here  
Inlet DP 12



<b>Gutter Geometry (Enter data in the blue cells)</b>																	
Maximum Allowable Width for Spread Behind Curb	$T_{BACK} = $ <input style="width: 50px;" type="text" value="8.0"/> ft																
Side Slope Behind Curb (leave blank for no conveyance credit behind curb)	$S_{BACK} = $ <input style="width: 50px;" type="text" value="0.020"/> ft/ft																
Manning's Roughness Behind Curb (typically between 0.012 and 0.020)	$n_{BACK} = $ <input style="width: 50px;" type="text" value="0.020"/>																
Height of Curb at Gutter Flow Line	$H_{CURB} = $ <input style="width: 50px;" type="text" value="6.00"/> inches																
Distance from Curb Face to Street Crown	$T_{CROWN} = $ <input style="width: 50px;" type="text" value="17.0"/> ft																
Gutter Width	$W = $ <input style="width: 50px;" type="text" value="2.00"/> ft																
Street Transverse Slope	$S_X = $ <input style="width: 50px;" type="text" value="0.020"/> ft/ft																
Gutter Cross Slope (typically 2 inches over 24 inches or 0.083 ft/ft)	$S_W = $ <input style="width: 50px;" type="text" value="0.083"/> ft/ft																
Street Longitudinal Slope - Enter 0 for sump condition	$S_O = $ <input style="width: 50px;" type="text" value="0.000"/> ft/ft																
Manning's Roughness for Street Section (typically between 0.012 and 0.020)	$n_{STREET} = $ <input style="width: 50px;" type="text" value="0.020"/>																
Max. Allowable Spread for Minor & Major Storm	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;"></th> <th style="width: 25%; text-align: center;">Minor Storm</th> <th style="width: 25%; text-align: center;">Major Storm</th> <th style="width: 10%;"></th> </tr> </thead> <tbody> <tr> <td><math>T_{MAX} = </math></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="17.0"/></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="17.0"/></td> <td style="text-align: right;">ft</td> </tr> <tr> <td><math>d_{MAX} = </math></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="5.1"/></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="7.8"/></td> <td style="text-align: right;">inches</td> </tr> <tr> <td></td> <td style="text-align: center;"><input type="checkbox"/></td> <td style="text-align: center;"><input type="checkbox"/></td> <td></td> </tr> </tbody> </table>		Minor Storm	Major Storm		$T_{MAX} = $	<input style="width: 40px;" type="text" value="17.0"/>	<input style="width: 40px;" type="text" value="17.0"/>	ft	$d_{MAX} = $	<input style="width: 40px;" type="text" value="5.1"/>	<input style="width: 40px;" type="text" value="7.8"/>	inches		<input type="checkbox"/>	<input type="checkbox"/>	
	Minor Storm	Major Storm															
$T_{MAX} = $	<input style="width: 40px;" type="text" value="17.0"/>	<input style="width: 40px;" type="text" value="17.0"/>	ft														
$d_{MAX} = $	<input style="width: 40px;" type="text" value="5.1"/>	<input style="width: 40px;" type="text" value="7.8"/>	inches														
	<input type="checkbox"/>	<input type="checkbox"/>															
Max. Allowable Depth at Gutter Flowline for Minor & Major Storm																	
Check boxes are not applicable in SUMP conditions																	
<b>MINOR STORM Allowable Capacity is based on Depth Criterion</b>																	
<b>MAJOR STORM Allowable Capacity is based on Depth Criterion</b>																	
$Q_{allow} = $	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;"></th> <th style="width: 25%; text-align: center;">Minor Storm</th> <th style="width: 25%; text-align: center;">Major Storm</th> <th style="width: 10%;"></th> </tr> </thead> <tbody> <tr> <td></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="SUMP"/></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="SUMP"/></td> <td style="text-align: right;">cfs</td> </tr> </tbody> </table>		Minor Storm	Major Storm			<input style="width: 40px;" type="text" value="SUMP"/>	<input style="width: 40px;" type="text" value="SUMP"/>	cfs								
	Minor Storm	Major Storm															
	<input style="width: 40px;" type="text" value="SUMP"/>	<input style="width: 40px;" type="text" value="SUMP"/>	cfs														

## INLET IN A SUMP OR SAG LOCATION

Version 4.05 Released March 2017




Design Information (Input)	MINOR	MAJOR	
Type of Inlet	CDOT Type R Curb Opening		
Local Depression (additional to continuous gutter depression 'a' from above)	3.00	3.00	inches
Number of Unit Inlets (Grate or Curb Opening)	2	2	
Water Depth at Flowline (outside of local depression)	5.1	7.8	inches
<b>Grate Information</b>	MINOR	MAJOR	<input checked="" type="checkbox"/> Override Depths
Length of a Unit Grate	N/A	N/A	feet
Width of a Unit Grate	N/A	N/A	feet
Area Opening Ratio for a Grate (typical values 0.15-0.90)	N/A	N/A	
Clogging Factor for a Single Grate (typical value 0.50 - 0.70)	N/A	N/A	
Grate Weir Coefficient (typical value 2.15 - 3.60)	N/A	N/A	
Grate Orifice Coefficient (typical value 0.60 - 0.80)	N/A	N/A	
<b>Curb Opening Information</b>	MINOR	MAJOR	
Length of a Unit Curb Opening	5.00	5.00	feet
Height of Vertical Curb Opening in Inches	6.00	6.00	inches
Height of Curb Orifice Throat in Inches	6.00	6.00	inches
Angle of Throat (see USDCM Figure ST-5)	63.40	63.40	degrees
Side Width for Depression Pan (typically the gutter width of 2 feet)	2.00	2.00	feet
Clogging Factor for a Single Curb Opening (typical value 0.10)	0.10	0.10	
Curb Opening Weir Coefficient (typical value 2.3-3.7)	3.60	3.60	
Curb Opening Orifice Coefficient (typical value 0.60 - 0.70)	0.67	0.67	
<b>Low Head Performance Reduction (Calculated)</b>	MINOR	MAJOR	
Depth for Grate Midwidth	N/A	N/A	ft
Depth for Curb Opening Weir Equation	0.26	0.48	ft
Combination Inlet Performance Reduction Factor for Long Inlets	0.48	0.74	
Curb Opening Performance Reduction Factor for Long Inlets	0.88	1.00	
Grated Inlet Performance Reduction Factor for Long Inlets	N/A	N/A	
<b>Total Inlet Interception Capacity (assumes clogged condition)</b>	MINOR	MAJOR	
<b>Q<sub>a</sub></b>	6.7	18.7	cfs
Q <sub>PEAK REQUIRED</sub>	6.2	17.2	cfs

**Inlet Capacity IS GOOD for Minor and Major Storms(>Q PEAK)**

**ALLOWABLE CAPACITY FOR ONE-HALF OF STREET (Minor & Major Storm)**

(Based on Regulated Criteria for Maximum Allowable Flow Depth and Spread)


Project: \_\_\_\_\_  
 Inlet ID: \_\_\_\_\_ Enter Your Project Name Here  
Inlet DP 13



Gutter Geometry (Enter data in the blue cells)										
Maximum Allowable Width for Spread Behind Curb	$T_{BACK} = $ <input style="width: 50px;" type="text" value="8.0"/> ft									
Side Slope Behind Curb (leave blank for no conveyance credit behind curb)	$S_{BACK} = $ <input style="width: 50px;" type="text" value="0.020"/> ft/ft									
Manning's Roughness Behind Curb (typically between 0.012 and 0.020)	$n_{BACK} = $ <input style="width: 50px;" type="text" value="0.020"/>									
Height of Curb at Gutter Flow Line	$H_{CURB} = $ <input style="width: 50px;" type="text" value="6.00"/> inches									
Distance from Curb Face to Street Crown	$T_{CROWN} = $ <input style="width: 50px;" type="text" value="17.0"/> ft									
Gutter Width	$W = $ <input style="width: 50px;" type="text" value="2.00"/> ft									
Street Transverse Slope	$S_X = $ <input style="width: 50px;" type="text" value="0.020"/> ft/ft									
Gutter Cross Slope (typically 2 inches over 24 inches or 0.083 ft/ft)	$S_W = $ <input style="width: 50px;" type="text" value="0.083"/> ft/ft									
Street Longitudinal Slope - Enter 0 for sump condition	$S_O = $ <input style="width: 50px;" type="text" value="0.000"/> ft/ft									
Manning's Roughness for Street Section (typically between 0.012 and 0.020)	$n_{STREET} = $ <input style="width: 50px;" type="text" value="0.020"/>									
Max. Allowable Spread for Minor & Major Storm	<table border="1" style="display: inline-table; border-collapse: collapse;"> <thead> <tr> <th style="width: 50px;">Minor Storm</th> <th style="width: 50px;">Major Storm</th> <th style="width: 20px;">ft</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"><math>T_{MAX} = </math> <input style="width: 40px;" type="text" value="17.0"/></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="17.0"/></td> <td></td> </tr> <tr> <td style="text-align: center;"><math>d_{MAX} = </math> <input style="width: 40px;" type="text" value="5.1"/></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="5.1"/></td> <td style="text-align: center;">inches</td> </tr> </tbody> </table>	Minor Storm	Major Storm	ft	$T_{MAX} = $ <input style="width: 40px;" type="text" value="17.0"/>	<input style="width: 40px;" type="text" value="17.0"/>		$d_{MAX} = $ <input style="width: 40px;" type="text" value="5.1"/>	<input style="width: 40px;" type="text" value="5.1"/>	inches
Minor Storm	Major Storm	ft								
$T_{MAX} = $ <input style="width: 40px;" type="text" value="17.0"/>	<input style="width: 40px;" type="text" value="17.0"/>									
$d_{MAX} = $ <input style="width: 40px;" type="text" value="5.1"/>	<input style="width: 40px;" type="text" value="5.1"/>	inches								
Max. Allowable Depth at Gutter Flowline for Minor & Major Storm										
Check boxes are not applicable in SUMP conditions	<input type="checkbox"/> <span style="margin-left: 100px;"><input type="checkbox"/></span>									
<b>MINOR STORM Allowable Capacity is based on Depth Criterion</b>										
<b>MAJOR STORM Allowable Capacity is based on Depth Criterion</b>										
Q <sub>allow</sub> =	<table border="1" style="display: inline-table; border-collapse: collapse;"> <thead> <tr> <th style="width: 50px;">Minor Storm</th> <th style="width: 50px;">Major Storm</th> <th style="width: 20px;">cfs</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"><input style="width: 40px;" type="text" value="SUMP"/></td> <td style="text-align: center;"><input style="width: 40px;" type="text" value="SUMP"/></td> <td></td> </tr> </tbody> </table>	Minor Storm	Major Storm	cfs	<input style="width: 40px;" type="text" value="SUMP"/>	<input style="width: 40px;" type="text" value="SUMP"/>				
Minor Storm	Major Storm	cfs								
<input style="width: 40px;" type="text" value="SUMP"/>	<input style="width: 40px;" type="text" value="SUMP"/>									

## INLET IN A SUMP OR SAG LOCATION

Version 4.05 Released March 2017



Design Information (Input)	MINOR	MAJOR	
Type of Inlet	CDOT Type R Curb Opening		
Local Depression (additional to continuous gutter depression 'a' from above)	3.00	3.00	inches
Number of Unit Inlets (Grate or Curb Opening)	1	1	
Water Depth at Flowline (outside of local depression)	5.1	7.8	inches
<b>Grate Information</b>	MINOR	MAJOR	<input checked="" type="checkbox"/> Override Depths
Length of a Unit Grate	N/A	N/A	feet
Width of a Unit Grate	N/A	N/A	feet
Area Opening Ratio for a Grate (typical values 0.15-0.90)	N/A	N/A	
Clogging Factor for a Single Grate (typical value 0.50 - 0.70)	N/A	N/A	
Grate Weir Coefficient (typical value 2.15 - 3.60)	N/A	N/A	
Grate Orifice Coefficient (typical value 0.60 - 0.80)	N/A	N/A	
<b>Curb Opening Information</b>	MINOR	MAJOR	
Length of a Unit Curb Opening	5.00	5.00	feet
Height of Vertical Curb Opening in Inches	6.00	6.00	inches
Height of Curb Orifice Throat in Inches	6.00	6.00	inches
Angle of Throat (see USDCM Figure ST-5)	63.40	63.40	degrees
Side Width for Depression Pan (typically the gutter width of 2 feet)	2.00	2.00	feet
Clogging Factor for a Single Curb Opening (typical value 0.10)	0.10	0.10	
Curb Opening Weir Coefficient (typical value 2.3-3.7)	3.60	3.60	
Curb Opening Orifice Coefficient (typical value 0.60 - 0.70)	0.67	0.67	
<b>Low Head Performance Reduction (Calculated)</b>	MINOR	MAJOR	
Depth for Grate Midwidth	N/A	N/A	ft
Depth for Curb Opening Weir Equation	0.26	0.48	ft
Combination Inlet Performance Reduction Factor for Long Inlets	0.65	1.00	
Curb Opening Performance Reduction Factor for Long Inlets	1.00	1.00	
Grated Inlet Performance Reduction Factor for Long Inlets	N/A	N/A	
<b>Total Inlet Interception Capacity (assumes clogged condition)</b>	MINOR	MAJOR	
<b>Q<sub>a</sub></b>	3.7	9.0	cfs
Q <sub>PEAK REQUIRED</sub>	1.2	5.9	cfs

**Inlet Capacity IS GOOD for Minor and Major Storms(>Q PEAK)**



## **EDB AND SFB DETAILS**




Figure SF-1. Sand Filter Plan and Sections




Figure SF-2. Geomembrane Liner/Underdrain Penetration Detail





Figure SF-3. Geomembrane Liner/Concrete Connection Detail




**FIGURE EDB-3**  
**EXTENDED DETENTION BASIN**

**Figure EDB-3. Extended Detention Basin (EDB) Plan and Profile**


Additional Details are provided in BMP Fact Sheet T-12. This includes outlet structure details including orifice plates and trash racks.

**HISTORIC, EXISTING AND PROPOSED DRAINAGE MAPS**





**STERLING RANCH**  
N.T.S.



**HISTORIC CONDITION**

BASIN SUMMARY			
BASIN	AREA (ACRES)	Q <sub>5</sub> (CFS)	Q <sub>100</sub> (CFS)
EX-1	24	3	40
EX-2	31	3	45
EX-3	311	49	341
EX-4	330	71	352
EX-5	152	14	209
EX-6	1692	118	2168
EX-7	165	12	197
EX-8	42	4	64
EX-9	132	11	149
EX-10	450	48	474
EX-11	209	17	261
EX-12	40	5	65
EX-13	89	6	114
OS-20	318	61	310
OS-21	33	8	38
OS-22	88	18	91
OS-23	78	34	84


\* NOTE: BASIN S OS-22 & OS-23 NOT PART OF THIS REPORT. FLOWS FOLLOW HISTORIC PATTERNS ON THE WEST SIDE OF VOLLNER ROAD.

**HISTORIC CONDITION**

DESIGN POINT	DESIGN POINTS			
	SQ. MI.	Q <sub>5</sub> (CFS)	Q <sub>100</sub> (CFS)	DBPS
1	0.09	5	84	
2	0.49	49	341	0.74
3	0.52	139	2610	4.33
4	0.26	12	197	
5	0.07	4	64	
6	0.21	11	149	
7	0.70	48	474	
8	0.39	18	305	
9	0.14	6	114	
10	2.64	122	2245	3.27
11	0.09	5	83	
12A	0.01	3	16	
12	0.27	10	200	
13	0.17	6	126	

\* NOTE: SQ. MI. ARE NOT CONSISTANT AT EACH DESIGN POINT DP-DBPS

0.48	#	55
0.53		56
5.38		60



- LEGEND**
- EXISTING MDDP BASIN ACREAGE
  - EXISTING FLOW RELEASE POINT
  - FLOW DIRECTION
  - BASIN BOUNDARY
  - FILING NO.1 & NO.2 DIVISION LINE
  - PROPERTY BOUNDARY
  - EXISTING CONTOUR
  - CULVERT PIPE

MS  
CIVIL CONSULTANTS, INC.  
15 NORTH NEVADA AVENUE  
COLORADO SPRINGS, CO 80903  
(719) 955-5485, FAX (719) 471-4812

**STERLING RANCH**  
**HISTORIC - DRAINAGE MAP**

PROJECT NO. 09-002	FILE: O:\dwg\Eng Exhibits\MDDP HISTORIC	SCALE	DATE: 2/6/17
DESIGNED BY: VAS	HORIZ: 1"=1000'	VERT: N/A	
DRAWN BY: VAS			
CHECKED BY: VAS			

SHEET 1 OF 1



WLD RIDGE  
FILING NO. 2  
EPC

SUB-BASIN EX3

SUB-BASIN EX3

SUB-BASIN EX3

EPC  
\*UNPLATTED\*

SUB-BASIN EX3

SUB-BASIN EX3

STERLING RANCH FILING NO. 1


PROPOSED FINAL DRAINAGE MAP

PROJECT NO. 09-002 DATE: 1/2/2018

DESIGNED BY: ET  
DRAWN BY: BB  
CHECKED BY: GT

SHEET 4 OF 4 SHEET 4

20 BOULDER CRESCENT SUITE 110  
COLORADO SPRINGS, CO 80903  
PHONE: 719.555.5485





FOR AND ON  
BEHALF OF  
M&S CIVIL  
CONSULTANTS,  
INC.

APPROVED BY: DATE: 1/2/2018

REVISIONS: NO. DATE: DESCRIPTION:

THE ENGINEER PREPARING THESE PLANS WILL NOT BE RESPONSIBLE FOR UNAUTHORIZED CHANGES TO OR USES OF THESE PLANS. ALL CHANGES TO THE PLANS MUST BE IN WRITING AND MUST BE APPROVED BY THE PREPARER OF THESE PLANS.

CAUTION



**LEGEND**

BASIN DESIGNATION: Z, C5, C100

ACRES: 25, .25, .35

- PIPE RUN REFERENCE LABEL
- SURFACE DESIGN POINT
- BASIN BOUNDARY
- EX CONTOUR
- PROP CONTOUR
- STORM SEWER PIPE
- CROSSSPAN
- INLET
- EX FLOW DIRECTION ARROW
- EMERGENCY OVERFLOW DIRECTION
- FLOW DIRECTION
- FLARED END SECTION
- FILING LINE

**BASIN SUMMARY**

BASIN	AREA (ACRES)	Q5	Q100	
B	5.39	8.0	19.3	
C	2.92	4.2	10.1	
E	8.24	12.2	29.6	
F	1.12	4.3	7.7	
G	0.61	0.5	1.9	
H	0.19	0.9	1.6	
I	2.1	8.9	15.9	
J	0.43	0.4	1.3	
K	0.61	0.5	1.9	
L	1.54	5.6	10.0	
M	1.15	1.0	3.6	
M2	1.60	0.4	3.2	
R	9.73	12.5	30.4	
S	1.97	0.7	5.3	
SUB-BASIN	OS1A	2.07	0.7	5.3
SUB-BASIN	OS1B	9.09	2.4	17.8
SUB-BASIN	OS1C	5.64	1.5	11.1
SUB-BASIN	OS1D	94.3	16.3	119.5
SUB-BASIN	DP9			
SUB-BASIN	V1A	0.31	1.4	2.6
SUB-BASIN	V1B	0.26	1.2	2.2
SUB-BASIN	V1C	0.21	1.0	1.7
SUB-BASIN	V1D	0.13	0.6	1.1
SUB-BASIN	V2	0.32	0.9	0.96
SUB-BASIN	W-2	10.0	0.35	
SUB-BASIN	OS1D	94.3	0.08	0.35
SUB-BASIN	OS1C	5.64	0.08	0.35
SUB-BASIN	V1C	0.21	0.90	0.96
SUB-BASIN	V1B	0.26	0.90	0.96
SUB-BASIN	V1A	0.31	0.90	0.96
SUB-BASIN	OS1A	2.70	0.08	0.35
SUB-BASIN	EX-4A	5.98	0.25	0.47
SUB-BASIN	EX-4B	186	0.08	0.35
SUB-BASIN	EX-4C	9.4	0.08	0.35
SUB-BASIN	EX-4D	186	0.08	0.35
SUB-BASIN	EX-4E	186	0.08	0.35
SUB-BASIN	EX-4F	186	0.08	0.35
SUB-BASIN	EX-4G	186	0.08	0.35
SUB-BASIN	EX-4H	186	0.08	0.35
SUB-BASIN	EX-4I	186	0.08	0.35
SUB-BASIN	EX-4J	186	0.08	0.35
SUB-BASIN	EX-4K	186	0.08	0.35
SUB-BASIN	EX-4L	186	0.08	0.35
SUB-BASIN	EX-4M	186	0.08	0.35
SUB-BASIN	EX-4N	186	0.08	0.35
SUB-BASIN	EX-4O	186	0.08	0.35
SUB-BASIN	EX-4P	186	0.08	0.35
SUB-BASIN	EX-4Q	186	0.08	0.35
SUB-BASIN	EX-4R	186	0.08	0.35
SUB-BASIN	EX-4S	186	0.08	0.35
SUB-BASIN	EX-4T	186	0.08	0.35
SUB-BASIN	EX-4U	186	0.08	0.35
SUB-BASIN	EX-4V	186	0.08	0.35
SUB-BASIN	EX-4W	186	0.08	0.35
SUB-BASIN	EX-4X	186	0.08	0.35
SUB-BASIN	EX-4Y	186	0.08	0.35
SUB-BASIN	EX-4Z	186	0.08	0.35

**STORM SEWER SUMMARY**


PIPE RUN	Q5	Q100	PIPE SIZE	CONTRIBUTING PIPES
2	8.0	19.3	36" RCP	DP2
3	11.6	27.6	36" RCP	DP5,PR2
4	21.8	42.1	36" RCP	DP6,PR3
5	4.2	10.1	18" RCP	DP3
6	16.8	29.4	30" RCP	DP4,PR5
10	12.5	30.4	30" RCP	DP9
11	2.7	36.2	30" RCP	OUTFLOW UD-DET3.04
12	26.5	200.3	60" RCP	SUM PR11,PR18
15	42.1	76.8	42" RCP	DP15 DEVELOPED
18A	18.9	133.7	54" RCP	DP59
18	23.8	164.1	54" RCP	PR18,PR1
70	0.5	4.9	18" CMP	OUTFLOW UD-DET3.04
72	0.7	5.3	EX 12" CMP	OS1A
77	4.8	26.1	24" RCP	DP63
78	2.2	12.3	18" RCP	DP64
79	7.0	38.2	30" RCP	PR77,PR78
80	0.6	8.8	18" RCP	DP61
81	7.6	46.8	30" RCP	PR79,PR80

**DESIGN POINT SUMMARY**

DESIGN POINT	Q5	Q100	BASIN	STRUCTURE
2	8.0	19.3	B	TSB/36" FES
3	4.2	10.1	C	TSB/18" FES
4	16.1	36.7	E,F	15" AT-GRADE INLET
5	4.2	19.7	G,H,FLOWBY DP4	15" AT-GRADE INLET
6	14.1	26.7	I,J,K,L	15" AT-GRADE INLET
9	12.5	30.4	R	TSB/30" FES
10	50.0	102.9	S,PR4,PR6,PR10	CUMULATIVE DETENTION POND 2.91'x9' INLET
11	18.9	162.1	PR11,PR18	SUMMED PEAK OUTFLOW
15	42.1	76.8	WP-3	TEMP SED POND
16	4.3	8.2	RP-2C	SHEET FLOW INTO POND W-9
17	4.9	9.9	RP-2B	PROP CDOT EMBANKMENT PROTEC.
58	4.7	15.0	EX4A	CUMULATIVE DETENTION POND 36" CMP RISER
59	31.2	166.7	W-2,V2,DP65	4'x14' MOD CDOT TYPE D INLET
61	8.9	21.3	M,M2,DP16,DP17	CUMULATIVE DETENTION POND 2.91'x2.91' INLET
62	1.6	6.9	SUB-BASIN OS1A,V1A	18" RCP
63	4.8	26.1	SUB-BASIN OS1B,V1B,DP62	2.9'x5.7' CDOT TYPE D INLET
64	2.2	12.3	SUB-BASIN OS1C,V1C	2.9'x2.9' CDOT TYPE C INLET
65	16.5	119.9	SUB-BASIN OS1D,V1D	EXISTING SWALE
66	26.4	193.7	SUB-BASIN EX-4B	PROPOSED SWALE
67	28.2	208.4	EX 4C,DP66,PR70	PROP SWALE OUTFALL SAND CREEK
DBPS 187	700	2380	SAND CREEK DRAINAGE BASIN PLANNING STUDY	

NOTE: GRADE CONTROL STRUCTURES IN SAND CREEK TO BE DESIGNED AND CONSTRUCTED BY DEVELOPER/METRO DISTRICT PRIOR TO DEVELOPMENT EAST OF SAND CREEK.

FOR BURIED UTILITY INFORMATION 48 HRS BEFORE YOU DIG CALL 1-800-922-1987



NOTE: TRACTS BB, K, G, E, C TO BE RE-PLATTED FOR DEVELOPMENT. A FINAL DRAINAGE REPORT WILL BE PROVIDED FOR EACH FINAL PLAT.



# HOMESTEAD AT STERLING RANCH FILING NO. 2

## COUNTY OF EL PASO, STATE OF COLORADO

### PROPOSED DRAINAGE MAP


JANUARY 2020

#### LEGEND

- BASIN DESIGNATION: BASIN DESIGNATION
- PIPE RUN REFERENCE LABEL: PIPE RUN REFERENCE LABEL
- SURFACE DESIGN POINT: SURFACE DESIGN POINT
- BASIN BOUNDARY: BASIN BOUNDARY
- EXISTING CONTOUR: EXISTING CONTOUR
- PROP CONTOUR: PROP CONTOUR
- HOMESTEAD FILING NOS. 2&3 BOUNDARY: HOMESTEAD FILING NOS. 2&3 BOUNDARY
- PROPOSED STORM SEWER PIPE: PROPOSED STORM SEWER PIPE
- EXISTING STORM SEWER PIPE: EXISTING STORM SEWER PIPE
- CROSSSPAN: CROSSSPAN
- INLET: INLET
- EXISTING FLOW DIRECTION ARROW: EXISTING FLOW DIRECTION ARROW
- PROPOSED FLOW DIRECTION ARROW: PROPOSED FLOW DIRECTION ARROW
- FLARED END SECTION: FLARED END SECTION
- H.P. X: HIGH POINT
- L.P. X: LOW POINT

**NOTE:**  
FOR CONSTRUCTION DRAWINGS AND DETAILS; SEE SAND CREEK BANK STABILIZATION PLAN, & GRADING AND EROSION CONTROL PLAN FOR HOMESTEAD AT STERLING RANCH FILING NO. 2 BY M&S CIVIL CONSULTANTS, INC.

SAND CREEK CHANNEL IMPROVEMENTS PLANS ARE FORTHCOMING PROVIDED BY KIWIA ENGINEERING. THESE PLANS WILL DEPICT THE IMPROVEMENTS TO THE SAND CREEK CHANNEL, THE FINAL TRAIL LOCATION AND MAINTENANCE ACCESS LOCATIONS FOR THE SAND CREEK DRAINAGE STRUCTURES.



STORM SEWER SUMMARY			
PIPE RUN	Q <sub>s</sub>	Q <sub>100</sub>	CONTRIBUTING PIPES/DESIGN POINTS
1	5.7	13.8	18" RCP DP7
2	4.9	11.8	18" RCP DP8
3	10.6	25.7	24" RCP PR1, PR2
4	12.4	30.1	30" RCP DP9, PR3
5	9.1	12.7	18" RCP DP10
6	1.9	12.7	18" RCP DP11
7	10.9	25.3	30" RCP PR5, PR6
8	6.2	17.2	24" RCP DP12
9	17.9	47.1	42" RCP DP13, PR7, PR8
10	0.7	23.5	24" RCP OUTLET STRUC.
11	42.1	76.8	42" RCP CONTINUED FROM MDDP PIPE#1
12	0.0	1.3	12" ADS LOTS 36-41
13	0.0	1.6	12" ADS LOTS 28-35
14	0.0	1.5	12" ADS LOTS 19-24
15	0.0	1.4	12" ADS LOTS 13-18
4*	21.8	42.1	36" RCP SEE MDDP*
6*	16.8	29.4	30" RCP SEE MDDP*
10*	12.5	30.4	30" RCP SEE MDDP*

BASIN SUMMARY			
BASIN	AREA (ACRES)	Q <sub>s</sub>	Q <sub>100</sub>
ONSITE BASINS			
J	0.43	0.4	1.3
K	0.61	0.5	1.9
P	4.42	5.7	13.8
Q	3.78	4.9	11.8
R	1.57	2.2	5.4
T	9.14	9.4	26.4
U	4.50	6.4	15.6
V1	1.48	2.1	5.0
V2	0.83	1.2	2.9
W1	0.56	0.2	1.7
W2	0.26	0.1	0.8
W3	0.56	0.2	1.7
X	0.22	0.2	0.8
X1	0.78	0.8	2.8
X2	1.04	1.1	3.7
Y	0.09	0.1	0.3
Y1	0.84	0.8	3.0
Y2	0.21	0.2	0.7
B*	5.39	8.0	19.3
C*	2.92	4.2	10.1
D*	2.90	4.3	10.4
E*	5.34	8.2	19.9
F*	1.12	0.9	2.2
G*	0.61	0.4	1.3
H*	0.19	0.2	0.6
I*	2.10	0.9	2.2
L*	1.54	0.9	2.2
M*	1.57	0.5	1.9
N*	1.12	0.9	2.2
O*	3.78	4.9	11.8
S*	1.97	0.8	3.0
V1	1.48	2.1	5.0
V2	0.83	1.2	2.9
W1	0.56	0.2	1.7
W2	0.26	0.1	0.8
W3	0.56	0.2	1.7
X	0.22	0.2	0.8
X1	0.78	0.8	2.8
X2	1.04	1.1	3.7
Y	0.09	0.1	0.3
Y1	0.84	0.8	3.0
Y2	0.21	0.2	0.7

FULL SPECTRUM DETENTION INTERIM POND 1	
WQ VOLUME	0.245 AC-FT
EURY VOLUME	0.741 AC-FT
100 YR STORAGE VOLUME	1.331 AC-FT
100 YR WATER SURFACE EL	7083.91
SPILLWAY CREST EL	7084.16
TOP OF EMBANKMENT EL	7086.00
SPILLWAY DESIGN FLOW DEPTH	0.84 FT

DESIGN POINT SUMMARY			
DESIGN POINT	Q <sub>s</sub>	Q <sub>100</sub>	STRUCTURE
2*	8.0	19.3	(2) EX. 15" AT-GRADE INLETS
3*	4.2	10.1	EX. 6" SUMP INLET
4*	16.1	36.7	D*, E*, F* EX. 15" AT-GRADE INLET
5*	4.2	19.7	G*, H*, FLOWBY DP4* EX. 15" AT-GRADE INLET
6*	14.1	26.7	I*, J*, K*, L* EX. 15" AT-GRADE INLET
7	5.7	13.8	P PROP. 10" SUMP INLET
8	4.9	11.8	Q PROP. 10" SUMP INLET
9	2.2	5.4	R PROP. 5" SUMP INLET
10	9.4	15.6	T PROP. 15" AT-GRADE INLET
11	1.9	15.6	V1 PROP. 15" AT-GRADE INLET
12	6.2	17.2	U, FLOWBY DP10 PROP. 10" SUMP INLET
13	1.2	5.9	V2, FLOWBY DP11 PROP. 5" SUMP INLET
14	19.6	52.4	W3, PR9 CUMULATIVE DETENTION POND

\* For detailed information on Design Points, Basins, Flowby, or Pipe Runs see Sterling Ranch Filing Nos. 1&2 MDDP prepared by M&S Civil Consultants, dated April 2017. Refer to Homestead at Sterling Ranch Filing No. 2 Grading and Erosion Control Plan for additional interim channel stabilization improvements. All elevations provided on map are referenced in NGVD29.

ACCESS TO MAINTAIN THESE SAND FILTER BASINS WILL BE FROM THE REGIONAL TRAIL ALONG SAND CREEK

File: 0:\08007A\Sterling Ranch No 2\Map\Eng Exhibit\Prop. Drain. Map Homestead Fil. No 2.dwg Plotstamp: 1/15/2020 11:17 AM

FOR LOCATING & MARKING GAS, ELECTRIC, WATER & TELEPHONE LINES  
FOR BURIED UTILITY INFORMATION  
48 HRS BEFORE YOU DIG  
CALL 1-800-922-1987

20 BOULDER CRESCENT, SUITE 110  
COLORADO SPRINGS, CO 80903  
PHONE: 719.955.5485

HOMESTEAD AT STERLING RANCH FIL. NO. 2  
PROPOSED DRAINAGE MAP

PROJECT NO. 09-007	SCALE: HORIZONTAL: 1"=100' VERTICAL: N/A	DATE: 01/15/2020
DESIGNED BY: CMN	CHECKED BY: VAS	SHEET 1 OF 1
		PDM