Stormwater Detention and Infiltration Design Data Sheet

Workbook Protected   Worksheet Protected

Stormwater Facility Name: PRIVATE FULL SPECTRUM DETENTION POND

Facility Location & Jurisdiction: CROSSROADS MIXED USE FILING NO. 1

User Input: Watershed Characteristics

Watershed Slope =	0.006	ft/ft
Watershed Length =	1725	ft
Watershed Area =	32.10	acres
Watershed Imperviousness =	78.7%	percent
Percentage Hydrologic Soil Group A =	100.0%	percent
Percentage Hydrologic Soil Group B =	0.0%	percent
Percentage Hydrologic Soil Groups C/D =	0.0%	percent
Location for 1-hr Rainfall Depths (use dropdown):		
User Input	▼	

WQCV Treatment Method = Extended Detention ▼

| User Defined Stage [ft]	User Defined Area [ft^2]	User Defined Stage [ft]	User Defined Discharge [cfs]
0.00	126	0.00	0.00
0.32	241	0.32	0.00
1.32	584	1.32	0.00
2.32	4,627	2.32	0.02
3.32	10,590	3.32	0.03
4.32	20,623	4.32	0.04
5.32	30,665	5.32	0.05
6.32	39,263	6.32	0.06
7.32	43,385	7.32	1.00
8.32	47,718	8.32	7.00
9.32	65,080	9.32	82.70

After completing and printing this worksheet to a pdf, go to:
https://maperture.digitaldataservices.com/gvh/?viewer=cswdif
create a new stormwater facility, and
attach the pdf of this worksheet to that record.

Routed Hydrograph Results

Design Storm Return Period =	WQCV	2 Year	5 Year	10 Year	50 Year	100 Year	
One-Hour Rainfall Depth =	0.53	1.19	1.50	1.75	2.25	2.52	in
Calculated Runoff Volume =	0.857	2.271	2.926	3.563	5.082	5.859	acre-ft
OPTIONAL Override Runoff Volume =							acre-ft
Inflow Hydrograph Volume =	0.856	2.271	2.925	3.563	5.073	5.852	acre-ft
Time to Drain 97% of Inflow Volume =	>144	>144	**>144**	>144	>144	>144	hours
Time to Drain 99% of Inflow Volume =	>144	>144	>144	>144	>144	**>144**	hours
Maximum Ponding Depth =	4.79	6.59	7.20	7.64	8.46	8.63	ft
Maximum Ponded Area =	0.58	0.93	0.98	1.03	1.15	**1.21**	acres
Maximum Volume Stored =	0.848	2.234	2.819	3.258	4.135	4.332	acre-ft

Stormwater Detention and Infiltration Design Data Sheet