

**FINAL DRAINAGE REPORT
FOR
GATEWAY TRUCKING**

**Gateway Trucking, LLC
11260 West Lane
Colorado Springs, CO 80929
(719) 492-7658
Contact: Perry Hastings**

**May 20th, 2022
Project No. 25215.00**

**Prepared By:
JR Engineering, LLC
5475 Tech Center Drive
Colorado Springs, CO 80919
719-593-2593**

El Paso County PCD File No. PPR-21-033

**Final Drainage Report
Gateway Trucking, LLC**

ENGINEER'S STATEMENT:

The attached drainage plan and report were prepared under my direction and supervision and are correct to the best of my knowledge and belief. Said drainage report has been prepared according to the criteria established by El Paso County for drainage reports and said report is in conformity with the master plan of the drainage basin. I accept responsibility for any liability caused by any negligent acts, errors, or omissions on my part in preparing this report.


Mike Bramlett, Colorado P.E. # 32314
For and On Behalf of JR Engineering, LLC



Date

6/14/22

DEVELOPER'S STATEMENT:

I, the developer, have read and will comply with all of the requirements specified in this drainage report and plan.

Business Name: Gateway Trucking, LLC

By: _____

Title: _____

Address: 11260 West Lane
Colorado Springs, CO 80929

El Paso County:

Filed in accordance with the requirements of the El Paso County Land Development Code, Drainage Criteria Manual, Volumes 1 and 2 and Engineering Criteria Manual, as amended.

Jennifer Irvine, P.E.
County Engineer/ ECM Administrator

Date

Conditions:



CONTENTS

PURPOSE.....	1
GENERAL LOCATION AND DESCRIPTION.....	1
LOCATION.....	1
DESCRIPTION OF PROPERTY.....	1
FLOODPLAIN STATEMENT.....	2
DRAINAGE BASINS AND SUBBASINS.....	2
EXISTING MAJOR BASIN DESCRIPTIONS.....	2
EXISTING SUB-BASIN DRAINAGE.....	2
PROPOSED SUB-BASIN DRAINAGE.....	4
DRAINAGE DESIGN CRITERIA.....	6
DEVELOPMENT CRITERIA REFERENCE.....	6
HYDROLOGIC CRITERIA.....	6
DRAINAGE FACILITY DESIGN.....	6
GENERAL CONCEPT.....	6
SPECIFIC DETAILS.....	7
<i>Four Step Process to Minimize Adverse Impacts of Urbanization</i>	7
<i>Erosion Control Plan</i>	8
<i>Operation & Maintenance</i>	8
<i>Drainage and Bridge Fees</i>	8
SUMMARY.....	8
REFERENCES:.....	9

APPENDICES

- A. Figures and Exhibits
- B. Hydrologic/Hydraulic Calculations
- C. Drainage Maps



PURPOSE

This document is the Drainage Report for Gateway Trucking, located along S. Franceville Coal Mine Road, County of El Paso, and State of Colorado. The project site is being developed for the purpose of having a parking area for commercial trucks and associated equipment. The land previous to this use was vacant and undeveloped. The purpose of this report is to:

1. Identify on-site and off-site drainage patterns.
2. Recommend storm water facilities to collect and convey storm runoff from the proposed development to adequate discharge and/or detention locations.
3. Recommend water quality and detention facilities to control discharge release rates to below historic.
4. Demonstrate compliance with surrounding major drainage basin planning studies, master development drainage plans and flood insurance studies.

GENERAL LOCATION AND DESCRIPTION

Location

The project property is approximately to the east of S. Franceville Coal Mine Road in the NW1/4, NW1/4 of Section 20, and that portion of the NE1/4, NE1/4 Section 19 T.14S., R.64W. of the 6th P.M. in El Paso County. The site consists of a portion of parcel 44000-00-531 totaling approximately 11.09 acres all bounded by fencing. The site is bounded to the west by S. Franceville Coal Mine Road, to the south by the remaining area of parcel 44000-00-531, to the east by the same parcel 44000-00-531, and to the north by parcel 44000-00-539 (same owner-Perry Hastings). A vicinity map is presented in Appendix A.

Description of Property

The subject site is currently a dirt area used as a parking area for commercial trucks with a surrounding undeveloped area consisting of sparse native vegetation coverage. There is an existing gravel access road from S. Franceville Coal Mine Road. This access road leads to the project site, existing dirt parking, and then continues to the east until it hits existing fence that encloses the project site. In general, the site slopes from the southeast to the northwest at slopes ranging from ~0-9% towards the existing low point and existing 30-inch CMP (corrugated metal pipe). That stormwater pipe is the only existing stormwater component located on the site. The ultimate outfall of this drainageway is Jimmy Camp Creek.

Per a NRCS web soil survey, the site is made up of Type B soils. Type B soils have a moderate infiltration when thoroughly wet. A NRCS soil survey map has been presented in Appendix A.

There are no known existing wells on the site.

Floodplain Statement

Based on the FEMA FIRM Map number 08041C0780G, dated December 7, 2018, the site lies within Zone X of the floodplain surrounding Jimmy Camp Creek. Zone X is defined as the area outside the Special Flood Hazard Area (SFHA) and higher than the elevation of the 500-yr floodplain. All proposed development on the Gateway Trucking Site will occur within Zone X.

The FIRM Map has been presented in Appendix A.

DRAINAGE BASINS AND SUB-BASINS

Existing Major Basin Descriptions

The site lies within the Jimmy Camp Creek Drainage Basin based on the “*Jimmy Camp Creek Drainage Basin Planning Study: Development of Alternatives & Design of Selected Plan Report*” prepared by Kiowa Engineering Corporation in March 2015. The Jimmy Camp Creek Drainage Basin is an east bank tributary to Fountain Creek and covers approximately 67.1 square miles located in El Paso County, CO. The basin generally slopes from north to south beginning near Garrett Road and outfalls into Fountain Creek just west of Old Pueblo Road (Main Street) near the City of Fountain’s historic downtown. The main channel of Jimmy Camp Creek has an approximate slope of 1.0% over the channel length of 24 miles.

The site is closest to the Franceville Tributary of Jimmy Camp Creek. As is shown in the appendices, the FIRM map states that the project site is located within floodplain Zone X. Therefore, the project site improvement will be conducted outside of the limit of the 500-year floodplain. No off-site channel improvements are recommended to be completed with the development this report supports.

Existing Sub-basin Drainage

On-site existing sub-basin drainage patterns are generally from southeast to northwest. The existing project site overall varies in slope depending on the location. The undeveloped areas (surrounding flat parking area) of the project site tend to have greater slopes ranging from as low as 7% (existing area draining towards existing 30” CMP) to as high as over 70% (slope towards from dirt area to local depression). The existing dirt parking area is generally flat and has less than 1% slope. The flat area drains to both the north and south through undefined drainage paths and eventually reaches a low point encased by a berm. Continuing further west after that existing berm is the existing outfall for the site which is a 30-inch CMP. There are no other existing stormwater facilities located on the site, and no existing utilities. The existing 30-inch culvert transports water from the east to the west-side of S. Franceville Coal Mine Road and into the existing drainageway. From there the water will follow the existing drainage patterns until it’s confluence with Jimmy Camp Creek, the ultimate receiving waters. There are no known wells or irrigation facilities located on-site. Below are existing basin descriptions. An existing drainage map is included in the appendices.

Existing off-site Basin OS1 is approximately 2.30 acres in area and consists completely of undeveloped, sparsely vegetated open space. Runoff generated ($Q_5=0.7$ cfs, and $Q_{100}= 4.4$ cfs), will flow west from the highpoint on the east to design point 1. Flow will then enter into existing Basin EX-A. Then it will follow the Basin EX-A flow path to the existing low point at design point 3.

Existing Basin EX-A is approximately 6.78 acres in area and consists of undeveloped, sparsely vegetated open space. Besides the undeveloped flat area, the surrounding sloped areas within the basin are also undeveloped. Runoff generated ($Q_5=1.3$ cfs, and $Q_{100}= 12.9$ cfs), will flow from east to west towards the existing basin low-point at design point 3. From design point 3, runoff will then enter into Basin EX-B flowing west to northwest and the flow will reach design point 5, which is the ultimate outfall for the project site.

Existing off-site Basin OS2 is approximately 4.64 acres in area and consists completely of undeveloped, sparsely vegetated open space. Runoff generated ($Q_5=1.2$ cfs, and $Q_{100}= 8.1$ cfs), will flow west from the highpoint on the east. Flow will then go from design point 2 into existing Basin EX-A. Then it will follow the Basin EX-A flow path to the existing low point at design point 3.

Existing off-site Basin OS3 is approximately 0.60 acres in area and consists of undeveloped, sparsely vegetated open space, as well as part of the existing S. Franceville Coal Mine Road. Runoff generated ($Q_5=0.4$ cfs, and $Q_{100}= 1.5$ cfs), will flow west from the highpoint on the south to design point 4. Runoff will then utilize the existing roadway swale along S. Franceville Coal Mine Road and flow into existing Basin EX-B. Then it will follow the Basin EX-B flow path to the existing site outfall at design point 5.

Existing Basin EX-B is approximately 3.76 acres in area and consists of undeveloped, sparsely vegetated open space. Part of Basin EX-B consists of runoff flowing from east to west along the south side of the existing gravel road. The apparent local depression to the north of the access road did not appear deep based on a site visit conducted. See the attached report for more information and pictures of the existing conditions. Runoff generated ($Q_5=0.4$ cfs, and $Q_{100}= 8.0$ cfs), will sheet flow from towards the ultimate outfall for the project site at design point 5. The other part of Basin EX-B consists of runoff from the southwest fence line to the north towards design point 5. This existing flow is directed by an existing berm that directs flows on the east and west sides, into either Basin EX-A or EX-B. Runoff flows towards the west side of S. Franceville Coal Mine Road and is directed by an existing swale running to the north towards the existing site outfall at design point 5 ($Q_5=3.8$ cfs, and $Q_{100}= 32.5$ cfs).

The proposed grading will better use a berm near the existing outfall to separate on-site treated flows as well as off-site flows that will be directed to the existing outfall. The proposed grading will eliminate the local low-point in Basin EX-A and create an extended detention basin where on-site flows will be directed.

Proposed Sub-basin Drainage

The proposed improvements for the project site include creating a “flat” gravel area for commercial parking. The approximately 4.3 acre gravel parking area will start at the access from the paved roadway onto the project site and extends to the east, west, and south before meeting existing grade. Proposed grass-lined swales and berms will border the north and south edges of the parking area to direct runoff towards a common riprap rundown area. From there the runoff will flow down the protected riprap rundown to the forebay and into the proposed extended detention basin.

Below are the proposed sub-basin descriptions. Refer to the appendices for a proposed conditions drainage map.

Proposed Basin A is approximately 3.48 acres in area and consists of the south half of the gravel parking area, undeveloped land surrounding the parking area, and proposed berms and swales. The entirety of proposed Basin A is to be graded per the proposed contours shown on the proposed conditions drainage map. Runoff generated ($Q_5=4.5$ cfs, and $Q_{100}= 11.2$ cfs) flows overland from the highpoint located on the northern edge of the basin to the southwest towards a proposed earth berm. The proposed southern berm will transport the runoff west along the south edge of the gravel parking area at design point 1. Flows here will then enter into the proposed southern riprap armored swale located within Basin A and will combine flows ($Q_5=9.3$ cfs, and $Q_{100}= 22.4$ cfs) at design point 2.1, the pond riprap rundown. For all swale calculations, see Appendix B.

Proposed Basin B is approximately 3.37 acres in area and consists of the north half of the gravel parking area, part of the paved access road from S. Franceville Coal Mine Road, a proposed swale and berm, and undeveloped land surrounding the parking area. The entirety of proposed Basin B is to be graded per the proposed contours shown on the proposed conditions drainage map. Runoff generated ($Q_5=4.9$ cfs, and $Q_{100}= 11.7$ cfs) flows overland from the highpoint located on the southern edge of the basin to the northwest towards a proposed earth berm. The proposed northern berm will transport runoff along the northern edge of the gravel parking area west towards the edge of the gravel parking area at design point 2. Flows here will then enter into the proposed northern riprap armored swale located within Basin B and will combine flows ($Q_5=9.3$ cfs, and $Q_{100}= 22.4$ cfs) at design point 2.1, the pond riprap rundown. For all swale calculations, see Appendix B.

Proposed Basin C is approximately 1.65 acres in area and consists of part of the paved access road from S. Franceville Coal Mine Road, a proposed swale and berm, and proposed undeveloped land bordering the southern edge of the basin containing a proposed swale. The area of proposed Basin C south of the paved road is to be graded per the proposed contours shown on the proposed conditions drainage map. Runoff generated ($Q_5=1.6$ cfs, and $Q_{100}= 5.0$ cfs) flows generally from northeast to southwest within the Basin. Runoff generated travels overland to the proposed grass swale along the southern edge of asphalt and flow in the swale is transported along the edge of asphalt until it reaches the proposed full-spectrum EDB at design point 3. Flows here are combined at design point 4, the total inflow into the pond.

Proposed Basin D is approximately 1.48 acres in area and consists of a proposed extended detention pond and associated structures (earth forebay, outlet structure, riprap rundown, etc.). The entirety of proposed Basin D is to be graded per the proposed contours shown on the proposed conditions drainage map. Runoff generated ($Q_5= 1.9$ cfs, and $Q_{100}= 5.8$ cfs) flows from east to west into the proposed detention pond. Flows from both the north and south swales also will combine at the proposed riprap rundown (design point 2.1) and then flow into the proposed forebay. Design point 4 ($Q_5= 12.1$ cfs, and $Q_{100}= 31.3$ cfs) is the total inflow into the proposed full-spectrum EDB.

Proposed off-site Basin OS1 is approximately 2.48 acres in area and consists of the previously defined Basin OS1 (totaling 2.29 acres) and some additional area. The area entirely is made up of undeveloped, sparsely vegetated open space. The Basin has no proposed grading and will remain in the existing condition. Runoff generated ($Q_5= 0.7$ cfs, and $Q_{100}= 4.6$ cfs) flows generally from the highpoint on the southeast and flows overland northwest towards design point 5. Flows will then be routed around the property by the proposed berm, flowing off-site northwest following the historic drainage pattern.

Proposed Basin F is approximately 0.40 acres in area and consists of the proposed berm on the eastern and northern borders of the property, as well as a part of the proposed paved driveway. All of the proposed grading within this Basin was designed to create a berm to block the adjacent neighbor's view of the parking area. The berm will direct the offsite flows north and route them around the property. Runoff generated ($Q_5= 0.2$ cfs, and $Q_{100}= 1.1$ cfs) flows from the southeast following the proposed berm north and then west along the property. This drainage path follows the historical drainage path from southeast to northwest as shown in the existing conditions drainage map. Untreated runoff is in accordance with Appendix I.7.1.B.7 of the ECM Stormwater Quality Policy and Procedure with proposed land disturbance to undeveloped land that will remain undeveloped. A berm and is created on undeveloped land within Basin F which will separate flows and remain undeveloped once completed. The driveway acreage within Basin E is 0.02 acres which is 0.2% of the development site, falling within the 20% limit listed in ECM Appendix I.7.1.C.1.

Proposed off-site Basins OS2 and OS3 have the same definition as listed above in the existing sub-basins section. These flows will be routed around the proposed detention pond and will flow to the existing outfall of the project site (existing 30-inch CMP). Runoff from OS2 will flow to design point 7 ($Q_5= 1.2$ cfs, and $Q_{100}= 8.1$ cfs) and runoff from OS3 will flow to design point 8 ($Q_5= 0.5$ cfs, and $Q_{100}= 1.6$ cfs), before they both combine at design point 9. The runoff from these basins ultimately will flow to the same historical outfall following the existing drainage path, guided by the proposed berm on the southwest of the site.

Proposed Basin E is approximately 0.70 acres in area and consists of undeveloped land as well as part of the proposed driveway. Only a small portion of Basin E will be graded per the proposed contours shown on the proposed conditions drainage map. All of the proposed grading within this Basin is designed to create a berm to separate the flows that will enter into the detention pond and the flows that will not. Runoff generated ($Q_5= 0.5$ cfs, and $Q_{100}= 2.1$ cfs) flows from the southeast

following the proposed berm around the proposed detention pond and into the existing drainage area for the project site (existing 30-inch CMP). This drainage path follows the historical drainage path from south to north as shown in the existing conditions drainage map. The flows meet at design point 9 ($Q_5= 1.9$ cfs, and $Q_{100}= 10.9$ cfs) where Basins OS2, OS3, and E combine. Development will be limited to up to 1 acre for areas that do not have a water quality feature downstream in order to satisfy Appendix I.7.1.B of the ECM Stormwater Quality Policy and Procedure. See highlighted areas on the proposed drainage map presented in Appendix D. The following from the PBMP applicability form applies: the project land disturbance to undeveloped land where undeveloped land remains undeveloped following the activity. A berm and swale is created on undeveloped land within Basin E which will separate flows and remain undeveloped once completed. The driveway acreage within Basin E is 0.06 acres which is 0.5% of the development site, falling within the 20% limit listed in ECM Appendix I.7.1.C.1. Flows from design point 9 combine with the maximum pond release rate flows at design point 9.1 ($Q_5= 4.0$ cfs, and $Q_{100}= 22.4$ cfs), the total flow to the existing 30" CMP.

DRAINAGE DESIGN CRITERIA

Development Criteria Reference

Storm drainage analysis and design criteria for this project were taken from the “*City of Colorado Springs/El Paso County Drainage Manual*” Volumes 1 and 2 (EPCDCM), dated October 12, 1994, the “*Urban Storm Drainage Criteria Manual*” Volumes 1-3 (USDCM), dated June, 2001 and Chapter 6 and Section 3.2.1 of Chapter 13 of the “*Colorado Springs Drainage Criteria Manual*” (CCSDCM), dated May 2014, as adopted by El Paso County.

Hydrologic Criteria

All hydrologic data was obtained from the “*El Paso Drainage Criteria Manual*” Volumes 1 and 2, and the “*Urban Drainage and Flood Control District Urban Storm Drainage Criteria Manual*” Volumes 1-3. On-site drainage improvements were designed based on the 5-year (minor) storm event and the 100-year (major) storm event. Rational Method calculations were prepared, in accordance with Section 13.3.2.1 of the CCSDCM, for the sub-basins that directly impact the sizing of ditches and local street culverts. Rational Method calculations are presented in the appendices.

DRAINAGE FACILITY DESIGN

General Concept

The proposed stormwater conveyance system was designed to convey the developed runoff from proposed Basins A-D to a proposed private full-spectrum extended detention basin (EDB). The pond was designed to detain the 100-year design storm or 0.817 acre-feet. Runoff generated on-site is tributary to the detention basin via several grass swales and earth berms that outfall into a proposed riprap rundown, and then into a forebay. The forebay was designed based on the guidance from the

MHFD methodology, having a minimum volume of 2% of the water quality capture volume (WQCV) and releasing 2% of the 100-year peak inflow to the pond. See the attached calculations for the required and provided forebay volume and release rate. The forebay will have a concrete bottom and will outfall via an angled notch in the concrete berm wall of the forebay, then enter the into the proposed 6-inch deep concrete trickle channel. The trickle channel slopes from the forebay to the outlet structure. The outlet structure uses a standard Type-C inlet grate and has been designed to detain the WQCV for 40 hours, the EURV for 72 hours, and to release the 100-year storm at a maximum rate less than or equal to the pre-development rate. The outlet structure will release these flows through a 24-inch RCP (reinforced concrete pipe) to the existing site outfall and then drain across S. Franceville Coal Mine road (existing 30-inch CMP). A site visit was conducted and the existing conditions of the roadway and culvert are shown in the attached report. Also attached is the HY-8 analysis summary for the existing 30" CMP. For the design flow, a combination of the untreated flows and the pond released flows was used. The flows from design point 9 in the 100-year storm are 10.9 cfs and combined with the 100-year release rate of the outlet structure of 11.5 cfs, the total design flow is 22.4 cfs (as shown on design point 9.1). The HY-8 results show that at this flow, the water is contained within the culvert and does not overtop the roadway. The pre-development release rate of the tributary area to the pond was 32.5 cfs. Since the release rate is less than half of the existing flow, the flow tributary to the existing 30" CMP is also lower.

The proposed pond also includes an emergency spillway which has been designed to pass the undetained, 100-year peak flow rate tributary to the pond at a flow depth of approximately 0.48 feet. The spillway will be armored with Type VL riprap at a minimum depth of 12 inches, sized per UDFCD Figure 12-21 as shown in Appendix B. The crest elevation is 6237.50' and the top of pond elevation is 6239.00', showing there is over a foot of freeboard above the design water surface elevation at the crest of the spillway to the top of the pond.

Specific Details

Four Step Process to Minimize Adverse Impacts of Urbanization

In accordance with the El Paso County Drainage Criteria Manual Appendix I.7.2, this site has implemented the four step process to minimize adverse impacts of urbanization. The four step process includes employing runoff reduction practices, stabilizing drainageways, treating the water quality capture volume (WQCV), and consider the need for Industrial Commercial BMP's.

Step 1, Employ Runoff Reduction Practices: As shown by the attached drainage maps and Rational Method calculations, the runoff leaving the subject site is less than the runoff presently leaving the site. The impervious area is minimized on the site and all impervious areas have runoff routed through pervious surfaces, thus reducing the runoff volumes generated from the site.

Step 2, Stabilize Drainageways: The proposed condition will reduce flows tributary to downstream drainageways to at or below pre-development rates. State Basin fees will be paid prior to

construction/ development of the site. Therefore, no downstream stabilizations BMP's are proposed as part of this project.

Step 3, Provide WQCV: All developed flows from the Basins A-D are treated via the proposed full-spectrum extended detention basin including a forebay, trickle channel, and full spectrum outlet structure. Other Basins that flow offsite satisfy the criteria set forth in Appendix I.7.1.B of the ECM Stormwater Quality Policy and Procedure. Therefore, the WQCV is treated.

Step 4 Consider the need for Industrial and Commercial BMP's: The proposed design utilizes site grading and a proposed extended detention basin to capture developed flows, and treat them on-site. Per the El Paso County DCM Volume 2 fact sheet, spill containment and the covering of storage/handling areas will be utilized for all on-site activities. Using these BMPs will ensure that no adverse downstream or adjacent impacts are created as a result of the proposed project site.

Erosion Control Plan

The El Paso County Drainage Criteria Manual specifies an Erosion Control Plan and associated cost estimate must be submitted with each Final Drainage Report. The Erosion Control Plan for this site is submitted concurrently with this report.

Operation & Maintenance

In order to ensure the function and effectiveness of the stormwater infrastructure, maintenance activities such as inspection, routine maintenance, restorative maintenance, rehabilitation and repair, are required. All proposed drainage structures will be maintained by the site owner/developer. A 10-foot wide earth berm has been included to access the trickle channel, low tailwater basin, and outlet structure of the Extended Detention Basin.

Drainage and Bridge Fees

Drainage fees are imposed with final plats, or vacate & replats, note site development plan; therefore, no drainage fees are due with this side development plan application.

The property is currently unplatted and therefore the basin drainage fees will be assessed on future plat application since no fees have been previously paid.

SUMMARY

The proposed development remains consistent with pre-development drainage conditions with the construction of the recommended drainage improvements, including berms, swales, and extended detention basin improvements. The proposed development will not adversely affect the offsite major Drainageways or surrounding development. This report meets the latest El Paso County Drainage Criteria requirements for this site and is in accordance with the previously approved reports.

REFERENCES

1. City of Colorado Springs Drainage Criteria Manual Volume 1, City of Colorado Springs, CO, May 2014.
2. Urban Storm Drainage Criteria Manual, Urban Drainage and Flood Control District, Latest Revision.
3. Jimmy Camp Creek Drainage Basin Planning Study: Development of Alternatives & Design of Selected Plan Report, prepared by Kiowa Engineering Corporation in March 2015.
4. “Hydrologic Soil Group Rating for El Paso County Area, Colorado”, USDA-Natural Resources Conservation Service, National Cooperative Soil Survey, June 21, 2017

APPENDIX A
FIGURES AND EXHIBITS

CORRAL VALLEY ROAD

HIGHWAY 94

N. BLANEY ROAD

N. FRANCEVILLE
COAL MINE ROAD

S. BLANEY ROAD

UPPER TRIBUTARY-
TO CHICO CREEK

KIRK DRIVE

SITE

HANDLE ROAD

ISAAC WALTON
RANGE

FRANCEVILLE TRIBUTARY-
JIMMY CAMP CREEK

MINES SUB-TRIBUTARY
TO CORRAL TRIBUTARY

S. FRANCEVILLE
COAL MINE ROAD



VICINITY MAP
GATEWAY TRUCKING, LLC
JOB NO. 25215.00
04/05/21
SHEET 1 OF 1

2000 1000 0 2000



ORIGINAL SCALE: 1" = 2000'




J·R ENGINEERING


A Westrian Company

Centennial 303-740-9393 • Colorado Springs 719-593-2593
Fort Collins 970-491-9888 • www.jrengineering.com

Hydrologic Soil Group—El Paso County Area, Colorado



Soil Map may not be valid at this scale.



MAP LEGEND

Area of Interest (AOI)









 Area of Interest (AOI)

Soils

Soil Rating Polygons





-  A
-  A/D
-  B
-  B/D
-  C
-  C/D
-  D
-  Not rated or not available

Soil Rating Lines

-  A
-  A/D
-  B
-  B/D
-  C
-  C/D
-  D
-  Not rated or not available

Soil Rating Points






-  A
-  A/D
-  B
-  B/D

-  C
-  C/D
-  D
-  Not rated or not available

Water Features

 Streams and Canals

Transportation

-  Rails
-  Interstate Highways
-  US Routes
-  Major Roads
-  Local Roads

Background

 Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:24,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: El Paso County Area, Colorado
 Survey Area Data: Version 18, Jun 5, 2020

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Sep 11, 2018—Oct 20, 2018

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Hydrologic Soil Group

Map unit symbol	Map unit name	Rating	Acres in AOI	Percent of AOI
28	Ellicott loamy coarse sand, 0 to 5 percent slopes	A	2.5	1.1%
56	Nelson-Tassel fine sandy loams, 3 to 18 percent slopes	B	83.3	35.6%
84	Stapleton sandy loam, 8 to 15 percent slopes	B	55.9	23.9%
89	Tassel fine sandy loam, 3 to 18 percent slopes	D	25.1	10.7%
115	Lithic Haplustepts-Rock outcrop complex	D	50.8	21.8%
124	Olnest sandy loam, 0 to 3 percent slopes	B	16.1	6.9%
Totals for Area of Interest			233.8	100.0%

Description

Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The soils in the United States are assigned to four groups (A, B, C, and D) and three dual classes (A/D, B/D, and C/D). The groups are defined as follows:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

If a soil is assigned to a dual hydrologic group (A/D, B/D, or C/D), the first letter is for drained areas and the second is for undrained areas. Only the soils that in their natural condition are in group D are assigned to dual classes.

Rating Options

Aggregation Method: Dominant Condition

Component Percent Cutoff: None Specified

Tie-break Rule: Higher

nes Subtributary
Corral Tributary

17

FRANCEVILLE COAL MINE RD

SITE

20

LIMIT OF STUDY



Franceville Tributary -
Jimmy Camp Creek

ZONE AE

EL PASO COUNTY
UNINCORPORATED AREAS
080059



MAP SCALE 1" = 1000'



NFP

PANEL 0780G

FIRM
FLOOD INSURANCE RATE MAP
EL PASO COUNTY,
COLORADO
AND INCORPORATED AREAS

PANEL 780 OF 1300

(SEE MAP INDEX FOR FIRM PANEL LAYOUT)

CONTAINS:

COMMUNITY	NUMBER	PANEL	SUFFIX
COLORADO SPRINGS, CITY OF	080060	0780	G
EL PASO COUNTY	080059	0780	G

Notice: This map was reissued on 05/15/2020 to make a correction. This version replaces any previous versions. See the Notice-to-User Letter that accompanied this correction for details.

Notice to User: The Map Number shown below should be used when placing map orders. The Community Number shown above should be used on insurance applications for the subject community.



MAP NUMBER
08041C0780G

MAP REVISED
DECEMBER 7, 2018

Federal Emergency Management Agency

Upper
to

This is an official FIRMette showing a portion of the above-referenced flood map created from the MSC FIRMette Web tool. This map does not reflect changes or amendments which may have been made subsequent to the date on the title block. For additional information about how to make sure the map is current, please see the Flood Hazard Mapping Updates Overview Fact Sheet available on the FEMA Flood Map Service Center home page at <https://msc.fema.gov>.

APPENDIX B

HYDROLOGIC/HYDRAULIC CALCULATIONS

COMPOSITE % IMPERVIOUS CALCULATIONS

Subdivision: _____
 Location: Colorado Springs _____
 Date: 5/19/22 _____

Project Name: Gateway Trucking-Existing _____
 Project No.: 25215.00 _____
 Calculated By: GAG _____

	Basin ID	Total Area (ac)	Paved Roadway 100%					Gravel 80%					Undeveloped 2%					Basins Total Weighted C Values		Basins Total Weighted % Imp.
			C ₅	C ₁₀₀	% Imp.	Area (ac)	Weighted % Imp.	C ₅	C ₁₀₀	% Imp.	Area (ac)	Weighted % Imp.	C ₅	C ₁₀₀	% Imp.	Area (ac)	Weighted % Imp.	C ₅	C ₁₀₀	
	EX-A	6.78	0.90	0.96	100%	0.00	0.0%	0.59	0.70	80%	0.00	0.0%	0.09	0.36	2%	6.78	2.0%	0.09	0.36	2.0%
	EX-B	3.76	0.90	0.96	100%	0.00	0.0%	0.59	0.70	80%	0.50	10.6%	0.09	0.36	2%	3.26	1.7%	0.16	0.41	12.4%
	OS1	2.30	0.90	0.96	100%	0.00	0.0%	0.59	0.70	80%	0.00	0.0%	0.09	0.36	2%	2.30	2.0%	0.09	0.36	2.0%
	OS2	4.64	0.90	0.96	100%	0.00	0.0%	0.59	0.70	80%	0.00	0.0%	0.09	0.36	2%	4.64	2.0%	0.09	0.36	2.0%
	OS3	0.60	0.90	0.96	100%	0.00	0.0%	0.59	0.70	80%	0.15	20.0%	0.09	0.36	2%	0.45	1.5%	0.22	0.45	21.5%
Total Existing Conditions		18.08																-	-	4.8%

STANDARD FORM SF-2 TIME OF CONCENTRATION

Subdivision: _____
 Location: Colorado Springs
 Date: 5/19/22

Project Name: Gateway Trucking-Existing
 Project No.: 25215.00
 Calculated By: GAG

NOTES:

$$t_c = t_i + t_t$$

Equation 6-2

$$t_i = \frac{0.395(1.1 - C_s)\sqrt{L_i}}{S_o^{0.333}}$$

Equation 6-3

Where:

t_c = computed time of concentration (minutes)
 t_i = overland (initial) flow time (minutes)
 t_t = channelized flow time (minutes).

Where:

t_i = overland (initial) flow time (minutes)
 C_s = runoff coefficient for 5-year frequency (from Table 6-4)
 L_i = length of overland flow (ft)
 S_o = average slope along the overland flow path (ft/ft).

$$t_t = \frac{L_t}{60K\sqrt{S_o}} = \frac{L_t}{60V_t}$$

Equation 6-4

$$t_c = (26 - 17i) + \frac{L_t}{60(14i + 9)\sqrt{S_t}}$$

Equation 6-5

Where:

t_t = channelized flow time (travel time, min)
 L_t = waterway length (ft)
 S_o = waterway slope (ft/ft)
 V_t = travel time velocity (ft/sec) = $K\sqrt{S_o}$
 K = NRCS conveyance factor (see Table 6-2).

Where:

t_c = minimum time of concentration for first design point when less than t_c from Equation 6-1.
 L_t = length of channelized flow path (ft)
 i = imperviousness (expressed as a decimal)
 S_t = slope of the channelized flow path (ft/ft).

Table 6-2. NRCS Conveyance factors, K

Type of Land Surface	Conveyance Factor, K
Heavy meadow	2.5
Tillage/field	5
Short pasture and lawns	7
Nearly bare ground	10
Grassed waterway	15
Paved areas and shallow paved swales	20

Use a minimum t_c value of 5 minutes for urbanized areas and a minimum t_c value of 10 minutes for areas that are not considered urban. Use minimum values even when calculations result in a lesser time of concentration.

SUB-BASIN						INITIAL/OVERLAND			TRAVEL TIME					t_c CHECK			FINAL t_c (min)
DATA						(T _i)			(T _t)					(URBANIZED BASINS)			
BASIN ID	D.A. (ac)	Hydrologic Soils Group	Impervious (%)	C ₅	C ₁₀₀	L (ft)	S _o (%)	t _i (min)	L _t (ft)	S _t (%)	K	VEL. (ft/s)	t _t (min)	COMP. t _c (min)	TOTAL LENGTH (ft)	Urbanized t _c (min)	
EX-A	6.78	B	2.0%	0.09	0.36	115	16.5%	7.8	1125	2.7%	10	1.6	11.5	19.2	1240.0	38.0	19.2
EX-B	3.76	B	12.4%	0.16	0.41	70	1.2%	13.4	775	4.9%	10	2.2	5.8	19.3	845.0	29.3	19.3
OS1	2.30	B	2.0%	0.09	0.36	300	6.1%	17.4	245	6.1%	10	2.5	1.7	19.0	545.0	27.4	19.0
OS2	4.64	B	2.0%	0.09	0.36	300	6.1%	17.4	845	6.1%	10	2.5	5.7	23.1	1145.0	31.8	23.1
OS3	0.60	B	21.5%	0.22	0.45	300	5.1%	16.2	250	5.0%	10	2.2	1.9	18.0	550.0	23.9	18.0

STANDARD FORM SF-3
STORM DRAINAGE SYSTEM DESIGN
(RATIONAL METHOD PROCEDURE)

Subdivision: _____
 Location: Colorado Springs _____
 Design Storm: 5-Year (1-hr point precipitation = 1.12) _____

Project Name: Gateway Trucking-Existing _____
 Project No.: 25215.00 _____
 Calculated By: GAG _____
 Checked By: _____
 Date: 5/19/22 _____

STREET	Design Point	DIRECT RUNOFF							TOTAL RUNOFF				STREET			PIPE				TRAVEL TIME			REMARKS
		Basin ID	Area (Ac)	Runoff Coeff.	t_c (min)	C*A (Ac)	I (in/hr)	Q (cfs)	t_c (min)	C*A (ac)	I (in/hr)	Q (cfs)	Q_{street} (cfs)	C*A (ac)	Slope (%)	Q_{pipe} (cfs)	C*A (ac)	Slope (%)	Pipe Size (inches)	Length (ft)	Velocity (fps)	t_t (min)	
	1	OS1	2.30	0.09	19.0	0.21	3.16	0.7															Flows overland to DP1. Flows combine with Basin EX-A at DP3.
	2	OS2	4.64	0.09	23.1	0.42	2.87	1.2															Flows overland to DP2. Flows combine with Basin EX-A at DP3.
	3	EX-A	6.78	0.09	19.2	0.42	3.15	1.3	23.1	1.05	2.87	3.0											Flows overland to DP3. Flows combine with DP1, DP2, and EX-A.
	4	OS3	0.60	0.22	18.0	0.13	3.24	0.4															Flows overland to DP4. Flows combine with Basin EX-B at DP5.
	5	EX-B	3.76	0.16	19.3	0.13	3.15	0.4	23.1	1.31	2.87	3.8											Flows overland to DP5. Flows combine with DP3, DP4, and Basin EX-B.

NOTES:
 Street and Pipe C*A values are determined by Q/I using the catchment's intensity value.

STANDARD FORM SF-3
STORM DRAINAGE SYSTEM DESIGN
(RATIONAL METHOD PROCEDURE)

Subdivision: _____
 Location: Colorado Springs
 Design Storm: 100-Year (1-hr point precipitation = 2.53)

Project Name: Gateway Trucking-Existing
 Project No.: 25215.00
 Calculated By: GAG
 Checked By: _____
 Date: 5/19/22

STREET	Design Point	DIRECT RUNOFF							TOTAL RUNOFF				STREET			PIPE				TRAVEL TIME			REMARKS
		Basin ID	Area (Ac)	Runoff Coeff.	t _c (min)	C*A (Ac)	I (in/hr)	Q (cfs)	t _c (min)	C*A (ac)	I (in/hr)	Q (cfs)	Q _{street} (cfs)	C*A (ac)	Slope (%)	Q _{pipe} (cfs)	C*A (ac)	Slope (%)	Pipe Size (inches)	Length (ft)	Velocity (fps)	t _t (min)	
	1	OS1	2.30	0.36	19.0	0.83	5.31	4.4															Flows overland to DP1. Flows combine with Basin EX-A at DP3.
	2	OS2	4.64	0.36	23.1	1.67	4.82	8.1															Flows overland to DP2. Flows combine with Basin EX-A at DP3.
	3	EX-A	6.78	0.36	19.2	2.44	5.28	12.9	23.1	4.94	4.82	23.8											Flows overland to DP3. Flows combine with DP1, DP2, and EX-A.
	4	OS3	0.60	0.45	18.0	0.27	5.45	1.5															Flows overland to DP4. Flows combine with Basin EX-B at DP5.
	5	EX-B	3.76	0.41	19.3	1.52	5.28	8.0	23.1	6.73	4.82	32.5											Flows overland to DP5. Flows combine with DP3, DP4, and Basin EX-B.

Notes:
 Street and Pipe C*A values are determined by Q/i using the catchment's intensity value.

COMPOSITE % IMPERVIOUS CALCULATIONS

Subdivision: _____
 Location: Colorado Springs _____
 Date: 5/19/22 _____

Project Name: Gateway Trucking _____
 Project No.: 25215.00 _____
 Calculated By: GAG _____

	Basin ID	Total Area (ac)	Paved Roadway/Water Surface					Gravel					Undeveloped					Basins Total Weighted C Values		Basins Total Weighted % Imp.
			100%					80%					2%					C ₅	C ₁₀₀	
			C ₅	C ₁₀₀	% Imp.	Area (ac)	Weighted % Imp.	C ₅	C ₁₀₀	% Imp.	Area (ac)	Weighted % Imp.	C ₅	C ₁₀₀	% Imp.	Area (ac)	Weighted % Imp.			
	A	3.48	0.90	0.96	100%	0.00	0.0%	0.59	0.70	80%	2.02	46.4%	0.09	0.36	2%	1.46	0.8%	0.38	0.56	47.3%
	B	3.37	0.90	0.96	100%	0.00	0.0%	0.59	0.70	80%	2.16	51.3%	0.09	0.36	2%	1.21	0.7%	0.41	0.58	52.0%
	C	1.65	0.90	0.96	100%	0.33	20.0%	0.59	0.70	80%	0.05	2.4%	0.09	0.36	2%	1.27	1.5%	0.27	0.49	24.0%
	D	1.48	0.90	0.96	100%	0.32	21.6%	0.59	0.70	80%	0.00	0.0%	0.09	0.36	2%	1.16	1.6%	0.27	0.49	23.2%
Total Proposed Pond Conditions		9.98	Includes Basin A-D in the Proposed Conditions														-	-	41.4%	
	E	0.70	0.90	0.96	100%	0.06	8.6%	0.59	0.70	80%	0.00	0.0%	0.09	0.36	2%	0.64	1.8%	0.16	0.45	10.4%
	OS2	4.64	0.90	0.96	100%	0.00	0.0%	0.59	0.70	80%	0.00	0.0%	0.09	0.36	2%	4.64	2.0%	0.09	0.36	2.0%
	OS3	0.60	0.90	0.96	100%	0.01	1.7%	0.59	0.70	80%	0.15	20.0%	0.09	0.36	2%	0.44	1.5%	0.23	0.46	23.1%
Total Existing Outfall Conditions		5.94	Includes Basin E and OS2-3 in the Proposed Conditions														-	-	5.1%	
	F	0.40	0.90	0.96	100%	0.02	5.0%	0.59	0.70	80%	0.00	0.0%	0.09	0.36	2%	0.38	1.9%	0.13	0.46	6.9%
	OS1	2.48	0.90	0.96	100%	0.00	0.0%	0.59	0.70	80%	0.00	0.0%	0.09	0.36	2%	2.48	2.0%	0.09	0.36	2.0%
Total Offsite Flow Conditions		2.88	Includes Basin F and OS1 in the Proposed Conditions														-	-	1.3%	

STANDARD FORM SF-2 TIME OF CONCENTRATION

Subdivision: _____
 Location: Colorado Springs
 Date: 5/19/22

Project Name: Gateway Trucking
 Project No.: 25215.00
 Calculated By: GAG

NOTES:

$$t_c = t_i + t_t$$

Equation 6-2

Where:

t_c = computed time of concentration (minutes)
 t_i = overland (initial) flow time (minutes)
 t_t = channelized flow time (minutes).

$$t_t = \frac{L_t}{60K\sqrt{S_o}} = \frac{L_t}{60V_t}$$

Equation 6-4

Where:

t_t = channelized flow time (travel time, min)
 L_t = waterway length (ft)
 S_o = waterway slope (ft/ft)
 V_t = travel time velocity (ft/sec) = $K\sqrt{S_o}$
 K = NRCS conveyance factor (see Table 6-2).

$$t_i = \frac{0.395(1.1 - C_3)\sqrt{L_i}}{S_o^{0.33}}$$

Equation 6-3

Where:

t_i = overland (initial) flow time (minutes)
 C_3 = runoff coefficient for 5-year frequency (from Table 6-4)
 L_i = length of overland flow (ft)
 S_o = average slope along the overland flow path (ft/ft).

$$t_c = (26 - 17i) + \frac{L_t}{60(14i + 9)\sqrt{S_i}}$$

Equation 6-5

Where:

t_c = minimum time of concentration for first design point when less than t_c from Equation 6-1.
 L_t = length of channelized flow path (ft)
 i = imperviousness (expressed as a decimal)
 S_i = slope of the channelized flow path (ft/ft).

Table 6-2. NRCS Conveyance factors, K

Type of Land Surface	Conveyance Factor, K
Heavy meadow	2.5
Tillage/field	5
Short pasture and lawns	7
Nearly bare ground	10
Grassed waterway	15
Paved areas and shallow paved swales	20

Use a minimum t_c value of 5 minutes for urbanized areas and a minimum t_c value of 10 minutes for areas that are not considered urban. Use minimum values even when calculations result in a lesser time of concentration.

SUB-BASIN DATA						INITIAL/OVERLAND (T _i)			TRAVEL TIME (T _t)					t _c CHECK (URBANIZED BASINS)			FINAL t _c
BASIN ID	D.A. (ac)	Hydrologic Soils Group	Impervious (%)	C ₅	C ₁₀₀	L (ft)	S _o (%)	t _i (min)	L _t (ft)	S _t (%)	K	VEL. (ft/s)	t _t (min)	COMP. t _c (min)	TOTAL LENGTH (ft)	Urbanized t _c (min)	t _c (min)
A	3.48	B	47%	0.38	0.56	440	8.3%	13.6	565	4.2%	20	4.1	2.3	15.9	1005.0	20.9	15.9
B	3.37	B	52%	0.41	0.58	400	8.3%	12.4	515	4.6%	20	4.3	2.0	14.4	915.0	19.6	14.4
C	1.65	B	24%	0.27	0.49	60	1.8%	9.6	770	5.0%	15	3.4	3.8	13.4	830.0	26.6	13.4
D	1.48	B	23%	0.27	0.49	40	25.0%	3.3	405	5.0%	10	2.2	3.0	6.3	445.0	24.5	6.3
E	0.70	B	10%	0.16	0.45	10	30.0%	1.7	1170	5.3%	10	2.3	8.5	10.2	1180.0	32.3	10.2
F	0.40	B	7%	0.13	0.46	10	30.0%	1.8	1560	4.5%	10	2.1	12.3	14.1	1570.0	37.1	14.1
OS1	2.48	B	2%	0.09	0.36	300	6.8%	16.8	435	3.7%	10	1.9	3.8	20.5	735.0	29.7	20.5
OS2	4.64	B	2%	0.09	0.36	300	6.1%	17.4	845	6.1%	10	2.5	5.7	23.1	1145.0	31.8	23.1
OS3	0.60	B	23%	0.23	0.46	225	4.3%	14.6	0	0.0%	10	0.1	0.0	14.6	225.0	22.1	14.6

STANDARD FORM SF-3
STORM DRAINAGE SYSTEM DESIGN
(RATIONAL METHOD PROCEDURE)

Subdivision: _____
 Location: Colorado Springs _____
 Design Storm: 5-Year (1-hr point precipitation = 1.12) _____

Project Name: Gateway Trucking _____
 Project No.: 25215.00 _____
 Calculated By: GAG _____
 Checked By: _____
 Date: 5/19/22 _____

STREET	Design Point	DIRECT RUNOFF							TOTAL RUNOFF				STREET			PIPE				TRAVEL TIME			REMARKS
		Basin ID	Area (Ac)	Runoff Coeff.	t _c (min)	C*A (Ac)	I (in/hr)	Q (cfs)	t _c (min)	C*A (ac)	I (in/hr)	Q (cfs)	Q _{street} (cfs)	C*A (ac)	Slope (%)	Q _{pipe} (cfs)	C*A (ac)	Slope (%)	Pipe Size (inches)	Length (ft)	Velocity (fps)	t _t (min)	
	1	A	3.48	0.38	15.9	1.32	3.44	4.5															Flows overland and parking area towards swale at DP1. Sized for berm/ swales. Flows are routed towards DP2.1.
	2	B	3.37	0.41	14.4	1.38	3.58	4.9															Flows overland and parking area towards swale at DP2. Sized for berm/ swales. Flows are routed towards DP2.1.
	2.1								15.9	2.70	3.44	9.3											Combination of DP1 and DP2. Combo, flow for riprap rundown. Flows enter into pond.
	3	C	1.65	0.27	13.4	0.44	3.69	1.6															Flows along driveway swale towards DP3. Flows combine at DP4.
	4	D	1.48	0.27	6.3	0.39	4.82	1.9	15.9	3.53	3.44	12.1											Flows overland into proposed pond at DP4. Combination of flows DP2.1, DP3, and Basin D.
	5	OS1	2.48	0.09	20.5	0.22	3.05	0.7															Flows overland to DP5. Flows offsite following historic drainage.
	6	F	0.40	0.13	14.1	0.05	3.62	0.2															Flows along berm to DP6. Flows offsite following historic drainage.
	7	OS2	4.64	0.09	23.1	0.42	2.87	1.2															Flows overland to DP7. Flows combine with Basin E at DP9.
	8	OS3	0.60	0.23	14.6	0.14	3.56	0.5															Flows overland to DP8. Flows combine with Basin E at DP9.
	9	E	0.70	0.16	10.2	0.11	4.10	0.5	23.1	0.67	2.87	1.9											Flows overland to existing 30" CMP at DP9. Combination of flows DP7, DP8 and Basin E.
	9.1	-	-	-	-	-	-	2.1	-	-	-	4.0											Direct summation of flows from DP9 and the maximum pond release from UD-Detention.

NOTES:
 Street and Pipe C*A values are determined by Q/i using the catchment's intensity value.
 Flow values in BLUE indicate they are from the UD-Detention pond spreadsheet.

STANDARD FORM SF-3
STORM DRAINAGE SYSTEM DESIGN
(RATIONAL METHOD PROCEDURE)

Subdivision: _____
Location: Colorado Springs
Design Storm: 100-Year (1-hr point precipitation = 2.53)

Project Name: Gateway Trucking
Project No.: 25215.00
Calculated By: GAG
Checked By: _____
Date: 5/19/22


STREET	Design Point	DIRECT RUNOFF							TOTAL RUNOFF				STREET			PIPE			TRAVEL TIME			REMARKS	
		Basin ID	Area (Ac)	Runoff Coeff.	t _c (min)	C*A (Ac)	I (in/hr)	Q (cfs)	t _c (min)	C*A (ac)	I (in/hr)	Q (cfs)	Q _{street} (cfs)	C*A (ac)	Slope (%)	Q _{pipe} (cfs)	C*A (ac)	Slope (%)	Pipe Size (inches)	Length (ft)	Velocity (fps)		t _t (min)
	1	A	3.48	0.56	15.9	1.94	5.77	11.2															Flows overland and parking area towards swale at DP1. Sized for berm/ swales. Flows are routed towards DP2.1.
	2	B	3.37	0.58	14.4	1.95	6.02	11.7															Flows overland and parking area towards swale at DP2. Sized for berm/ swales. Flows are routed towards DP2.1.
	2.1								15.9	3.89	5.77	22.4											Combination of DP1 and DP2. Combo, flow for riprap rundown. Flows enter into pond.
	3	C	1.65	0.49	13.4	0.81	6.19	5.0															Flows along driveway swale towards DP3. Flows combine at DP4.
	4	D	1.48	0.49	6.3	0.72	8.09	5.8	15.9	5.42	5.77	31.3											Flows overland into proposed pond at DP4. Combination of flows DP2.1, DP3, and Basin D.
	5	OS1	2.48	0.36	20.5	0.89	5.12	4.6															Flows overland to DP5. Flows offsite following historic drainage.
	6	F	0.40	0.46	14.1	0.18	6.07	1.1															Flows along berm to DP6. Flows offsite following historic drainage.
	7	OS2	4.64	0.36	23.1	1.67	4.82	8.1															Flows overland to DP7. Flows combine with Basin E at DP9.
	8	OS3	0.60	0.46	14.6	0.27	5.98	1.6															Flows overland to DP8. Flows combine with Basin E at DP9.
	9	E	0.70	0.45	10.2	0.31	6.88	2.1	23.1	2.25	4.82	10.9											Flows overland to existing 30" CMP at DP9. Combination of flows DP7, DP8 and Basin E.
	9.1	-	-	-	-	-	-	11.5				22.4											Direct summation of flows from DP9 and the maximum pond release from UD-Detention.

Notes:
Street and Pipe C*A values are determined by Q/I using the catchment's intensity value.
Flow values in BLUE indicate they are from the UD-Detention pond spreadsheet.

DETENTION BASIN STAGE-STORAGE TABLE BUILDER

MHFD-*Detention*, Version 4.04 (February 2021)

Project: Gateway Trucking
 Basin ID: Proposed Full Spectrum EDB Basins (A-D)



Watershed Information

Selected BMP Type =	EDB	
Watershed Area =	9.98	acres
Watershed Length =	940	ft
Watershed Length to Centroid =	560	ft
Watershed Slope =	0.060	ft/ft
Watershed Imperviousness =	41.40%	percent
Percentage Hydrologic Soil Group A =	0.0%	percent
Percentage Hydrologic Soil Group B =	100.0%	percent
Percentage Hydrologic Soil Groups C/D =	0.0%	percent
Target WQCV Drain Time =	40.0	hours
Location for 1-hr Rainfall Depths =	User Input	

After providing required inputs above including 1-hour rainfall depths, click "Run CUHP" to generate runoff hydrographs using the embedded Colorado Urban Hydrograph Procedure.

Water Quality Capture Volume (WQCV) =	0.153	acre-feet
Excess Urban Runoff Volume (EURV) =	0.435	acre-feet
2-yr Runoff Volume (P1 = 1.19 in.) =	0.413	acre-feet
5-yr Runoff Volume (P1 = 1.5 in.) =	0.614	acre-feet
10-yr Runoff Volume (P1 = 1.75 in.) =	0.793	acre-feet
25-yr Runoff Volume (P1 = 2 in.) =	1.048	acre-feet
50-yr Runoff Volume (P1 = 2.25 in.) =	1.248	acre-feet
100-yr Runoff Volume (P1 = 2.52 in.) =	1.507	acre-feet
500-yr Runoff Volume (P1 = 3 in.) =	1.906	acre-feet
Approximate 2-yr Detention Volume =	0.322	acre-feet
Approximate 5-yr Detention Volume =	0.448	acre-feet
Approximate 10-yr Detention Volume =	0.613	acre-feet
Approximate 25-yr Detention Volume =	0.683	acre-feet
Approximate 50-yr Detention Volume =	0.716	acre-feet
Approximate 100-yr Detention Volume =	0.817	acre-feet

Optional User Overrides

	1.19	inches
	1.50	inches
	1.75	inches
	2.00	inches
	2.25	inches
	2.52	inches
	3.00	inches



Define Zones and Basin Geometry

Zone 1 Volume (WQCV) =	0.153	acre-feet
Zone 2 Volume (EURV - Zone 1) =	0.282	acre-feet
Zone 3 Volume (100-year - Zones 1 & 2) =	0.382	acre-feet
Total Detention Basin Volume =	0.817	acre-feet
Initial Surge Volume (ISV) =	user	ft ³
Initial Surge Depth (ISD) =	user	ft
Total Available Detention Depth (H _{total}) =	user	ft
Depth of Trickle Channel (H _{tc}) =	user	ft
Slope of Trickle Channel (S _{tc}) =	user	ft/ft
Slopes of Main Basin Sides (S _{main}) =	user	H:V
Basin Length-to-Width Ratio (R _{L/W}) =	user	
Initial Surge Area (A _{ISV}) =	user	ft ²
Surge Volume Length (L _{ISV}) =	user	ft
Surge Volume Width (W _{ISV}) =	user	ft
Depth of Basin Floor (H _{FLOOR}) =	user	ft
Length of Basin Floor (L _{FLOOR}) =	user	ft
Width of Basin Floor (W _{FLOOR}) =	user	ft
Area of Basin Floor (A _{FLOOR}) =	user	ft ²
Volume of Basin Floor (V _{FLOOR}) =	user	ft ³
Depth of Main Basin (H _{MAIN}) =	user	ft
Length of Main Basin (L _{MAIN}) =	user	ft
Width of Main Basin (W _{MAIN}) =	user	ft
Area of Main Basin (A _{MAIN}) =	user	ft ²
Volume of Main Basin (V _{MAIN}) =	user	ft ³
Calculated Total Basin Volume (V _{total}) =	USER	acre-feet

Depth Increment = 0.50 ft		Optional Override Stage (ft)	Length (ft)	Width (ft)	Area (ft ²)	Optional Override Area (ft ²)	Area (acre)	Volume (ft ³)	Volume (ac-ft)
Top of Micropool		0.00	--	--	--	13	0.000		
6232	--	1.00	--	--	--	303	0.007	158	0.004
6233	--	2.00	--	--	--	2,350	0.054	1,484	0.034
6234	--	3.00	--	--	--	6,312	0.145	5,815	0.134
6235	--	4.00	--	--	--	9,368	0.215	13,655	0.313
6236	--	5.00	--	--	--	11,130	0.256	23,904	0.549
6237	--	6.00	--	--	--	13,036	0.299	35,987	0.826
6237.5	--	6.50	--	--	--	14,043	0.322	42,757	0.982
6238	--	7.00	--	--	--	15,046	0.345	50,029	1.149
6239	--	8.00	--	--	--	17,379	0.399	66,242	1.521

DETENTION BASIN STAGE-STORAGE TABLE BUILDER


MHFD-Detention, Version 4.04 (February 2021)



DETENTION BASIN OUTLET STRUCTURE DESIGN

MHFD-Detention, Version 4.04 (February 2021)

Project: Gateway Trucking
Basin ID: Proposed Full Spectrum EDB Basins (A-D)



	Estimated Stage (ft)	Estimated Volume (ac-ft)	Outlet Type
Zone 1 (WQCV)	3.13	0.153	Orifice Plate
Zone 2 (EURV)	4.54	0.282	Circular Orifice
Zone 3 (100-yr)	5.98	0.382	Weir&Pipe (Restrict)
Total (all zones)		0.817	

User Input: Orifice at Underdrain Outlet (typically used to drain WQCV in a Filtration BMP)

Underdrain Orifice Invert Depth =	N/A	ft (distance below the filtration media surface)
Underdrain Orifice Diameter =	N/A	inches

Calculated Parameters for Underdrain	
Underdrain Orifice Area =	N/A ft ²
Underdrain Orifice Centroid =	N/A feet

User Input: Orifice Plate with one or more orifices or Elliptical Slot Weir (typically used to drain WQCV and/or EURV in a sedimentation BMP)

Invert of Lowest Orifice =	0.00	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Orifice Plate =	4.54	ft (relative to basin bottom at Stage = 0 ft)
Orifice Plate: Orifice Vertical Spacing =	N/A	inches
Orifice Plate: Orifice Area per Row =	0.60	sq. inches (diameter = 7/8 inch)

Calculated Parameters for Plate	
WQ Orifice Area per Row =	4.167E-03 ft ²
Elliptical Half-Width =	N/A feet
Elliptical Slot Centroid =	N/A feet
Elliptical Slot Area =	N/A ft ²

User Input: Stage and Total Area of Each Orifice Row (numbered from lowest to highest)

	Row 1 (required)	Row 2 (optional)	Row 3 (optional)	Row 4 (optional)	Row 5 (optional)	Row 6 (optional)	Row 7 (optional)	Row 8 (optional)
Stage of Orifice Centroid (ft)	0.00	1.51	3.03					
Orifice Area (sq. inches)	0.60	0.60	0.60					

	Row 9 (optional)	Row 10 (optional)	Row 11 (optional)	Row 12 (optional)	Row 13 (optional)	Row 14 (optional)	Row 15 (optional)	Row 16 (optional)
Stage of Orifice Centroid (ft)								
Orifice Area (sq. inches)								

User Input: Vertical Orifice (Circular or Rectangular)

	Zone 2 Circular	Not Selected	
Invert of Vertical Orifice =	3.13	N/A	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Vertical Orifice =	4.54	N/A	ft (relative to basin bottom at Stage = 0 ft)
Vertical Orifice Diameter =	0.86	N/A	inches

Calculated Parameters for Vertical Orifice	
Zone 2 Circular	Not Selected
Vertical Orifice Area =	0.00 ft ²
Vertical Orifice Centroid =	0.04 feet

User Input: Overflow Weir (Dropbox with Flat or Sloped Gate and Outlet Pipe OR Rectangular/Trapezoidal Weir (and No Outlet Pipe))

	Zone 3 Weir	Not Selected	
Overflow Weir Front Edge Height, H _o =	4.55	N/A	ft (relative to basin bottom at Stage = 0 ft)
Overflow Weir Front Edge Length =	2.92	N/A	feet
Overflow Weir Gate Slope =	0.00	N/A	H:V
Horiz. Length of Weir Sides =	2.92	N/A	feet
Overflow Gate Type =	Type C Gate	N/A	
Debris Clogging % =	50%	N/A	%

Calculated Parameters for Overflow Weir	
Zone 3 Weir	Not Selected
Height of Gate Upper Edge, H _u =	4.55 feet
Overflow Weir Slope Length =	2.92 feet
Gate Open Area / 100-yr Orifice Area =	5.96
Overflow Gate Open Area w/o Debris =	5.93 ft ²
Overflow Gate Open Area w/ Debris =	2.97 ft ²

User Input: Outlet Pipe w/ Flow Restriction Plate (Circular Orifice, Restrictor Plate, or Rectangular Orifice)

	Zone 3 Restrictor	Not Selected	
Depth to Invert of Outlet Pipe =	0.33	N/A	ft (distance below basin bottom at Stage = 0 ft)
Outlet Pipe Diameter =	24.00	N/A	inches
Restrictor Plate Height Above Pipe Invert =	8.50		inches

Calculated Parameters for Outlet Pipe w/ Flow Restriction Plate	
Zone 3 Restrictor	Not Selected
Outlet Orifice Area =	1.00 ft ²
Outlet Orifice Centroid =	0.41 feet
Half-Central Angle of Restrictor Plate on Pipe =	1.27 radians

User Input: Emergency Spillway (Rectangular or Trapezoidal)

Spillway Invert Stage =	6.50	ft (relative to basin bottom at Stage = 0 ft)
Spillway Crest Length =	24.00	feet
Spillway End Slopes =	4.00	H:V
Freeboard above Max Water Surface =	1.00	feet

Calculated Parameters for Spillway	
Spillway Design Flow Depth =	0.48 feet
Stage at Top of Freeboard =	7.98 feet
Basin Area at Top of Freeboard =	0.40 acres
Basin Volume at Top of Freeboard =	1.51 acre-ft




Routed Hydrograph Results

The user can override the default CUHP hydrographs and runoff volumes by entering new values in the Inflow Hydrographs table (Columns W through AF).

	WQCV	EURV	2 Year	5 Year	10 Year	25 Year	50 Year	100 Year	500 Year
Design Storm Return Period =									
One-Hour Rainfall Depth (in) =	N/A	N/A	1.19	1.50	1.75	2.00	2.25	2.52	3.00
CUHP Runoff Volume (acre-ft) =	0.153	0.435	0.413	0.614	0.793	1.048	1.248	1.507	1.906
Inflow Hydrograph Volume (acre-ft) =	N/A	N/A	0.413	0.614	0.793	1.048	1.248	1.507	1.906
CUHP Predevelopment Peak Q (cfs) =	N/A	N/A	1.3	3.6	5.3	9.5	11.9	14.8	19.3
OPTIONAL Override Predevelopment Peak Q (cfs) =	N/A	N/A							
Predevelopment Unit Peak Flow, q (cfs/acre) =	N/A	N/A	0.13	0.36	0.54	0.95	1.19	1.48	1.93
Peak Inflow Q (cfs) =	N/A	N/A	7.0	10.7	13.4	18.0	21.4	25.8	32.2
Peak Outflow Q (cfs) =	0.1	0.1	0.1	1.9	4.3	9.1	11.0	11.5	13.7
Ratio Peak Outflow to Predevelopment Q =	N/A	N/A	N/A	0.5	0.8	1.0	0.9	0.8	0.7
Structure Controlling Flow =	Vertical Orifice 1	Vertical Orifice 1	Vertical Orifice 1	Overflow Weir 1	Overflow Weir 1	Overflow Weir 1	Outlet Plate 1	Outlet Plate 1	Spillway
Max Velocity through Gate 1 (fps) =	N/A	N/A	N/A	0.3	0.7	1.5	1.8	1.9	2.0
Max Velocity through Gate 2 (fps) =	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Time to Drain 97% of Inflow Volume (hours) =	38	68	66	69	67	65	63	61	58
Time to Drain 99% of Inflow Volume (hours) =	40	72	71	75	74	73	72	71	69
Maximum Ponding Depth (ft) =	3.14	4.54	4.36	4.76	4.92	5.16	5.34	5.84	6.58
Area at Maximum Ponding Depth (acres) =	0.15	0.24	0.23	0.25	0.25	0.26	0.27	0.29	0.33
Maximum Volume Stored (acre-ft) =	0.154	0.436	0.391	0.486	0.526	0.590	0.638	0.776	1.004

DETENTION BASIN OUTLET STRUCTURE DESIGN

MHFD-Detention, Version 4.04 (February 2021)



S-A-V-D Chart Axis Override	X-axis	Left Y-Axis	Right Y-Axis
minimum bound			
maximum bound			

DETENTION BASIN OUTLET STRUCTURE DESIGN

Outflow Hydrograph Workbook Filename: _____

Inflow Hydrographs

The user can override the calculated inflow hydrographs from this workbook with inflow hydrographs developed in a separate program.

Time Interval	SOURCE	WQCV [cfs]	EURV [cfs]	2 Year [cfs]	5 Year [cfs]	10 Year [cfs]	25 Year [cfs]	50 Year [cfs]	100 Year [cfs]	500 Year [cfs]
5.00 min	0:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.07	0.01	0.17
	0:15:00	0.00	0.00	0.60	0.99	1.23	0.83	1.03	1.01	1.34
	0:20:00	0.00	0.00	2.12	2.79	3.53	2.07	2.41	2.59	3.29
	0:25:00	0.00	0.00	5.14	8.09	10.89	5.05	6.03	6.84	9.95
	0:30:00	0.00	0.00	6.95	10.68	13.38	15.41	18.64	21.30	27.11
	0:35:00	0.00	0.00	6.54	9.78	12.14	17.99	21.42	25.80	32.24
	0:40:00	0.00	0.00	5.76	8.42	10.48	17.41	20.59	24.65	30.68
	0:45:00	0.00	0.00	4.80	7.12	9.07	15.30	18.10	22.38	27.86
	0:50:00	0.00	0.00	4.02	6.09	7.62	13.74	16.25	19.97	24.85
	0:55:00	0.00	0.00	3.37	5.05	6.40	11.45	13.57	17.19	21.40
	1:00:00	0.00	0.00	2.93	4.36	5.65	9.51	11.32	14.87	18.60
	1:05:00	0.00	0.00	2.63	3.88	5.12	8.28	9.90	13.42	16.82
	1:10:00	0.00	0.00	2.24	3.45	4.62	6.94	8.33	10.98	13.86
	1:15:00	0.00	0.00	1.88	2.93	4.13	5.78	6.96	8.86	11.28
	1:20:00	0.00	0.00	1.55	2.39	3.42	4.60	5.52	6.79	8.63
	1:25:00	0.00	0.00	1.27	1.92	2.65	3.56	4.26	5.00	6.35
	1:30:00	0.00	0.00	1.08	1.64	2.19	2.58	3.07	3.52	4.51
	1:35:00	0.00	0.00	0.99	1.51	1.92	2.01	2.40	2.64	3.42
	1:40:00	0.00	0.00	0.95	1.33	1.73	1.67	1.98	2.13	2.76
	1:45:00	0.00	0.00	0.93	1.19	1.60	1.45	1.71	1.76	2.30
	1:50:00	0.00	0.00	0.91	1.09	1.51	1.29	1.52	1.51	1.98
	1:55:00	0.00	0.00	0.80	1.02	1.40	1.20	1.40	1.34	1.75
	2:00:00	0.00	0.00	0.70	0.93	1.25	1.13	1.31	1.22	1.59
	2:05:00	0.00	0.00	0.53	0.70	0.93	0.85	0.97	0.89	1.16
	2:10:00	0.00	0.00	0.40	0.52	0.68	0.62	0.71	0.65	0.84
	2:15:00	0.00	0.00	0.29	0.38	0.49	0.45	0.52	0.48	0.62
	2:20:00	0.00	0.00	0.22	0.28	0.36	0.33	0.38	0.35	0.45
	2:25:00	0.00	0.00	0.16	0.20	0.26	0.24	0.27	0.25	0.33
	2:30:00	0.00	0.00	0.11	0.14	0.18	0.17	0.19	0.18	0.23
	2:35:00	0.00	0.00	0.08	0.09	0.13	0.12	0.14	0.13	0.16
	2:40:00	0.00	0.00	0.05	0.06	0.08	0.08	0.09	0.08	0.11
	2:45:00	0.00	0.00	0.03	0.04	0.05	0.05	0.05	0.05	0.06
	2:50:00	0.00	0.00	0.01	0.02	0.02	0.02	0.03	0.03	0.03
	2:55:00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01
	3:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:15:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:20:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:15:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:20:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:15:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:20:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Channel Report

N. Berm

User-defined

Invert Elev (ft) = 100.00
Slope (%) = 0.41
N-Value = 0.040

Calculations


Compute by: Known Q
Known Q (cfs) = 11.70

Highlighted

Depth (ft) = 1.45
Q (cfs) = 11.70
Area (sqft) = 6.31
Velocity (ft/s) = 1.85
Wetted Perim (ft) = 9.17
Crit Depth, Yc (ft) = 0.99
Top Width (ft) = 8.70
EGL (ft) = 1.50

(Sta, El, n)-(Sta, El, n)...

(0.00, 100.00)-(7.50, 102.50, 0.040)-(9.50, 102.50, 0.040)-(17.00, 100.00, 0.040)



Channel Report

N. Parking Area Swale (to combo)

Triangular

Side Slopes (z:1) = 4.00, 4.00
Total Depth (ft) = 2.00


Invert Elev (ft) = 100.00
Slope (%) = 15.12
N-Value = 0.053

Calculations

Compute by: Known Q
Known Q (cfs) = 11.70

Highlighted

Depth (ft) = 0.74
Q (cfs) = 11.70
Area (sqft) = 2.19
Velocity (ft/s) = 5.34
Wetted Perim (ft) = 6.10
Crit Depth, Yc (ft) = 0.89
Top Width (ft) = 5.92
EGL (ft) = 1.18



Channel Report

N. Driveway Swale

Triangular

Side Slopes (z:1) = 3.00, 3.00
Total Depth (ft) = 1.50


Invert Elev (ft) = 100.00
Slope (%) = 3.07
N-Value = 0.040

Calculations

Compute by: Known Q
Known Q (cfs) = 5.00

Highlighted

Depth (ft) = 0.73
Q (cfs) = 5.000
Area (sqft) = 1.60
Velocity (ft/s) = 3.13
Wetted Perim (ft) = 4.62
Crit Depth, Yc (ft) = 0.71
Top Width (ft) = 4.38
EGL (ft) = 0.88



Channel Report

S. Berm

User-defined

Invert Elev (ft) = 100.00
Slope (%) = 0.47
N-Value = 0.040

Calculations


Compute by: Known Q
Known Q (cfs) = 11.20

Highlighted

Depth (ft) = 1.40
Q (cfs) = 11.20
Area (sqft) = 5.88
Velocity (ft/s) = 1.90
Wetted Perim (ft) = 8.85
Crit Depth, Yc (ft) = 0.98
Top Width (ft) = 8.40
EGL (ft) = 1.46

(Sta, El, n)-(Sta, El, n)...

(0.00, 100.00)-(7.50, 102.50, 0.040)-(9.50, 102.50, 0.040)-(17.00, 100.00, 0.040)



Channel Report

S. Parking Area Swale (to combo)

Triangular

Side Slopes (z:1) = 4.00, 4.00
Total Depth (ft) = 2.00


Invert Elev (ft) = 100.00
Slope (%) = 6.00
N-Value = 0.053

Calculations

Compute by: Known Q
Known Q (cfs) = 11.20

Highlighted

Depth (ft) = 0.86
Q (cfs) = 11.20
Area (sqft) = 2.96
Velocity (ft/s) = 3.79
Wetted Perim (ft) = 7.09
Crit Depth, Yc (ft) = 0.87
Top Width (ft) = 6.88
EGL (ft) = 1.08



Channel Report

Riprap Rundown (combo swale)

Triangular

Side Slopes (z:1) = 3.00, 3.00
Total Depth (ft) = 2.00


Invert Elev (ft) = 100.00
Slope (%) = 19.97
N-Value = 0.057

Calculations

Compute by: Known Q
Known Q (cfs) = 22.40

Highlighted

Depth (ft) = 1.02
Q (cfs) = 22.40
Area (sqft) = 3.12
Velocity (ft/s) = 7.18
Wetted Perim (ft) = 6.45
Crit Depth, Yc (ft) = 1.29
Top Width (ft) = 6.12
EGL (ft) = 1.82



Channel Report

SW. Berm

User-defined

Invert Elev (ft) = 6244.45
Slope (%) = 5.81
N-Value = 0.040

Highlighted


Depth (ft) = 0.77
Q (cfs) = 10.90
Area (sqft) = 2.41
Velocity (ft/s) = 4.53
Wetted Perim (ft) = 6.44
Crit Depth, Yc (ft) = 0.86
Top Width (ft) = 6.25
EGL (ft) = 1.09

Calculations

Compute by: Known Q
Known Q (cfs) = 10.90

(Sta, El, n)-(Sta, El, n)...

(0.00, 6245.58) -(12.18, 6246.57, 0.040) -(20.18, 6244.45, 0.040) -(33.18, 6247.44, 0.040) -(35.18, 6247.44, 0.040) -(36.51, 6247.17, 0.040)



Channel Report

NE. Berm

User-defined

Invert Elev (ft) = 6292.00
Slope (%) = 3.00
N-Value = 0.040

Highlighted


Depth (ft) = 0.34
Q (cfs) = 4.600
Area (sqft) = 2.06
Velocity (ft/s) = 2.23
Wetted Perim (ft) = 9.83
Crit Depth, Yc (ft) = 0.32
Top Width (ft) = 9.72
EGL (ft) = 0.42

Calculations

Compute by: Known Q
Known Q (cfs) = 4.60

(Sta, El, n)-(Sta, El, n)...

(0.00, 6292.00)-(10.01, 6295.00, 0.040)-(12.01, 6295.00, 0.040)-(22.01, 6292.00, 0.040)-(24.42, 6292.00, 0.040)-(65.66, 6294.78, 0.040)



FOREBAY VOLUME AND RELEASE REQUIREMENTS

Equation 3-1	$WQCV = a(0.91I^3 - 1.19I^2 + 0.781I)$		
Pond Forebay	WQCV=watershed-inches, I=% Impervious, a=1 (40 hour drain time)		
	I (Impervious,%) =	41.40%	WQCV = 0.18353
Equation 3-3	$V = (WQCV/12)A$		
Pond Forebay	V=Volume (ac-ft.), A=Area (acres)		
	A (ac.) =	9.98	V (ac-ft.) = 0.1526
2% OF WQCV	$(V_{req}) = .02(V)$		
Forebay Required Volume			
		V_{req} (ac-ft.) =	0.003
		V_{req} (ft ³) =	133
Volume Provided For Pond Forebay =		V_{prop} (ft ³) =	176
Forebay Release Rate	2% OF Q_{100} Inflow Into Pond		
Q_{100} Discharges			
		Q_{100} (cfs) =	25.8
		Q_{out} (cfs) =	0.52

Weir Report

Forebay Release Rate 2% Q100,in (cfs)

V-Notch Weir


Crest = Sharp
Angle (Deg) = 19
Total Depth (ft) = 1.50

Highlighted

Depth (ft) = 1.08
Q (cfs) = 0.520
Area (sqft) = 0.19
Velocity (ft/s) = 2.67
Top Width (ft) = 0.36

Calculations

Weir Coeff. Cw = 0.43
Compute by: Known Q
Known Q (cfs) = 0.52



Channel Report

Pond Trickle Channel Capacity - 2% Q100,in (cfs)

Rectangular

Bottom Width (ft) = 6.00
Total Depth (ft) = 0.50


Invert Elev (ft) = 100.00
Slope (%) = 1.50
N-Value = 0.013

Calculations

Compute by: Known Q
Known Q (cfs) = 0.52

Highlighted

Depth (ft) = 0.05
Q (cfs) = 0.520
Area (sqft) = 0.30
Velocity (ft/s) = 1.73
Wetted Perim (ft) = 6.10
Crit Depth, Yc (ft) = 0.07
Top Width (ft) = 6.00
EGL (ft) = 0.10



Channel Report

Outlet Structure Pipe- 5 Year

Circular

Diameter (ft) = 2.00

Invert Elev (ft) = 100.00

Slope (%) = 0.36

N-Value = 0.013

Calculations

Compute by: Known Q

Known Q (cfs) = 2.10

Highlighted

Depth (ft) = 0.53

Q (cfs) = 2.100

Area (sqft) = 0.67


Velocity (ft/s) = 3.12

Wetted Perim (ft) = 2.17

Crit Depth, Y_c (ft) = 0.51

Top Width (ft) = 1.77

EGL (ft) = 0.68



Channel Report

Outlet Structure Pipe- 100 Year

Circular

Diameter (ft) = 2.00

Invert Elev (ft) = 100.00

Slope (%) = 0.36

N-Value = 0.013

Calculations

Compute by: Known Q

Known Q (cfs) = 11.50

Highlighted

Depth (ft) = 1.42

Q (cfs) = 11.50

Area (sqft) = 2.39


Velocity (ft/s) = 4.82



Wetted Perim (ft) = 4.01

Crit Depth, Y_c (ft) = 1.22

Top Width (ft) = 1.81

EGL (ft) = 1.78





Slope = 25%




Figure 12-21. Embankment protection details and rock sizing chart (adapted from Arapahoe County)

HY-8 Culvert Analysis Report

Existing 30" CMP

Crossing Discharge Data

Discharge Selection Method: Specify Minimum, Design, and Maximum Flow

Minimum Flow: 4 cfs

Design Flow: 22.4 cfs

Maximum Flow: 22.4 cfs

Table 1 - Summary of Culvert Flows at Crossing: Design Point 9.1

Headwater Elevation (ft)	Total Discharge (cfs)	Ex. 30 Discharge (cfs)	Roadway Discharge (cfs)	Iterations
6230.60	4.00	4.00	0.00	1
6230.62	5.84	5.84	0.00	1
6230.65	7.68	7.68	0.00	1
6230.69	9.52	9.52	0.00	1
6230.74	11.36	11.36	0.00	1
6230.79	13.20	13.20	0.00	1
6230.86	15.04	15.04	0.00	1
6230.93	16.88	16.88	0.00	1
6231.01	18.72	18.72	0.00	1
6231.10	20.56	20.56	0.00	1
6231.19	22.40	22.40	0.00	1
6233.80	42.85	42.85	0.00	Overtopping

Rating Curve Plot for Crossing: Design Point 9.1

Total Rating Curve

Crossing: Design Point 9.1




Table 2 - Culvert Summary Table: Ex. 30


Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)	Tailwater Velocity (ft/s)
4.00	4.00	6230.60	1.004	2.520	7-A2c	-1.000	0.657	0.657	0.494	3.883	0.226
5.84	5.84	6230.62	1.229	2.542	7-A2c	-1.000	0.799	0.799	0.606	4.321	0.253
7.68	7.68	6230.65	1.422	2.572	7-A2c	-1.000	0.921	0.921	0.701	4.681	0.274
9.52	9.52	6230.69	1.603	2.611	7-A2c	-1.000	1.030	1.030	0.784	4.995	0.292
11.36	11.36	6230.74	1.776	2.658	7-A2c	-1.000	1.129	1.129	0.858	5.278	0.307
13.20	13.20	6230.79	1.944	2.714	7-A2c	-1.000	1.221	1.221	0.927	5.540	0.320
15.04	15.04	6230.86	2.109	2.777	7-A2c	-1.000	1.308	1.308	0.990	5.788	0.332
16.88	16.88	6230.93	2.276	2.849	7-A2c	-1.000	1.389	1.389	1.049	6.026	0.342
18.72	18.72	6231.01	2.445	2.929	7-A2c	-1.000	1.466	1.466	1.105	6.256	0.352
20.56	20.56	6231.10	2.619	3.018	7-A2c	-1.000	1.540	1.540	1.157	6.481	0.362
22.40	22.40	6231.19	2.801	3.115	7-A2c	-1.000	1.610	1.610	1.207	6.704	0.370

Straight Culvert

Inlet Elevation (invert): 6228.08 ft, Outlet Elevation (invert): 6229.75 ft

Culvert Length: 55.23 ft, Culvert Slope: -0.0303


Culvert Performance Curve Plot: Ex. 30



Water Surface Profile Plot for Culvert: Ex. 30

Crossing - Design Point 9.1, Design Discharge - 22.4 cfs

Culvert - Ex. 30, Culvert Discharge - 22.4 cfs



Site Data - Ex. 30

Site Data Option: Culvert Invert Data

Inlet Station: 55.20 ft

Inlet Elevation: 6228.08 ft

Outlet Station: 0.00 ft

Outlet Elevation: 6229.75 ft

Number of Barrels: 1

Culvert Data Summary - Ex. 30

Barrel Shape: Circular

Barrel Diameter: 2.50 ft

Barrel Material: Corrugated Aluminum

Embedment: 0.00 in

Barrel Manning's n: 0.0310

Culvert Type: Straight

Inlet Configuration: Thin Edge Projecting

Inlet Depression: None

Table 3 - Downstream Channel Rating Curve (Crossing: Design Point 9.1)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)	Velocity (ft/s)	Shear (psf)	Froude Number
4.00	6230.19	0.49	0.23	0.00	0.06
5.84	6230.31	0.61	0.25	0.00	0.07
7.68	6230.40	0.70	0.27	0.00	0.07
9.52	6230.48	0.78	0.29	0.00	0.07
11.36	6230.56	0.86	0.31	0.01	0.07
13.20	6230.63	0.93	0.32	0.01	0.07
15.04	6230.69	0.99	0.33	0.01	0.07
16.88	6230.75	1.05	0.34	0.01	0.07
18.72	6230.80	1.10	0.35	0.01	0.07
20.56	6230.86	1.16	0.36	0.01	0.07
22.40	6230.91	1.21	0.37	0.01	0.07

Tailwater Channel Data - Design Point 9.1

Tailwater Channel Option: Trapezoidal Channel

Bottom Width: 26.00 ft

Side Slope (H:V): 20.00 (_:1)

Channel Slope: 0.0001

Channel Manning's n: 0.0350

Channel Invert Elevation: 6229.70 ft

Roadway Data for Crossing: Design Point 9.1

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 11.70 ft

Crest Elevation: 6233.80 ft

Roadway Surface: Paved

Roadway Top Width: 37.00 ft

**EXISTING ROADWAY/ DRAINAGE CONDITIONS
AT
SOUTH FRANCEVILLE COAL MINE ROAD
FOR
GATEWAY TRUCKING**

**Gateway Trucking, LLC
11260 West Lane
Colorado Springs, CO 80929
(719) 492-7658
Contact: Perry Hastings**

**November 3, 2021
Project No. 25215.00**

**Prepared By:
JR Engineering, LLC
5475 Tech Center Drive
Colorado Springs, CO 80919
719-593-2593**

El Paso County PCD File No. PPR-31-033

The pictures attached show the existing conditions of the roadway and drainage at the Gateway Trucking, LLC site. The foreslopes/ditch sections appeared to be well maintained and the roadway appeared to have a satisfactory crown as described in the traffic report. The existing roadway conveys stormwater from the roadway to the roadside.



Figure 1: S. Franceville Coal Mine Rd. in front of site access driveway facing South.



Figure 2: S. Franceville Coal Mine Rd. in front of site access driveway facing North.



Figure 3: S. Franceville Coal Mine Rd. in front of site access driveway facing East toward the site.



Figure 6: S. Franceville Coal Mine Rd. North-most profile showing creek on the right end.

The existing culvert located along S. Franceville Coal Mine Rd. is south of the site access and drains to the West under S. Franceville Coal Mine Rd.



Figure 7: Culvert Entrance, 30" diameter.



Figure 8: Culvert Exit, 30" diameter.

The culvert did not show any signs of damage, however the surrounding vegetation may need to be trimmed back to ensure the existing culvert operates properly.

North of the site is a creek that crosses under S. Franceville Coal Mine Rd. Existing drainage shows that the roadside drainage North of the site access driveway flows North into this creek.



Figure 9: Creek Entrance under S. Franceville Coal Mine Rd, site shown in the distance to the South.
Drainage path shown along roadside draining into the creek.



Figure 10: Creek Entrance under S. Franceville Coal Mine Rd.

APPENDIX C
DRAINAGE MAPS


GATEWAY TRUCKING EXISTING DRAINAGE MAP

PARCEL NUMBER 44000-00-459
OWNER:
PIKES PEAK CHAPTER - IZAAK WALTON LEAGUE
450 SOUTH FRANCEVILLE COAL MINE ROAD
COLORADO SPRINGS, CO 80929
ZONE: A-5
USE: GUN CLUB / SHOOTING RANGE

PARCEL NUMBER 44000-00-529
OWNER:
PERRY HASTINGS
11260 WEST LAKE
COLORADO SPRINGS, CO 80929
ZONE: A-5, RR-5
USE: VACANT

PARCEL NUMBER 44000-00-530
OWNER:
SHIRLEY BOUCHER LIVING TRUST
2440 PALMER PARK BLVD., APT 105
COLORADO SPRINGS, CO 80909
ZONE: RR-5
USE: RESIDENTIAL

PARCEL NUMBER 44000-00-531
OWNER:
PERRY HASTINGS
11260 WEST LAKE
COLORADO SPRINGS, CO 80929
ZONE: RR-5
USE: STORAGE / PARKING




LAYER LINETYPE LEGEND

	EXISTING	PROPOSED
SECTION LINE	-----	-----
BOUNDARY LINE	=====	=====
PROPERTY LINE	- - - - -	- - - - -
EASEMENT LINE	- - - - -	- - - - -
RIGHT OF WAY	=====	=====
CENTERLINE	-----	-----
STORM SEWER	=====	=====
SWALE/WATERWAY FLOWLINE	~~~~~	~~~~~
INDEX CONTOUR	~~~~~ 6100	~~~~~ 6100
INTERMEDIATE CONTOUR	~~~~~	~~~~~
BASIN ID		
DESIGN POINT DESIGNATION		
FLOW DIRECTION (PROPOSED)	→	→
FLOW DIRECTION (EXISTING)	⇨	⇨
SUB-BASIN DRAINAGE AREA	-----	-----
EXEMPT BASIN TO FLOW OFF-SITE UNTREATED		

BASIN SUMMARY TABLE

Tributary Sub-basin	Area (acres)	Percent Impervious	C _s	C ₁₀₀	t _c (min)	Q _s (cfs)	Q ₁₀₀ (cfs)
EX-A	6.78	2.0%	0.09	0.36	19.2	1.3	12.9
EX-B	3.76	12.4%	0.16	0.41	19.3	0.4	8.0
OS1	2.30	2.0%	0.09	0.36	19.0	0.7	4.4
OS2	4.64	2.0%	0.09	0.36	23.1	1.2	8.1
OS3	0.60	21.5%	0.22	0.45	18.0	0.4	1.5

Design Point	Contributing Area (ac)	Q _s (cfs)	Q ₁₀₀ (cfs)
1	2.30	0.7	4.4
2	4.64	1.2	8.1
3	13.72	3.0	23.8
4	0.60	0.4	1.5
5	18.08	3.8	32.5




EXISTING DRAINAGE MAP
GATEWAY TRUCKING
JOB NO. 25215.00
05/19/22
SHEET 1 OF 2



Centennial 303-740-9393 • Colorado Springs 719-593-2593
Fort Collins 970-491-9888 • www.jrengineering.com

GATEWAY TRUCKING PROPOSED DRAINAGE MAP



LAYER LINETYPE LEGEND

	EXISTING	PROPOSED
SECTION LINE	—	—
BOUNDARY LINE	—	—
PROPERTY LINE	—	—
EASEMENT LINE	—	—
RIGHT OF WAY	—	—
CENTERLINE	—	—
STORM SEWER	—	—
SWALE/WATERWAY FLOWLINE	—	—
INDEX CONTOUR	—	—
INTERMEDIATE CONTOUR	—	—
BASIN ID		
DESIGN POINT DESIGNATION		
FLOW DIRECTION (PROPOSED)		
FLOW DIRECTION (EXISTING)		
SUB-BASIN DRAINAGE AREA		
EXEMPT BASIN TO FLOW OFF-SITE UNTREATED		


BASIN SUMMARY TABLE

Tributary Sub-basin	Area (acres)	Percent Impervious	C ₅	C ₁₀₀	t _c (min)	Q ₅ (cfs)	Q ₁₀₀ (cfs)
A	3.48	47.3%	0.38	0.56	15.9	4.5	11.2
B	3.37	52.0%	0.41	0.58	14.4	4.9	11.7
C	1.65	24.0%	0.27	0.49	13.4	1.6	5.0
D	1.48	23.2%	0.27	0.49	6.3	1.9	5.8
E	0.70	10.4%	0.16	0.45	10.2	0.5	2.1
F	0.40	6.9%	0.13	0.46	14.1	0.2	1.1
OS1	2.48	2.0%	0.09	0.36	20.5	0.7	4.6
OS2	4.64	2.0%	0.09	0.36	23.1	1.2	8.1
OS3	0.60	23.1%	0.23	0.46	14.6	0.5	1.6

Design Point	Contributing Area (ac)	Q ₅ (cfs)	Q ₁₀₀ (cfs)
1	3.48	4.5	11.2
2	3.37	4.9	11.7
2.1	6.85	9.3	22.4
3	1.65	1.6	5.0
4	9.98	12.1	31.3

5	2.48	0.7	4.6
6	0.40	0.2	1.1

7	4.64	1.2	8.1
8	0.60	0.5	1.6
9	5.94	1.9	10.9
9.1	15.92	4.0	22.4



PROPOSED DRAINAGE MAP
GATEWAY TRUCKING
JOB NO. 25215.00
05/20/22
SHEET 2 OF 2

J-R ENGINEERING
A Westrian Company

Centennial 303-740-9393 • Colorado Springs 719-593-2593
Fort Collins 970-491-9888 • www.jrengineering.com