

COMMISSIONERS: MARK WALLER (CHAIR) LONGINOS GONZALEZ, JR. (VICE-CHAIR)

## **COLORADO**

HOLLY WILLIAMS STAN VANDERWERF CAMI BREMER

PLANNING AND COMMUNITY DEVELOPMENT DEPARTMENT CRAIG DOSSEY, EXECUTIVE DIRECTOR

## PRE-CONSTRUCTION MEETING

FILE: VR-1818

DATE:

7/9/2019

SUBDIVISION:

Gleneagle Golf Course Residential Infill Dev. Filing #2

DEVELOPER(S):

G & S Development Inc.

ENGINEER(S):

RESPEC

CONTRACTOR(S):

TBD PATE (STORM, WATER, SEWER)

GEOTECHNICAL:

TBD MG

DEVELOPER CONTACT:

Scott Gratrix, (720) 490-4250, sgratrix@gandsdevelopment.com

EPC PCD CONTACT:

Matt Arcidiacono, (719) 425-7088 - cell, mattarcidiacono@elpasoco.com

PODTLICOMBIC /NOTE

## OTHER PUBLIC ENTITIES (i.e. utilities);

- 1) Donala Water and Sanitation District
- 2) Black Hills Energy-Aquila
- 3) Mountain View Electric Associates

4)

#### APPROVAL CHECKLIST:

REQUIREMENT	APPROVED	FORTHCOMING / NOTE N/A	
⊠ Early Grading	6/4/2019		
☐ Preliminary ☐ Final Drainage Report	6/4/2019		
Financial Assurance Estimate	6/4/2019		
Surety Posted     Surety Posted	7/9/2019	$\boxtimes$	
Grading Permit Acknowledgement	date.		
Grading Permit Right-of-Access	date.		
Grading Permit	date.		
☑ EPC Construction Permit	7/9/2019	Pending	
CDPHE Construction Permit (APEN)	date.		$\boxtimes$
EPC Health Dept. Air Quality Permit	7/9/2019	□ Pending	
SWMP	6/4/2019		
Colorado Discharge Permit	7/9/2019	Pending, (>1ac)	
☐ Initial BMP Installation / Inspection	7/9/2019	Pending, Prior to NTP	
EPC DPW Right-of-Way Permit	date.	- Pending	<b>S</b>
⊠ ESQCP	6/4/2019		
Construction Schedule	date.		$\boxtimes$
Correct number of APPROVED plan sets	7/9/2019		
Construction Permit Fee	\$1,837.00		

ADDDOVED

ALL APPLICABLE FEDERAL, STATE AND LOCAL PERMITS, INSURANCE AND BONDING ARE TO BE OBTAINED PRIOR TO START OF CONSTRUCTION.

2880 International circle, Suite 110
Phone: (719) 520-6300

COLORADO SPRINGS, CO 80910-3127 FAX: (719) 520-6695 SUBDIVISION: VR-1818

#### TESTING CONTRACTOR:

#### Requirements:

- 1) Add EPC PCD to the distribution list for all testing reports, in a timely fashion, necessary to comply with the ECM Standards. A summary sheet of typical requirements is included with this document.
- 2) Minimum testing intervals of 250 LF applicable to trenches, 250 Lane ft. subgrade.
- 3) Testing of trenches / embankments not to exceed 2 foot depth intervals.
- 4) Provide pavement design along with HBP mix design to EPC PCD for review / approval at least 10 working days prior to anticipated date of placement.
- 5) Contact EPC PCD for subgrade inspection / proof roll prior to placement of gravel or pavement.

#### APPROVED PLAN SPECIFIC DESIGN REVIEW:

ITEM	COMMENTS
Excavation and Embankment	Per plan.
Utilities	Per plan.
Hydrants / Cisterns	N/A
Drainage Facilities	Per plan.
Off-site Drainage	Per plan.
Slope / Off-site Easements	Per plan.
Mail Box / Cluster	Per plan.
Sub Base / Base	Per plan.
ABC Surfacing	Per plan.
HBP Surfacing	Per plan.
Curb / Gutter / Cross Pans	N/A
Sidewalks	N/A
ADA Ramps	N/A
Signage	Per plan.
Striping	N/A
Fugitive Dust Control	Per plan
Concrete	N/A
Reinforcing Steel	N/A AASHTO M284 epoxy coated reinforcing bars

### WHEN ALL ITEMS (Subdivision Improvements) HAVE BEEN COMPLETED:

- 1) Submit written request for inspection punch list from EPC PCD.
- 2) Provide letters of acceptance for perpetual maintenance from all utilities providers.
- 3) Provide design engineer's signed and stamped certification letter of substantial compliance.
- 4) Upon satisfactory completion of punch list items and posting of applicable Defect Warranty surety a request for EPC DPW maintenance acceptance may be submitted to EPC.

5)	Warranty period commences on date of preliminary acceptance by EPC BoCC.
No	tice-to-Proceed will be issued once initial stormwater inspection has been completed.
SIC	El Paso County PCD Representative

## PRE-CONSTRUCTION MEETING ATTENDANCE LIST

Name: Brad Walters	Name: Matt Arcidiacono
Company: El Paso County PCD	Company: El Paso County PCD
Address: 2880 Intl. Cir #110	Address: 2880 Intl. Cir #110
City/St/Z: Colo. Spgs., CO 80910	City/St/Z: Colo. Spgs., CO 80910
Office: 520-6819	Office: 719-520-6314
Mobile: 332-3599	Mobile: 719-425-7088
Email: bradwalters@elpasoco.com	Email: mattarcidiacono@elpasoco.com

Name: Elizabeth Nijkamp	Name: Steve Kuehster
Company: El Paso County PCD	Company: El Paso County PCD
Address: 2880 Intl. Cir #110	Address: 2880 Intl. Cir #110
City/St/Z: Colo. Spgs., CO 80910	City/St/Z: Colo. Spgs., CO 80910
Office: 520-7852	Office: 520-6813
Mobile:	Mobile:
Email: ElizabethNijkamp@elpasoco.com	Email: stevekuehster@elpasoco.com

Name: Kari Parsons	Name:
Company: El Paso County PCD	Company:
Address: 2880 Intl. Cir #110	Address:
City/St/Z: Colo. Spgs., CO 80910	City/St/Z:
Office 719-520-6306	Office:
Mobile:	Mobile:
Email kariparsons@elpasoco.com	Email:

Name:	Name:	
Company:	Company:	
Address:	Address:	
City/St/Z:	City/St/Z:	
Office:	Office:	
Mobile:	Mobile:	
Email:	Email:	

SUBDIVISION: VR-1818

# PRE-CONSTRUCTION MEETING ATTENDANCE LIST

Name:	Name:
Company:	Company:
Address:	Address:
City/St/Z:	City/St/Z;
Office:	Office:
Mobile:	Mobile:
Email:	Email:
Name:	Name:
Company:	Company:
Address:	Address:
City/St/Z:	City/St/Z:
Office:	Office:
Mobile:	Mobile:
Email:	Email:
Name:	Name:
Company:	Company:
Address:	Address:
City/St/Z:	City/St/Z:
Office:	Office:
Mobile:	Mobile:
Email:	Email:
Name:	Name:
Company:	Company:
Address:	Address:
City/St/Z:	City/St/Z:
Office:	Office:
Mobile:	Mobile:
Email:	Email:

## Signing and Striping Notes:

- 1. All signs and pavement markings shall be in compliance with the current Manual on Uniform Traffic Control Devices (MUTCD).
- 2. Removal of existing pavement markings shall be accomplished by a method that does not materially damage the pavement. The pavement markings shall be removed to the extent that they will not be visible under day or night conditions. At no time will it be acceptable to paint over existing pavement markings.
- 3. Any deviation from the striping and signing plan shall be approved by El Paso County Planning and Community Development.
- 4. All signs shown on the signing and striping plan shall be new signs. Existing signs may remain or be reused if they meet current El Paso County and MUTCD standards.
- 5. Street name and regulatory stop signs shall be on the same post at intersections.
- 6. All removed signs shall be disposed of in a proper manner by the contractor.
- 7. All street name signs shall have "D" series letters, with local roadway signs being 4" upper-lower case lettering on 8" blank and non-local roadway signs being 6" lettering, upper-lower case on 12" blank, with a white border that is not recessed. Multi-lane roadways with speed limit of 40 mph or higher shall have 8" upper-lower case lettering on 18" blank with a white border that is not recessed. The width of the non-recessed white borders shall match page 255 of the 2012 MUTCD "Standard Highway Signs"
- 8. All traffic signs shall have a minimum High Intensity Prismatic grade sheeting.
- 9. All local residential street signs shall be mounted on a 1.75" x 1.75" square tube sign post and stub post base. For other applications, refer to the CDOT Standard S-614-8 regarding use of the P2 tubular steel post slipbase design.
- 10. All signs shall be single sheet aluminum with 0.100" minimum thickness.
- 11. All limit lines/stop lines, crosswalk lines, pavement legends, and arrows shall be a minimum 125 mil thickness preformed thermoplastic pavement markings with tapered leading edges per CDOT Standard S-627-1. Word and symbol markings shall be the narrow type. Stop bars shall be 24" in width. Crosswalks lines shall be 12" wide and 8' long per CDOT S-627-1.
- 12. All longitudinal lines shall be a minimum 15 mil thickness epoxy paint. All non-local residential roadways shall include both right and left edge line striping and any additional striping as required by CDOT S-627-1.
- 13. The contractor shall notify El Paso County PCD (719) 520-6819 prior to and upon completion of signing and striping.
- 14. The contractor shall obtain a work in the right of way permit from the El Paso County Department of Works (DPW) prior to any signage or striping work within an existing El Paso County roadway.

 $\label{eq:local_point} \mbox{Appendix J Roadway Inspections and Testing}$ 

Adopted: 1/9/2006 Revised: 7/28/2015

Revision 5

## J.5 TESTING SUMMARY

Table J-3 and Table J-4 summarize the testing requirements outlined in Appendix J.

Table J-3. Summary Minimum Testing Requirements

No.	Item	Type Of Test	Minimum Frequency	Min.#	Act.#
1	Utilities: Water,	Moisture/Density	1 per every 250 L.F. or		
	Sewer, Gas,		fraction thereof, every		
	Electric, Phone		2' elevation. Each		
	and Cable		structure (manhole,		
	Trenches		valve, etc.) every 2'		<u> </u>
			elevations. This		
			requirement also		
			applies to every		
			service.		
2	Storm Sewer	Moisture/Density	Same as above. Each		
	Trench		structure (manhole,		
			inlet, etc.) every 2'		
	<u> </u>	_	elevations.		
3	Inlets Concrete	Air Slump	First load or until		
	Testing		compliance. Minimum		
			1 per day.		
		Cylinders	1 set (4) per project for		
			every 100 C.Y. or		
		0. 1	fraction thereof.		
		Steel	Visual and		
	0 1 10 11	8.8 · · · · /D · · · · ·	Documentation		
4	Curb and Gutter	Moisture/Density	1 per every 250 L.F. or fraction thereof.		
		Proof-Roll			
			All final subgrade.		
		Air/Slump	First load or until compliance. Minimum		
			1 per every 2,000 L.F.		
			or fraction thereof.		
		Cylinders	1 set (4) per day		
		Cymiders	every 2,000 L.F. or		
			fraction thereof.		

Appendix J Roadway Inspections and Testing Adopted: 1/9/2006 Revised: 7/28/2015 REVISION 5

Table J-4. Summary of Minimum Testing Requirements

No.	ltem	Type of Test	Minimum Frequency	Min.#	Act.#
5	Sidewalk	Moisture/Density	1 per every 250		
		·	L.F. or fraction		
			thereof.		
		Air/Slump	First load or until		
			compliance.		
			Minimum 1 per		
			every 1,000 S.Y.		
			or fraction		
			thereof.		
		Cylinders	1 set (4) per		
			day 1,000 S.Y. or		
			fraction		
			thereof.		
6	Roadway	Moisture/Density	1 per every 500		
	Subgrade: Fills		Lane Ft. or		
	and Cuts		fraction thereof,		
			every 2'		
	1		elevation. Cuts to		
			be scarified to a		
			depth of 1',		
			recondition as		
			needed and		
			recompact.		
			All final subgrade.		
7	Roadway	Air/Slump	First 3 loads or		
	(Concrete)		until compliance,		
			then every 1,250		
			C.Y. or fraction		
			thereof.		
		Cylinders	1 set (4) per		
			project for every		
			1,250 C.Y. or		
			fraction thereof.		