Stormwater Detention and Infiltration Design Data Sheet

SDI-Design Data v2.00, Released January 2020

Stormwater Facility Name: Pond G

Facility Location & Jurisdiction: Rolling Hills Ranch, MSMD, 38°59.2'N, 104°34.4W

User Input: Watershed Characteristics

Extended Detention Basin (EDB)	▼	EDB	
Watershed Area	e e	836.00	acres
Watershed Length	า =	10,760	ft
Watershed Length to Centroid	1 =	4,740	ft
Watershed Slope	9 =	0.025	ft/ft
Watershed Imperviousness	s =	14.4%	percent
Percentage Hydrologic Soil Group A	+ =	0.0%	percent
Percentage Hydrologic Soil Group E	3 =	100.0%	percent
Percentage Hydrologic Soil Groups C/D) =	0.0%	percent
Target WQCV Drain Time	e =	40.0	hours
Location for 1-hr Rainfall Depths	; (u	se dropdown):
User Input		•	-

After providing required inputs above including 1-hour rainfall depths, click 'Run CUHP' to generate runoff hydrographs using the embedded Colorado Urban Hydrograph Procedure.

Once CUHP has been run and the Stage-Area-Discharge information has been provided, click 'Process Data' to interpolate the Stage-Area-Volume-Discharge data and generate summary results in the table below. Once this is complete, click 'Print to PDF'.

After completing and printing this worksheet to a pdf, go to:				
https://maperture.digitaldataservices.com/gvh/?viewer=cswdif				
Create a new stormwater facility, and attach the PDF of this				
worksheet to that record.				

Routed H	ydrogra	ph Results

One-Hour Rainfall Depth = N/A 0.93 1.21 1.47 2.16 2.50 in CUHP Runoff Volume = Inflow Hydrograph Volume = 1.550 6.411 13.684 25.538 76.596 104.683 acre-ft Time to Drain 97% of Inflow Volume = 0.893 6.616 15.839 27.760 73.164 100.932 acre-ft Time to Drain 97% of Inflow Volume = 0.893 6.616 15.839 27.74 20.5 18.0 hours Maximum Ponding Depth = 1.89 3.31 4.11 4.60 6.17 6.99 ft Maximum Ponded Area = 1.28 4.01 5.21 5.78 6.33 6.52 acres Maximum Volume Stored = 0.702 4.475 8.229 10.913 20.524 25.786 acre-ft WQCV should be around 40 hrs.	Design Storm Return Perio	= WQCV	2 Year	5 Year	10 Year	50 Year	100 Year]
CUHP Runoff Volume 1.550 6.411 13.684 25.538 76.596 104.683 acre-ft Inflow Hydrograph Volume 0.893 6.616 15.839 27.760 73.164 100.932 acre-ft Time to Drain 97% of Inflow Volume 59.8 53.1 35.9 27.4 20.5 18.0 hours Time to Drain 99% of Inflow Volume 164.6 68.6 62.8 52.0 29.2 26.6 hours Maximum Ponding Depth 1.89 3.31 4.11 4.60 6.17 6.99 ft Maximum Ponded Area 1.28 4.01 5.21 5.78 6.33 6.52 acres Maximum Volume Stored 0.702 4.475 8.229 10.913 20.524 25.786 acre-ft WQCV should be around 40 hrs. 1 10.913 20.524 25.786 acre-ft How could the 100yr volume defined stage/discharge based on the MH-Detention Maximum Ponded Area 4.475 4.475 4.475 4.475 4.475 4.475 4.475 4.475 4.475 4.475 4.475 4.475 4.475 4	One-Hour Rainfall Dept	n = N/A	0.93	1.21	1.47	2.16	2.50	in
Inflow Hydrograph Volume = 0.893 6.616 15.839 27.760 73.164 100.932 acre-ft Time to Drain 97% of Inflow Volume = 59.8 53.1 35.9 27.4 20.5 18.0 hours Time to Drain 99% of Inflow Volume = 64.6 68.6 62.8 52.0 29.2 26.6 hours Maximum Ponding Depth = 1.89 3.31 4.11 4.60 6.17 6.99 ft Maximum Volume Stored = 1.28 4.01 5.21 5.78 6.33 6.52 acres Maximum Volume Stored = 0.702 4.475 8.229 10.913 20.524 25.786 acres ft WQCV should be around 40 hrs. How could the 100yr volume drain quicker than the other design storm? Update user defined stage/discharge based on the MH-Detention	CUHP Runoff Volum	e = 1.550	6.411	13.684	25.538	76.596	104.683	acre-ft
Time to Drain 97% of Inflow Volume 59.8 53.1 35.9 27.4 20.5 18.0 hours Time to Drain 99% of Inflow Volume 1 64.6 68.6 62.8 52.0 29.2 26.6 hours Maximum Ponding Depth 1.89 3.31 4.11 4.60 6.17 6.99 ft Maximum Ponded Area 1.28 4.01 5.21 5.78 6.33 6.52 acres Maximum Volume Stored 0.702 4.475 8.229 10.913 20.524 25.786 acres WQCV should be around 40 hrs.	Inflow Hydrograph Volum	e = 0.893	6.616	15.839	27.760	73.164	100.932	acre-ft
Time to Drain 99% of Inflow Volume = 164.6 68.6 62.8 52.0 29.2 26.6 hours Maximum Ponding Depth = 1.89 3.31 4.11 4.60 6.17 6.99 ft Maximum Volume Stored = 1.28 4.01 5.21 5.78 6.33 6.52 acres Maximum Volume Stored = 0.702 4.475 8.229 10.913 20.524 25.786 acres around 40 hrs. How could the 100yr volume drain quicker than the other design storm? Update user defined stage/discharge based on the MH-Detention	Time to Drain 97% of Inflow Volum	e = 59.8	53.1	35.9	27.4	20.5	18.0	hours
Maximum Ponding Depth 1.89 3.31 4.11 4.60 6.17 6.99 ft Maximum Ponded Area 1.28 4.01 5.21 5.78 6.33 6.52 acres Maximum Volume Stored 0.702 4.475 8.229 10.913 20.524 25.786 acres WQCV should be around 40 hrs. 0.702 4.475 8.229 10.913 20.524 25.786 acres How could the 100yr volume drain quicker than the other design storm? Update user defined stage/discharge based on the MH-Detention MH-Detention How could the function How could the function	Time to Drain 99% of Inflow Volum	e = 🌈 64.6	68.6	62.8	52.0	29.2	26.6	hours
Maximum Volume Stored 1.28 4.01 5.21 5.78 6.33 6.52 acres Maximum Volume Stored 0.702 4.475 8.229 10.913 20.524 25.786 acre-ft WQCV should be around 40 hrs. How could the 100yr volume drain quicker than the other design storm? Update user defined stage/discharge based on the MH-Detention	Maximum Ponding Dept	n = / 1.89	3.31	4.11	4.60	6.17	6.99	ft
Maximum Volume Stored = 0.702 4.475 8.229 10.913 20.524 25.786 acre-ft WQCV should be around 40 hrs. How could the 100yr volume drain quicker than the other design storm? Update user defined stage/discharge based on the MH-Detention	Maximum Ponded Are	a = / 1.28	4.01	5.21	5.78	6.33	6.52	acres
WQCV should be around 40 hrs. How could the 100yr volume drain quicker than the other design storm? Update user defined stage/discharge based on the MH-Detention	Maximum Volume Store	l≠ 0.702	4.475	8.229	10.913	20.524	25.786	acre-ft
	How could the 100yr volume drain quicker than the other design storm? Update user defined stage/discharge based on the MH-Detention							

User Defined	User Defined	User Defined	User Defined
Stage [ft]	Area [ft^2]	Stage [ft]	Discharge [cfs]
0.00	0	0.00	0.00
0.70	2,232	0.70	0.05
1.70	39,917	1.70	0.17
2.70	126,469	2.70	3.70
3.20	166,675	3.20	4.83
3.70	206,880	3.70	5.74
4.20	232,032	4.20	24.56
4.70	257,183	4.70	62.47
5.20	264,196	5.20	132.61
5.70	271,209	5.70	221.75
6.20	276,106	6.20	328.73
6.70	281,003	6.70	450.47
7.20	286,003	7.20	490.94
7.70	291,002	7.70	516.23
8.20	296,443	8.20	540.35
8.70	301,883	8.70	701.32
9.20	309,236	9.20	975.60
9.70	316,589	9.70	1323.45

3/4/2020, 7:54 AM



Stormwater Detention and Infiltration Design Data Sheet



Pond G SDI_Design_Data_v2.00 HEC-HMS, Design Data

3/4/2020, 7:54 AM