Forsgren Associates, LLC 56 Inverness Drive East, Suite 112 Englewood, CO 80128 (720) 214-5884

June 25, 2019 El Paso County Development Services Attn: Nina Ruiz 2880 International Circle, Ste 110 Colorado Springs, CO 80910

SUBJECT: 1920 E Baptist Rd LLC

2-Lot Subdivision Drainage Memo

Dear Nina Ruiz.



This letter is being presented to discuss existing and future drainage features of the proposed site at 1920 E Baptist Rd. Monument, CO 80132 and to provide a description of the proposed work. Justification will be provided showing there will be no negative impact to existing drainage features or downstream conditions.

This project is located in the southwest 1/4 of Section 21, Township 11 South, and Range 66 West of the 6th Principal Meridian. The property is located at 1920 E Baptist Rd. Monument, CO 80132. It has a tax ID number of 6100000519 and is zoned RR-5. The streets that border the project area are E Baptist Rd. to the South and Roller Coaster Rd. to the East. Currently, there is a single-family residential home on the northwest portion of the property.

Description of Property

The property has an area of 36.65 acres and has a single-family residential home located on the northwest portion of the property. Runoff from the site flows in various directions from the site. Approximately 16% of runoff flows, generally, to the northwest and overland across neighboring properties. Approximately 40% of runoff flows, generally, to the southeast, to various culverts that deliver water across Baptist Road. Approximately 44% of runoff flows, generally, to the northeast, and along a roadside ditch to the north. The soil type for the property consists of approximately 30% Kettle gravelly loamy sand at slopes of 8-40%, 25% Peyton-Pring complex at 3-8% slopes, 35% Tomah-Crowfoot loamy sands at 3-8% slopes, and 10% Tomah-Crowfoot complex at 8-15% slopes. All soil types on site are of the hydrologic soil group B. See Appendix for the Custom Soils Resource Report for the site obtained from the National Cooperative Soil Survey

(https://websoilsurvey.sc.egov.usda.gov/App/HomePage.htm).

Major Basin Description

The site is located within the Smith Creek and West Cherry Creek Drainage Basins. All flows from the site flow, generally, to the south and end up, eventually, in Fountain Creek.

Floodplain Statement

The proposed improvements are not within a 100-year floodplain, FIRM #08041C0285G; dated December 7, 2018. See Appendix for FEMA FIRM Floodplain maps.

Subbasin Description

The site lies in between the Smith Creek and West Cherry Creek drainage basins. Stormwater runoff flowing off site shall generally flow to the south to various storm structures.

Four Step Process to Minimize Adverse Impacts of Urbanization

El Paso County requires the UDFCD Four Step Process be utilized for receiving waters protection. The goal of the Four Step Process is to reduce runoff volumes, treat the water quality capture volume of runoff, stabilize drainageways, and implement long-term source controls. Since no onsite improvements are to be made at this time, the four step process shall not be addressed.

Drainage Basin and Bridge Fees

Per the El Paso County Land Development Code, Section 8.5.5.C.2, drainage basin and bridge fees shall be paid prior to filing of the Final Plat. It is estimated that the impervious area of the 8.011-acre Lot 2 shall be approximately 14,500 ft². This was determined by assuming a similar size home that is currently on Lot 1 which has an area of 5,500 ft². It is assumed that the new home shall be near the back of the site, which is approximately 750-feet from Baptist Road. Assuming a 12-foot roadway from the road to the house, this would add approximately 9,000 ft² of impervious area to the lot. Thus, the total impervious area would be 14,500 ft². Given a reduction of 25% for lots larger than 2.5-acres, fees shall be assessed for 10,875 ft², or 0.25-acres.

Per the 2019 El Paso County Drainage Basin Fees, the cost per impervious acre for Smith Creek is \$7,481 for drainage fees and \$1,004 for bridge fees. Prior to the Final Plat being recorded, drainage fees in the amount of \$1,870.25 and bridge fees in the amount of \$251 shall be paid.

Proposed Conditions

No site improvements are being proposed at this time. The amount of pervious and impervious areas on site shall remain the same. The current property has a single home with an access road located at the northwest corner of the property. No offsite roadway improvements are required for this two-lot subdivision. When builders are selected for the various parcels to be developed, each individual homeowner shall pay all required drainage fees to the County. Each individual owner and builder shall also conduct their own due-diligence when developing each lot.

It is the professional opinion of the engineer that the proposed improvements will not have any negative impacts on the existing site conditions or the storm drainage system's ability to convey flows from the site and will not adversely affect the downstream and surrounding developments.

Please let me know if you have any questions.

Sincerely,

Forsgren Associates, Inc

Conner Burba, P.E. Project Manager

Design Engineer's Statement:

The attached drainage plan and report were prepared under my direction and supervision and are correct to the best of my knowledge and belief. Said drainage report has been prepared according to the criteria established by the County for drainage reports and said report is in conformity with the applicable master plan of the drainage basin. I accept responsibility for any liability caused by any negligent acts, errors or omissions on my part in preparing this report.

Conner Burba, P.E. #51257

Owner/Developer's Statement:

l, the owner/developer have read and will comply with all of the requirements specified in this drainage report and plan.

Barry Curtis

1920 E Baptist Rd

Monument, CO 80132

NOTES TO USERS

This map is for use in administering the National Flood Insurance Program. It does not necessarily identify all areas subject to flooding, particularly from local drainage sources of small size. The community map repository should be consulted for possible updated or additional flood hazard information.

To obtain more detailed information in areas where Base Flood Elevations (BFEs) and/or floodways have been determined, users are encouraged to consult the Flood Profiles and Floodway Data and/or Summary of Stillwater Elevations tables contained within the Flood Insurance Study (FIS) report that accompanies this FIRM. Users should be aware that BFEs shown on the FIRM represent rounded whole-foot elevations. These BFEs are intended for flood insurance rating purposes only and should not be used as the sole source of flood elevation information. Accordingly, flood elevation data presented in the FIS report should be utilized in conjunction with the FIRM for purposes of construction and/or floodplain management.

Coastal Base Flood Elevations shown on this map apply only landward of 0.0' North American Vertical Datum of 1988 (NAVD88). Users of this FIRM should be aware that coastal flood elevations are also provided in the Summary of Stillwater Elevations table in the Flood Insurance Study report for this jurisdiction. Elevations shown in the Summary of Stillwater Elevations table should be used for construction and/or floodplain management purposes when they are higher than the elevations shown on this FIRM.

Boundaries of the floodways were computed at cross sections and interpolated between cross sections. The floodways were based on hydraulic considerations with regard to requirements of the National Flood Insurance Program. Floodway widths and other pertinent floodway data are provided in the Flood Insurance Study report for this jurisdiction.

Certain areas not in Special Flood Hazard Areas may be protected by flood control structures. Refer to section 2.4 "Flood Protection Measures" of the Flood Insurance Study report for information on flood control structures for this jurisdiction.

The projection used in the preparation of this map was Universal Transverse Mercator (UTM) zone 13. The horizontal datum was NAD83, GRS80 spheroid. Differences in datum, spheroid, projection or UTM zones zones used in the production of FIRMs for adjacent jurisdictions may result in slight positional differences in map features across jurisdiction boundaries. These differences do not affect the accuracy of this FIRM.

Flood elevations on this map are referenced to the North American Vertical Datum of 1988 (NAVD88). These flood elevations must be compared to structure and ground elevations referenced to the same **vertical datum**.For information regarding conversion between the National Geodetic Vertical Datum of 1929 and the North American Vertical Datum of 1988, visit the National Geodetic Survey website a http://www.ngs.noaa.gov/ or contact the National Geodetic Survey at the following

NGS Information Services NOAA, N/NGS12 National Geodetic Survey SSMC-3, #9202 1315 East-West Highway Silver Spring, MD 20910-3282

To obtain current elevation, description, and/or location information for bench marks shown on this map, please contact the Information Services Branch of the National Geodetic Survey at (301) 713-3242 or visit its website at http://www.ngs.noaa.gov/.

Base Map information shown on this FIRM was provided in digital format by El Paso County, Colorado Springs Utilities, City of Fountain, Bureau of Land Management, National Oceanic and Atmospheric Administration, United States Geological Survey, and Anderson Consulting Engineers, Inc. These data are current as of 2006.

This map reflects more detailed and up-to-date stream channel configurations and floodplain delineations than those shown on the previous FIRM for this jurisdiction. The floodplains and floodways that were transferred from the previous FIRM may have been adjusted to conform to these new stream channel configurations. As a result, the Flood Profiles and Floodway Data tables in the Flood Insurance Study Report (which contains authoritative hydraulic data) may reflect stream channel distances that differ from what is shown on this map. The profile baselines depicted on this map represent the hydraulic modeling baselines that match the flood profiles and Floodway Data Tables if applicable, in the FIS report. As a result, the profile paselines may deviate significantly from the new base map channel representation and may appear outside of the floodplain.

Corporate limits shown on this map are based on the best data available at the time of publication. Because changes due to annexations or de-annexations may have occurred after this map was published, map users should contact appropriate community officials to verify current corporate limit locations.

Please refer to the separately printed Map Index for an overview map of the county showing the layout of map panels; community map repository addresses; and a Listing of Communities table containing National Flood Insurance Program dates for each community as well as a listing of the panels on which each community is

Contact FEMA Map Service Center (MSC) via the FEMA Map Information eXchange (FMIX) 1-877-336-2627 for information on available products associated with this FIRM. Available products may include previously issued Letters of Map Change, a Flood Insurance Study Report, and/or digital versions of this map. The MSC may also be reached by Fax at 1-800-358-9620 and its website a http://www.msc.fema.gov/.


If you have questions about this map or questions concerning the National Flood Insurance Program in general, please call 1-877-FEMA MAP (1-877-336-2627) or visit the FEMA website at http://www.fema.gov/business/nfip.

El Paso County Vertical Datum Offset Table

FOR STREAM BY STREAM VERTICAL DATUM CONVERSION INFORMATION

Flooding Source REFER TO SECTION 3.3 OF THE EL PASO COUNTY FLOOD INSURANCE STUDY


Panel Location Map



This Digital Flood Insurance Rate Map (DFIRM) was produced through a Cooperating Technical Partner (CTP) agreement between the State of Colorado Water Conservation Board (CWCB) and the Federal Emergency Management Agency (FEMA).



Additional Flood Hazard information and resources are available from local communities and the Colorado Water Conservation Board.



LEGEND

SPECIAL FLOOD HAZARD AREAS (SFHAS) SUBJECT TO INUNDATION BY THE 1% ANNUAL CHANCE FLOOD

The 1% annual chance flood (100-year flood), also known as the base flood, is the flood that has a 1% chance of being equaled or exceeded in any given year. The Special Flood Hazard Area is the area subject to flooding by the 1% annual chance flood. Areas of Special Flood Hazard include Zones A, AE, AH, AO, AR, A99, V, and VE. The Base Flood Elevation is the water-surface elevation of the 1% annual chance flood.

ZONE A No Base Flood Elevations determined. **ZONE AE** Base Flood Elevations determined.

Flood depths of 1 to 3 feet (usually areas of ponding); Base Flood Elevations determined

ZONE AO Flood depths of 1 to 3 feet (usually sheet flow on sloping terrain); average depths determined. For areas of alluvial fan flooding, velocities also

ZONE AR Special Flood Hazard Area Formerly protected from the 1% annual chance

AR indicates that the former flood control system is being restored to provide protection from the 1% annual chance or greater flood. **ZONE A99** Area to be protected from 1% annual chance flood by a Federal flood

flood by a flood control system that was subsequently decertified. Zone

protection system under construction; no Base Flood Elevations Coastal flood zone with velocity hazard (wave action); no Base Flood

Elevations determined. ZONE VE Coastal flood zone with velocity hazard (wave action); Base Flood

Elevations determined. FLOODWAY AREAS IN ZONE AE

The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 1% annual chance flood can be carried without substantial increases in flood heights.

OTHER FLOOD AREAS

Areas of 0.2% annual chance flood; areas of 1% annual chance flood with average depths of less than 1 foot or with drainage areas less than 1 square mile; and areas protected by levees from 1% annual chance flood.

OTHER AREAS

Areas determined to be outside the 0.2% annual chance floodplain. Areas in which flood hazards are undetermined, but possible.

COASTAL BARRIER RESOURCES SYSTEM (CBRS) AREAS

OTHERWISE PROTECTED AREAS (OPAs)

CBRS areas and OPAs are normally located within or adjacent to Special Flood Hazard Areas. Floodplain boundary

> Floodway boundary Zone D Boundary

••••••• CBRS and OPA boundary

> Boundary dividing Special Flood Hazard Areas of different Base Flood Elevations, flood depths or flood velocities. Base Flood Elevation line and value; elevation in feet*

(EL 987) Base Flood Elevation value where uniform within zone; elevation in feet*

* Referenced to the North American Vertical Datum of 1988 (NAVD 88) Cross section line

97° 07' 30 00" Geographic coordinates referenced to the North American 32° 22' 30.00" Datum of 1983 (NAD 83)

1000-meter Universal Transverse Mercator grid ticks,

5000-foot grid ticks: Colorado State Plane coordinate 6000000 FT system, central zone (FIPSZONE 0502),

Bench mark (see explanation in Notes to Users section of

this FIRM panel)

MAP REPOSITORIES

Refer to Map Repositories list on Map Index EFFECTIVE DATE OF COUNTYWIDE FLOOD INSURANCE RATE MAP

MARCH 17, 1997

EFFECTIVE DATE(S) OF REVISION(S) TO THIS PANEL **DECEMBER 7, 2018** - to update corporate limits, to change Base Flood Elevations and Special Flood Hazard Areas, to update map format, to add roads and road names, and to incorporate previously issued Letters of Map Revision.

For community map revision history prior to countywide mapping, refer to the Community Map History Table located in the Flood Insurance Study report for this jurisdiction.

To determine if flood insurance is available in this community, contact your insurance

agent or call the National Flood Insurance Program at 1-800-638-6620.

PANEL 0285G

FIRM FLOOD INSURANCE RATE MAP

EL PASO COUNTY, COLORADO AND INCORPORATED AREAS

PANEL 285 OF 1300

(SEE MAP INDEX FOR FIRM PANEL LAYOUT)

NUMBER

080059

CONTAINS: EL PASO COUNTY

PANEL

Notice to User: The Map Number shown below should be used when placing map orders: the Community Number shown above should be used on insurance applications for the



MAP REVISED

MAP NUMBER 08041C0285G

DECEMBER 7, 2018


Federal Emergency Management Agency



VRCS

Natural Resources Conservation Service A product of the National Cooperative Soil Survey, a joint effort of the United States Department of Agriculture and other Federal agencies, State agencies including the Agricultural Experiment Stations, and local participants

Custom Soil Resource Report for El Paso County Area, Colorado



Preface

Soil surveys contain information that affects land use planning in survey areas. They highlight soil limitations that affect various land uses and provide information about the properties of the soils in the survey areas. Soil surveys are designed for many different users, including farmers, ranchers, foresters, agronomists, urban planners, community officials, engineers, developers, builders, and home buyers. Also, conservationists, teachers, students, and specialists in recreation, waste disposal, and pollution control can use the surveys to help them understand, protect, or enhance the environment.

Various land use regulations of Federal, State, and local governments may impose special restrictions on land use or land treatment. Soil surveys identify soil properties that are used in making various land use or land treatment decisions. The information is intended to help the land users identify and reduce the effects of soil limitations on various land uses. The landowner or user is responsible for identifying and complying with existing laws and regulations.

Although soil survey information can be used for general farm, local, and wider area planning, onsite investigation is needed to supplement this information in some cases. Examples include soil quality assessments (http://www.nrcs.usda.gov/wps/portal/nrcs/main/soils/health/) and certain conservation and engineering applications. For more detailed information, contact your local USDA Service Center (https://offices.sc.egov.usda.gov/locator/app?agency=nrcs) or your NRCS State Soil Scientist (http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/contactus/?cid=nrcs142p2 053951).

Great differences in soil properties can occur within short distances. Some soils are seasonally wet or subject to flooding. Some are too unstable to be used as a foundation for buildings or roads. Clayey or wet soils are poorly suited to use as septic tank absorption fields. A high water table makes a soil poorly suited to basements or underground installations.

The National Cooperative Soil Survey is a joint effort of the United States Department of Agriculture and other Federal agencies, State agencies including the Agricultural Experiment Stations, and local agencies. The Natural Resources Conservation Service (NRCS) has leadership for the Federal part of the National Cooperative Soil Survey.

Information about soils is updated periodically. Updated information is available through the NRCS Web Soil Survey, the site for official soil survey information.

The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, age, disability, and where applicable, sex, marital status, familial status, parental status, religion, sexual orientation, genetic information, political beliefs, reprisal, or because all or a part of an individual's income is derived from any public assistance program. (Not all prohibited bases apply to all programs.) Persons with disabilities who require

alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD). To file a complaint of discrimination, write to USDA, Director, Office of Civil Rights, 1400 Independence Avenue, S.W., Washington, D.C. 20250-9410 or call (800) 795-3272 (voice) or (202) 720-6382 (TDD). USDA is an equal opportunity provider and employer.

Contents

Preface	2
How Soil Surveys Are Made	
Soil Map	
Soil Map (1920 E Baptist Rd)	9
Legend	10
Map Unit Legend (1920 E Baptist Rd)	11
Map Unit Descriptions (1920 E Baptist Rd)	11
El Paso County Area, Colorado	
40—Kettle gravelly loamy sand, 3 to 8 percent slopes	13
41—Kettle gravelly loamy sand, 8 to 40 percent slopes	14
68—Peyton-Pring complex, 3 to 8 percent slopes	15
92—Tomah-Crowfoot loamy sands, 3 to 8 percent slopes	16
93—Tomah-Crowfoot complex, 8 to 15 percent slopes	18
Soil Information for All Uses	
Soil Reports	21
Soil Physical Properties	21
Engineering Properties (1920 E Baptist Rd)	21
References	28

How Soil Surveys Are Made

Soil surveys are made to provide information about the soils and miscellaneous areas in a specific area. They include a description of the soils and miscellaneous areas and their location on the landscape and tables that show soil properties and limitations affecting various uses. Soil scientists observed the steepness, length, and shape of the slopes; the general pattern of drainage; the kinds of crops and native plants; and the kinds of bedrock. They observed and described many soil profiles. A soil profile is the sequence of natural layers, or horizons, in a soil. The profile extends from the surface down into the unconsolidated material in which the soil formed or from the surface down to bedrock. The unconsolidated material is devoid of roots and other living organisms and has not been changed by other biological activity.

Currently, soils are mapped according to the boundaries of major land resource areas (MLRAs). MLRAs are geographically associated land resource units that share common characteristics related to physiography, geology, climate, water resources, soils, biological resources, and land uses (USDA, 2006). Soil survey areas typically consist of parts of one or more MLRA.

The soils and miscellaneous areas in a survey area occur in an orderly pattern that is related to the geology, landforms, relief, climate, and natural vegetation of the area. Each kind of soil and miscellaneous area is associated with a particular kind of landform or with a segment of the landform. By observing the soils and miscellaneous areas in the survey area and relating their position to specific segments of the landform, a soil scientist develops a concept, or model, of how they were formed. Thus, during mapping, this model enables the soil scientist to predict with a considerable degree of accuracy the kind of soil or miscellaneous area at a specific location on the landscape.

Commonly, individual soils on the landscape merge into one another as their characteristics gradually change. To construct an accurate soil map, however, soil scientists must determine the boundaries between the soils. They can observe only a limited number of soil profiles. Nevertheless, these observations, supplemented by an understanding of the soil-vegetation-landscape relationship, are sufficient to verify predictions of the kinds of soil in an area and to determine the boundaries.

Soil scientists recorded the characteristics of the soil profiles that they studied. They noted soil color, texture, size and shape of soil aggregates, kind and amount of rock fragments, distribution of plant roots, reaction, and other features that enable them to identify soils. After describing the soils in the survey area and determining their properties, the soil scientists assigned the soils to taxonomic classes (units). Taxonomic classes are concepts. Each taxonomic class has a set of soil characteristics with precisely defined limits. The classes are used as a basis for comparison to classify soils systematically. Soil taxonomy, the system of taxonomic classification used in the United States, is based mainly on the kind and character of soil properties and the arrangement of horizons within the profile. After the soil

scientists classified and named the soils in the survey area, they compared the individual soils with similar soils in the same taxonomic class in other areas so that they could confirm data and assemble additional data based on experience and research.

The objective of soil mapping is not to delineate pure map unit components; the objective is to separate the landscape into landforms or landform segments that have similar use and management requirements. Each map unit is defined by a unique combination of soil components and/or miscellaneous areas in predictable proportions. Some components may be highly contrasting to the other components of the map unit. The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The delineation of such landforms and landform segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, onsite investigation is needed to define and locate the soils and miscellaneous areas.

Soil scientists make many field observations in the process of producing a soil map. The frequency of observation is dependent upon several factors, including scale of mapping, intensity of mapping, design of map units, complexity of the landscape, and experience of the soil scientist. Observations are made to test and refine the soil-landscape model and predictions and to verify the classification of the soils at specific locations. Once the soil-landscape model is refined, a significantly smaller number of measurements of individual soil properties are made and recorded. These measurements may include field measurements, such as those for color, depth to bedrock, and texture, and laboratory measurements, such as those for content of sand, silt, clay, salt, and other components. Properties of each soil typically vary from one point to another across the landscape.

Observations for map unit components are aggregated to develop ranges of characteristics for the components. The aggregated values are presented. Direct measurements do not exist for every property presented for every map unit component. Values for some properties are estimated from combinations of other properties.

While a soil survey is in progress, samples of some of the soils in the area generally are collected for laboratory analyses and for engineering tests. Soil scientists interpret the data from these analyses and tests as well as the field-observed characteristics and the soil properties to determine the expected behavior of the soils under different uses. Interpretations for all of the soils are field tested through observation of the soils in different uses and under different levels of management. Some interpretations are modified to fit local conditions, and some new interpretations are developed to meet local needs. Data are assembled from other sources, such as research information, production records, and field experience of specialists. For example, data on crop yields under defined levels of management are assembled from farm records and from field or plot experiments on the same kinds of soil.


Predictions about soil behavior are based not only on soil properties but also on such variables as climate and biological activity. Soil conditions are predictable over long periods of time, but they are not predictable from year to year. For example, soil scientists can predict with a fairly high degree of accuracy that a given soil will have a high water table within certain depths in most years, but they cannot predict that a high water table will always be at a specific level in the soil on a specific date.

After soil scientists located and identified the significant natural bodies of soil in the survey area, they drew the boundaries of these bodies on aerial photographs and

identified each as a specific map unit. Aerial photographs show trees, buildings, fields, roads, and rivers, all of which help in locating boundaries accurately.

Soil Map

The soil map section includes the soil map for the defined area of interest, a list of soil map units on the map and extent of each map unit, and cartographic symbols displayed on the map. Also presented are various metadata about data used to produce the map, and a description of each soil map unit.



MAP LEGEND

Area of Interest (AOI)

Area of Interest (AOI)

Soils

Soil Map Unit Polygons



Soil Map Unit Lines



Soil Map Unit Points

Special Point Features

(

Blowout

 \boxtimes

Borrow Pit

Ж

Clay Spot

 \wedge

Closed Depression

~

.

Gravelly Spot

0

Landfill

٨.

Lava Flow

Marsh or swamp

_

Mine or Quarry

仌

Miscellaneous Water

0

Perennial Water

 \vee

Rock Outcrop

+

Saline Spot Sandy Spot

۰.۰

Severely Eroded Spot

_

Sinkhole

3>

Slide or Slip

Ø

Sodic Spot

LEGEND



Spoil Area Stony Spot



Very Stony Spot



Wet Spot Other



Special Line Features

Water Features

_

Streams and Canals

Transportation

ransp

Rails

~

Interstate Highways

US Routes

 \sim

Major Roads

~

Local Roads

Background

1

Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:24.000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service

Web Soil Survey URL: Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: El Paso County Area, Colorado Survey Area Data: Version 15, Oct 10, 2017

Soil map units are labeled (as space allows) for map scales 1:50.000 or larger.

Date(s) aerial images were photographed: Feb 22, 2014—Mar 9, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Map Unit Legend (1920 E Baptist Rd)

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
40	Kettle gravelly loamy sand, 3 to 8 percent slopes	0.6	0.4%
41	Kettle gravelly loamy sand, 8 to 40 percent slopes	77.4	47.4%
68	Peyton-Pring complex, 3 to 8 percent slopes	34.1	20.9%
92	Tomah-Crowfoot loamy sands, 3 to 8 percent slopes	25.7	15.7%
93	Tomah-Crowfoot complex, 8 to 15 percent slopes	25.6	15.7%
Totals for Area of Interest		163.4	100.0%

Map Unit Descriptions (1920 E Baptist Rd)

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however, onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. Except for differences in texture of the surface layer, all the soils of a series have major horizons that are similar in composition, thickness, and arrangement.

Soils of one series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A *complex* consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An association is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An *undifferentiated group* is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous areas*. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

El Paso County Area, Colorado

40—Kettle gravelly loamy sand, 3 to 8 percent slopes

Map Unit Setting

National map unit symbol: 368g Elevation: 7,000 to 7,700 feet

Farmland classification: Not prime farmland

Map Unit Composition

Kettle and similar soils: 85 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Kettle

Setting

Landform: Hills

Landform position (three-dimensional): Side slope

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Sandy alluvium derived from arkose

Typical profile

E - 0 to 16 inches: gravelly loamy sand *Bt - 16 to 40 inches:* gravelly sandy loam

C - 40 to 60 inches: extremely gravelly loamy sand

Properties and qualities

Slope: 3 to 8 percent

Depth to restrictive feature: More than 80 inches Natural drainage class: Somewhat excessively drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): High (2.00 to 6.00

in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water storage in profile: Low (about 3.4 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: B Hydric soil rating: No

Minor Components

Other soils

Percent of map unit: Hydric soil rating: No

Pleasant

Percent of map unit: Landform: Depressions Hydric soil rating: Yes

41—Kettle gravelly loamy sand, 8 to 40 percent slopes

Map Unit Setting

National map unit symbol: 368h Elevation: 7,000 to 7,700 feet

Farmland classification: Not prime farmland

Map Unit Composition

Kettle and similar soils: 85 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Kettle

Setting

Landform: Hills

Landform position (three-dimensional): Side slope

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Sandy alluvium derived from arkose

Typical profile

E - 0 to 16 inches: gravelly loamy sand *Bt - 16 to 40 inches:* gravelly sandy loam

C - 40 to 60 inches: extremely gravelly loamy sand

Properties and qualities

Slope: 8 to 40 percent

Depth to restrictive feature: More than 80 inches Natural drainage class: Somewhat excessively drained

Runoff class: Medium

Capacity of the most limiting layer to transmit water (Ksat): High (2.00 to 6.00

in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water storage in profile: Low (about 3.4 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 7e

Hydrologic Soil Group: B Hydric soil rating: No

Minor Components

Other soils

Percent of map unit: Hydric soil rating: No

Pleasant

Percent of map unit:

Landform: Depressions Hydric soil rating: Yes

68—Peyton-Pring complex, 3 to 8 percent slopes

Map Unit Setting

National map unit symbol: 369f Elevation: 6,800 to 7,600 feet

Farmland classification: Not prime farmland

Map Unit Composition

Peyton and similar soils: 40 percent Pring and similar soils: 30 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Peyton

Setting

Landform: Hills

Landform position (three-dimensional): Side slope

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Arkosic alluvium derived from sedimentary rock and/or arkosic

residuum weathered from sedimentary rock

Typical profile

A - 0 to 12 inches: sandy loam
Bt - 12 to 25 inches: sandy clay loam
BC - 25 to 35 inches: sandy loam
C - 35 to 60 inches: sandy loam

Properties and qualities

Slope: 3 to 5 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high (0.20

to 0.60 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water storage in profile: Moderate (about 7.3 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 4c

Hydrologic Soil Group: B

Ecological site: Sandy Divide (R049BY216CO)

Hydric soil rating: No

Description of Pring

Setting

Landform: Hills

Landform position (three-dimensional): Side slope

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Arkosic alluvium derived from sedimentary rock

Typical profile

A - 0 to 14 inches: coarse sandy loam
C - 14 to 60 inches: gravelly sandy loam

Properties and qualities

Slope: 3 to 8 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): High (2.00 to 6.00

in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water storage in profile: Low (about 6.0 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 3e

Hydrologic Soil Group: B

Ecological site: Loamy Park (R048AY222CO)

Hydric soil rating: No

Minor Components

Other soils

Percent of map unit: Hydric soil rating: No

Pleasant

Percent of map unit: Landform: Depressions Hydric soil rating: Yes

92—Tomah-Crowfoot loamy sands, 3 to 8 percent slopes

Map Unit Setting

National map unit symbol: 36b9 Elevation: 7,300 to 7,600 feet

Farmland classification: Not prime farmland

Map Unit Composition

Tomah and similar soils: 50 percent Crowfoot and similar soils: 30 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Tomah

Setting

Landform: Alluvial fans, hills

Landform position (three-dimensional): Side slope, crest

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Alluvium derived from arkose and/or residuum weathered from

arkose

Typical profile

A - 0 to 10 inches: loamy sand E - 10 to 22 inches: coarse sand C - 48 to 60 inches: coarse sand

Properties and qualities

Slope: 3 to 8 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Medium

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to

high (0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water storage in profile: Very low (about 2.0 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: B

Ecological site: Sandy Divide (R049BY216CO)

Hydric soil rating: No

Description of Crowfoot

Settina

Landform: Alluvial fans, hills

Landform position (three-dimensional): Side slope, crest

Down-slope shape: Linear Across-slope shape: Linear Parent material: Alluvium

Typical profile

A - 0 to 12 inches: loamy sand E - 12 to 23 inches: sand

Bt - 23 to 36 inches: sandy clay loam C - 36 to 60 inches: coarse sand

Properties and qualities

Slope: 3 to 8 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Medium

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to

high (0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water storage in profile: Low (about 4.7 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: B

Ecological site: Sandy Divide (R049BY216CO)

Hydric soil rating: No

Minor Components

Other soils

Percent of map unit: Hydric soil rating: No

Pleasant

Percent of map unit: Landform: Depressions Hydric soil rating: Yes

93—Tomah-Crowfoot complex, 8 to 15 percent slopes

Map Unit Setting

National map unit symbol: 36bb Elevation: 7,300 to 7,600 feet

Farmland classification: Not prime farmland

Map Unit Composition

Tomah and similar soils: 50 percent Crowfoot and similar soils: 30 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Tomah

Setting

Landform: Alluvial fans, hills

Landform position (three-dimensional): Side slope, crest

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Alluvium derived from arkose and/or residuum weathered from

arkose

Typical profile

A - 0 to 10 inches: loamy sand E - 10 to 22 inches: coarse sand C - 48 to 60 inches: coarse sand

Properties and qualities

Slope: 8 to 15 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Medium

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to

high (0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water storage in profile: Very low (about 2.0 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: B

Ecological site: Sandy Divide (R049BY216CO)

Hydric soil rating: No

Description of Crowfoot

Setting

Landform: Hills, alluvial fans

Landform position (three-dimensional): Side slope, crest

Down-slope shape: Linear Across-slope shape: Linear Parent material: Alluvium

Typical profile

A - 0 to 12 inches: loamy sand E - 12 to 23 inches: sand

Bt - 23 to 36 inches: sandy clay loam

C - 36 to 60 inches: coarse sand

Properties and qualities

Slope: 8 to 15 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Medium

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to

high (0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water storage in profile: Low (about 4.7 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: B

Ecological site: Sandy Divide (R049BY216CO)

Hydric soil rating: No

Minor Components

Other soils

Percent of map unit: Hydric soil rating: No

Pleasant

Percent of map unit: Landform: Depressions Hydric soil rating: Yes

Soil Information for All Uses

Soil Reports

The Soil Reports section includes various formatted tabular and narrative reports (tables) containing data for each selected soil map unit and each component of each unit. No aggregation of data has occurred as is done in reports in the Soil Properties and Qualities and Suitabilities and Limitations sections.

The reports contain soil interpretive information as well as basic soil properties and qualities. A description of each report (table) is included.

Soil Physical Properties

This folder contains a collection of tabular reports that present soil physical properties. The reports (tables) include all selected map units and components for each map unit. Soil physical properties are measured or inferred from direct observations in the field or laboratory. Examples of soil physical properties include percent clay, organic matter, saturated hydraulic conductivity, available water capacity, and bulk density.

Engineering Properties (1920 E Baptist Rd)

This table gives the engineering classifications and the range of engineering properties for the layers of each soil in the survey area.

Hydrologic soil group is a group of soils having similar runoff potential under similar storm and cover conditions. The criteria for determining Hydrologic soil group is found in the National Engineering Handbook, Chapter 7 issued May 2007(http://directives.sc.egov.usda.gov/OpenNonWebContent.aspx?content=17757.wba). Listing HSGs by soil map unit component and not by soil series is a new concept for the engineers. Past engineering references contained lists of HSGs by soil series. Soil series are continually being defined and redefined, and the list of soil series names changes so frequently as to make the task of maintaining a single national list virtually impossible. Therefore, the criteria is now used to calculate the HSG using the component soil properties and no such national series lists will be maintained. All such references are obsolete and their use should be discontinued. Soil properties that influence runoff potential are those that influence the minimum rate of infiltration for a bare soil after prolonged wetting and when not frozen. These properties are depth to a seasonal high water table, saturated hydraulic conductivity after prolonged wetting, and depth to a layer with a very slow water transmission

rate. Changes in soil properties caused by land management or climate changes also cause the hydrologic soil group to change. The influence of ground cover is treated independently. There are four hydrologic soil groups, A, B, C, and D, and three dual groups, A/D, B/D, and C/D. In the dual groups, the first letter is for drained areas and the second letter is for undrained areas.

The four hydrologic soil groups are described in the following paragraphs:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

Depth to the upper and lower boundaries of each layer is indicated.

Texture is given in the standard terms used by the U.S. Department of Agriculture. These terms are defined according to percentages of sand, silt, and clay in the fraction of the soil that is less than 2 millimeters in diameter. "Loam," for example, is soil that is 7 to 27 percent clay, 28 to 50 percent silt, and less than 52 percent sand. If the content of particles coarser than sand is 15 percent or more, an appropriate modifier is added, for example, "gravelly."

Classification of the soils is determined according to the Unified soil classification system (ASTM, 2005) and the system adopted by the American Association of State Highway and Transportation Officials (AASHTO, 2004).

The Unified system classifies soils according to properties that affect their use as construction material. Soils are classified according to particle-size distribution of the fraction less than 3 inches in diameter and according to plasticity index, liquid limit, and organic matter content. Sandy and gravelly soils are identified as GW, GP, GM, GC, SW, SP, SM, and SC; silty and clayey soils as ML, CL, OL, MH, CH, and OH; and highly organic soils as PT. Soils exhibiting engineering properties of two groups can have a dual classification, for example, CL-ML.

The AASHTO system classifies soils according to those properties that affect roadway construction and maintenance. In this system, the fraction of a mineral soil that is less than 3 inches in diameter is classified in one of seven groups from A-1 through A-7 on the basis of particle-size distribution, liquid limit, and plasticity index. Soils in group A-1 are coarse grained and low in content of fines (silt and clay). At the other extreme, soils in group A-7 are fine grained. Highly organic soils are classified in group A-8 on the basis of visual inspection.

If laboratory data are available, the A-1, A-2, and A-7 groups are further classified as A-1-a, A-1-b, A-2-4, A-2-5, A-2-6, A-2-7, A-7-5, or A-7-6. As an additional refinement, the suitability of a soil as subgrade material can be indicated by a group

index number. Group index numbers range from 0 for the best subgrade material to 20 or higher for the poorest.

Percentage of rock fragments larger than 10 inches in diameter and 3 to 10 inches in diameter are indicated as a percentage of the total soil on a dry-weight basis. The percentages are estimates determined mainly by converting volume percentage in the field to weight percentage. Three values are provided to identify the expected Low (L), Representative Value (R), and High (H).

Percentage (of soil particles) passing designated sieves is the percentage of the soil fraction less than 3 inches in diameter based on an ovendry weight. The sieves, numbers 4, 10, 40, and 200 (USA Standard Series), have openings of 4.76, 2.00, 0.420, and 0.074 millimeters, respectively. Estimates are based on laboratory tests of soils sampled in the survey area and in nearby areas and on estimates made in the field. Three values are provided to identify the expected Low (L), Representative Value (R), and High (H).

Liquid limit and plasticity index (Atterberg limits) indicate the plasticity characteristics of a soil. The estimates are based on test data from the survey area or from nearby areas and on field examination. Three values are provided to identify the expected Low (L), Representative Value (R), and High (H).

References:

American Association of State Highway and Transportation Officials (AASHTO). 2004. Standard specifications for transportation materials and methods of sampling and testing. 24th edition.

American Society for Testing and Materials (ASTM). 2005. Standard classification of soils for engineering purposes. ASTM Standard D2487-00.

Absence of an entry indicates that the data were not estimated. The asterisk '*' denotes the representative texture; other possible textures follow the dash. The criteria for determining the hydrologic soil group for individual soil components is found in the National Engineering Handbook, Chapter 7 issued May 2007(http://directives.sc.egov.usda.gov/OpenNonWebContent.aspx?content=17757.wba). Three values are provided to identify the expected Low (L), Representative Value (R), and High (H).

				Engineering F	roperties-E	I Paso Cou	nty Area,	Colorado						
Map unit symbol and	Pct. of	Hydrolo	Depth	USDA texture	Classi	fication	Pct Fra	gments	Percent	ercentage passing sieve number—				Plasticit
soil name	map unit	gic group			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200	limit	y index
			In				L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H
40—Kettle gravelly loamy sand, 3 to 8 percent slopes														
Kettle	85	В	0-16	Gravelly loamy sand	SC-SM, SM, SW-SM	A-1-b, A-2	0- 0- 0	0- 8- 15	60-73- 85	55-65- 75	30-43- 55	10-15- 20	20-23 -25	NP-3 -5
			16-40	Gravelly sandy loam	GM, SC- SM, SM	A-1-b, A-2	0- 0- 0	0- 8- 15	60-70- 80	50-63- 75	35-43- 50	20-25- 30	20-23 -25	NP-3 -5
			40-60	Extremely gravelly loamy sand, extremely gravelly loamy coarse sand	GP, GW	A-1	0- 5- 10	0-10- 20	15-23- 30	10-18- 25	5-13- 20	0- 3- 5	_	NP
41—Kettle gravelly loamy sand, 8 to 40 percent slopes														
Kettle	85	В	0-16	Gravelly loamy sand	SC-SM, SM, SW-SM	A-1-b, A-2	0- 0- 0	0- 8- 15	60-73- 85	55-65- 75	30-43- 55	10-15- 20	20-23 -25	NP-3 -5
			16-40	Gravelly sandy loam	GM, SC- SM, SM	A-1-b, A-2	0- 0- 0	0- 8- 15	60-70- 80	50-63- 75	35-43- 50	20-25- 30	20-23 -25	NP-3 -5
			40-60	Extremely gravelly loamy sand, extremely gravelly loamy coarse sand	GP, GW	A-1	0- 5- 10	0-10- 20	15-23- 30	10-18- 25	5-13- 20	0- 3- 5	_	NP

				Engineering F	Properties-E	I Paso Cou	nty Area,	Colorado						
Map unit symbol and	Pct. of	Hydrolo	Depth	USDA texture	Classi	fication	Pct Fragments		Percent	age passi	ng sieve ı	number—		
soil name	map unit	gic group			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200	limit	y index
			In				L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H
68—Peyton-Pring complex, 3 to 8 percent slopes														
Peyton	40	В	0-12	Sandy loam	SC, SC- SM	A-2-4, A-4	0- 0- 0	0- 0- 0	85-93-1 00	80-90-1 00	50-60- 70	25-33- 40	25-28 -30	5-8 -10
			12-25	Sandy clay loam	CL, CL- ML, SC, SC-SM	A-2, A-4, A-6	0- 0- 0	0- 0- 0	85-93-1 00	80-90-1 00	65-78- 90	30-43- 55	25-30 -35	5-10-15
			25-35	Sandy clay loam, sandy loam	CL-ML, SC, SC- SM	A-2, A-4	0- 0- 0	0- 0- 0	85-93-1 00	80-90-1 00	50-70- 90	25-40- 55	25-28 -30	5-8 -10
			35-60	Sandy loam	SM	A-2-4, A-4	0- 0- 0	0- 0- 0	85-93-1 00	80-90-1 00	50-60- 70	25-33- 40	20-23 -25	NP-3 -5
Pring	30	В	0-14	Coarse sandy loam	SC, SC- SM	A-2-4, A-1	0- 0- 0	0- 5- 10	85-93-1 00	80-90-1 00	45-55- 65	20-25- 30	25-28 -30	5-8 -10
			14-60	Gravelly sandy loam	GC-GM, SC-SM, SM	A-1-b, A-2	0- 0- 0	0- 5- 10	60-80-1 00	55-78-1 00	35-43- 50	20-25- 30	20-23 -25	NP-3 -5

				Engineering P	roperties-E	I Paso Cou	nty Area,	Colorado						
Map unit symbol and	Pct. of	Hydrolo	Depth	USDA texture	Classi	fication	Pct Fra	gments	Percent	age passi	ng sieve ı	number—	Liquid	Plasticit
soil name map unit	map unit	gic group			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200	limit	y index
			In				L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H
92—Tomah-Crowfoot loamy sands, 3 to 8 percent slopes														
Tomah	50	В	0-10	Loamy sand	SM	A-2-4	0- 0- 0	0- 0- 0	100-100 -100	100-100 -100	50-60- 70	15-23- 30	20-23 -25	NP-3 -5
			10-22	Coarse sand	SP-SM, SW-SM	A-1, A-2, A-3	0- 0- 0	0- 0- 0	100-100 -100	100-100 -100	45-55- 65	5- 8- 10	_	NP
			22-48	Stratified coarse sand to sandy clay loam	SC, SM, SP-SM, SC-SM	A-2-4, A-1, A-4	0- 0- 0	0- 0- 0	85-93-1 00	80-90-1 00	35-63- 90	5-28- 50	20-25 -30	NP-5 -10
			48-60	Coarse sand, loamy coarse sand	SC-SM, SM, SP- SM	A-2-4, A-1, A-3	0- 0- 0	0- 0- 0	85-93-1 00	80-90-1 00	35-53- 70	5-15- 25	20-23 -25	NP-3 -5
Crowfoot	30	В	0-12	Loamy sand	SM	A-2-4, A-1	0- 0- 0	0- 5- 10	85-93-1 00	80-90-1 00	40-58- 75	15-23- 30	20-23 -25	NP-3 -5
			12-23	Sand	SM, SP- SM	A-1, A-2, A-3	0- 0- 0	0- 5- 10	85-93-1 00	80-90-1 00	40-55- 70	5-10- 15	_	NP
			23-36	Sandy clay loam	CL-ML, SC, SC- SM	A-2-4, A-4, A-6	0- 0- 0	0- 5- 10	85-93-1 00	80-90-1 00	65-78- 90	30-43- 55	25-30 -35	5-10-15
			36-60	Coarse sand, loamy coarse sand	SM, SP- SM	A-1, A-2	0- 0- 0	0- 5- 10	85-93-1 00	80-90-1 00	35-53- 70	5-15- 25		NP

				Engineering P	roperties-E	I Paso Cou	nty Area,	Colorado						
soil name map	Pct. of	Hydrolo	Depth	USDA texture	Classi	fication	Pct Fra	gments	Percent	age passi	ng sieve ı	number—	Liquid	Plasticit
	map unit	gic group			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200	limit	y index
			In				L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H	L-R-H
93—Tomah-Crowfoot complex, 8 to 15 percent slopes														
Tomah	50	В	0-10	Loamy sand	SM	A-2-4	0- 0- 0	0- 0- 0	100-100 -100	100-100 -100	50-60- 70	15-23- 30	20-23 -25	NP-3 -5
			10-22	Coarse sand	SP-SM, SW-SM	A-1, A-2, A-3	0- 0- 0	0- 0- 0	100-100 -100	100-100 -100	45-55- 65	5- 8- 10	_	NP
			22-48	Stratified coarse sand to sandy clay loam	SC, SM, SP-SM, SC-SM	A-1, A-4, A-2-4	0- 0- 0	0- 0- 0	85-93-1 00	80-90-1 00	35-63- 90	5-28- 50	20-25 -30	NP-5 -10
			48-60	Coarse sand, loamy coarse sand	SC-SM, SM, SP- SM	A-1, A-3, A-2-4	0- 0- 0	0- 0- 0	85-93-1 00	80-90-1 00	35-53- 70	5-15- 25	20-23 -25	NP-3 -5
Crowfoot	30	В	0-12	Loamy sand	SM	A-1, A-2-4	0- 0- 0	0- 5- 10	85-93-1 00	80-90-1 00	40-58- 75	15-23- 30	20-23 -25	NP-3 -5
			12-23	Sand	SM, SP- SM	A-1, A-2, A-3	0- 0- 0	0- 5- 10	85-93-1 00	80-90-1 00	40-55- 70	5-10- 15	_	NP
			23-36	Sandy clay loam	CL-ML, SC, SC- SM	A-4, A-6, A-2-4	0- 0- 0	0- 5- 10	85-93-1 00	80-90-1 00	65-78- 90	30-43- 55	25-30 -35	5-10-15
			36-60	Coarse sand, loamy coarse sand	SM, SP- SM	A-1, A-2	0- 0- 0	0- 5- 10	85-93-1 00	80-90-1 00	35-53- 70	5-15- 25	_	NP

References

American Association of State Highway and Transportation Officials (AASHTO). 2004. Standard specifications for transportation materials and methods of sampling and testing. 24th edition.

American Society for Testing and Materials (ASTM). 2005. Standard classification of soils for engineering purposes. ASTM Standard D2487-00.

Cowardin, L.M., V. Carter, F.C. Golet, and E.T. LaRoe. 1979. Classification of wetlands and deep-water habitats of the United States. U.S. Fish and Wildlife Service FWS/OBS-79/31.

Federal Register. July 13, 1994. Changes in hydric soils of the United States.

Federal Register. September 18, 2002. Hydric soils of the United States.

Hurt, G.W., and L.M. Vasilas, editors. Version 6.0, 2006. Field indicators of hydric soils in the United States.

National Research Council. 1995. Wetlands: Characteristics and boundaries.

Soil Survey Division Staff. 1993. Soil survey manual. Soil Conservation Service. U.S. Department of Agriculture Handbook 18. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_054262

Soil Survey Staff. 1999. Soil taxonomy: A basic system of soil classification for making and interpreting soil surveys. 2nd edition. Natural Resources Conservation Service, U.S. Department of Agriculture Handbook 436. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2 053577

Soil Survey Staff. 2010. Keys to soil taxonomy. 11th edition. U.S. Department of Agriculture, Natural Resources Conservation Service. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2 053580

Tiner, R.W., Jr. 1985. Wetlands of Delaware. U.S. Fish and Wildlife Service and Delaware Department of Natural Resources and Environmental Control, Wetlands Section.

United States Army Corps of Engineers, Environmental Laboratory. 1987. Corps of Engineers wetlands delineation manual. Waterways Experiment Station Technical Report Y-87-1.

United States Department of Agriculture, Natural Resources Conservation Service. National forestry manual. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/home/?cid=nrcs142p2_053374

United States Department of Agriculture, Natural Resources Conservation Service. National range and pasture handbook. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/landuse/rangepasture/?cid=stelprdb1043084

United States Department of Agriculture, Natural Resources Conservation Service. National soil survey handbook, title 430-VI. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/scientists/?cid=nrcs142p2_054242

United States Department of Agriculture, Natural Resources Conservation Service. 2006. Land resource regions and major land resource areas of the United States, the Caribbean, and the Pacific Basin. U.S. Department of Agriculture Handbook 296. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053624

United States Department of Agriculture, Soil Conservation Service. 1961. Land capability classification. U.S. Department of Agriculture Handbook 210. http://www.nrcs.usda.gov/Internet/FSE_DOCUMENTS/nrcs142p2_052290.pdf

El Paso County Drainage Basin Fees Resolution No. 18-470

Basin	Receiving	Year	Drainage Basin Name	2019 Drainage Fee	2019 Bridge Fee
Number	Waters	Studied		(per Impervious Acre)	(per Impervious Acre)
Drainage Basins w	vith DBPS's:				
CHMS0200	Chico Creek	2013	Haegler Ranch	\$10,324	\$1,524
HWS1200	Chico Creek	2001	Bennett Ranch	\$11,558	\$4,433
HWS1400	Chico Creek	2013	Falcon	\$29,622	\$4,069
OFO2000	Fountain Creek	2001	West Fork Jimmy Camp Creek	\$12,564	\$3,717
OFO2600	Fountain Creek	1991*	Big Johnson / Crews Gulch	\$18,350	\$2,370
OFO2800	Fountain Creek	1988*	Widefield	\$18,350	\$0
OFO2900	Fountain Creek	1988*	Security	\$18,350	\$0
OFQ3000	Fountain Creek	1991*	Windmill Gulch	\$18,350	\$275
OFO3000 OFO3100 / FOFO32		1988*	Carson Street / Little Johnson	\$11,192	\$0
			Peterson Field	\$13,235	\$1,004
OFO3400	Fountain Creek	1984*		\$18,350	\$0
OFO3600	Fountain Creek	1991*	Fisher's Canyon	· •	
OFO4000	Fountain Creek	1996	Sand Creek	\$18,940	\$5,559
OFO4200	Fountain Creek	1977	Spring Creek	\$9,517	\$0
OFO4600	Fountain Creek	1984*	Southwest Area	\$18,350	\$0
OFO4800	Fountain Creek	1991	Bear Creek	\$18,350	\$1,004
OFO5400	Fountain Creek	1977	21st Street	\$5, 52 1	\$0
OFO5600	Fountain Creek	1964	19th Street	\$3,611	\$0
OFO5800	Fountain Creek	1964	Camp Creek	\$2,033	\$0
OMO0400	Monument Creek	1986"	Mesa	\$9,598	\$0
OMO1000	Monument Creek	1981	Douglas Creek	\$11,540	\$255
OMO1200	Monument Creek	1977	Templeton Gap	\$11,847	\$275
OMO1400	Monument Creek	1976	Pope's Bluff	\$3,676	\$627
OMO1600	Monument Creek	1976	South Rockrimmon	\$4,314	\$0
OMO1800	Monument Creek	1973	North Rockrimmon	\$5,521	\$0
OMO2000	Monument Creek	1971	Pulpit Rock	\$6,085	\$0
OMO2200	Monument Creek	1994	Cottonwood Creek / S. Pine	\$18,350	\$1,004
OMO2400	Monument Creek	1966	Dry Creek	\$14,486	\$524
		1989*	Black Squirrel Creek	\$8,331	\$524
OMO3600	Monument Creek		Middle Tributary	\$15,312	\$0
OMO3700	Monument Creek	1987*	•	• •	\$0
OMO3800	Monument Creek	1987*	Monument Branch	\$18,350	
OMO4000	Monument Creek	1996	Smith Creek	\$7,481	\$1,004
OMO4200	Monument Creek	1989*	Black Forest	\$18,350	\$500
FOMO5200	Monument Creek	1993*	Dirty Woman Creek	\$18,350	\$1,004
OMO5300	Fountain Creek	1993*	Crystal Creek	\$18,350	\$1,004
Miscellaneous Dra	ainage Basins: 1				
CHBS0800	Chico Creek		Book Ranch	\$17,217	\$2,492
CHEC0400	Chico Creek		Upper East Chico	\$9,380	\$272
CHWS0200	Chico Creek		Telephone Exchange	\$10,306	\$241
CHWS0400	Chico Creek		Livestock Company	\$16,976	\$202
CHWS0600	Chico Creek		West Squirrel	\$8,849	\$3,672
CHWS0800	Chico Creek		Solberg Ranch	\$18,350	\$0
				•	\$0
OFO1200	Fountain Creek		Crooked Canyon	\$5,540 \$4,625	\$270
OFO1400	Fountain Creek		Calhan Reservoir		
OFO1600	Fountain Creek		Sand Canyon	\$3,342	\$0
OFO2000	Fountain Creek		Jimmy Camp Creek ³	\$18,350	\$858
OFO2200	Fountain Creek		Fort Carson	\$14,486	\$524
OFO2700	Fountain Creek		West Little Johnson	\$1,209	\$0
OFO3800	Fountain Creek		Stratton	\$8,801	\$394
OFO5000	Fountain Creek		Midland	\$14,486	\$524
OFO6000	Fountain Creek		Palmer Trail	\$14,486	\$524
OFO6800	Fountain Creek		Black Canyon	\$14,486	\$524
OMO4600	Monument Creek		Beaver Creek	\$10,970	\$0
OMO3000	Monument Creek		Kettle Creek	\$9,909	\$0
OMO3400	Monument Creek		Elkhom	\$1,665	\$0
OMO5000	Monument Creek		Monument Rock	\$7,953	\$0
,	Monument Creek		Palmer Lake	\$12,717	\$0
OMO5400					\$0 \$0
FOMO5600	Monument Creek		Raspberry Mountain Bald Mountain	\$4,278 \$9,116	\$0 \$0
PLPL0200	Monument Creek		Daid MOUNTAIN	\$9,116	ΦU
nterim Drainage I			Little Fountain Creat	¢2 246	60
OFO1800	Fountain Creek		Little Fountain Creek	\$2,346 \$7,363	\$0 \$ 0
	Monument Creek		Jackson Creek	\$7,263	3SU
OMO4400 OMO4800	Monument Creek		Teachout Creek	\$5,044	\$758

^{1.} The miscellaneous drainage fee previous to September 1999 resolution was the average of all drainage fees for basins with Basin Planning Studies perform

EPC Stormwater Management

Jennifer	Invine	PF
Jennie	HVIIIC,	r.L

^{2.} Interim Drainage Fees are based upon draft Drainage Basin Planning Studies or the Drainage Basin Identification and Fee Estimation Report. (Best available

^{3.} This is an interim fee and will be adjusted when a DBPS is completed. In addition to the Drainage Fee a surety in the amount of \$7,285 per impervious acre shifted DBPS results in a fee greater than the current fee. Fees paid in excess of the future revised fee will be reimbursed. See Resolution 06-326 (9/14/06) and Resolution 06-326 (9/14/06) an

